

# SLOVENSKI STANDARD SIST CWA 16926-67:2023

01-april-2023

Specifikacija vmesnika razširitev za finančne storitve (XFS), izdaja 3.50 - 67. del: Razred vmesnika depozitne naprave - Referenca za programerje - Prehod z različice 3.40 (CWA 16926:2020) na različico 3.50 (ta CWA)

Extensions for Financial Services (XFS) interface specification Release 3.50 - Part 67: Depository Device Class Interface - Programmer's Reference - Migration from Version 3.40 (CWA 16926:2020) to Version 3.50 (this CWA)

# (standards.iteh.ai)

#### SIST CWA 16926-67:2023

https://standards.iteh.ai/catalog/standards/sist/687a4b9f-d8cf-4285-a433-48766629fb0f/sist cwa-16926-67-2023

Ta slovenski standard je istoveten z: CWA 16926-67:2023

## ICS:

35	5.200	Vmesniška in povezovalna oprema	Interface and interconnection equipment
35	5.240.15	Identifikacijske kartice. Čipne kartice. Biometrija	Identification cards. Chip cards. Biometrics
35	5.240.40	Uporabniške rešitve IT v bančništvu	IT applications in banking

SIST CWA 16926-67:2023 en,fr,de

SIST CWA 16926-67:2023

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST CWA 16926-67:2023

https://standards.iteh.ai/catalog/standards/sist/687a4b9f-d8cf-4285-a433-48766629fb0f/sist-cwa-16926-67-2023

**CEN** 

CWA 16926-67

WORKSHOP

January 2023

# **AGREEMENT**

ICS 35.200; 35.240.15; 35.240.40

#### **English** version

Extensions for Financial Services (XFS) interface specification Release 3.50 - Part 67: Depository Device Class Interface - Programmer's Reference - Migration from Version 3.40 (CWA 16926:2020) to Version 3.50 (this CWA)

This CEN Workshop Agreement has been drafted and approved by a Workshop of representatives of interested parties, the constitution of which is indicated in the foreword of this Workshop Agreement.

The formal process followed by the Workshop in the development of this Workshop Agreement has been endorsed by the National Members of CEN but neither the National Members of CEN nor the CEN-CENELEC Management Centre can be held accountable for the technical content of this CEN Workshop Agreement or possible conflicts with standards or legislation.

This CEN Workshop Agreement can in no way be held as being an official standard developed by CEN and its Members.

This CEN Workshop Agreement is publicly available as a reference document from the CEN Members National Standard Bodies.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

# **Table of Contents**

European Foreword3			
1.		Introduction	7
	1.1	Background to Release 3.50	7
	1.2	XFS Service-Specific Programming	7
2.		Depository Unit	8
3.		References	9
4.		Info Commands	10
	4.1	WFS_INF_DEP_STATUS	10
	4.2	WFS_INF_DEP_CAPABILITIES	15
5.		Execute Commands	18
	5.1	WFS_CMD_DEP_ENTRY	18
	5.2	WFS_CMD_DEP_DISPENSE	20
	5.3		
	5.4	WFS_CMD_DEP_RESET_COUNT	22
	5.5	WFS_CMD_DEP_RESET	23
	5.6	WFS_CMD_DEP_SET_GUIDANCE_LIGHT	24
	5.7	WFS_CMD_DEP_SUPPLY_REPLENISH	26
	5.8	WFS_CMD_DEP_POWER_SAVE_CONTROL	27
	5.9	WFS_CMD_DEP_SYNCHRONIZE_COMMAND	28
6.		Events	29
	6.1	WFS_SRVE_DEP_ENVTAKEN	29
	6.2	WFS_EXEE_DEP_ENVDEPOSITED	30
	6.3	WFS_EXEE_DEP_DEPOSITERROR	31
	6.4	WFS_USRE_DEP_DEPTHRESHOLD	32
	6.5	WFS_USRE_DEP_TONERTHRESHOLD	33
	6.6	WFS_USRE_DEP_ENVTHRESHOLD	34
	6.7	WFS_SRVE_DEP_CONTINSERTED	35
	6.8	WFS_SRVE_DEP_CONTREMOVED	36
	6.9	WFS_SRVE_DEP_ENVINSERTED	37
	6.10	0 WFS_SRVE_DEP_MEDIADETECTED	38
	6.1	1 WFS_EXEE_DEP_INSERTDEPOSIT	39
	6.12	2 WFS_SRVE_DEP_DEVICEPOSITION	40
	6.13	3 WFS_SRVE_DEP_POWER_SAVE_CHANGE	41
7.		C - Header file	42

# **European Foreword**

This CEN Workshop Agreement has been developed in accordance with the CEN-CENELEC Guide 29 "CEN/CENELEC Workshop Agreements – The way to rapid consensus" and with the relevant provisions of CEN/CENELEC Internal Regulations – Part 2. It was approved by a Workshop of representatives of interested parties on 2022-11-08, the constitution of which was supported by CEN following several public calls for participation, the first of which was made on 1998-06-24. However, this CEN Workshop Agreement does not necessarily include all relevant stakeholders.

The final text of this CEN Workshop Agreement was provided to CEN for publication on 2022-11-18.

The following organizations and individuals developed and approved this CEN Workshop Agreement:

- AURIGA SPA
- CIMA SPA
- DIEBOLD NIXDORF SYSTEMS GMBH
- FIS BANKING SOLUTIONS UK LTD (OTS)
- FUJITSU TECHNOLOGY SOLUTIONS
- GLORY LTD
- GRG BANKING EQUIPMENT HK CO LTD
- HITACHI CHANNEL SOLUTIONS CORP
- HYOSUNG TNS INC
- JIANGSU GUOGUANG ELECTRONIC INFORMATION TECHNOLOGY
- KAL
- KEBA HANDOVER AUTOMATION GMBH
- NCR FSG
- NEXUS SOFTWARE
- OBERTHUR CASH PROTECTION
- OKI ELECTRIC INDUSTRY SHENZHEN
- SALZBURGER BANKEN SOFTWARE
- SECURE INNOVATION
- SIGMA SPA

It is possible that some elements of this CEN/CWA may be subject to patent rights. The CEN-CENELEC policy on patent rights is set out in CEN-CENELEC Guide 8 "Guidelines for Implementation of the Common IPR Policy on Patents (and other statutory intellectual property rights based on inventions)". CEN shall not be held responsible for identifying any or all such patent rights.

The Workshop participants have made every effort to ensure the reliability and accuracy of the technical and non-technical content of CWA 16926-8, but this does not guarantee, either explicitly or implicitly, its correctness. Users of CWA 16926-8 should be aware that neither the Workshop participants, nor CEN can be held liable for damages

or losses of any kind whatsoever which may arise from its application. Users of CWA 16926-8 do so on their own responsibility and at their own risk.

The CWA is published as a multi-part document, consisting of:

Part 1: Application Programming Interface (API) - Service Provider Interface (SPI) - Programmer's Reference

Part 2: Service Classes Definition - Programmer's Reference

Part 3: Printer and Scanning Device Class Interface - Programmer's Reference

Part 4: Identification Card Device Class Interface - Programmer's Reference

Part 5: Cash Dispenser Device Class Interface - Programmer's Reference

Part 6: PIN Keypad Device Class Interface - Programmer's Reference

Part 7: Check Reader/Scanner Device Class Interface - Programmer's Reference

Part 8: Depository Device Class Interface - Programmer's Reference

Part 9: Text Terminal Unit Device Class Interface - Programmer's Reference

Part 10: Sensors and Indicators Unit Device Class Interface - Programmer's Reference

Part 11: Vendor Dependent Mode Device Class Interface - Programmer's Reference

Part 12: Camera Device Class Interface - Programmer's Reference

Part 13: Alarm Device Class Interface - Programmer's Reference

Part 14: Card Embossing Unit Device Class Interface - Programmer's Reference

Part 15: Cash-In Module Device Class Interface - Programmer's Reference

Part 16: Card Dispenser Device Class Interface - Programmer's Reference

Part 17: Barcode Reader Device Class Interface - Programmer's Reference

Part 18: Item Processing Module Device Class Interface - Programmer's Reference

Part 19: Biometrics Device Class Interface - Programmer's Reference

Parts 20 - 28: Reserved for future use.

Parts 29 through 47 constitute an optional addendum to this CWA. They define the integration between the SNMP standard and the set of status and statistical information exported by the Service Providers.

Part 29: XFS MIB Architecture and SNMP Extensions - Programmer's Reference

Part 30: XFS MIB Device Specific Definitions - Printer Device Class

Part 31: XFS MIB Device Specific Definitions - Identification Card Device Class

Part 32: XFS MIB Device Specific Definitions - Cash Dispenser Device Class

Part 33: XFS MIB Device Specific Definitions - PIN Keypad Device Class

Part 34: XFS MIB Device Specific Definitions - Check Reader/Scanner Device Class

Part 35: XFS MIB Device Specific Definitions - Depository Device Class

Part 36: XFS MIB Device Specific Definitions - Text Terminal Unit Device Class

Part 37: XFS MIB Device Specific Definitions - Sensors and Indicators Unit Device Class

Part 38: XFS MIB Device Specific Definitions - Camera Device Class

Part 39: XFS MIB Device Specific Definitions - Alarm Device Class

Part 40: XFS MIB Device Specific Definitions - Card Embossing Unit Class

Part 41: XFS MIB Device Specific Definitions - Cash-In Module Device Class

Part 42: Reserved for future use.

Part 43: XFS MIB Device Specific Definitions - Vendor Dependent Mode Device Class

Part 44: XFS MIB Application Management

Part 45: XFS MIB Device Specific Definitions - Card Dispenser Device Class

- Part 46: XFS MIB Device Specific Definitions Barcode Reader Device Class
- Part 47: XFS MIB Device Specific Definitions Item Processing Module Device Class
- Part 48: XFS MIB Device Specific Definitions Biometrics Device Class
- Parts 49 60 are reserved for future use.
- Part 61: Application Programming Interface (API) Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Service Provider Interface (SPI) Programmer's Reference
- Part 62: Printer and Scanning Device Class Interface Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Programmer's Reference
- Part 63: Identification Card Device Class Interface Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Programmer's Reference
- Part 64: Cash Dispenser Device Class Interface Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Programmer's Reference
- Part 65: PIN Keypad Device Class Interface Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Programmer's Reference
- Part 66: Check Reader/Scanner Device Class Interface Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Programmer's Reference
- Part 67: Depository Device Class Interface Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Programmer's Reference
- Part 68: Text Terminal Unit Device Class Interface Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Programmer's Reference
- Part 69: Sensors and Indicators Unit Device Class Interface Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Programmer's Reference
- Part 70: Vendor Dependent Mode Device Class Interface Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Programmer's Reference
- Part 71: Camera Device Class Interface Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Programmer's Reference SIST CWA 16926-67:2023
- Part 72: Alarm Device Class Interface Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Programmer's Reference
- Part 73: Card Embossing Unit Device Class Interface Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Programmer's Reference
- Part 74: Cash-In Module Device Class Interface Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Programmer's Reference
- Part 75: Card Dispenser Device Class Interface Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Programmer's Reference
- Part 76: Barcode Reader Device Class Interface Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Programmer's Reference
- Part 77: Item Processing Module Device Class Interface Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Programmer's Reference
- Part 78: Biometric Device Class Interface Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) Programmer's Reference
- In addition to these Programmer's Reference specifications, the reader of this CWA is also referred to a complementary document, called Release Notes. The Release Notes contain clarifications and explanations on the CWA specifications, which are not requiring functional changes. The current version of the Release Notes is available online from: <a href="https://www.cencenelec.eu/areas-of-work/cen-sectors/digital-society-cen/cwa-download-area/">https://www.cencenelec.eu/areas-of-work/cen-sectors/digital-society-cen/cwa-download-area/</a>.
- The information in this document represents the Workshop's current views on the issues discussed as of the date of publication. It is provided for informational purposes only and is subject to change without notice. CEN makes no warranty, express or implied, with respect to this document.

### Revision History:

3.00	October 18, 2000	Initial Release.
3.10	November 29, 2007	For a description of changes from version 3.00 to version 3.10 see the DEP 3.10 Migration document.
3.20	March 2, 2011	For a description of changes from version 3.10 to version 3.20 see the DEP 3.20 Migration document.
3.30	March 19, 2015	For a description of changes from version 3.20 to version 3.30 see the DEP 3.30 Migration document.
3.40	December 06, 2019	For a description of changes from version 3.30 to version 3.40 see the DEP 3.40 Migration document.
3.50	November 18, 2022	For a description of changes from version 3.40 to version 3.50 see the DEP 3.50 Migration document.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST CWA 16926-67:2023</u> https://standards.iteh.ai/catalog/standards/sist/687a4b9f-d8cf-4285-a433-48766629fb0f/sist cwa-16926-67-2023

### 1. Introduction

## 1.1 Background to Release 3.50

The CEN/XFS Workshop aims to promote a clear and unambiguous specification defining a multi-vendor software interface to financial peripheral devices. The XFS (eXtensions for Financial Services) specifications are developed within the CEN (European Committee for Standardization/Information Society Standardization System) Workshop environment. CEN Workshops aim to arrive at a European consensus on an issue that can be published as a CEN Workshop Agreement (CWA).

The CEN/XFS Workshop encourages the participation of both banks and vendors in the deliberations required to create an industry standard. The CEN/XFS Workshop achieves its goals by focused sub-groups working electronically and meeting quarterly.

Release 3.50 of the XFS specification is based on a C API and is delivered with the continued promise for the protection of technical investment for existing applications. This release of the specification extends the functionality and capabilities of the existing devices covered by the specification:

- Addition of E2E security
- PIN Password Entry

## 1.2 XFS Service-Specific Programming

The service classes are defined by their service-specific commands and the associated data structures, error codes, messages, etc. These commands are used to request functions that are specific to one or more classes of Service Providers, but not all of them, and therefore are not included in the common API for basic or administration functions.

When a service-specific command is common among two or more classes of Service Providers, the syntax of the command is as similar as possible across all services, since a major objective of XFS is to standardize function codes and structures for the broadest variety of services. For example, using the **WFSExecute** function, the commands to read data from various services are as similar as possible to each other in their syntax and data structures.

In general, the specific command set for a service class is defined as a superset of the specific capabilities likely to be provided by the developers of the services of that class; thus any particular device will normally support only a subset of the defined command set.

There are three cases in which a Service Provider may receive a service-specific command that it does not support:

The requested capability is defined for the class of Service Providers by the XFS specification, the particular vendor implementation of that service does not support it, and the unsupported capability is *not* considered to be fundamental to the service. In this case, the Service Provider returns a successful completion, but does no operation. An example would be a request from an application to turn on a control indicator on a passbook printer; the Service Provider recognizes the command, but since the passbook printer it is managing does not include that indicator, the Service Provider does no operation and returns a successful completion to the application.

The requested capability is defined for the class of Service Providers by the XFS specification, the particular vendor implementation of that service does not support it, and the unsupported capability *is* considered to be fundamental to the service. In this case, a WFS\_ERR\_UNSUPP\_COMMAND error for Execute commands or WFS\_ERR\_UNSUPP\_CATEGORY error for Info commands is returned to the calling application. An example would be a request from an application to a cash dispenser to retract items where the dispenser hardware does not have that capability; the Service Provider recognizes the command but, since the cash dispenser it is managing is unable to fulfil the request, returns this error.

The requested capability is *not* defined for the class of Service Providers by the XFS specification. In this case, a WFS\_ERR\_INVALID\_COMMAND error for Execute commands or WFS\_ERR\_INVALID\_CATEGORY error for Info commands is returned to the calling application.

This design allows implementation of applications that can be used with a range of services that provide differing subsets of the functionalities that are defined for their service class. Applications may use the **WFSGetInfo** and **WFSAsyncGetInfo** commands to inquire about the capabilities of the service they are about to use, and modify their behavior accordingly, or they may use functions and then deal with error returns to make decisions as to how to use the service.

# 2. Depository Unit

This specification describes the functionality of the services provided by the Depository (DEP) services under XFS, by defining the service-specific commands that can be issued, using the WFSGetInfo, WFSAsyncGetInfo, WFSExecute and WFSAsyncExecute functions.

A Depository is used for the acceptance and deposit of media into the device or terminal. There are two main types of depository: an envelope depository for the deposit of media in envelopes and a night safe depository for the deposit of bags containing bulk media.

An envelope depository accepts media, prints on the media and deposits the media into a holding container or bin. Some envelope depositories offer the capability to dispense an envelope to the customer at the start of a transaction. The customer takes this envelope, fills in the deposit media, possibly inscribes it and puts it into the deposit slot. The envelope is then accepted, printed and transported into a deposit container.

The envelope dispense mechanism may be part of the envelope depository device mechanism with the same entry/exit slot or it may be a separate mechanism with separate entry/exit slot.

Envelopes dispensed and not taken by the customer can be retracted back into the device. When the dispenser is a separate mechanism the envelope is retracted back into the dispenser container. When the dispenser is a common mechanism the envelope is retracted into the depository container.

A night safe depository normally only logs the deposit of a bag and does not print on the media.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST CWA 16926-67:2023</u> https://standards.iteh.ai/catalog/standards/sist/687a4b9f-d8cf-4285-a433-48766629fb0f/sist cwa-16926-67-2023

# 3. References

1. XFS Application Programming Interface (API)/Service Provider Interface (SPI), Programmer's Reference Revision 3.4050

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST CWA 16926-67:2023</u> https://standards.iteh.ai/catalog/standards/sist/687a4b9f-d8cf-4285-a433-48766629fb0f/sist

# 4. Info Commands

#### 4.1 WFS\_INF\_DEP\_STATUS

**Description** This command reports the full range of information available, including the information that is

provided by the Service Provider.

Input Param None.

Output Param LPWFSDEPSTATUS lpStatus;

```
typedef struct _wfs_dep_status
WORD
                      fwDevice;
WORD
                      fwDepContainer;
WORD
                      fwDepTransport;
WORD
                      fwEnvSupply;
WORD
                      fwEnvDispenser;
WORD
                      fwPrinter;
WORD
                      fwToner;
WORD
                      fwShutter;
WORD
                      wNumOfDeposits;
LPSTR
                      lpszExtra;
DWORD
                      dwGuidLights[WFS DEP GUIDLIGHTS SIZE];
WORD
                      fwDepositLocation;
WORD
                      wDevicePosition;
                      usPowerSaveRecoveryTime;
USHORT
                      wAntiFraudModule;
WORD
} WFSDEPSTATUS, *LPWFSDEPSTATUS;
```

*fwDevice* 

Specifies the state of the Depository device as one of the following flags:

Value	Meaning
WFS_DEP_DEVONLINE SIST CWA 16926-67:20	The device is online (i.e. powered on and operable).
ds WFS_DEP_DEVOFFLINE s/sist/687a4b9f-c	The device is off-line (e.g. the operator has taken the device offline by turning a switch).
WFS_DEP_DEVPOWEROFF	The device is powered off or physically not connected.
WFS_DEP_DEVNODEVICE	There is no device intended to be there; e.g. this type of self service machine does not contain such a device or it is internally not configured.
WFS_DEP_DEVHWERROR	The device is inoperable due to a hardware error. The device is present but a hardware fault prevents it from being used.
WFS_DEP_DEVUSERERROR	The device is present but a person is preventing proper operation. The application should suspend the device operation or remove the device from service until the Service Provider generates a device state change event indicating the condition of the device has changed, i.e. the error is removed or a permanent error condition has occurred.
WFS_DEP_DEVBUSY	The device is busy and not able to process an Execute command at this time.
WFS_DEP_DEVFRAUDATTEMPT	The device is present but is inoperable because it has detected a fraud attempt.
WFS_DEP_DEVPOTENTIALFRAUD	The device has detected a potential fraud attempt and is capable of remaining in service. In this case the application should make the decision as to whether to take the device offline.

#### fwDepContainer

Specifies the state of the deposit container that contains the deposited envelopes or bags as one of the following flags:

Value	Meaning
WFS_DEP_DEPOK	The deposit container is in a good state.
WFS_DEP_DEPHIGH	The deposit container is almost full
	(threshold).
WFS_DEP_DEPFULL	The deposit container is full.
WFS_DEP_DEPINOP	The deposit container is inoperable.
WFS_DEP_DEPMISSING	The deposit container is missing.
WFS_DEP_DEPUNKNOWN	Due to a hardware error or other condition,
	the state of the deposit container cannot be
	determined.
WFS_DEP_DEPNOTSUPP	The physical device is not able to determine
	the status of the deposit container.

#### fwDepTransport

Specifies the state of the deposit transport mechanism that transports the envelope into the deposit container. Specified as one of the following flags:

Value	Meaning
WFS_DEP_DEPOK	The deposit transport is in a good state.
WFS_DEP_DEPINOP	The deposit transport is inoperative due to a
	hardware failure or media jam.
WFS_DEP_DEPUNKNOWN	Due to a hardware error or other condition,
	the state of the deposit transport cannot be
	determined.
WFS_DEP_DEPNOTSUPP /-	The physical device has no deposit transport.

#### fwEnvSupply

Specifies the state of the envelope supply unit as one of the following flags:

Value	Meaning
WFS_DEP_ENVOKIST_CWA_16926-67-20	The envelope supply unit is in a good state
	(and locked).
WFS_DEP_ENVLOW	The envelope supply unit is present but low.
WFS DEP ENVEMPTY 2-16926-67-2023	The envelope supply unit is present but
	empty. No envelopes can be dispensed.
WFS DEP ENVINOP	The envelope supply unit is in an inoperable
	state. No envelopes can be dispensed.
WFS_DEP_ENVMISSING	The envelope supply unit is missing.
WFS DEP ENVNOTSUPP	The physical device has no envelope supply.
WFS_DEP_ENVUNLOCKED	The envelope supply unit is unlocked.
WFS_DEP_ENVUNKNOWN	Due to a hardware error or other condition,
	the state of the envelope supply cannot be
	determined.

#### *fwEnvDispenser*

Specifies the state of the envelope dispenser. Specified as one of the following flags:

Value	Meaning
WFS_DEP_ENVOK	The envelope dispenser is present and in a
	good state.
WFS_DEP_ENVINOP	The envelope dispenser is present but in an
	inoperable state. No envelopes can be
	dispensed.
WFS_DEP_ENVUNKNOWN	Due to a hardware error or other condition,
	the state of the envelope dispenser cannot be
	determined.
WFS_DEP_ENVNOTSUPP	The physical device has no envelope
	dispenser.

#### fwPrinter

Specifies the state of the printer. Specified as one of the following flags: