



SLOVENSKI STANDARD SIST CWA 16926-75:2023

01-april-2023

Specifikacija vmesnika razširitev za finančne storitve (XFS), izdaja 3.50 - 75. del: Vmesnik razreda naprave za izdajo kartic - Referenca za programerje - Prehod z različice 3.40 (CWA 16926:2020) na različico 3.50 (ta CWA)

Extensions for Financial Services (XFS) interface specification Release 3.50 - Part 75: Card Dispenser Device Class Interface - Programmer's Reference - Migration from Version 3.40 (CWA 16926:2020) to Version 3.50 (this CWA)

(standards.iteh.ai)

[SIST CWA 16926-75:2023](https://standards.iteh.ai/catalog/standards/sist/904148b3-99a6-468e-af3e-ad2d63fcc99f/sist-cwa-16926-75-2023)

<https://standards.iteh.ai/catalog/standards/sist/904148b3-99a6-468e-af3e-ad2d63fcc99f/sist-cwa-16926-75-2023>

Ta slovenski standard je istoveten z: CWA 16926-75:2023

ICS:

35.200	Vmesniška in povezovalna oprema	Interface and interconnection equipment
35.240.15	Identifikacijske kartice. Čipne kartice. Biometrija	Identification cards. Chip cards. Biometrics
35.240.40	Uporabniške rešitve IT v bančništvu	IT applications in banking

SIST CWA 16926-75:2023

en,fr,de

CEN**CWA 16926-75****WORKSHOP**

January 2023

AGREEMENT

ICS 35.240.40; 35.240.15; 35.200

English version

**Extensions for Financial Services (XFS) interface
specification Release 3.50 - Part 75: Card Dispenser Device
Class Interface - Programmer's Reference - Migration from
Version 3.40 (CWA 16926:2020) to Version 3.50 (this
CWA)**

This CEN Workshop Agreement has been drafted and approved by a Workshop of representatives of interested parties, the constitution of which is indicated in the foreword of this Workshop Agreement.

The formal process followed by the Workshop in the development of this Workshop Agreement has been endorsed by the National Members of CEN but neither the National Members of CEN nor the CEN-CENELEC Management Centre can be held accountable for the technical content of this CEN Workshop Agreement or possible conflicts with standards or legislation.

This CEN Workshop Agreement can in no way be held as being an official standard developed by CEN and its Members.

This CEN Workshop Agreement is publicly available as a reference document from the CEN Members National Standard Bodies.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

© 2023 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.

Ref. No.:CWA 16926-75:2023 E

Table of Contents

European Foreword	3
1. Introduction	7
1.1 Background to Release 3.50	7
1.2 XFS Service-Specific Programming	7
2. Card Dispensers	9
3. References	10
4. Info Commands	11
4.1 WFS_INF_CRD_STATUS	11
4.2 WFS_INF_CRD_CAPABILITIES	14
4.3 WFS_INF_CRD_CARD_UNIT_INFO	16
5. Execute Commands	18
5.1 WFS_CMD_CRD_DISPENSE_CARD	18
5.2 WFS_CMD_CRD_EJECT_CARD	19
5.3 WFS_CMD_CRD_RETAIN_CARD	20
5.4 WFS_CMD_CRD_RESET	21
5.5 WFS_CMD_CRD_SET_CARD_UNIT_INFO	22
5.6 WFS_CMD_CRD_SET_GUIDANCE_LIGHT	23
5.7 WFS_CMD_CRD_POWER_SAVE_CONTROL	25
5.8 WFS_CMD_CRD_SYNCHRONIZE_COMMAND	26
6. Events	27
6.1 WFS_SRVE_CRD_MEDIAREMOVED.....	27
6.2 WFS_SRVE_CRD_MEDIADETECTED	28
6.3 WFS_USRE_CRD_CARDUNITTHRESHOLD	29
6.4 WFS_SRVE_CRD_CARDUNITINFOCHANGED.....	30
6.5 WFS_EXEE_CRD_CARDUNITERROR.....	31
6.6 WFS_SRVE_CRD_DEVICEPOSITION.....	32
6.7 WFS_SRVE_CRD_POWER_SAVE_CHANGE	33
7. C-Header File	34

European Foreword

This CEN Workshop Agreement has been developed in accordance with the CEN-CENELEC Guide 29 “CEN/CENELEC Workshop Agreements – The way to rapid consensus” and with the relevant provisions of CEN/CENELEC Internal Regulations - Part 2. It was approved by a Workshop of representatives of interested parties on 2022-11-08, the constitution of which was supported by CEN following several public calls for participation, the first of which was made on 1998-06-24. However, this CEN Workshop Agreement does not necessarily include all relevant stakeholders.

The final text of this CEN Workshop Agreement was provided to CEN for publication on 2022-11-18. The following organizations and individuals developed and approved this CEN Workshop Agreement:

- AURIGA SPA
- CIMA SPA
- DIEBOLD NIXDORF SYSTEMS GMBH
- FIS BANKING SOLUTIONS UK LTD (OTS)
- FUJITSU TECHNOLOGY SOLUTIONS
- GLORY LTD
- GRG BANKING EQUIPMENT HK CO LTD
- HITACHI CHANNEL SOLUTIONS CORP
- HYOSUNG TNS INC
- JIANGSU GUO GUANG ELECTRONIC INFORMATION TECHNOLOGY
- KAL
- KEBA HANDOVER AUTOMATION GMBH
- NCR FSG
- NEXUS SOFTWARE
- OBERTHUR CASH PROTECTION
- OKI ELECTRIC INDUSTRY SHENZHEN
- SALZBURGER BANKEN SOFTWARE
- SECURE INNOVATION
- SIGMA SPA

It is possible that some elements of this CEN/CWA may be subject to patent rights. The CEN-CENELEC policy on patent rights is set out in CEN-CENELEC Guide 8 “Guidelines for Implementation of the Common IPR Policy on Patents (and other statutory intellectual property rights based on inventions)”. CEN shall not be held responsible for identifying any or all such patent rights.

The Workshop participants have made every effort to ensure the reliability and accuracy of the technical and non-technical content of CWA 16926-16, but this does not guarantee, either explicitly or implicitly, its correctness. Users of CWA 16926-16 should be aware that neither the Workshop participants, nor CEN can be held liable for damages or losses of any kind whatsoever which may arise from its application. Users of CWA 16926-16 do so on their own responsibility and at their own risk.

The CWA is published as a multi-part document, consisting of:

CWA 16926-75:2023 (E)

- Part 1: Application Programming Interface (API) - Service Provider Interface (SPI) - Programmer's Reference
- Part 2: Service Classes Definition - Programmer's Reference
- Part 3: Printer and Scanning Device Class Interface - Programmer's Reference
- Part 4: Identification Card Device Class Interface - Programmer's Reference
- Part 5: Cash Dispenser Device Class Interface - Programmer's Reference
- Part 6: PIN Keypad Device Class Interface - Programmer's Reference
- Part 7: Check Reader/Scanner Device Class Interface - Programmer's Reference
- Part 8: Depository Device Class Interface - Programmer's Reference
- Part 9: Text Terminal Unit Device Class Interface - Programmer's Reference
- Part 10: Sensors and Indicators Unit Device Class Interface - Programmer's Reference
- Part 11: Vendor Dependent Mode Device Class Interface - Programmer's Reference
- Part 12: Camera Device Class Interface - Programmer's Reference
- Part 13: Alarm Device Class Interface - Programmer's Reference
- Part 14: Card Embossing Unit Device Class Interface - Programmer's Reference
- Part 15: Cash-In Module Device Class Interface - Programmer's Reference
- Part 16: Card Dispenser Device Class Interface - Programmer's Reference
- Part 17: Barcode Reader Device Class Interface - Programmer's Reference
- Part 18: Item Processing Module Device Class Interface - Programmer's Reference
- Part 19: Biometrics Device Class Interface - Programmer's Reference
- Parts 20 - 28: Reserved for future use.
- Parts 29 through 47 constitute an optional addendum to this CWA. They define the integration between the SNMP standard and the set of status and statistical information exported by the Service Providers.
- Part 29: XFS MIB Architecture and SNMP Extensions - Programmer's Reference
- Part 30: XFS MIB Device Specific Definitions - Printer Device Class
- Part 31: XFS MIB Device Specific Definitions - Identification Card Device Class
- Part 32: XFS MIB Device Specific Definitions - Cash Dispenser Device Class
- Part 33: XFS MIB Device Specific Definitions - PIN Keypad Device Class
- Part 34: XFS MIB Device Specific Definitions - Check Reader/Scanner Device Class
- Part 35: XFS MIB Device Specific Definitions - Depository Device Class
- Part 36: XFS MIB Device Specific Definitions - Text Terminal Unit Device Class
- Part 37: XFS MIB Device Specific Definitions - Sensors and Indicators Unit Device Class
- Part 38: XFS MIB Device Specific Definitions - Camera Device Class
- Part 39: XFS MIB Device Specific Definitions - Alarm Device Class
- Part 40: XFS MIB Device Specific Definitions - Card Embossing Unit Class
- Part 41: XFS MIB Device Specific Definitions - Cash-In Module Device Class
- Part 42: Reserved for future use.
- Part 43: XFS MIB Device Specific Definitions - Vendor Dependent Mode Device Class
- Part 44: XFS MIB Application Management
- Part 45: XFS MIB Device Specific Definitions - Card Dispenser Device Class
- Part 46: XFS MIB Device Specific Definitions - Barcode Reader Device Class
- Part 47: XFS MIB Device Specific Definitions - Item Processing Module Device Class

Part 48: XFS MIB Device Specific Definitions - Biometrics Device Class

Parts 49 - 60 are reserved for future use.

Part 61: Application Programming Interface (API) - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Service Provider Interface (SPI) - Programmer's Reference

Part 62: Printer and Scanning Device Class Interface - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Programmer's Reference

Part 63: Identification Card Device Class Interface - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Programmer's Reference

Part 64: Cash Dispenser Device Class Interface - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Programmer's Reference

Part 65: PIN Keypad Device Class Interface - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Programmer's Reference

Part 66: Check Reader/Scanner Device Class Interface - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Programmer's Reference

Part 67: Depository Device Class Interface - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Programmer's Reference

Part 68: Text Terminal Unit Device Class Interface - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Programmer's Reference

Part 69: Sensors and Indicators Unit Device Class Interface - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Programmer's Reference

Part 70: Vendor Dependent Mode Device Class Interface - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Programmer's Reference

Part 71: Camera Device Class Interface - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Programmer's Reference

Part 72: Alarm Device Class Interface - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Programmer's Reference

Part 73: Card Embossing Unit Device Class Interface - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Programmer's Reference

Part 74: Cash-In Module Device Class Interface - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Programmer's Reference

Part 75: Card Dispenser Device Class Interface - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Programmer's Reference

Part 76: Barcode Reader Device Class Interface - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Programmer's Reference

Part 77: Item Processing Module Device Class Interface - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Programmer's Reference

Part 78: Biometric Device Class Interface - Migration from Version 3.40 (CWA 16296:2020) to Version 3.50 (this CWA) - Programmer's Reference

In addition to these Programmer's Reference specifications, the reader of this CWA is also referred to a complementary document, called Release Notes. The Release Notes contain clarifications and explanations on the CWA specifications, which are not requiring functional changes. The current version of the Release Notes is available online from: <https://www.cenelec.eu/areas-of-work/cen-sectors/digital-society-cen/cwa-download-area/>.

The information in this document represents the Workshop's current views on the issues discussed as of the date of publication. It is provided for informational purposes only and is subject to change without notice. CEN makes no warranty, express or implied, with respect to this document.

Revision History:

CWA 16926-75:2023 (E)

3.10	November 29, 2007	Initial Release.
3.20	March 2, 2011	For a description of changes from version 3.10 to version 3.20 see the CRD 3.20 Migration document.
3.30	March 19, 2015	For a description of changes from version 3.20 to version 3.30 see the CRD 3.30 Migration document.
3.40	December 06, 2019	For a description of changes from version 3.30 to version 3.40 see the CRD 3.40 Migration document.
3.50	November 18, 2022	For a description of changes from version 3.40 to version 3.50 see the CRD 3.50 Migration document.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST CWA 16926-75:2023

<https://standards.iteh.ai/catalog/standards/sist/904148b3-99a6-468e-af3e-ad2d63fcc99f/sist-cwa-16926-75-2023>

1. Introduction

1.1 Background to Release 3.50

The CEN/XFS Workshop aims to promote a clear and unambiguous specification defining a multi-vendor software interface to financial peripheral devices. The XFS (eXtensions for Financial Services) specifications are developed within the CEN (European Committee for Standardization/Information Society Standardization System) Workshop environment. CEN Workshops aim to arrive at a European consensus on an issue that can be published as a CEN Workshop Agreement (CWA).

The CEN/XFS Workshop encourages the participation of both banks and vendors in the deliberations required to create an industry standard. The CEN/XFS Workshop achieves its goals by focused sub-groups working electronically and meeting quarterly.

Release 3.50 of the XFS specification is based on a C API and is delivered with the continued promise for the protection of technical investment for existing applications. This release of the specification extends the functionality and capabilities of the existing devices covered by the specification:

- Addition of E2E security
- PIN Password Entry

1.2 XFS Service-Specific Programming

The service classes are defined by their service-specific commands and the associated data structures, error codes, messages, etc. These commands are used to request functions that are specific to one or more classes of Service Providers, but not all of them, and therefore are not included in the common API for basic or administration functions.

When a service-specific command is common among two or more classes of Service Providers, the syntax of the command is as similar as possible across all services, since a major objective of XFS is to standardize function codes and structures for the broadest variety of services. For example, using the **WFSExecute** function, the commands to read data from various services are as similar as possible to each other in their syntax and data structures.

In general, the specific command set for a service class is defined as a superset of the specific capabilities likely to be provided by the developers of the services of that class; thus any particular device will normally support only a subset of the defined command set.

There are three cases in which a Service Provider may receive a service-specific command that it does not support:

The requested capability is defined for the class of Service Providers by the XFS specification, the particular vendor implementation of that service does not support it, and the unsupported capability is *not* considered to be fundamental to the service. In this case, the Service Provider returns a successful completion, but does no operation. An example would be a request from an application to turn on a control indicator on a passbook printer; the Service Provider recognizes the command, but since the passbook printer it is managing does not include that indicator, the Service Provider does no operation and returns a successful completion to the application.

The requested capability is defined for the class of Service Providers by the XFS specification, the particular vendor implementation of that service does not support it, and the unsupported capability *is* considered to be fundamental to the service. In this case, a `WFS_ERR_UNSUPP_COMMAND` error for Execute commands or `WFS_ERR_UNSUPP_CATEGORY` error for Info commands is returned to the calling application. An example would be a request from an application to a cash dispenser to retract items where the dispenser hardware does not have that capability; the Service Provider recognizes the command but, since the cash dispenser it is managing is unable to fulfil the request, returns this error.

The requested capability is *not* defined for the class of Service Providers by the XFS specification. In this case, a `WFS_ERR_INVALID_COMMAND` error for Execute commands or `WFS_ERR_INVALID_CATEGORY` error for Info commands is returned to the calling application.

This design allows implementation of applications that can be used with a range of services that provide differing subsets of the functionalities that are defined for their service class. Applications may use the **WFSGetInfo** and **WFSAsyncGetInfo** commands to inquire about the capabilities of the service they are about to use, and modify their behavior accordingly, or they may use functions and then deal with error returns to make decisions as to how

CWA 16926-75:2023 (E)

to use the service.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST CWA 16926-75:2023

<https://standards.iteh.ai/catalog/standards/sist/904148b3-99a6-468e-af3e-ad2d63fcc99f/sist-cwa-16926-75-2023>

2. Card Dispensers

This specification describes the functionality of the services provided by the Card Dispenser (CRD) device class under XFS, by defining the service-specific commands that can be issued, using the **WFSGetInfo**, **WFSAsyncGetInfo**, **WFSExecute** and **WFSAsyncExecute** functions.

A Card Dispenser is used to dispense a single card to a consumer from one or more bins. Most card dispensers also have the ability to retain a card to a bin.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST CWA 16926-75:2023](https://standards.iteh.ai/catalog/standards/sist/904148b3-99a6-468e-af3e-ad2d63fcc99f/sist-cwa-16926-75-2023)

<https://standards.iteh.ai/catalog/standards/sist/904148b3-99a6-468e-af3e-ad2d63fcc99f/sist-cwa-16926-75-2023>

CWA 16926-75:2023 (E)

3. References

1. XFS Application Programming Interface (API)/Service Provider Interface (SPI), Programmer's Reference Revision 3.4050

2. XFS Identification Card Device Class Interface - Programmer's Reference, Revision 3.4050

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST CWA 16926-75:2023](https://standards.iteh.ai/catalog/standards/sist/904148b3-99a6-468e-af3e-ad2d63fcc99f/sist-cwa-16926-75-2023)

<https://standards.iteh.ai/catalog/standards/sist/904148b3-99a6-468e-af3e-ad2d63fcc99f/sist-cwa-16926-75-2023>

4. Info Commands

4.1 WFS_INF_CRD_STATUS

Description This command is used to request status information for the device.

Input Param None.

Output Param LPWFSCRDSTATUS lpStatus;

```
typedef struct _wfs_crd_status
{
    WORD                fwDevice;
    WORD                fwDispenser;
    WORD                fwTransport;
    WORD                fwMedia;
    WORD                fwShutter;
    LPSTR               lpSzExtra;
    DWORD               dwGuidLights[WFS_CRD_GUIDLIGHTS_SIZE];
    WORD                wDevicePosition;
    USHORT              usPowerSaveRecoveryTime;
    WORD                wAntiFraudModule;
} WFS_CRD_STATUS, *LPWFSCRDSTATUS;
```

fwDevice

Specifies the state of the card dispensing device as one of the following flags:

Value	Meaning
WFS_CRD_DEVONLINE	The device is online (i.e. powered on and operable).
WFS_CRD_DEVOFFLINE	The device is offline (e.g. the operator has taken the device offline by turning a switch).
WFS_CRD_DEVPOWEROFF	The device is powered off or physically not connected.
WFS_CRD_DEVNODEVICE	There is no device intended to be there; e.g. this type of self service machine does not contain such a device or it is internally not configured.
WFS_CRD_DEVHWERROR	The device is inoperable due to a hardware error.
WFS_CRD_DEVUSERERROR	The device is present but a person is preventing proper device operation.
WFS_CRD_DEVBUSY	The device is busy and unable to process an execute command at this time.
WFS_CRD_DEVFRAUDATTEMPT	The device is present but is inoperable because it has detected a fraud attempt.
WFS_CRD_DEVPOTENTIALFRAUD	The device has detected a potential fraud attempt and is capable of remaining in service. In this case the application should make the decision as to whether to take the device offline.

fwDispenser

Specifies the state of the card units including all retain bins as one of the following flags:

Value	Meaning
WFS_CRD_DISPCUOK	All card units present are in a good state.
WFS_CRD_DISPCUSTATE	One or more of the card units is in a low, empty or inoperative condition. Items can still be dispensed from at least one of the card units.
WFS_CRD_DISPCUSTOP	Due to a card unit failure dispensing is impossible. No items can be dispensed because all of the card units are in an empty or inoperative condition.