

---

---

**Electrically propelled mopeds and  
motorcycles — Safety specifications —**

**Part 3:  
Electrical safety**

*Cyclomoteurs et motocycles à propulsion électrique — Spécifications  
de sécurité —*

*Partie 3: Sécurité électrique*

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO 13063-3:2022

<https://standards.iteh.ai/catalog/standards/sist/028596d6-0bce-47d6-9fdc-adff43fc947f/iso-13063-3-2022>



iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO 13063-3:2022

<https://standards.iteh.ai/catalog/standards/sist/028596d6-0bce-47d6-9fdc-adff43fc947f/iso-13063-3-2022>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
<b>FOREWORD</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Abbreviated terms</b> .....	<b>7</b>
<b>5 Voltage classes</b> .....	<b>7</b>
<b>6 General requirements</b> .....	<b>8</b>
6.1 Environmental and operational conditions .....	8
6.2 Marking .....	8
6.2.1 Marking of voltage class B electric components .....	8
6.2.2 Marking of voltage class B wiring .....	8
<b>7 Requirements for protection against electric shock</b> .....	<b>8</b>
7.1 General requirements .....	8
7.1.1 General requirements for connected sections of a circuit .....	8
7.1.2 General requirements for voltage class B .....	9
7.1.3 Requirements for voltage class A .....	9
7.1.4 Requirements of voltage class A power cables and conduits .....	10
7.2 Basic protection .....	10
7.3 Fault protection and additional measures .....	10
7.3.1 Equipotential bonding .....	10
7.3.2 Isolation resistance .....	11
7.3.3 Provisions for capacitive coupling and capacitive discharge .....	12
7.3.4 Alternative electrical or mechanical measures .....	12
7.3.5 De-energization .....	13
7.3.6 Provision for chassis-connected voltage class B circuit .....	13
7.4 General requirements for protective provisions .....	13
7.4.1 General .....	13
7.4.2 Requirements for insulation of voltage class B .....	13
7.4.3 Requirements of protective barrier and protective enclosures of voltage class B electric components .....	14
7.5 Requirements for connectors .....	14
7.6 Insulation coordination .....	15
7.7 Alternative approach for protection against electric shock .....	15
<b>8 Protection against thermal incidents</b> .....	<b>15</b>
8.1 Overload protection .....	15
8.2 Short-circuit protection .....	15
<b>9 Requirements for vehicle power supply circuit</b> .....	<b>15</b>
<b>10 Owner's guide manual</b> .....	<b>15</b>
<b>11 Test procedures</b> .....	<b>16</b>
11.1 General .....	16
11.2 Continuity test for equipotential bonding .....	16
11.3 Isolation resistance measurements for voltage class B electric circuits .....	16
11.3.1 Preconditioning and conditioning .....	16
11.3.2 Isolation resistance measurements of the balance of electric circuits .....	16
11.3.3 Isolation resistance measurement of the voltage class B electric power sources .....	17
11.3.4 Isolation resistance measurement of entire electric circuits .....	19
11.4 Test for isolation resistance monitoring system .....	19
11.5 Touch current .....	19
11.6 Withstand voltage test .....	20

11.6.1	General.....	20
11.6.2	Preconditioning and conditioning.....	20
11.6.3	Test procedure.....	21
11.6.4	Test criteria.....	21
11.7	Test method of voltage class A wiring.....	21
11.7.1	Test method for the movable part of the voltage class A wiring.....	21
11.7.2	Test method for withstand voltage.....	21
<b>Bibliography.....</b>		<b>23</b>

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

[ISO 13063-3:2022](https://standards.iteh.ai/catalog/standards/sist/028596d6-0bce-47d6-9fdc-adff43fc947f/iso-13063-3-2022)

<https://standards.iteh.ai/catalog/standards/sist/028596d6-0bce-47d6-9fdc-adff43fc947f/iso-13063-3-2022>

## FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 38, *Motorcycles and mopeds*.

This first edition of ISO 13063-3, together with ISO 13063-1 and ISO 13063-2, cancels and replaces ISO 13063:2012, which has been technically revised.

The main changes are as follows:

- extension of protection against electric shock to all electric safety requirements;
- alignment of structure and requirements as possible with ISO 6469-3:2018;
- splitting the document into three documents which consist of the following parts, under the general title *Electrically propelled mopeds and motorcycles — Safety specifications*:
  - *Part 1: On-board rechargeable energy storage system (RESS)*;
  - *Part 2: Vehicle operational safety*;
  - *Part 3: Electrical safety*;
- addition of specific requirements for capacitive discharge;
- new test specification for the isolation resistance monitoring system;
- new requirements and test for touch current; and
- the requirements for conductive connection to an external electric power supply can be covered by ISO 18246.

A list of all parts in the ISO 13063 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).



# Electrically propelled mopeds and motorcycles — Safety specifications —

## Part 3: Electrical safety

### 1 Scope

This document specifies electric safety requirements for protection against electric shock and thermal incidents of electric propulsion systems and conductively connected auxiliary electric systems of electrically propelled mopeds and motorcycles when used in normal conditions. It is applicable to a maximum working voltage of the on-board electrical circuit up to 1 000 V alternating current (a.c.) or 1 500 V direct current (d.c.). This document does not provide comprehensive safety information for manufacturing, maintenance and repair personnel.

NOTE Requirements for conductive connections of electrically propelled mopeds and motorcycles to an external electric power supply are described in ISO 18246.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 20653, *Road vehicles — Degrees of protection (IP-code) — Protection of electrical equipment against foreign objects, water and access*

IEC 60227-1, *Polyvinyl chloride insulated cables of rated voltages up to and including 450/750 V — Part 1: General requirements*

IEC 60245-1, *Rubber insulated cables — Rated voltages up to and including 450/750 V — Part 1: General requirements*

IEC 60990:2016, *Methods of measurement of touch current and protective conductor current*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

#### 3.1

##### **auxiliary electric system**

vehicle system, other than the *propulsion system* (3.46), that operates on electric energy

[SOURCE: ISO 6469-3:2021, 3.1]

3.2

**balance of electric circuit**

remaining section of an electric circuit when all electric power sources that are energized (e.g. *RESS* (3.23) and fuel cell stacks) are disconnected

[SOURCE: ISO 6469-3:2021, 3.2]

3.3

**protective barrier**

part providing protection against *direct contact* (3.9) from any usual direction of access

[SOURCE: IEC 60050-826:2004, 826-12-23, modified — Domain “<electrically>” was removed.]

3.4

**basic insulation**

insulation of *hazardous live parts* (3.35) which provides *basic protection* (3.5)

Note 1 to entry: This concept does not apply to insulation used exclusively for functional purposes.

Note 2 to entry: Where insulation is not provided by solid insulation only, it is complemented with *protective barriers* (3.3) or *protective enclosures* (3.15) to prevent access to *live parts* (3.19) in order to achieve basic protection.

[SOURCE: IEC 60050-581:2008, 581-21-24, modified — “Note 2 to entry was added.”]

3.5

**basic protection**

protection against *electric shock* (3.13) under fault-free conditions.

[SOURCE: IEC 60050-195:2021, 195-06-01, modified — “normal” was replaced by “fault-free”.]

3.6

**conductive part**

part which can carry electric current

[SOURCE: IEC 60050-195:2021, 195-01-06]

3.7

**conductor**

*conductive part* (3.6) intended to carry a specified electric current

[SOURCE: IEC 60050-195:2021, 195-01-07]

3.8

**creepage distance**

shortest distance along the surface of a solid insulating material between two *conductive parts* (3.6)

[SOURCE: IEC 60050-151:2001, 151-15-50]

3.9

**direct contact**

electric contact of persons or animals with *live parts* (3.19)

[SOURCE: IEC 60050-826:2004, 826-12-03]

3.10

**double insulation**

insulation comprising both *basic insulation* (3.4) and *supplementary insulation* (3.25)

[SOURCE: IEC 60050-195:2021, 195-06-08]



**3.11****electric chassis**

*conductive parts* (3.6) of a vehicle that are electrically connected and whose potential is taken as reference

**3.12****electric drive**

combination of traction motor, power electronics and their associated controls for the conversion of electric to mechanical power and vice versa

[SOURCE: ISO 6469-3:2021, 3.13]

**3.13****electric shock**

physiological effect resulting from an electric current passing through a human body or animal body

[SOURCE: IEC 60050-826:2004, 826-12-01]

**3.14****electrically propelled vehicle**

vehicle with one or more *electric drive(s)* (3.12) for vehicle propulsion

[SOURCE: ISO 6469-3:2021, 3.15]

**3.15****protective enclosure**

electrical enclosure surrounding internal parts of equipment to prevent access to *hazardous live parts* (3.35) from any direction

[SOURCE: IEC 60050-195:2021, 195-06-14, modified — Domain “<electrically>” was removed.]

**3.16****exposed conductive part**

*conductive part* (3.6) of equipment which can be touched and which is not normally live, but which can become live when *basic insulation* (3.4) fails

Note 1 to entry: A conductive part of electrical equipment which can become live only through contact with an exposed conductive part which has become live is not considered to be an exposed conductive part itself.

[SOURCE: IEC 60050-442:1998, 442-01-21]

**3.17****isolation resistance monitoring system**

system that periodically or continuously monitors the *isolation resistance* (3.18) between *live parts* (3.19) and the *electric chassis* (3.11)

[SOURCE: ISO 6469-3:2021, 3.24]

**3.18****isolation resistance**

insulation resistance

resistance between *live parts* (3.19) of an electric circuit and the *electric chassis* (3.11) as well as other electric circuits which are insulated from this electric circuit

[SOURCE: ISO 6469-3:2021, 3.23]

### 3.19

#### live part

*conductor* (3.7) or *conductive part* (3.6) intended to be energized in normal use, but by convention not the *electric chassis* (3.11)

[SOURCE: IEC 60050-442:1998, 442-01-40, modified — “including a neutral conductor” and Note were removed, and “combined protective and neutral conductor (PEN)” was replaced by “electric chassis”.]

### 3.20

#### maximum working voltage

highest value of AC voltage (rms) or of DC voltage that can occur under any normal operating conditions according to the manufacturers’ specifications, disregarding transients and ripple

[SOURCE: ISO 6469-3:2021, 3.26]

### 3.21

#### equipotential bonding

provision of electric connections between *conductive parts* (3.6), intended to achieve equipotentiality

[SOURCE: IEC 60050-826:2004, 826-13-19]

### 3.22

#### degree of protection

IP  
protection provided by an enclosure or barriers against access, foreign objects and/or water and verified by standardized test methods in accordance with ISO 20653

[SOURCE: ISO 20653:2013, 3.2, modified — The term “IP” and the phrase “in accordance with ISO 20653” were added.]

### 3.23

#### rechargeable energy storage system

RESS <https://standards.iteh.ai/catalog/standards/sist/028596d6-0bce-47d6-9fdc-adff43fc947f/iso-rechargeable-system-that-stores-energy-for-delivery-of-electric-energy-for-the-electric-drive> (3.12)

EXAMPLE Battery, capacitor, flywheel.

[SOURCE: ISO 6469-3:2021, 3.31]

### 3.24

#### reinforced insulation

insulation of *hazardous live parts* (3.35) which provides protection against *electric shock* (3.13) equivalent to *double insulation* (3.10)

Note 1 to entry: Reinforced insulation may comprise several layers that cannot be tested singly as *basic insulation* (3.4) or *supplementary insulation* (3.25).

[SOURCE: IEC 60050-581:2008, 581-21-27]

### 3.25

#### supplementary insulation

independent insulation applied in addition to *basic insulation* (3.4) for *fault protection* (3.29)

[SOURCE: IEC 60050-195:2021, 195-06-07]

### 3.26

#### voltage class

classification of an electric component or circuit according to its *maximum working voltage* (3.20)

[SOURCE: ISO 6469-3:2021, 3.36]

**3.27****wiring**

system of wires providing electric circuits and including cables and connectors

**3.28****service disconnect**

device for deactivation of the electrical circuit when conducting checks and services of the vehicle, *RESS* (3.23), etc.

**3.29****fault protection**

protection against *electric shock* (3.13) under single-fault conditions

[SOURCE: IEC 60050-195:2021, 195-06-02]

**3.30****functional insulation**

insulation between *conductive parts* (3.6), necessary for the proper functioning of the component

[SOURCE: IEC 60050-195:2021, 195-02-41, modified — "equipment" replaces "component".]

**3.31****touch current**

electric current passing through a human body or through livestock when it touches one or more accessible parts of cables or equipment

[SOURCE: ISO 17409:2020, 3.57, modified — "cables" replaces "an installation".]

**3.32****vehicle power supply circuit**

*voltage class* (3.26) B electric circuit which includes all parts that are conductively connected to the *vehicle inlet* (3.33) [*case B* (3.40), *case C* (3.41)] or the *plug* (3.45) [*case A* (3.39)]

[SOURCE: ISO 6469-2:2022, 3.18, modified — "conductively" replaces "galvanically" and "and that is operational when connected to an external electric power supply" was deleted.]

**3.33****vehicle inlet**

part of a vehicle coupler incorporated in, or fixed to, the electric vehicle

[SOURCE: IEC 62196-1:2014, 3.3.2, modified — "electric vehicle inlet" was deleted.]

**3.34****removable RESS**

*RESS* (3.23) that by design can be taken out from the vehicle by the vehicle user for off-board charging and/or other operation

**3.35****hazardous live part**

*live part* (3.19) which, under certain conditions, can give a harmful *electric shock* (3.13)

Note 1 to entry: For guidance on harmful physiological effects see IEC 61140:2016.

[SOURCE: IEC 60050-195:2021, 195-06-05, modified — Note 1 to entry was replaced.]

### 3.36

#### **specific voltage condition**

condition that the maximum voltage of a conductively connected electric circuit between a DC *live part* (3.19) and any other live part (DC or AC) is  $\leq 30$  V a.c. (rms) and  $\leq 60$  V d.c.

Note 1 to entry: When a DC live part of such an electric circuit is connected to chassis and the specific voltage condition applies, the maximum voltage between any live part and the *electric chassis* (3.11) is  $\leq 30$  V a.c. (rms) and  $\leq 60$  V d.c.

Note 2 to entry: For pulsating DC voltages (alternating voltages without change of polarity) the DC threshold is applied.

### 3.37

#### **chassis-connected electric circuit**

electric circuit that is conductively connected to each other, where the DC part of this circuit is connected to the *electric chassis* (3.11) and the *specific voltage condition* (3.36) is fulfilled

### 3.38

#### **clearance**

shortest distance in air between two *conductive parts* (3.6)

[SOURCE: IEC 60050-581:2008, 581-27-76]

### 3.39

#### **case A**

connection of an EV to the supply network with a *plug* (3.45) and cable permanently attached to the EV

[SOURCE: IEC 61851-1:2017, 3.1.10]

### 3.40

#### **case B**

connection of an EV to the AC supply network with a *cable assembly detachable at both ends*

[SOURCE: IEC 61851-1:2017, 3.1.11] <https://standards.iteh.ai/catalog/standards/sist/028596d6-0bce-47d6-9fdc-adff43fc947f/iso-13063-3-2022>

### 3.41

#### **case C**

connection of an EV to the AC supply network utilizing a cable and vehicle connector permanently attached to the EV charging station

[SOURCE: IEC 61851-1:2017, 3.1.12]

### 3.42

#### **conductively connected circuit**

two electric circuits are considered conductively connected unless they are separated by at least *basic insulation* (3.4)

[SOURCE: ISO/TR 8713:2019, 3.26]

### 3.43

#### **overload protection**

protection intended to operate in the event of overload on the protected section

[SOURCE: IEC 60050-448:1995, 448-14-31]

### 3.44

#### **overcurrent protection**

protection intended to operate when the current is in excess of a predetermined value

[SOURCE: IEC 60050-448:1995, 448-14-26]