

SLOVENSKI STANDARD oSIST prEN ISO 21368:2023

01-julij-2023

Lepila - Smernice za izdelavo lepljenih konstrukcij in postopki poročanja, primerni za oceno tveganja pri takšnih konstrukcijah (ISO 21368:2022)

Adhesives - Guidelines for the fabrication of adhesively bonded structures and reporting procedures suitable for the risk evaluation of such structures (ISO 21368:2022)

Klebstoffe - Richtlinien für die Herstellung geklebter Strukturen und Berichtsverfahren, die für die Risikobewertung solcher Strukturen geeignet sind (ISO 21368:2022)

Adhésifs - Lignes directrices pour la fabrication des structures collées par adhésifs et procédures pour l'établissement de rapports pour l'évaluation des risques liés à ces structures (ISO 21368:2022)

Ta slovenski standard je istoveten z: prEN ISO 21368

<u>ICS:</u>

83.180 Lepila

Adhesives

oSIST prEN ISO 21368:2023

en,fr,de

2003-01. Slovenski inštitut za standardizacijo. Razmnoževanje celote ali delov tega standarda ni dovoljeno.

oSIST prEN ISO 21368:2023

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>oSIST prEN ISO 21368:2023</u> https://standards.iteh.ai/catalog/standards/sist/09fd6814-9882-44f2-9208-2b2fd92567e8/osist-pren-iso-21368-2023

INTERNATIONAL STANDARD

ISO 21368

Second edition 2022-03

Adhesives — Guidelines for the fabrication of adhesively bonded structures and reporting procedures suitable for the risk evaluation of such structures

Adhésifs — Lignes directrices pour la fabrication des structures collées par adhésifs et procédures pour l'établissement de rapports pour l'évaluation des risques liés à ces structures

<u>oSIST prEN ISO 21368:2023</u> https://standards.iteh.ai/catalog/standards/sist/09fd6814-9882-44f2-9208-2b2fd92567e8/osist-pren-iso-21368-2023



Reference number ISO 21368:2022(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 21368:2023 https://standards.iteh.ai/catalog/standards/sist/09fd6814-9882-44f2-9208-2b2fd92567e8/osist-pren-iso-21368-2023



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents								
For	eword		vi					
Intr	oductio	on	vii					
1	Scor	0e	1					
2	 Normative references 							
2	Torms and definitions							
3	Terr							
4	Lore element 1: Classification of adhesively bonded joints according to safety requirements							
	4.1	General						
	4.2	Definition of safety classes	10					
	4.3	Documentation of the classification according to safety classes	11					
5	Core element 2: Adhesive bonding personnel (ABP)— Competences, knowledge							
	5 1	General	11					
	5.2	Adhesive bonding operators (ABO)						
	-	5.2.1 General	12					
		5.2.2 Functions	12					
		5.2.3 Duties	12					
	F 0	5.2.4 Competences, knowledge and experiences	12					
	5.3	Adhesive bonding coordinator (ABC)	13 12					
		5.3.2 Functions	13 13					
		5.3.3 Duties						
		5.3.4 Competences	15					
		5.3.5 Organizational integration of adhesive bonding coordination	15					
	5.4 Levels of competences, knowledge and experiences for adhesive bonding							
		personnel (ABP)	16 16					
		5.4.1 General sources and experiences by the second experiences and experiences and experiences and experiences and experiences are second experiences.	10 16					
	5.5	Assignment of the three competence levels to the safety classes depending on the	10					
		respective scope of work — Correlation of the core elements	18					
	5.6	Comparability of competences, knowledge and experience	19					
	5.7	Monitoring, inspection and testing personnel	19					
6	Core element 3: Design and verification of adhesively bonded joints							
	6.1	General	19					
	6.2	Assignment to safety classes	19					
	6.3	Requirements to be met by the adhesively bonded joints	20					
	6.4 6.5	Adherends	20 20					
	6.6	Adhesive						
	6.7	Surface treatment						
	6.8	Factors affecting the adhesive bonding process	21					
	6.9	Verification	21					
		6.9.1 General	21					
		6.9.2 Method 1 — Load In use < maximum load capacity	21 22					
		6.9.4 Method 3 — Documented experience						
		6.9.5 Method 4 — Combination of methods 1 to 3						
7	Drat	fting contracts and subcontracting (outsourcing)	22					
'	71 General							
	7.2	Subcontracting (Outsourcing)	23					
		7.2.1 General	23					
		7.2.2 Deciding on subcontracting	24					

		7.2.3	Details and documentation of procurement	24			
		7.2.4	Selection of external service provider (subcontractor/supplier) and				
		705	contracting				
		7.2.5	Management of external service providers (subcontractors/suppliers)				
8	Wor	Workmanship					
	8.1	Gener	al	25			
	8.2	Gener	al process requirements	25			
		8.2.1	Production planning	25			
		8.2.2	Process design				
		8.2.3	Planning the use of production aids and tools				
		8.2.4	Production documents	27			
		8.2.5	Process approval				
		8.2.6	adherends	27			
		8.2.7	Production environment				
		8.2.8	Materials	29			
		8.2.9	Preparation of work stations and acclimatization of materials	29			
		8.2.10	Health and safety and environmental protection	30			
		8.2.11	Checking for fitting accuracy concerning shape, position and dimension	30			
		8.2.12	Checks prior to start of production	30			
		8.2.13	Treatment of the adherend surfaces	31			
		8.2.14	Dosing, mixing and application	32			
		8.2.15	Inspection and testing during adhesive bonding and adhesive solidification	33			
		8.2.16	Joining the adherends	33			
		8.2.17	Fixing Fixing	34			
		8.2.18	Solidification of the adhesive	34			
		8.2.19	Inspection and testing of finished components	35			
		8.2.20	Packaging and transport of adhesively bonded components	35			
	8.3	Work	instructions: minimum requirements	35			
	8.4	Proce	ss reliability	37			
		8.4.1	General and Standards/Standar	37			
		8.4.2	Quality planning 092067e8/osist-pren-iso-21368-2023	37			
		8.4.3	Control of planning and manufacturing documents	37			
		8.4.4	Process validation	37			
		8.4.5	Production-accompanying work samples as proof of application quality				
		8.4.6	Quality control of process reliability/traceability				
		8.4.7	Instruction of adhesive bonding personnel (ABP)	40			
	05	8.4.8	Post-adhesive bonding finishing	40			
	8.5	Rewo	rk	40			
	8.6	Qualit	ty assurance	40			
		8.6.1	General	40			
		8.6.2	Quality planning	40			
		8.6.3	Quality inspection	41			
		8.6.4	Action in the case of deviations	41			
		8.6.5	tools	42			
		8.6.6	Impertections in adhesively bonded joints	42			
		8.6.7	Control of non-conforming products	43			
		8.6.8	Preventive and corrective action	43			
9	Mair	ntenanc	e and repair	43			
	9.1	Gener	al	43			
	9.2	Plann	ing of maintenance and repair	43			
	9.3	Maint	enance and repair instructions	44			
	9.4	Perfor	rming maintenance work/execution rules				
	9.5	Docur	mentation	45			
	9.6	Sub-c	ontracting	45			
Anne	ex A (in	formativ	ve) Assistance for providing adhesive bonding technology competences				

Annex B (informative) Requirements	63		
Annex C (informative) Guideline for the implementation of the design of adhesively bonded joints and its verification	64		
Annex D (informative) Criteria for choosing an adhesive bonding system	83		
Annex E (informative) Description of non-destructive and destructive testing methods	86		
Annex F (informative) Description of accelerating ageing tests			
Annex G (informative) Examples of non-decorative and decorative imperfections of adhesive bonds	93		
Annex H (informative) Example of a job history sheet	95		
Annex I (informative) Notes on quality planning			
Bibliography			

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 21368:2023 https://standards.iteh.ai/catalog/standards/sist/09fd6814-9882-44f2-9208-2b2fd92567e8/osist-pren-iso-21368-2023

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 61, *Plastics*, Subcommittee SC 11, *Products*.

<u>05151 prEN 150 21368:2023</u>

This second edition cancels and replaces the first edition (ISO 21368:2005), which has been technically revised. 2b2fd92567e8/osist-pren-iso-21368-2023

The main changes compared to the previous edition are as follows:

- broadening of the terms and definitions to include relevant processing and manufacturing terms;
- classification of adhesively bonded joints according to safety requirements;
- clarification of the competences, knowledge and experience of adhesive bonding personnel;
- comprehensive explanation the design of adhesively bonded joints;
- thorough description of surface treatment procedures;
- extensive account of how to assemble/manufacture of adhesively bonded joints.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

Introduction

Adhesive bonding technology is used widely internationally to fabricate many of the structures in the adhesive-using industry. In some companies, it is the key feature to production. Such structures range from microelectronic encapsulation to the structure and reinforcement of aircraft wings and bridges. Adhesive bonding technology appeals to industry across sectors and applications because it allows flexibility in the selection of materials, product design and product manufacture up to the final assembly. As such, adhesive bonding technology exerts a profound influence on the cost of fabrication and the quality of the product, thus allowing significant production savings and a competitive advantage in comparison with traditional methods of manufacture. It is important, therefore, to ensure that adhesive bonding technology is carried out in the most effective way and that appropriate control is exercised over all aspects of the operation. If used properly and professionally, the adhesive bonding technology is undoubtedly able to meet the requirements of circular economy and eco-design.

Within the ISO 9000 series of standards for quality systems, adhesive bonding technology is to be treated as a "special process" since adhesively bonded joints cannot be fully verified by subsequent inspection and testing of the product to ensure the required quality standards have been met.

As per today's knowledge, adhesively bonded joints cannot be inspected into a product. The task is to install them faultlessly from the outset. Even the most extensive and sophisticated non-destructive testing does not improve the quality of adhesively bonded joints.

For adhesively bonded structures to be effective and fit for purpose in service, there is a need to provide controls from the design stage through material selection to manufacture and subsequent inspection. Poor design for adhesive bonding creates serious risks and costly difficulties in the workshop, on site or in service. Inadequate consideration of the materials to be adhesively bonded and the choice of adhesive may result in adhesive bonding problems such as lack of adhesion or inadequate gap-filling of the structure. It is therefore essential for adhesive bonding procedures to be correctly formulated and approved to avoid imperfections. Comprehensive and qualified supervision ensures that the specified quality is achieved.

To ensure the quality of adhesively bonded structures on an international level and to make the quality of adhesively bonded structures internationally comparable, the task of management is to:

- identify possible sources of error;
- create organizational structures that prevent these sources of error from the outset; and
- introduce suitable quality procedures.

For these reasons, this document represents the state of the art for the professional organization of adhesive bonding processes in all areas of industry and trade in a holistic and international view. It also applies analogously to sealing processes if the function of the seal is only to secure and support adhesively bonded joints. The consideration of adhesive bonding technology according to this document comprises, starting with the first idea, the development of adhesively bonded joints (pre-production), continues through production, i.e. the manufacture of adhesively bonded joints (in-production), to the finished adhesively bonded product including its maintenance, repair and disposal (post-production).

This holistic approach also includes the quality assurance of production, inspection and maintenance, including the repair and disposal of adhesively bonded joints. The approach according to this document is, without exception and in any case, independent of the lot size as well as the respective area of application.

This document establishes definitions and sets out organizational, management technical, contractual and technical principles to be followed when manufacturing adhesively bonded joints. This is achieved by defining three essential core elements:

<u>Core element 1</u>: the classification of each adhesive bond according to safety requirements (see <u>Clause 4</u>);

ISO 21368:2022(E)

- <u>Core element 2</u>: the appointment of supervisory personnel [Adhesive Bonding Coordinators (ABCs)] and execution personnel (Adhesive Bonding Operators) who are both capable of objectively verifying the necessary and required adhesive bonding competence, knowledge and experience in each case (see <u>Clause 5</u>);
- Core element 3: the verification that the real load of the respective adhesive bond in the use and application of the adhesively bonded product is in any case less than the maximum load bearing capacity (see <u>Clause 6</u>).

The above-mentioned, necessary worldwide comparability in quality and implementation is achieved through a uniform implementation of these three core elements at the international level.

Since the all numerical values described in this document are reference values, it is advisable for the practitioners to decide on their own when implementing them.

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN ISO 21368:2023 https://standards.iteh.ai/catalog/standards/sist/09fd6814-9882-44f2-9208-2b2fd92567e8/osist-pren-iso-21368-2023

Adhesives — Guidelines for the fabrication of adhesively bonded structures and reporting procedures suitable for the risk evaluation of such structures

1 Scope

This document provides guidelines describing the adhesive bonding quality requirements suitable for use by adhesive user-companies utilizing adhesive bonding as a means of fabrication. In particular, the guidelines define various approaches to meeting quality requirements for fabrication and reporting procedures, both in workshops and on site. These guidelines aim to convey the importance of maintaining quality standards in fabrication and reporting procedures, keeping records and thus enabling documentation to provide the basis for risk evaluation of adhesively bonded structures in service and in use.

These guidelines have been prepared such that:

- a) they are independent of the type of adhesively bonded structure;
- b) they are independent of adhesive user-companies' and suppliers' product recommendations;
- c) they define the quality requirements for adhesive bonding in terms of fabrication and reporting procedures, both in workshops and on site;
- d) they can be used as the basis for risk evaluation of adhesively bonded structures in service and in use;
- e) they can be used as a basis for assessing a fabricator's capability to produce adhesively bonded structures fulfilling specified quality requirements when they are detailed in one or more of the following:
 - a contract between the parties involved;
 - an application standard;
 - a regulatory statement.

The guidelines contained within this document can be adopted in full or selectively chosen by the adhesive user to suit the structure concerned. The guidelines provide a flexible framework for the control of adhesive bonding activities in the following cases.

Case 1

The provision of specific requirements for adhesive bonding in contracts that require the adhesive user to have a quality system other than ISO 9001.

Case 2

The provision of specific requirements for adhesive bonding as guidance to an adhesive user developing a quality system.

Case 3

The provision of specific requirements for references in application standards that uses adhesive bonding as part of its requirements or in a contract between relevant parties.

Case 4

The provision of a framework for fabrication and reporting procedures to a quality standard, suitable in particular as a basis for the risk evaluation of adhesively bonded structures.

Normative references 2

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 472, Plastics — Vocabulary

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 472 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at https://www.electropedia.org/ IEN SIANDARD PREVIEW

3.1

adherend

substrate

object or semi-finished product (for example, sheet metal, wires, metal extruded, moulded plastic, fabrics, glass, etc.) on which an adhesive is applied

Note 1 to entry: In adhesive bonding processes, the term adherend is often used as a synonym for substrate.

3.2

adhesion

interaction between the adhesive and the *adherend/substrate* (3.1) surface

Note 1 to entry: The interactions that make up adhesion are based on forces between the surface of the adherend/ substrate and the adhesive film and include physical interactions, chemical bonds and micromechanical interlocking.

Note 2 to entry: Adhesion occurs in nm-dimensions.

3.3

adhesion promotor primer

liquid used in surface treatment to improve the adhesion of the adhesive to the substrate/adherend (3.1)

Note 1 to entry: Adhesion promotors often are named as primers, accelerators or activators.

3.4

adhesive

non-metallic material, which joins two *adherends/substrates* (3.1) together via adhesion and cohesion

3.5

adhesive bonding

special process for joining of *adherends/substrates* (3.1) by using an adhesive

Note 1 to entry: The adherends/substrates can be made of the same as well as of different materials and can have different surface characteristics.

3.6 adhesive bonding area

area used to join two *adherends/substrates* (3.1) using an adhesive

Note 1 to entry: Usually the product of the overlap length and overlap width of the adherends/substrates.

3.7

adhesive bonding coordinator ABC

responsible adhesive bonding coordinator rABC

competent person with proven professional skills in adhesive bonding technology responsible for the supervision and release of the adhesive bonding processes and for all activities associated with it including the release

Note 1 to entry: The responsible adhesive coordinator (rABC) is the appointed head of all adhesive bonding processes including their release and with the appropriate decision-making managerial authority concerning the adhesive technology within the company.

3.8

adhesive bonding operator

ABO

execution personnel with proven corresponding knowledge applying or executing independently the adhesive bonding process to manufacture, maintain or repair components according to approved work instructions

3.9

adhesive bonding personnel ARP (standards.iteh.ai)

people involved in the design, planning, manufacturing, quality assurance and maintenance/repair related to the adhesive bonding process

Note 1 to entry: As a rule, this employee group consists of *ABCs* (3.7) and *ABOs* (3.8).^{2–9208–}

2b2fd92567e8/osist-pren-iso-21368-2023

3.10

adhesive bonding procedure

all processes concerned with adhesive bonding such as surface treatment, processing the adhesive, application of the adhesive, joining the *adherends/substrates* (<u>3.1</u>), and solidification (curing/hardening)

3.11

adhesive bonding surface

area prepared for adhesive bonding, or on which the adhesive is applied, or the surface of the part to be adhesively bonded with adhesive between two parts to be adhesively bonded [length of overlap × width of overlap mm)]

3.12

adhesively bonded joint

connection of two or more substrates (adherends) from the same material or different materials with the use of an adhesive

Note 1 to entry: An adhesively bonded joint can be defined as rigid coupling, flexible coupling or joint sealing. All three types of junction are based on the same principles of operation.

3.13

adhesively bonded structure

structure

structure used for a partially or fully finished constituent or any other form of adhesively bonded item and designed mainly to transmit mechanical loads

Note 1 to entry: The loadbearing function is the main role of the adhesively bonded item ensuring reliability and fitness-for-purpose throughout the life cycle of the finished product.

ISO 21368:2022(E)

3.14

adhesive tape

flexible backing or carrier coated with a pressure-sensitive, moisture- or heat-activated adhesive

3.15

ageing

entirety of all irreversible chemical and physical processes occurring in a material in the course of time

Note 1 to entry: This can relate to:

- evolution of the properties of adhesively bonded joints with time;
- reproduction of the real operating life through accelerating (reduce time) test of ageing in appropriated environment (chemical and mechanical).

3.16

application

placement of the adhesive during the adhesive bonding procedure

3.17

assembly

group of parts that has been placed together for adhesive bonding or has been adhesively bonded

3.18

clamping

holding of an adhesively bonded joint under pressure with clamps during solidification of the adhesive between the adherends

3.19

cohesion

(stanuarus.nten.ar)

internal strength that, for example, keep the molecules of an adhesive together

Note 1 to entry: These forces are based on attractive physical forces between the polymer chains, entanglement of the polymer chains, and chemical bonds inside and between the adhesive polymer chains.

3.20

component

one part of an adhesive system

Note 1 to entry: In adhesive bonding technology, the parts of an adhesive system (resin and hardener) are called components (component A and component B).

3.21

conditioning

exposure of *components* (3.20) and joining parts required for the adhesive bonding process for a reasonable period in compliance with the specified requirements

3.22

curing

chemical solidification of the adhesive

Note 1 to entry: Chemical reactions leading to solidification of the adhesive in the form of thermoplastic, elastomeric or thermoset polymers.

Note 2 to entry: This refers to chemically curing adhesives.

3.23

curing time

period of time required to solidify an adhesive *curing* (3.22) by chemical reactions

3.24

destructive testing

analyses, tests and surveys carried out for the definition of information of qualitative/quantitative about specific properties of the analysed system, obtained following the destruction of the system itself

Note 1 to entry: The test specimen will be destroyed during the test and cannot be used afterwards.

3.25

exposure time

length of time for which adhesively bonded joints are exposed under specified conditions

3.26

fabricator

adhesive bonding workshops and/or sites under the same technical and quality management

Note 1 to entry: See *user-company* (3.59).

3.27

flash off-time

minimum waiting time when using cleaners, activators or primers until the solvent has completely evaporated

3.28

high-modulus adhesive load-bearing adhesive structural adhesive adhesive where strength and stiffness are the most important properties after solidification

Note 1 to entry: In contrast, there are low-modulus adhesives.

Note 2 to entry: After solidification, high-modulus adhesives concentrate on their strength and stiffness, and less on their formability.

Note 3 to entry: The property transitions between high and low-modulus adhesives are fluid and not precisely defined [see low-modulus adhesive (3.37)].

Note 4 to entry: The term "structural adhesives" is often used for high-modulus adhesives. For the purposes of this document, the term "structural adhesives" is replaced by "load-bearing adhesives" (analogous: "load-bearing adhesive bonds" instead of "structural bonds").

3.29

hot spot

small region or area with a high value of a quantity

EXAMPLE Stress, strain, energy.

Note 1 to entry: A hot spot can be calculated with FEM.

3.30

joining

assembling of *components* (3.20) to become a whole

EXAMPLE Adhesive bonding is just one joining method. Other examples are welding, screwing and riveting.

3.31

influence

non-mechanical parameters that are applied to a material which changes its properties

Note 1 to entry: The nature of the non-mechanical parameters influences the material behaviour (loading) and the load capacity to be selected.

Note 2 to entry: Further influences can have an impact on the adhesive selection.