



Designation: ~~D7318-07~~ Designation: D7318 - 11

Standard Test Method for Total Existing Inorganic Sulfate in Ethanol by Potentiometric Titration¹

This standard is issued under the fixed designation D7318; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This test method covers a potentiometric titration procedure for determining the ~~total existing~~ inorganic sulfate content of hydrous, anhydrous ethanol, and anhydrous denatured ethanol, which is added as a blending agent with spark ignition fuels. It is intended for the analysis of denatured ethanol samples containing between 1.0–20 mg/kg ~~total existing~~ inorganic sulfate.

1.2 The values stated in SI units are to be regarded as the standard. ~~The values given in parentheses~~ No other units of measurement are for information only included in this standard.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* Material Safety Data Sheets are available for reagents and materials. Review them for hazards prior to usage.

2. Referenced Documents

2.1 ASTM Standards:²

D1193 Specification for Reagent Water

D4052 Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter

D4057 Practice for Manual Sampling of Petroleum and Petroleum Products

D4177 Practice for Automatic Sampling of Petroleum and Petroleum Products

D6299 Practice for Applying Statistical Quality Assurance and Control Charting Techniques to Evaluate Analytical Measurement System Performance

3. Terminology

3.1 Definitions:

3.1.1 ~~inorganic sulfate~~ existing inorganic sulfate, n —sulfate species present as sulfuric acid, ionic salts of this acid, or mixtures of these.

3.1.1.1 *Discussion*—Specifically in this test method, inorganic sulfate is present as sulfate in ethanol.

4. Summary of Test Method

4.1 An ethanol sample containing inorganic sulfate is titrated in ethanolic medium with a standard lead nitrate solution. Lead sulfate precipitate is formed during the titration. Perchloric acid is added to remove possible interference from carbonate. The endpoint is signaled by an increase in lead ion activity, as measured by a lead-selective electrode.

5. Significance and Use

5.1 Ethanol is used as a blending agent added to gasoline. Sulfates are indicated in filter plugging deposits and fuel injector deposits. When fuel ethanol is burned, sulfates may contribute to sulfuric acid emissions. Ethanol acceptability for use depends on the sulfate content. Sulfate content, as measured by this test method, can be used as one measure of determination of the acceptability of ethanol for automotive spark-ignition engine fuel use.

¹ This test method is under the jurisdiction of ASTM Committee D02 on Petroleum Products and Lubricants and is the direct responsibility of Subcommittee D02.03 on Elemental Analysis.

Current edition approved Feb. 1, 2007. Published March 2007. DOI: 10.1520/D7318-07.

Current edition approved July 1, 2011. Published August 2011. Originally approved in 2007. Last previous edition approved in 2007 as D7318-07. DOI: 10.1520/D7318-07.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

*A Summary of Changes section appears at the end of this standard.

6. Apparatus

6.1 *Potentiometric Titration Assembly*—A titration assembly consisting of an automatic titrator fitted with a lead ion-selective electrode, a double-junction reference electrode, buret, and stirring is used. Stirring may be accomplished by means of magnetic or propeller type stirrer mechanisms. The buret size should ideally be 10 or 20 mL.

6.2 *Reference Electrode*—A double junction reference electrode with the inner electrode composed of silver/silver chloride with a potassium chloride solution as internal electrolyte. The external solution is composed of 1 M lithium chloride in ethanol. This configuration is used to prevent silver ion, a lead electrode poison, from leaching into the analyte solution during titration. Preferred electrolytes for use in double junction electrodes may vary with the manufacturer; use the manufacturer's recommended electrolytes for the application. Other types of reference electrodes may be considered with some caveats (for example, single junction, combination, or glassy carbon), but the data presented in this test method were generated using exclusively a double junction electrode, which is the best choice for this determination.

6.3 *Lead Electrode*—A lead sulfide-based crystalline sensor type lead ion selective electrode (ISE) is used.

6.4 *Drying Oven*—A drying oven for drying sodium sulfate at 110°C is required.

6.5 *Pipets or Volumetric Transferring Devices*—Class A glass pipets or their equivalent.

6.6 *Polishing Material*—Lead sulfide based crystalline sensor electrodes require polishing to remove oxidation products. These materials are supplied with the electrode from the manufacturer.

6.7 *pH Test Strips*—Test strips in the range of pH 1 to pH 7.

6.8 *Titration Vessels*—Standard glass beakers or titration vessels supplied with titration equipment.

7. Reagents and Materials

7.1 *Lead Nitrate*—Reagent grade, 99% minimum purity. (**Warning**—Poison, harmful by inhalation and if ingested. Avoid contact with the skin.) Dispose of this material in accordance with accepted local requirements.

7.2 *Sodium Sulfate*—Anhydrous, reagent grade, 99% minimum purity. (**Warning**—Do not ingest. Avoid unnecessary exposure.)

7.3 *Perchloric Acid 70%*—A.C.S. reagent grade, minimum purity with sulfate concentration <0.001% (m/M). Dispose of this material in accordance with accepted local requirements. It must contain no measurable sulfate. (**Warning**—Corrosive; keep away from skin and eyes. Perchloric acid is a strong oxidizer.)

7.4 *Ethanol*—Denatured with methanol, formula 3A or histological grade ethanol, anhydrous, denatured with ethyl acetate, methyl isobutyl ketone and hydrocarbon naphtha. It must be free of any measurable sulfate. (**Warning**—Flammable, toxic, may be harmful or fatal if ingested or inhaled. Avoid skin contact.)

7.5 *Ethanol*—Absolute, 200 proof, 99.5%, A.C.S. reagent grade.

7.6 *Lithium Chloride*—99+%, A.C.S. reagent grade.

7.7 *Water*—Type III reagent water conforming to Specification D1193.

7.8 *Anhydrous Calcium Sulfate Desiccant*.

8. Preparation of Standard Solutions

8.1 *Lead Nitrate Titrant, 0.0025 M*—Dissolve 0.833 g lead nitrate in 300 mL water. Pour into a 1-L bottle and fill with denatured ethanol and mix well. Standardize in accordance with 10.1.

8.1.1 Alternatively, this solution may be purchased from a commercial vendor, and its exact molarity shall be determined in accordance with 10.1.

8.2 *Aqueous Sulfate Standard, 0.01 M*—Dry 5 g anhydrous sodium sulfate at 110°C for 1 h. Remove it from the oven, and allow it to cool in a desiccator over anhydrous calcium sulfate. Accurately weigh about 0.70 g on an analytical balance to the nearest tenth of a milligram, and place it in a 500-mL volumetric flask. Add Type III water to dissolve the sodium sulfate, then dilute to volume. Calculate the exact concentration in accordance with Eq 1.

$$\frac{G}{(142.02)(0.500)} = \text{Molarity} \quad (1)$$

Molarity = molarity of sulfate standard solution, mol/L,

G = weight in grams of Na_2SO_4 , dissolved in 500 mL, and

142.02 = gram molecular weight of Na_2SO_4 .

8.3 *Aqueous Sulfate Stock Solution for Standards in Ethanol, 2000 mg/L*—Accurately weigh 2.95 g anhydrous sodium sulfate to the nearest tenth of a milligram and transfer it to a 1-L volumetric flask. (Dried anhydrous sodium sulfate should be stored in a desiccator.) Add Type III water to dissolve the sodium sulfate, and make to volume. Calculate the concentration of sulfate in the solution in accordance with Eq 2.

$$\text{Aqueous Stock Sulfate (mg/L)} = \frac{(\text{g Na}_2\text{SO}_4) (0.6764) (1000 \text{ mg/g})}{1 \text{ L}} \quad (2)$$

g Na₂SO₄ = weight in grams of Na₂SO₄ dissolved in 1 L, and
 0.6764 = fraction of sulfate in Na₂SO₄.

8.4 *Sulfate Standards in Ethanol*—Ethanol (denatured containing no measurable sulfate) is weighed into a container (equipped with a closure to prevent evaporation) in accordance with Table 1 to achieve the desired standard. Aqueous sulfate stock solution from 8.3 is added to the solution in accordance with Table 1, and the final weight of the solution recorded. Standards should be remade weekly or if recovery of less than 90% is noted. The concentration of the standard is calculated by dividing the number of milligrams sulfate from the sulfate stock solution and dividing by the final solution weight in accordance with Eq 3.

$$\text{EtOH Sulfate Standard (mg/kg)} = \frac{V \times C}{W} \quad (3)$$

V = volume of aqueous sulfate stock (8.3), mL,
C = concentration of aqueous sulfate stock (8.3), mg/L, and
W = final weight of ethanol and aqueous sulfate stock aliquot, g.

8.5 *Aqueous Sulfate Blank Solution, 0.01 M*—This is the same solution as in 8.2. This solution contains sulfate and will be added to all samples to allow a measurable sulfate blank to be measured.

8.6 *Dilute Perchloric Acid, 0.1 M*—Dissolve 8.8 mL perchloric acid (7.3) in 250-mL water in a 1-L volumetric flask. Mix well and dilute to the mark with Type III water.

8.7 *Lithium Chloride in Ethanol, 1 M*—Add lithium chloride (8.49 g) to absolute ethanol (200 mL) while stirring until it is dissolved.

9. Titration Equipment Preparation

9.1 *Titrator*—Prepare the titrator by filling the titrator reservoir with lead titrant (8.1). Follow the manufacturer’s procedure for filling the buret. Perform titrations in monotonic titration mode, using either 25-μL or 50-μL titrant addition increments. Use a 10 mV/min drift condition or 20-s wait time between additions (whichever is achieved first).

9.2 *Electrode Preparation*—Proper care of the lead-selective electrode is essential for obtaining high-quality titration curves. Preparation of the lead electrode should be performed as specified by the manufacturer. A lead electrode utilizing a solid crystal sensor requires polishing when performance deteriorates. The voltage range for a 10 ppm sulfate in ethanol titration should span at least 50 mV and produce an acceptably shaped titration curve (see Fig. 1). If this level of electrode performance is not met, this indicates a need for lead electrode polishing. The lead electrode normally comes supplied with a polishing grit and a cloth rectangle. The polishing grit medium is placed on the cloth, wet with ethanol or water, moved over the surface of the cloth for a minute, rinsed with water to remove the polishing medium, and wiped dry with a tissue. The electrode is then soaked in lead titrant (8.1) for 2 min to re-equilibrate the electrode surface. The double junction reference electrode is filled with 1 M lithium chloride in absolute ethanol (8.7) in the outer chamber.

<https://standards.nich.gov/catalog/standards/sist/68cead41-0525-4a6a-84ed-63b07cceda28/astm-d7318-11>

10. Standardization

10.1 Measure the exact concentration of the lead nitrate titrant by titration of the sulfate standard (8.2).

10.1.1 Transfer 1.00 mL of the 0.01 M aqueous sulfate standard solution (8.2) into a 150-mL beaker. Record this volume as *V*.

10.1.2 Add approximately 100 mL of denatured ethanol (7.4) and 1 mL of 0.1 M perchloric acid (8.6).

10.1.3 Prepare the autotitrator for operation, immerse the electrodes in the titration solution, initiate stirring, and titrate to the potentiometric endpoint with lead titrant. Titration should require approximately 4.0-mL of lead solution to reach the endpoint. Record this volume as *T*.

10.2 Titrate a blank denatured ethanol sample in the same manner without addition of sulfate standard. Record this volume as *T_b*.

10.3 Calculate the concentration of the lead nitrate titrant as shown in Eq 4. The standardization should be repeated until precision comparable to that shown in Section 15 and Table 2 has been achieved.

$$M_{pb} = \frac{V \times S}{T - T_b} \quad (4)$$

TABLE 1 Preparation of Sulfate Standards in Ethanol

Ethanolic Sulfate Standard, mg sulfate/kg ethanol	Ethanol, g	Aqueous Sulfate Stock Solution, mL
50	975	25
20	990	10
10	995	5
5	997.5	2.5
1	999.5	0.5