

---

**Cestna vozila - Komunikacijski vmesnik med vozilom in omrežjem - 9. del: Preskus skladnosti fizične in podatkovne povezovalne plasti za brezžično komunikacijsko omrežje (ISO 15118-9:2022)**

Road vehicles - Vehicle to grid communication interface - Part 9: Physical and data link layer conformance test for wireless communication (ISO 15118-9:2022)

Straßenfahrzeuge - Kommunikationsschnittstelle zwischen Fahrzeug und Ladestation - Teil 9: Konformitätsprüfungen für die Bitübertragungs- und Sicherungsschicht für drahtlose Kommunikation (ISO 15118-9:2022)

Véhicules routiers - Interface de communication entre véhicule et réseau électrique - Partie 9: Essai de conformité relatif à la couche physique et à la couche liaison de données pour la communication sans-fil (ISO 15118-9:2022)

**Ta slovenski standard je istoveten z: prEN ISO 15118-9**

---

**ICS:**

35.100.05	Večslojne uporabniške rešitve	Multilayer applications
43.040.15	Avtomobilska informatika. Vgrajeni računalniški sistemi	Car informatics. On board computer systems

**oSIST prEN ISO 15118-9:2023**

**en,fr,de**



INTERNATIONAL  
STANDARD

ISO  
15118-9

First edition  
2022-11

---

---

**Road vehicles — Vehicle to grid  
communication interface —**

**Part 9:  
Physical and data link layer  
conformance test for wireless  
communication**

*Véhicules routiers — Interface de communication entre véhicule et  
réseau électrique —*

*Partie 9: Essai de conformité relatif à la couche physique et à la  
couche liaison de données pour la communication sans-fil*

<https://standards.iteh.ai/catalog/standards/sist/2953ff7b-cb03-4917-bb1e-c450f4c62fa6/osist-pren-iso-15118-9-2023>



Reference number  
ISO 15118-9:2022(E)

© ISO 2022

# iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN ISO 15118-9:2023](https://standards.iteh.ai/catalog/standards/sist/2953ff7b-cb03-4917-bb1e-c450f4c62fa6/osist-pren-iso-15118-9-2023)

<https://standards.iteh.ai/catalog/standards/sist/2953ff7b-cb03-4917-bb1e-c450f4c62fa6/osist-pren-iso-15118-9-2023>



## **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

Foreword.....	iv
Introduction.....	v
<b>1 Scope.....</b>	<b>1</b>
<b>2 Normative references.....</b>	<b>1</b>
<b>3 Terms and definitions.....</b>	<b>2</b>
<b>4 Abbreviated terms.....</b>	<b>6</b>
<b>5 Conventions.....</b>	<b>7</b>
5.1 Requirement structure.....	7
5.2 Test system description.....	8
<b>6 Test architecture reference model.....</b>	<b>8</b>
6.1 General information.....	8
6.2 Platform adapter interface.....	8
6.3 SUT adapter interfaces.....	9
6.4 Codecs.....	9
<b>7 Test suite conventions.....</b>	<b>10</b>
7.1 General information.....	10
7.2 Test suite structure (TSS).....	10
7.3 Test profiles.....	11
7.3.1 Test configurations.....	12
7.3.2 Components and ports.....	12
7.3.3 Protocol implementation conformance statement (PICS) definition.....	14
7.3.4 Protocol implementation extra information for testing (PIXIT) definition.....	14
7.3.5 Test control.....	15
7.4 Test suite identifiers.....	15
7.4.1 Module identifiers.....	15
7.4.2 Test case identifiers.....	16
7.4.3 Template identifiers.....	16
7.4.4 Function identifiers.....	17
7.4.5 Timer identifiers.....	18
7.4.6 PICS/PIXIT identifiers.....	18
7.4.7 Verdict identifiers.....	19
7.5 Test suite coverage.....	19
7.6 Test case description.....	22
<b>8 Test case descriptions for ISO 15118-8 requirements.....</b>	<b>23</b>
8.1 General information.....	23
8.2 SECC test cases.....	23
8.3 EVCC test cases.....	43
<b>Bibliography.....</b>	<b>72</b>

## ISO 15118-9:2022(E)

### Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives) or [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)) or the IEC list of patent declarations received (see <https://patents.iec.ch>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html). In the IEC, see [www.iec.ch/understanding-standards](http://www.iec.ch/understanding-standards).

This document was prepared jointly by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 31, *Data communication*, and Technical Committee IEC/TC 69, *Electrical power/energy transfer systems for electrically propelled road vehicles and industrial trucks*.

A list of all parts in the ISO 15118 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html) and [www.iec.ch/national-committees](http://www.iec.ch/national-committees).

## Introduction

Resulting from the wireless physical and data link layer requirements defined in ISO 15118-8, a corresponding set of abstract test cases is necessary to verify the conformance of implementations. This document, therefore, defines a conformance test suite for the wireless physical and data link layer protocols in order to derive a common and agreed basis for conformance tests. The resulting test suite is a prerequisite for downstream interoperability tests. Since interoperability furthermore involves the actual application logic of an implementation, those tests are beyond the scope of this document. Hence, this document focuses on the interface aspects and the corresponding requirements given in ISO 15118-8 only.

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

[oSIST prEN ISO 15118-9:2023](https://standards.iteh.ai/catalog/standards/sist/2953ff7b-cb03-4917-bb1e-c450f4c62fa6/osist-pren-iso-15118-9-2023)

<https://standards.iteh.ai/catalog/standards/sist/2953ff7b-cb03-4917-bb1e-c450f4c62fa6/osist-pren-iso-15118-9-2023>





# Road vehicles — Vehicle to grid communication interface —

## Part 9:

# Physical and data link layer conformance test for wireless communication

## 1 Scope

This document specifies conformance tests in the form of an abstract test suite (ATS) for a system under test (SUT) implementing an electric-vehicle or supply-equipment communication controller (EVCC or SECC) with support for WLAN-based high-level communication (HLC) according to ISO 15118-8 and against the background of ISO 15118-1. These conformance tests specify the testing of capabilities and behaviours of an SUT, as well as checking what is observed against the conformance requirements specified in ISO 15118-8 and against what the implementer states the SUT implementation's capabilities are.

The capability tests within the ATS check that the observable capabilities of the SUT are in accordance with the static conformance requirements defined in ISO 15118-8. The behaviour tests of the ATS examine an implementation as thoroughly as practical over the full range of dynamic conformance requirements defined in ISO 15118-8 and within the capabilities of the SUT (see NOTE below).

A test architecture is described in correspondence to the ATS. The abstract test cases in this document are described leveraging this test architecture and are specified in descriptive tabular format for the ISO/OSI physical and data link layers (layers 1 and 2).

In terms of coverage, this document only covers normative sections and requirements in ISO 15118-8. This document can additionally refer to specific tests for requirements on referenced standards (e.g. IEEE, or industry consortia standards, like WiFi Alliance) as long as they are relevant in terms of conformance for implementations according to ISO 15118-8. However, it is explicitly not intended to widen the scope of this conformance specification to such external standards, if it is not technically necessary for the purpose of conformance testing for ISO 15118-8. Furthermore, the conformance tests specified in this document do not include the assessment of performance nor robustness or reliability of an implementation. They cannot provide judgments on the physical realization of abstract service primitives, how a system is implemented, how it provides any requested service, nor the environment of the protocol implementation. Furthermore, the abstract test cases defined in this document only consider the communication protocol and the system's behaviour defined ISO 15118-8. The power flow between the EVSE and the EV is not considered.

**NOTE** Practical limitations make it impossible to define an exhaustive test suite, and economic considerations can restrict testing even further. Hence, the purpose of this document is to increase the probability that different implementations are able to interwork. This is achieved by verifying them by means of a protocol test suite, thereby increasing the confidence that each implementation conforms to the protocol specification. However, the specified protocol test suite cannot guarantee conformance to the specification since it detects errors rather than their absence. Thus, conformance to a test suite alone cannot guarantee interworking. Instead, it gives confidence that an implementation has the required capabilities and that its behaviour conforms consistently in representative instances of communication.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

## ISO 15118-9:2022(E)

ISO 15118-1, *Road vehicles — Vehicle to grid communication interface — Part 1: General information and use-case definition*

ISO 15118-2, *Road vehicles — Vehicle-to-Grid Communication Interface — Part 2: Network and application protocol requirements*

ISO 15118-8:2020, *Road vehicles — Vehicle to grid communication interface — Part 8: Physical layer and data link layer requirements for wireless communication*

ISO 15118-20, *Road vehicles — Vehicle to grid communication interface — Part 20: 2nd generation network layer and application layer requirements*

ETSI ES 201 873-5 V4.9.1<sup>1)</sup>, *Methods for Testing and Specification (MTS) — The Testing and Test Control Notation version 3 — Part 5: TTCN-3 Runtime Interface (TRI) (April 2022)*

ETSI ES 201 873-6 V4.13.1<sup>2)</sup>, *Methods for Testing and Specification (MTS) — The Testing and Test Control Notation version 3 — Part 6: TTCN-3 Control Interface (TCI) (April 2022)*

IEEE 802.11-2012, *IEEE Standard for Information technology — Telecommunications and information exchange between systems — Local and metropolitan area networks — specific requirements: Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 15118-1, ISO 15118-2, ISO 15118-8, ISO 15118-20 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <https://www.electropedia.org/>  
<https://standards.iteh.ai/catalog/standards/sist/2953ff7b-cb03-4917-bb1e-c450f4c62fa6/osist-pren-iso-15118-9-2023>

**3.1**  
**abstract test case**  
 complete and independent specification of the actions required to achieve a specific *test purpose* (3.25), defined at the level of abstraction of a particular abstract test method, starting in a stable testing state and ending in a stable testing state and optionally involves one or more consecutive or concurrent connections

Note 1 to entry: The specification should be complete in the sense that it is sufficient to enable a *test verdict* (3.29) to be assigned unambiguously to each potentially observable test outcome (i.e. sequence of test events).

Note 2 to entry: The specification should be independent in the sense that it should be possible to execute the derived *executable test case* (3.7) in isolation from other such test cases (i.e. the specification should always include the possibility of starting and finishing in the 'idle' state).

[SOURCE: ITU-T X.290:1995, 3.3.3].

**3.2**  
**ATS**  
 abstract test suite  
 test suite composed of *abstract test cases* (3.1)

[SOURCE: ITU-T X.290:1995, 3.3.6]

1) Available at [https://www.etsi.org/deliver/etsi\\_es/201800\\_201899/20187305/04.09.01\\_60/es\\_20187305v040901p.pdf](https://www.etsi.org/deliver/etsi_es/201800_201899/20187305/04.09.01_60/es_20187305v040901p.pdf).

2) Available at [https://www.etsi.org/deliver/etsi\\_es/201800\\_201899/20187306/04.13.01\\_60/es\\_20187306v041301p.pdf](https://www.etsi.org/deliver/etsi_es/201800_201899/20187306/04.13.01_60/es_20187306v041301p.pdf).

### 3.3

#### **APUT**

access point under test

ISO/OSI layer 1 and 2 component of the SECC [*system under test (SUT)* (3.19)] for establishing a wireless communication connection

### 3.4

#### **black box test**

method of testing that examines the behaviour of a *system under test (SUT)* (3.19) without considering the internal implementation and structure of the SUT, thus relying on the SUT's open interface for testing

### 3.5

#### **conformance requirement**

conformance of a real system consisting of conformance to each requirement and conformance to the set

Note 1 to entry: Set of interrelated requirements which together define the behaviour of the system and its communication. Conformance of a real system will, therefore, be expressed at two levels, conformance to each individual requirement and conformance to the set. Applicable conformance tests defined in this document, include requirements and transfer syntax requirements as far as they can be validated by *black box tests* (3.4).

Note 2 to entry: See also *static conformance requirement* (3.17) and *dynamic conformance requirement* (3.6).

### 3.6

#### **dynamic conformance requirement**

one of the requirements which specifies what observable behaviour is permitted by the relevant specification(s) in instances of communication

Note 1 to entry: The requirements for this conformance specification are defined in ISO 15118-8.

[SOURCE: ITU-T X.290:1995, 3.3.29, modified — Note 1 to entry has been added.]

### 3.7

#### **executable test case**

realization of an *abstract test case* (3.1)

[SOURCE: ITU-T X.290:1995, 3.3.31]

### 3.8

#### **expected behaviour**

exact response of the *system under test (SUT)* (3.19) according to the underlying protocol specification to the stimulus defined in the *test behaviour* (3.20)

### 3.9

#### **ICS**

implementation conformance statement

statement made by the supplier of an implementation or system claimed to conform to a given specification, stating which capabilities have been implemented

Note 1 to entry: The given specification for this conformance specification is ISO 15118-8.

[SOURCE: ITU-T X.290:1995, 3.3.39, modified — "The ICS can take several forms: protocol ICS, profile ICS, profile specific ICS, and information object ICS." has been removed from the definition and Note 1 to entry has been added.]

## ISO 15118-9:2022(E)

## 3.10

**IXIT**

implementation extra information for testing

statement made by a supplier or implementer of a *system under test (SUT)* (3.19) which contains or references all of the information [in addition to that given in the *implementation conformance statement (ICS)* (3.9)] related to the SUT and its testing environment, which will enable the test laboratory to run an appropriate test suite against the SUT

[SOURCE: ITU-T X.290:1995, 3.3.41, modified — "An IXIT can take several forms: protocol IXIT, profile IXIT, profile specific IXIT, and information object IXIT, TMP implementation statement." removed from the definition and IUT replaced by SUT.]

## 3.11

**MTC**

main test component

single *test component* (3.21) in a test component configuration responsible for creating and controlling *parallel test components* (3.12) and computing and assigning the *test verdict* (3.29)

[SOURCE: ITU-T X.292:2002, 3.6.43]

## 3.12

**parallel test component****PTC**

*test component* (3.21) created by the *main test component* (3.11)

[SOURCE: ITU-T X.292:2002, 3.6.53]

## 3.13

**post-condition**

test steps needed to define the path from the end of the *test behaviour* (3.20) up to the finishing stable state for the test case

[oSIST prEN ISO 15118-9:2023](https://standards.iteh.ai/catalog/standards/sist/2953ff7b-cb03-4917-bb1e-c450f4c62fa6/osist-pren-iso-15118-9-2023)

## 3.14

**pre-condition**

test steps needed to define the path from the starting stable state of the test case up to the initial state from which the *test behaviour* (3.20) will start

## 3.15

**PICS**

protocol implementation conformance statement

*implementation conformance statement (ICS)* (3.9) for an implementation or system claimed to conform to a given protocol specification

Note 1 to entry: The given protocol specification for this conformance specification is ISO 15118-8.

[SOURCE: ITU-T X.290:1995, 3.3.80, modified — Note 1 to entry has been added.]

## 3.16

**PIXIT**

protocol implementation extra information for testing

*implementation extra information for testing (IXIT)* (3.10) related to testing for conformance to a given protocol specification

Note 1 to entry: The given protocol specification for this conformance specification is ISO 15118-8.

[SOURCE: ITU-T X.290:1995, 3.3.81, modified — Note 1 to entry has been added.]

**3.17****static conformance requirement**

one of the requirements that specify the limitations on the combinations of implemented capabilities permitted in a real open system which is claimed to conform to the relevant specification(s)

[SOURCE: ITU-T X.290:1995, 3.3.95]

**3.18****STAUT**

station under test

ISO/OSI layer 1 and 2 component of the EVCC [*system under test (SUT)* (3.19)] for establishing a wireless communication connection

**3.19****SUT**

system under test

real open system in which the implementation of one or more OSI protocols in an adjacent user/provider relationship are to be studied by testing.

Note 1 to entry: Adapted from ITU-T X.290:1995, 3.3.103 and 3.3.43.

**3.20****test behaviour**

set of test steps (test body) which are essential in order to achieve the *test purpose* (3.25) and assign verdicts to the possible outcomes

**3.21****test component**

named subdivision of a concurrent test case capable of being executed in parallel and declared as having a fixed number of points of control and observation and a fixed or maximal number of co-ordination points

[SOURCE: ITU-T X.292:2002, 3.6.72, modified — "in parallel with other test components" has been replaced by "in parallel".]

**3.22****TCI**

TTCN-3 control interfaces

four interfaces that define the interaction of the TTCN-3 Executable with the test management, the coding and decoding, the *test component* (3.21) handling and the logging in a *test system* (3.27)

[SOURCE: ETSI ES 201 873-6 V4.13.1:2022, 3.1]

**3.23****test execution**

interpretation or execution of an *abstract test suite* (3.2)

Note 1 to entry: Conceptually, the test execution can be decomposed into three interacting entities: an executable test suite, a *test framework* (3.24) and an optional internal encoding/decoding system entity.

**3.24****test framework**

entity to perform all actions of test cases or functions

Note 1 to entry: The test framework interacts with the test management, *system under test (SUT)* (3.19) adaptor and platform adaptor entities via *TTCN-3 control interfaces (TCI)* (3.22) and *test runtime interface (TRI)* (3.26) and additionally manages the executable test suite and encoding/decoding system entities. It initializes adaptors as well as executable test suite and encoding/decoding system entities. This entity performs all the actions necessary to properly start the execution of a test case or function with parameters in the executable test suite entity. It queries the test management entity for module parameter values required by the executable test suite and sends logging information to it. It also collects and resolves associated verdicts returned by the executable test suite entity.

**ISO 15118-9:2022(E)**

Note 2 to entry: In this document, the TTCN-3 runtime system is used to explain a test framework functionality.

**3.25****test purpose**

prose description of a well-defined objective of testing, focusing on a single *conformance requirement* (3.5) or a set of related conformance requirements as specified in the appropriate OSI specification

EXAMPLE Verifying the support of a specific value of a specific parameter.

[SOURCE: ITU-T X.290:1995, 3.3.118]

**3.26****TRI**

test runtime interface

two interfaces that define the interaction of the TTCN-3 executable between the *system under test (SUT)* (3.19) and the platform adapter (PA) and the system adapter (SA) in a *test system* (3.27)

[SOURCE: ETSI ES 201 873-5 V4.9.1:2022, 3.1, modified — The term was originally TTCN-3 runtime interface.]

**3.27****test system**

real system combining the *test framework* (3.24), *abstract test suite* (3.2), *test execution* (3.23) and adapters as well as codecs

Note 1 to entry: Typically, also containing a common runtime environment based on an operating system.

**3.28****TSI**

test system interface

*test component* (3.21) that provides a mapping of the ports available in the (abstract) TTCN-3 *test system* (3.27) to those offered by a real test system

[SOURCE: ETSI ES 201 873-5 V4.9.1:2022, 3.1]

**3.29****test verdict**

statement of 'pass', 'fail' or 'inconclusive', as specified in an *abstract test case* (3.1), concerning conformance of a *system under test (SUT)* (3.19) with respect to that test case when it is executed

[SOURCE: ITU-T X.290:1995, 3.3.124, modified — IUT was replaced by SUT.]

**4 Abbreviated terms**

For the purposes of this document, the following abbreviated terms apply:

AP	(wireless) access point
APUT	access point under test
ATS	abstract test suite
EDCA	enhanced distributed channel access
ETSI	european telecommunications standards institute
EV	electric vehicle
EVCC	electric vehicle communication controller

EVSE	electric vehicle supply equipment
HAL	hardware abstraction layer
ICS	implementation conformance statement
ITB	invalid test behaviour
MAC	media access control
MTC	main test component
PICS	protocol implementation conformance statement
PIXIT	protocol implementation extra information for testing
PTC	parallel test component
SECC	supply equipment communication controller
STA	(wireless) station
STAUT	station under test
SUT	system under test
TC	test case
TCI	TTCN-3 control interface
TCI-CD	TCI-coding and decoding
TE	test execution
TRI	TTCN-3 runtime interface
TSI	TTCN-3 system interface
TSS	test suite structure
TTCN-3	testing and test control notation version 3
V2G	vehicle-to-grid
VTB	valid test behaviour

## 5 Conventions

### 5.1 Requirement structure

This document uses unique number identifiers for each individual requirement. This requirement structure allows for easier requirement tracking and management. The following format is used throughout this document:

'[V2G'Y'-'XXX']' requirement text

Where:

- 'V2G' represents the ISO 15118 series;
- Y represents the document part of the ISO 15118 series, for this document Y = 9;