



**SLOVENSKI STANDARD**  
**SIST-TS ISO/TS 15311-1:2023**

**01-april-2023**

**Nadomešča:**

**SIST-TS ISO/TS 15311-1:2020**

---

**Grafična tehnologija - Zahteve za tiskovine za komercialno in industrijsko proizvodnjo - 1. del: Metode merjenja in shema poročil**

Graphic technology - Requirements for printed matter for commercial and industrial production - Part 1: Measurement methods and reporting schema

iteh STANDARD PREVIEW  
(standards.iteh.ai)

Technologie graphique — Exigences relatives aux imprimés destinés à la production commerciale et industrielle — Partie 1: Méthodes de mesure et schémas de rapport

https://standards.iteh.ai/catalog/standards/sist/ts-15311-1/2023/sist-ts-iso-ts-15311-1-2023

**Ta slovenski standard je istoveten z: ISO/TS 15311-1:2020**

---

**ICS:**

37.100.01	Grafična tehnologija na splošno	Graphic technology in general
-----------	---------------------------------	-------------------------------

<b>SIST-TS ISO/TS 15311-1:2023</b>	<b>en</b>
------------------------------------	-----------



TECHNICAL  
SPECIFICATION

ISO/TS  
15311-1

Third edition  
2020-12

---

---

**Graphic technology — Requirements  
for printed matter for commercial and  
industrial production —**

**Part 1:  
Measurement methods and reporting  
schema**

*Technologie graphique — Exigences relatives aux imprimés destinés à  
la production commerciale et industrielle —*

*Partie 1: Méthodes de mesure et schémas de rapport*

SIST-TS ISO/TS 15311-1:2023

<https://standards.iteh.ai/catalog/standards/sist/31fb324c-fa80-4eb3-884e-b9995c7cd7bf/sist-ts-iso-ts-15311-1-2023>



Reference number  
ISO/TS 15311-1:2020(E)

© ISO 2020

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

[SIST-TS ISO/TS 15311-1:2023](https://standards.iteh.ai/catalog/standards/sist/31fb324c-fa80-4eb3-884e-b9995c7cd7bf/sist-ts-iso-ts-15311-1-2023)

<https://standards.iteh.ai/catalog/standards/sist/31fb324c-fa80-4eb3-884e-b9995c7cd7bf/sist-ts-iso-ts-15311-1-2023>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>2</b>
<b>4 Requirements</b> .....	<b>4</b>
4.1 General.....	4
4.2 Single or multiple sheet assessment.....	4
4.2.1 General.....	4
4.2.2 Total number of sheets.....	4
4.2.3 Number of sheets measured.....	4
4.2.4 Reporting.....	5
4.3 Print quality measures.....	6
4.3.1 Overview.....	6
4.3.2 Colour, tone reproduction and gloss.....	6
4.3.3 Uniformity.....	14
4.3.4 Detail rendition capabilities.....	17
4.3.5 Permanence.....	22
4.3.6 Artefacts.....	27
4.4 Printing conditions.....	28
<b>Annex A (informative) Sampling of sheets</b> .....	<b>29</b>
<b>Annex B (informative) Estimation of BlackPoint from control strip</b> .....	<b>31</b>
<b>Annex C (informative) Calculation of 95<sup>th</sup> percentile</b> .....	<b>32</b>
<b>Bibliography</b> .....	<b>35</b>

## ISO/TS 15311-1:2020(E)

### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 130, *Graphic technology*.

This third edition of cancels and replaces the second edition (ISO/TS 15311-1:2019), which has been technically revised.

The main changes compared to the previous edition are as follows:

- the following new subclauses have been added:
  - [4.3.2.8](#), Computing and analysing colour gamut
  - [4.3.5.3](#), Indoor light stability (display window)
  - [4.3.6.2](#), Contouring
  - [4.3.4.8](#), Perceived resolution
  - [4.3.3.8](#), Macroscopic uniformity
- [4.3.5.2](#), Indoor light stability (home and office display) has been modified.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

When producing a colour reproduction, it is important that the persons responsible for data creation, colour separation, proofing and printing operations have previously agreed a minimum set of parameters that define the visual characteristics and other technical properties of the planned print product. This document identifies a number of metrics that can be applied to printed sheets and that can be used as the basis for such communication. The range of metrics is large, and it is not intended that all of these metrics are to be applied to any given printed product and for any given application. The range of metrics is to be carefully selected, for example based on subsequent parts of ISO/TS 15311.

The metrics described by this document can be applied to any type of print. They are likely most often to be applied to digitally printed prints.

When selecting the set of metrics, only those metrics that have a clear specification and that correlate well with human perception are included in this document. Since this is an area of significant research activity, new metrics are expected to emerge and existing metrics to be revised in the next few years. For this reason, we anticipate the need to revise this document within a very short time scale as new metrics are tested and found to be reliable.

Additional tests to those specified in this document, for example visual assessment of smoothness, images and other elements may be required when assessing print quality.

As with any parameter that is used as part of a product specification, it is important for readers to understand clearly what the metric means. For this reason, a reporting schema is to be followed when reporting measurements in conformance with this document.

(standards.iteh.ai)

[SIST-TS ISO/TS 15311-1:2023](https://standards.iteh.ai/catalog/standards/sist/31fb324c-fa80-4eb3-884e-b9995c7cd7bf/sist-ts-iso-ts-15311-1-2023)

<https://standards.iteh.ai/catalog/standards/sist/31fb324c-fa80-4eb3-884e-b9995c7cd7bf/sist-ts-iso-ts-15311-1-2023>





# Graphic technology — Requirements for printed matter for commercial and industrial production —

## Part 1: Measurement methods and reporting schema

### 1 Scope

This document defines print quality metrics, measurement methods and reporting requirements for printed sheets that are suitable for all classes of printed products.

Guidance as to which of these metrics to apply to any given product category along with acceptable conformance criteria is provided in subsequent parts of ISO/TS 15311.

Although this document is expected to be used primarily to measure prints from digital printing systems, the metrics are general and can be applied to other kinds of print.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2813, *Paints and varnishes — Determination of gloss value at 20°, 60° and 85°*

ISO 8254-1, *Paper and board — Measurement of specular gloss — Part 1: 75 degree gloss with a converging beam, TAPPI method*

ISO 12642-2, *Graphic technology — Input data for characterization of 4-colour process printing — Part 2: Expanded data set*

ISO 12647-8, *Graphic technology — Process control for the production of half-tone colour separations, proof and production prints — Part 8: Validation print processes working directly from digital data*

ISO 13655, *Graphic technology — Spectral measurement and colorimetric computation for graphic arts images*

ISO 15184, *Paints and varnishes — Determination of film hardness by pencil test*

ISO 18619, *Image technology colour management — Black point compensation*

ISO/TS 18621-11, *Image quality evaluation methods for printed matter — Part 11: Colour gamut analysis*

ISO/TS 18621-21, *Graphic technology — Image quality evaluation methods for printed matter — Part 21: Measurement of 1D distortions of macroscopic uniformity utilizing scanning spectrophotometers*

ISO/TS 18621-31, *Graphic technology — Image quality evaluation methods for printed matter — Part 31: Evaluation of the perceived resolution of printing systems with the contrast-resolution chart*

ISO 18924, *Imaging materials — Test method for Arrhenius-type predictions*

ISO 18930, *Imaging materials — Pictorial colour reflection prints — Methods for evaluating image stability under outdoor conditions*

ISO 18935, *Imaging materials — Colour images — Determination of water resistance of printed colour images*

## ISO/TS 15311-1:2020(E)

ISO 18936, *Imaging materials — Processed colour photographs — Methods for measuring thermal stability*

ISO 18937, *Imaging materials — Photographic reflection prints — Methods for measuring indoor light stability*

ISO 18947, *Imaging materials — Photographic reflection prints — Determination of abrasion resistance of photographic images*

ISO/TS 21139-21, *Permanence and durability of commercial prints — Part 21: In-window display — Light and ozone stability*

ISO/IEC 24790, *Information technology — Office equipment — Measurement of image quality attributes for hardcopy output — Monochrome text and graphic images*

ISO/IEC 29112, *Information technology — Office equipment — Test pages and methods for measuring monochrome printer resolution*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

#### 3.1 banding

appearance of one dimensional variation within an area that should be homogeneous

#### 3.2 CIEDE2000 colour difference

method of/formula for calculating colour difference,  $\Delta E_{00}$ /CIEDE00

Note 1 to entry: See ISO/CIE 11664-6 for details.

#### 3.3 colour deviation

colour difference between the colour aim value and a colour measurement or the mean of a set of colour measurements

Note 1 to entry: In addition to the  $\Delta E_{00}$  the  $\Delta L^*$  with  $\Delta a^*$  and  $\Delta b^*$  and/or with  $\Delta C^*$  and  $\Delta H^*$  may be reported.

#### 3.4 colour variation

colour difference between the mean of a set of colour measurements and each sample

Note 1 to entry: Colour variation is also known as colour fluctuation and may be reported as the mean or 95<sup>th</sup> percentile.

#### 3.5 digital printing

process for text and image reproduction with a colour marker on a medium using a marking device, on which the marking information is generated from digital data directly to the medium

Note 1 to entry: Digital printing differs from traditional ink-based printing on which the marking information is generated from a form produced offline prior to imaging on the medium.

**3.6****permanence**

ability to remain chemically and physically stable over long periods of time

[SOURCE: ISO 18913:2012, 3.134]

**3.7****image quality**

impression of the overall merit or excellence of an image, as perceived by an observer

Note 1 to entry: For a meaningful technical evaluation of image quality, the evaluation should be based on a third-party assessment, i.e. by an observer neither associated with the artistic creation of the image, nor closely or emotionally involved with the subject matter being depicted. This restriction is designed to eliminate sources of variability that arise from more idiosyncratic aspects of image perception that are outside control of imaging system designers.

[SOURCE: Handbook of Image Quality: Characterization and prediction]

**3.8****printing condition**

set of primary process parameters which describe the conditions associated with a specific printed output, associated with spectral, colorimetric and/or densitometric aim values

Note 1 to entry: Such parameters usually include (as a minimum) printing process, paper category, printing ink, screening and printing sequence. The aim values typically comprise the colorant description and tone value increase aims.

Note 2 to entry: For the purposes of colour management, a printing condition is fully characterized by giving the relationship between the digital input values (for example as stipulated in ISO 12642-2) and the corresponding measured colorimetric values.

Note 3 to entry: Based on a given set of characterization data according to 3.9, Note 2 to entry and a definition of achromatic perception, a grey printing condition might be extracted.

<https://standards.iteh.ai/catalog/standards/sist/31fb324c-fa80-4eb3-884e-b9995c7cd7bf/sist-ts-iso-ts-15311-1-2023>

**3.9****tone value**

proportional printing value encoded in a data file and interpreted as defined in the file format specification

$$A=100\times\left(\frac{V_p-V_0}{V_{100}-V_0}\right)\%$$

where

$V_p$  is the integer value of the pixel;

$V_0$  is the integer value corresponding to a tone value of 0 %;

$V_{100}$  is the integer value corresponding to a tone value of 100 %.

Note 1 to entry: Tone value is expressed in units of percent.

Note 2 to entry: Most files store these data as 8-bit integer values, i.e. 0 to 255. The tone value of a pixel is typically computed from the formula.

**3.10****URI****Uniform Resource Identifier**

compact sequence of characters that identifies an abstract or physical resource

Note 1 to entry: See IETF RFC 3986 for details.

## ISO/TS 15311-1:2020(E)

### 3.11

#### CIELAB chromaticness difference

$\Delta C_h$

difference between two colours of approximately the same lightness projected onto a constant lightness plane in the CIELAB colour space

Note 1 to entry: This is calculated as  $\Delta C_h = \sqrt{(\text{CIE } \alpha_1^* - \text{CIE } \alpha_2^*)^2 + (\text{CIE } b_1^* - \text{CIE } b_2^*)^2}$

Note 2 to entry: [SOURCE: ISO 13655:2017, 3.5]

## 4 Requirements

### 4.1 General

The following subclauses provide a number of metrics that define attributes of printed sheets and requirements for reporting them.

In many cases, the existing standards use CIE  $\Delta E_{ab}^*$  rather than CIEDE2000. Although these are not interchangeable quantities,  $\Delta E_{ab}^*$  has been superseded by CIEDE2000 in ISO/TC 130 standards. For this reason, CIEDE2000 shall be used to report colour difference metrics in this document.

Similarly, printing density is seldom used to measure colour and where the referenced standards specify printing density, approximately equivalent CIELAB colour measurements shall be used.

### 4.2 Single or multiple sheet assessment

#### 4.2.1 General

Unless otherwise specified, metrics shall be assumed to apply to the assessment of a single sheet.

In many cases, it is useful to be able to report metrics for a set of sheets. For example, the set of sheets produced in a single print run or the set of sheets to be delivered as part of an order for print. In these cases, it is important to be able to indicate the likely variation across the entire set of sheets.

Sheets should be selected randomly with no replacement.

NOTE Best practice sampling is time-stamped to demonstrate what time and date the sample was taken.

Samples should be selected with the following provisos:

- a) sheets should be selected throughout the entire press run;
- b) sheets should not be selected synchronous to any press event.

In cases where metrics are reported for a set of sheets, the report shall indicate the following: the total number of sheets in the set to be assessed, the number of sheets measured and, unless random selection with no replacement is used, the sampling method used to select the sheets shall be indicated.

#### 4.2.2 Total number of sheets

The total number of sheets in the set of sheets assessed shall be reported. Details of the printing system used to create the sheets should also be reported.

#### 4.2.3 Number of sheets measured

Conformance with this document requires only that values measured for the sampled set of sheets are reported. As a general rule, the higher the number of sheets measured from the set, the closer this value will be to that of the entire set of sheets. Where there are a large number of sheets in the set, it may be

impractical to measure a high percentage of these sheets and so the likely spread of values may be high. [Table 1](#) provides guidelines for the suggested number of sheets to be assessed for different numbers of sheets in the set.

**Table 1 — Guidelines for the number of sheets to be assessed**

Total number of sheets in set	Suggested number of sheets to be measured
50	12
100	13
1 000 and greater	15

[Table 1](#) provides typical sampling strategies used in the industry today. Users should be aware that where these values are used, the average value (and the 95<sup>th</sup> percentile) for the total set of sheets may vary substantially from the average measured for the sample set. [Annex A](#) provides details of how the likely difference between these two values varies with the sample size and provides a method for finding the sampling rate needed to increase the confidence in the metric to a required level.

NOTE ISO 186 suggests increasing the number of samples to 20 for run lengths greater than 5 000.

In order to verify whether the difference between the two values is statistically significant, the variable E of [Annex A](#) can be used as a point of reference. The number of samples may be chosen to avoid overlapping error bars by selecting an appropriate value for E.

#### 4.2.4 Reporting

When multiple sheets are assessed, the total number of sheets and the number of sheets assessed shall be reported as shown in the example below.

EXAMPLE 1 Sheets assessed: 15 (500).

When multiple sheets are assessed, the mean and standard deviation for each metric shall be reported as shown below except when reporting colour difference metrics.

EXAMPLE 2 Estimated line width: sample mean = 0,12 mm, sample standard deviation = 0,01 mm.

When reporting colour difference metrics for a single colour measured on multiple sheets, both the colour deviation and colour variation should be reported.

The colour deviation shall be calculated as follows: calculate the mean CIELAB value of the samples. The colour deviation is given by the CIEDE2000 colour difference between the CIELAB colour aim value and the mean CIELAB value. In addition to the  $\Delta E_{00}$  value the  $\Delta L^*$ ,  $\Delta a^*$  and  $\Delta b^*$  values (Mean - Reference) should be reported.

EXAMPLE 3 Colour deviation 3,2  $\Delta E_{00}$ ,  $\Delta L^* = 2,8$ ,  $\Delta a^* = 0,3$ ,  $\Delta b^* = 1,4$ .

The colour variation shall be calculated as follows: calculate the mean CIELAB value of the samples. Calculate the CIEDE2000 colour differences between this mean and the CIELAB of each sample. The colour variation is given by the mean value of these CIEDE2000 colour differences or the corresponding 95<sup>th</sup> percentile. Refer to [Annex C](#) for details on the calculation of the 95<sup>th</sup> percentile.

EXAMPLE 4 Colour variation 0,8  $DE_{00}$ .

Where the spread of colour variation is reported, the mean colour difference and the 95<sup>th</sup> percentile (and not the standard deviation) should be used.

EXAMPLE 5 Colour variation 0,8  $DE_{00}$ , 95<sup>th</sup> percentile 1,2  $DE_{00}$ .

NOTE Standard deviation is not an appropriate measure for colour difference as this assumes a normal distribution, whereas colour differences are not normally distributed. The 95 percentile provides a more reliable estimate of the spread of values.