FINAL **DRAFT**

INTERNATIONAL **STANDARD**

ISO/FDIS 12858-2

ISO/TC 172/SC 6

Secretariat: SNV

Voting begins on: 2020-03-12

Voting terminates on:

2020-05-07

Optics and optical instruments — Ancillary devices for geodetic

Tripods
Optique et instruments d'optique — Équipements annexes pour les

Anents

2:
 .ipods

Optique et instruments d'optinstruments géodésiques

Partie 2: Trépieds

Partie 4: Trépieds

Interes d'optinstruments d'optinstruments géodésiques

Partie 2: Trépieds

Interes d'optinstruments d'optinstruments géodésiques

Partie 2: Trépieds

Interes d'optinstruments d'optinstruments d'optinstruments d'optinstruments géodésiques

Partie 2: Trépieds d'optinstruments d'optinstruments d'optinstruments géodésiques d'optinstruments d'optinstruments

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STAN-DARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number ISO/FDIS 12858-2:2020(E) 

COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

CO	ntents		Page		
Fore	eword		iv		
Intr	oduction		v		
1	Scope		1		
2	Normative references				
3	Terms and definitions				
4					
_					
5	General features — Dimensions		L		
6					
	6.1 Tripod head		3		
	6.2 Joints		3		
	6.3 Clamping screw		3		
	6.4 Tripod legs		3		
	6.5 Tripod shoes		3		
	6.6 Torsional rigidity		7		
	6.7 Height stability under load	<u>, S</u>	7		
	6.8 Material	0,00	7		
	6.9 Protection from corrosion	Property of the state of the st	7		
7	Tools	O hid	7		
0	Designation and modeling	ite and asse	7		
8					
Ann	ex A (informative) Parallel screw threa	ds of Whitworth form	9		
Bibl	liography	112 12 12 12 12 12 12 12 12 12 12 12 12	10		
	eli (St	Fit alicie dise			

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 172, *Optics and photonics*, Subcommittee SC 6, *Geodetic and surveying instruments*

This second edition cancels and replaces the first edition (ISO 12858-2:1999), which has been technically revised. It also incorporates the Amendment ISO 12858-2:1999/Amd 1:2013. The changes compared to the previous edition are as follows:

editorial corrections.

A list of all parts in the ISO 12858 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

ISO 12858 consists of a series of parts which detail specifications for ancillary devices to be used with geodetic instruments in surveying. This second part specifies requirements for tripods.

Additional parts, covering further ancillary devices, may be added to ISO 12858 as the need arises.

I ch S A D A Reliand Strate of Sandard State of Sandard State of Sandard Strate of Sandard State of Sandard Sandard State of Sandard Sandard State of Sandard Sandard State of Sandard Sandard State of Sandard Sandard State of Sandard Sandard Sandard Sandard State of Sandard San

Optics and optical instruments — Ancillary devices for geodetic instruments —

Part 2:

Tripods

1 Scope

This part of ISO 12858 specifies the most important requirements of telescopic tripods for surveying instruments and the connection between instrument and tripod.

The requirements in this part of ISO 12858 enable instruments and tripods of different manufacturers to be joined to one another, without prejudicing their performance and their usefulness.

This part of ISO 12858 is applicable to tripods which are used for levels, theodolites, tacheometers, GPS equipment, EDM instruments and in combination with targets, reflectors, antennae, etc.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 9849, Optics and optical instruments — Geodetic and surveying instruments — Vocabulary

ISO 2768-1, General tolerances — Part 1: Tolerances for linear and angular dimensions without individual tolerance indications

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 9849 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at http://www.electropedia.org/


4 Design

Two main types of tripod with telescopic legs are used:

- Type L: for light-weight or small instruments, with flat head (LF) or spherical head (LS);
- Type H: for heavy instruments.

5 General features — Dimensions

The mechanical properties of the tripod shall conform to the values given in <u>Table 1</u>. The shape of the tripod and the details as shown in <u>Figure 1</u> are examples for information only.



Parameter	Tell	Et Fillighed The	Type of head			
rarameter		Flat head		Spherical head		
Description	Unit	TypeLF	Туре Н	Type LS		
Design		light-weight	heavy-weight	light-weight		
Mass of tripod	kg (max.)	1/5th 5,5	7	5,5		
Suitable for instruments weighing	kg (max.)	5 S	15	5		
Symbol ^a in <u>Figure 1</u>						
$\overline{l_1}$	mm	1 650	1 700	1 650		
l_2	mm	1 200	1 200	1 200		
d	mm	125	150	125		
Z	mm	25	35	25		
t	mm	110	125	110		

Where

 l_1 is the minimum length of tripod, legs extended;

 l_2 is the maximum length of tripod, legs retracted;

d is the minimum diameter of tripod platform;

z is the minimum diameter of rotating piece;

t is the minimum distance between step and point.

Requirements

6.1 Tripod head

An instrument set on the tripod shall be able to be rotated easily and evenly on the tripod head when the clamping screw is loosened. Additional devices fixed to the tripod head shall not hamper the ability of the tripod to be used with instruments from different manufacturers. Either flat or spherical heads may be used with the tripod.

6.2 **Joints**

The joints on the tripod legs shall be designed in such a way that the tripod can be set up quickly. The friction of the joints shall be adjustable.

6.3 Clamping screw

The clamping screw shall be provided with a 5/8 in (inch) bolt thread and the instrument base plate with a 5/8 in nut thread. The clamping screw shall be securely fixed to the tripod head such that the centring of the instrument shall not be hindered. The clamping screw shall be hollow with an internal diameter of at least 8 mm, in order that optical centring devices can be used. The suspension point of a plumb line or solid plumb shall be arranged in such a way that a centring accuracy of 2 mm is ensured.

The dimensions given in Figure 2 and Table 2 (for flat heads) and in Figure 3 and Table 3 (for spherical heads) respectively shall be observed.

6.4 Tripod legsFor tripods with wooden legs, the wood metal connections shall be sufficiently adjustable so that even

after shrinkage the fittings sit firmly.

6.5 Tripod shoes

The tripod shoes shall be provided with a step. The tripod shoes shall be made of unhardened steel.