

INTERNATIONAL
STANDARD

ISO
27509

Second edition

Petroleum and natural gas industries — Compact flanged connections with IX seal ring

*Industries du pétrole et du gaz naturel — Raccordements à brides
compactes avec bague d'étanchéité IX*

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standard/sist/137e9af7-15e4-40dd-a706-e645c292d15e/iso-prf-27509>

PROOF/ÉPREUVE



Reference number
ISO 27509:2020(E)

© ISO 2020

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standard/sist/137e9af7-7958-40dd-a706-e645c292d15e/iso-prf-2750>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	v
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Abbreviations and symbols	2
4.1 Abbreviated terms	2
4.2 Symbols	3
5 Design	5
5.1 General	5
5.2 Design principles	6
5.3 Assembly requirements	8
5.4 Standard components	8
5.5 Units of measurements	9
5.6 Rounding	9
5.7 Conformance with piping design codes	9
5.8 Conformance with this document	10
6 Designation	10
6.1 Designation of flanges	10
6.2 Designation of seal rings	10
7 Materials	11
7.1 General	11
7.2 Flange materials	11
7.3 Bolting materials	11
7.4 Seal ring materials	12
8 Strength, pressure/temperature ratings and leak tightness	13
8.1 General	13
8.2 Pressure/temperature ratings	13
8.3 Pressure testing and leak tightness	14
9 Dimensions of flanges	14
9.1 General	14
9.2 Weld neck dimensions	15
9.3 Blind flange (BL) dimensions	26
9.4 Integral flange (IF) dimensions	28
9.5 Rigid interface dimensions	38
9.6 Dimensions of paddle blanks (PB) and paddle spacers (PS)	41
9.7 Handle and lifting lugs	43
9.8 Dimensions of orifice spacers (OS)	43
9.9 Dimensions of reducing threaded flanges	45
9.10 Auxiliary connections	46
9.11 Flange tolerances	46
9.12 Surface finish	48
10 Marking of flanges	49
10.1 Flanges other than integral flanges	49
10.2 Manufacturer's name or trademark	49
10.3 Nominal size	49
10.4 Pressure class designation	50
10.5 Pipe dimensions	50
10.6 Material identification	50
10.7 Identification of internally threaded flanges	50

10.8	Material traceability	50
10.9	Marking examples	50
10.10	Stamping.....	51
11	Dimensions of seal rings	51
12	Manufacture, testing and inspection of IX seal rings.....	54
13	Coating and colour coding.....	54
14	Marking of seal rings.....	55
15	Quality management systems.....	55
16	Bolt dimensions and masses.....	55
Annex A (normative) Pressure temperature ratings and load capacity.....		56
Annex B (normative) Integral flange angle selection.....		60
Annex C (normative) Bolt dimensions and masses.....		71
Annex D (normative) Handling, installation, assembly and repair of flanges		78
Annex E (informative) Mass of flanges.....		91
Annex F (informative) Metric bolting		101
Annex G (informative) Additional information on bibliographical references		103
Bibliography.....		105

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/137e9af7-2058>
40dd-a706-e645c292d15e/iso-prf-27509

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 67, *Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries*, Subcommittee SC 6, *Processing equipment and systems*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 12, *Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 27509:2012), which has been technically revised. It also incorporates the Technical Corrigendum ISO 27509:2012/Cor.1:2013. The main changes compared to the previous edition are as follows:

- [Annexes B](#) and [D](#) ([Annex E](#) in previous edition) have become normative annexes;
- more stringent quality requirements regarding manufacture of products and assembly instructions have been introduced. These include
 - a) ultrasonic testing of products in accordance with new requirements in ASME VIII div. 2 (in [Clause 7](#)),
 - b) requirements to material strength and machining strictly in accordance with given tolerances for IX seal rings (in [Clause 12](#)),
 - c) new and better coating requirements for IX seal rings (in [Clause 13](#) and [Annex D](#)),
 - d) excluding use of IX seal rings to assist alignment by transfer of significant shear load during assembly (in [Annex D](#)),
 - e) more comprehensive and detailed guidelines on the evaluation of damages to products and the repair of such damages (in [Annex D](#)),
 - f) more comprehensive requirements to qualification of bolt tensioning procedures (in [Annex D](#)), and

- g) the elastoplastic deformation of flanges by first assembly has been better explained in [5.3](#) and in [Annex D](#), in order to prevent unnecessary re-machining or rejection when flange bevel angles have changed.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standard/sist/137e9af7-7958-40dd-a706-e645c292d15e/iso-prf-2750>

Introduction

This document, which is originally based on NORSO L-005, has been developed to provide an International Standard for compact flanged connections that constitutes an alternative to conventional flanges as specified in ASME standards, European standards and other standards, with reduced mass and smaller overall dimensions, as well as increased reliability in leak tightness by means of its inherent design features and make up procedures. CFCs can also provide an alternative to other types of clamp and hub type mechanical connectors.

The use of load carrying sealing elements, traditionally referred to as "gaskets", does not conform with the requirements of this document.

This document has been developed for use in process piping systems, which are designed in accordance with codes for pressure piping, e.g. ASME B31.3. See [5.7](#) for more details.

The flange designs have been selected to achieve a minimum safety factor of 2,0 when subjected to a design pressure equal to ASME B16.5 pressure temperature ratings within the temperature limits of this document.

The main body of this document contains all necessary information on how to manufacture and supply flange and seal ring materials, such as

- flange dimensions and material requirements;
- seal ring dimensions and material requirements;
- bolting dimensions and material requirements;
- requirements to tolerances and surface finish; and
- requirements to designation and marking of finished products.

The normative [annexes A, B, C](#) and [D](#) cover the following topics:

- structural capacity equations for flange assemblies;
- how to apply the flanges to special geometries of valves and equipment nozzles;
- bolt dimensions and masses;
- installation and assembly instructions, and guidelines on how to repair damage and irregularities on sealing surfaces.

The informative [annexes E, F](#) and [G](#) cover the following topics:

- masses of all standard components;
- suitable dimensions of alternative metric bolting;
- additional information on bibliographical references.

In this document, the following verbal forms are used:

- "shall" indicates a requirement;
- "should" indicates a recommendation;
- "may" indicates a permission;
- "can" indicates a possibility or a capability.

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standard/sist/137e9af7-7958-40dd-a706-c645c292d15e/iso-prf-2750>

Petroleum and natural gas industries — Compact flanged connections with IX seal ring

1 Scope

This document specifies detailed manufacturing requirements for circular steel and nickel alloy compact flanged connections and associated seal rings, for designated pressures and temperatures in class designations CL 150 (PN 20) to CL 1500 (PN 260) for nominal sizes from DN 15 (NPS $\frac{1}{2}$) to DN 1200 (NPS 48), and for CL 2500 (PN 420) for nominal sizes from DN 15 (NPS $\frac{1}{2}$) to DN 600 (NPS 24).

NOTE NPS is expressed in accordance with ASME B36.10M and ASME B36.19M.

This document is applicable to welding neck flanges, blind flanges, paddle spacers and spacer blinds (paddle blanks), valve/equipment integral flanges, orifice spacers, reducing threaded flanges and rigid interfaces for use in process piping for the petroleum, petrochemical and natural gas industries.

This document is applicable within a temperature range from -196°C to $+250^{\circ}\text{C}$.

This document is not applicable for external pressure.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2768-1, *General tolerances — Part 1: Tolerances for linear and angular dimensions without individual tolerance indications*

ISO 4287, *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Terms, definitions and surface texture parameters*

ISO 4288, *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Rules and procedures for the assessment of surface texture*

ISO 5167-1, *Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full — Part 1: General principles and requirements*

ISO 5167-2:2003, *Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full — Part 2: Orifice plates*

ISO 14313, *Petroleum and natural gas industries — Pipeline transportation systems — Pipeline valves*

ISO 80000-1:2009, *Quantities and units — Part 1: General*

EN 1591-4, *Flanges and their joints — Part 4: Qualification of personnel competency in the assembly of the bolted connections of critical service pressurized systems*

EN 1779, *Non-destructive testing — Leak testing — Criteria for method and technique selection*

ASME B16.5, *Pipe Flanges and Flanged Fittings: NPS 1/2 through NPS 24 Metric/Inch Standard*

ASME B16.34, *Valves — Flanged, Threaded and Welding End*

ASME B1.20.1, *Pipe Threads, General Purpose (Inch)*

ASME B31.3:2018, *Process Piping*

ASTM B568, *Standard Test Method for Measurement of Coating Thickness by X-Ray Spectrometry*

ASTM B571, *Standard Practice for Qualitative Adhesion Testing of Metallic Coatings*

ASME VIII Div. 2: *Boiler and Pressure Vessel Code — Alternative Rules*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1 class CL

pressure class in accordance with specific values

Note 1 to entry: The values shall be in accordance with ASME B16.5 and ASME B16.34

3.2 compact flanged connection CFL

non-gasketed bolted static pipe connection including two flanges and where the bolt loads are transferred through metal to metal contact between the flange faces

3.3 gasket

barrier to prevent the passage of fluids, but which does not transmit all loads between flanges

3.4 purchaser

individual or organization that buys the pipe connection on behalf of the user and/or operator or for its own use

3.5 seal

component providing a barrier to prevent the passage of fluids, transmitting no significant loads between the flanges

3.6 supplier

individual or organization that takes the responsibility for the supply of the pipe connection

4 Abbreviations and symbols

4.1 Abbreviated terms

BL	blind flange
DN	nominal pipe diameter (expressed in millimetres)
ID	internal diameter
IF	integral flange (as part of some other equipment or component)

IX	special metallic seal ring applied in this document
LB	line blinds (including PS and PB)
NPS	nominal pipe size (expressed in inches)
OD	outer diameter
OS	orifice spacer
PB	paddle blank
PN	nominal pressure (expressed in bar)
PS	paddle spacer
PTFE	polytetrafluoroethylene
RI	rigid interface
RT	reducing threaded flange
WN	weld neck

4.2 Symbols

A	outside diameter of neck
A_{\max}	maximum outer diameter to accommodate standard tools
A_{\min}	minimum neck outer diameter listed in Table 7 to Table 12
A_{C015}	cross-sectional area of the neck/pipe calculated from t_{015}
A_{Ceqv}	cross-sectional area of a special flange neck geometry calculated from Formula (B.1)
A_{Cb}	total cross-sectional area of bolting, based on root area
A_T	hub diameter of reducing threaded flange
a	maximum allowable alignment gap between mating flanges (see Figure D.4)
a_{Cb}	bolt root area
B	bore diameter, where the bore should not exceed the maximum listed bore in this document
B_{\max}	maximum listed bore diameter
B_{\min}	minimum bore diameter for which the face angles are valid
B_1	minimum bore diameter for flange to be blinded
	NOTE B_1 is also the start diameter for blind and reducing threaded flange face angles.
B_{CD}	bolt circle diameter
d_B	bolt size (nominal bolt diameter)
d_n	effective contact diameter of nut face (average between width of cross flats and diameter of bolt hole)

d_p	average diameter of neck end = $(A+B)/2$
d_t	effective (mean) contact diameter of bolting threads
D_{A1}	internal diameter of groove
D_{A3}	outer diameter of groove
D_{Gn}	seal ring seal dimension (see Figure 13)
D_{W1}	inner recess diameter
D_{W2}	outer recess diameter
D_{W3}	outside diameter of flange
D_{W4}	flange to neck fillet outer diameter
e	radial distance between B_{CD} and d_p
E_1	depth of groove
E_2	depth of recess
F_A	applied axial force
F_{cB}	bolt total plastic capacity (root area \times number of bolts \times yield strength)
F_f	flange axial load capacity without effect of bolt prying
F_{fp}	flange axial load capacity including the effect of bolt prying
F_{End}	end cap force calculated to seal ring seal diameter
F_P	required bolt preload
F_R	resulting force from external tension force F_A and external bending moment M_A
f_y	flange material yield strength at temperature
f_{yb}	bolt material yield strength at temperature
H_{Gn}	seal ring seal dimension (see Figure 13)
H_{P1}	thickness of PB, PS and OS
H_{W3}	flange thickness
H_{W5}, H_{T5}	overall length
L	bolt hole diameter
L_1, L_2, L_3	bolt hole depths (see Figure 5 and Table 22)
l	clear bolt length between engaged threads with the nuts
M_A	applied bending moment
n	number of bolts
P_t	thread pitch of bolting

p	internal pressure in N/mm ²
R	Radius
R_C	radius (maximum value tabulated)
R_{V1}	neck to flange ring radius on integral flanges
T	torque applied to the bolt
t	pipe wall thickness
t_{\min}	minimum neck thickness that can be used which is defined by the standard pipe outer diameter, A , and maximum listed bore diameter, B_{\max} .
t_{\max}	maximum neck thickness that can be used which is defined by A_{\max} and the minimum listed bore diameter
t_{015}	wall thickness giving the smallest possible face angle (0,15°)
t_{eqv}	equivalent wall thickness calculated from A_{Ceqv} over H_{W5}
W_f	Warping moment capacity of flange
X	half major ellipse axis
Y	half minor ellipse axis
α_{A2}	groove angle
α_{B1}	flange face bevel angle
α_{B2}	effective face angle/rear face bevel angle
Δ	fraction of the initially applied pre-stress lost in transfer of bolt load from tension tool to the nut
ψ	flange utilization ratio
μ_n	coefficient of friction of nut bearing surface
μ_t	coefficient of friction of bolting threads

5 Design

5.1 General

CFCs shall:

- a) be designed for face-to-face make-up for transfer of the bolt loading through the flange faces;
- b) be designed so that a static mode is maintained in the bolted joint up to 1,5 times the specified pressure/temperature rating, see 8.2. Static mode is maintained as long as the difference between maximum and minimum nominal stress sustained by the bolts in the joint does not exceed 5 % of the minimum values specified in Table 3;
- c) be standardized to cover as a minimum the same pressure temperature class designations and sizes as can be found in ASME B16.5 with equal or better performance;