

ISO/~~DIS~~**DIS** 20766-8:~~2021~~**2022**(E)

Date: 2022-~~01-13~~**10-17**

ISO TC 22/SC 41

Secretariat: UNI

**Road vehicles — Liquefied petroleum gas (LPG) fuel system components —  
Part 8: Fuel pump**

*Véhicules routiers — Équipements pour véhicules utilisant le gaz de pétrole liquéfié (GPL) comme  
combustible — Partie 8: Pompe à carburant*  
*Partie 8: Pompe à carburant*

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO 20766-8:2023

<https://standards.iteh.ai/catalog/standards/sist/fca1c922-bc33-4c53-b16c-91b6d73624c9/iso-20766-8-2023>

© ISO ~~2021~~2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO Copyright Office  
CP 401 • CH-1214 Vernier, Geneva  
Phone: + 41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)  
Published in Switzerland.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 20766-8:2023

<https://standards.iteh.ai/catalog/standards/sist/fca1c922-bc33-4c53-b16c-91b6d73624c9/iso-20766-8-2023>

<b>Contents</b>	<b>Page</b>
Foreword .....	iv
1 Scope .....	1
2 Normative references .....	1
3 Terms and definitions .....	1
4 Markings .....	2
5 Construction and assembly.....	2
6 Tests .....	3
6.1 Applicability .....	3
6.2 Hydrostatic strength.....	3
6.3 High temperature.....	4
6.4 Low temperature.....	4
<b>1 Scope .....</b>	<b>4</b>
<b>2 Normative references .....</b>	<b>4</b>
<b>3 Terms and definitions .....</b>	<b>5</b>
<b>4 Markings.....</b>	<b>5</b>
<b>5 Construction and assembly.....</b>	<b>5</b>
<b>6 Tests.....</b>	<b>6</b>
<b>6.1 Applicability.....</b>	<b>6</b>
<b>6.2 Hydrostatic strength.....</b>	<b>7</b>
<b>6.3 High temperature.....</b>	<b>7</b>
<b>6.4 Low temperature.....</b>	<b>7</b>

iTech STANDARD PREVIEW  
 (standards.iteh.ai)  
 ISO 20766-8:2022  
 91b6d73624e9/iso-20766-8-2023

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 41, *Specific aspects for gaseous fuels*.

A list of all parts in the ISO 20766 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

# Road vehicles — Liquefied petroleum gas (LPG) fuel system components — Part 8: Fuel ~~Pump~~~~pump~~

## 1 Scope

This document specifies general requirements ~~and definitions~~ for the fuel pump component of liquefied petroleum gas fuel, intended for use on the types of motor vehicles as defined in ISO 3833. It also provides general design principles, and specifies requirements for instructions and marking.

This document is applicable to vehicles (mono-fuel, bi-fuel or dual-fuel applications) using gaseous fuels in accordance with ISO 9162. It is not applicable to the following:

- a) fuel containers;
- b) stationary gas engines;
- c) container mounting hardware;
- d) electronic fuel management;
- e) refuelling receptacles.

It is recognized that miscellaneous components not specifically addressed herein can be examined for compliance with the criteria of any applicable part of the ISO 20766 series, including testing to the appropriate functional tests.

All references to pressure in this document are considered gauge pressures unless otherwise specified.

This document applies to device which have a service pressure in the range of 110 kPa (butane rich at 20 °C) and 840 kPa (propane rich at 20 °C), hereinafter referred to in this document. Other service pressures can be accommodated by adjusting the pressure by the appropriate factor (ratio).

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 20766-1, *Road vehicles — Liquefied petroleum gas (LPG) fuel systems components — Part 1: General requirements and definitions*

ISO 20766-2, *Road vehicles — Liquefied petroleum gas (LPG) fuel systems components — Part 2: Performance and general test methods*

IEC 60529, *Degrees of protection provided by enclosures (IP Code)*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 20766-1 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

## **4 Markings**

Every fuel pump shall bear, the following clearly legible and indelible identification markings consisting of characters, figures or symbols:

- a) the manufacturer's or agent's name, trademark or symbol;
- b) the model designation (part number);
- c) the working pressure and temperature range;
- d) the year and month of fabrication.

The following additional markings are recommended:

- the direction of flow (when necessary for correct installation);
- the type of fuel;
- electrical ratings (if applicable);
- the symbol of the certification agency;
- the type approval number;
- the serial number or date code;
- a reference to this document, i.e. ISO 20766-8.

## **5 Construction and assembly**

**5.1** The fuel pump shall be designed to withstand the maximum operating pressure as applicable.

**5.2** The fuel pump shall be designed to withstand a temperature between the minimum operating temperature and the maximum operating temperature as defined in ISO 20766-1.

**5.3** ~~Electrically-operated fuel pumps containing LPG shall be designed and manufactured in order to prevent electrical sparking; in the event case of fracture of the component fracture. They shall, the electrically operated fuel pumps containing LPG shall:~~

- a) be insulated in a manner that no current is conducted through LPG containing parts;
- b) have the electrical system of the device isolated:
  - i) from the body;
  - ii) from the container for the fuel pump.

~~Isolation~~The isolation resistance shall be >10 MΩ.

5.4 The electrical connections of fuel pump inside the boot and passenger's compartment if any shall comply with protection degree class IP 40 according to IEC 60529.

5.5 Fuel pumps with liquid LPG at a pressure  $\leq 3\ 000$  kPa shall be designed so that the outlet pressure never exceeds 3 000 kPa, when there is, for example, blocking of the tubing or not opening of a shut-off valve. This can be realized by switching off the pump or by recirculating to the container.

5.6 Fuel pump with liquid LPG at a pressure  $>3\ 000$  kPa shall be designed so that the outlet pressure never exceeds the working pressure of the components downstream of the pump, when there is, for example, blocking of the tubing or not opening of a shut-off valve. This can be realised by switching off the pump or by recirculation to the container.

## 6 Tests

### 6.1 Applicability

The tests required to be carried out are indicated in Table 1.

**Table 1 — Applicable tests**

Test	Applicable	Test procedure as required by ISO 20766-2	Specific test requirements of this document
Hydrostatic strength	X	X	X (see 6.2)
External leakage	X	X	
High temperature	X		X (see 6.3)
Low temperature	X		X (see 6.4)
Non-metallic material immersion (LPG compatibility)	X <sup>a</sup>	X	
Corrosion resistance	X <sup>a</sup>	X	
Resistance to dry heat	X <sup>a</sup>	X	
Ozone ageing	X <sup>a</sup>	X	
Creep	X <sup>a</sup>	X	
Temperature cycle	X <sup>a</sup>	X	
<sup>a</sup> —Only if applicable. A fuel pump mounted inside the container shall undergo LPG compatibility test only if it is already tested for other applicable tests along with container. <sup>a</sup> Only if applicable.			

### 6.2 Hydrostatic strength

Test the fuel pump according to the procedure for testing hydrostatic strength specified in ISO 20766-2. The test pressure shall be 2,25 times the working pressure.