
**Information security — Redaction of
authentic data —**

**Part 1:
General**

Sécurité de l'information — Rédaction de données authentifiées —

Partie 1: Généralités
iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 23264-1:2021

<https://standards.iteh.ai/catalog/standards/sist/fl e3e300-a08c-4aea-b669-9108cc01c578/iso-iec-23264-1-2021>



iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 23264-1:2021](https://standards.iteh.ai/catalog/standards/sist/f1e3e300-a08c-4aea-b669-9108cc01c578/iso-iec-23264-1-2021)

<https://standards.iteh.ai/catalog/standards/sist/f1e3e300-a08c-4aea-b669-9108cc01c578/iso-iec-23264-1-2021>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier; Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and conventions	5
4.1 Symbols.....	5
4.2 Conventions.....	5
5 General model and processes	5
5.1 General.....	5
5.2 Parties and processes.....	5
5.3 General model.....	6
5.4 Specification of processes.....	7
5.4.1 Key generation process.....	7
5.4.2 Redactable attestation process.....	7
5.4.3 Redaction process.....	8
5.4.4 Verification process.....	8
6 Cryptographic properties of redactable attestation schemes	9
6.1 Required cryptographic properties.....	9
6.1.1 Correctness.....	9
6.1.2 Unforgeability.....	9
6.1.3 Privacy.....	9
6.2 Optional cryptographic properties.....	10
6.2.1 Undetectability of redactions.....	10
6.2.2 Detectability of redactions.....	10
6.2.3 Unlinkability of redactions.....	10
6.2.4 Disclosure control.....	10
6.2.5 Consecutive redaction control.....	10
6.2.6 Mergeability.....	10
Bibliography	11

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see <http://patents.iec.ch>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 27, *Information security, cybersecurity and privacy protection*.

A list of all parts in the ISO/IEC 23264 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Digital attestation schemes, in particular digital signature schemes or message authentication codes, can be used to provide data integrity and data origin authentication. A redactable attestation scheme enables the attestation of a message in such a way that, if certain parts of the attested message (known as fields) are redacted (erased, blanked out or permanently removed), the attestation of the redacted message can still be verified. More precisely, upon attesting a message, the attestor knowing the private attestation key can define which parts of the message can later be redacted (in the sense of ISO/IEC 27038) by any entity only knowing the message, the attestation, and the attestor's redaction key. Any other modification of the attested message (e.g. redaction of other message parts or insertion/modification of any parts) invalidates the attestation.

Redactable attestation schemes are a basic building block in many privacy-preserving applications, such as privacy-preserving data sharing or authentication, where an entity can decide to only reveal the information that is absolutely necessary to forward to a receiver, while the latter is still assured that the received information was previously attested, e.g. by a public authority.

The goal of the ISO/IEC 23264 series is to remedy existing incompatibilities or inconsistently defined properties in existing specifications of such schemes, and to ease the real-world adoption of this technology. Specifically, the goal of this document is to lay the foundations for subsequent parts (e.g. focusing on concrete algorithms for the authenticity-preserving redaction of specific document formats like text, pictures, video, etc.) by specifying and defining common terminology and properties for such schemes.

The ISO/IEC 23264 series complements ISO/IEC 27038, which specifies the redaction of digital documents without addressing the authenticity of the data.

ITeH STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 23264-1:2021
<https://standards.iteh.ai/catalog/standards/sist/fl e3e300-a08c-4aea-b669-9108cc01c578/iso-iec-23264-1-2021>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 23264-1:2021](https://standards.iteh.ai/catalog/standards/sist/f1e3e300-a08c-4aea-b669-9108cc01c578/iso-iec-23264-1-2021)

<https://standards.iteh.ai/catalog/standards/sist/f1e3e300-a08c-4aea-b669-9108cc01c578/iso-iec-23264-1-2021>

Information security — Redaction of authentic data —

Part 1: General

1 Scope

This document specifies properties of cryptographic mechanisms to redact authentic data. In particular, it defines the processes involved in those mechanisms, the participating parties, and the cryptographic properties.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>
<https://standards.iso.org/standards/catalog/standards/siv/iec/3500-a08c-4aea-b669-9108cc01c578/iso-iec-23264-1-2021>

3.1

admissible changes

description of all possible modifications of a *message* (3.12) attested with a *redactable attestation scheme* (3.16) that can be applied within the *redaction process* (3.23) without invalidating the resulting *redacted attestation* (3.18)

Note 1 to entry: The set of admissible changes is called non-trivial, if the admissible changes allow for at least one modification of the original message yielding a redacted message different from the original message.

Note 2 to entry: In the context of this document, the possible modifications of a message are limited to removal of some fields of a message.

3.2

attestation key

private attestation key

secret data item specific to an *attestor* (3.4) and usable only by this entity in the *redactable attestation process* (3.15)

Note 1 to entry: Except for the term “redactable attestation process” instead of “signature process”, this definition is consistent with “signature key” as defined in ISO/IEC 14888-1:2008, 3.13.

3.3

attested message

set of data items consisting of the *redactable attestation* (3.14), the *admissible changes* (3.1) and the *fields* (3.10) of the *message* (3.12) which are attested

Note 1 to entry: Depending on the instantiation, if not all admissible changes are part of the attested message, then at least those admissible changes that are relevant for the verification process can be reconstructed from the redactable attestation in combination with the fields of the message which are attested and the verification key.

3.4

attestor

entity using its *private attestation key* (3.2) to perform the *redactable attestation process* (3.15), producing an *attested message* (3.3)

3.5

confidentiality

property that information is not made available or disclosed to unauthorized individuals, entities or processes

[SOURCE: ISO/IEC 7498-2:1989, 3.3.16, modified — The article has been removed.]

3.6

data integrity

property that data has not been altered or destroyed in an unauthorized manner

[SOURCE: ISO/IEC 7498-2:1989, 3.3.21, modified — The article has been removed.]

3.7

digital attestation

data appended to, or a cryptographic transformation of, a *message* (3.12) that allows a recipient of the data to verify the source and *data integrity* (3.6) of the *message* (3.12)

3.8

domain

set of entities operating under a single security policy

Note 1 to entry: In the context of this document, a domain contains all participating attestors, redactors and verifiers.

[SOURCE: ISO/IEC 14888-1:2008, 3.4, modified — Note 1 to entry has been added.]

3.9

domain parameter

data item which is common to and known by or accessible to all entities within the *domain* (3.8)

[SOURCE: ISO/IEC 14888-1:2008, 3.5, modified — The article has been removed.]

3.10

field

sub-string of any length of the *message* (3.12)

3.11

key generation process

process for generating cryptographic keys

3.12

message

string of bits of any length

Note 1 to entry: In the context of this document, the message is always composed of one or several field(s). The exact composition and a decomposition is always obtainable from the message.

[SOURCE: ISO/IEC 14888-1:2008, 3.10, modified — Note 1 to entry has been added.]

3.13

modification instruction

instruction that describes the message redaction, i.e. how a *message* (3.12) is to be redacted by the *redactor* (3.24) within a *redaction process* (3.23)

Note 1 to entry: Modification instructions are called non-trivial if the message input to, and the message obtained by, the redaction process are not identical.

3.14**redactable attestation
redactable digital attestation**

data resulting from the redactable attestation process that is appended to a *message* (3.12) that allows a recipient of this data to verify the source and integrity of the *message* (3.12)

Note 1 to entry: This string of bits may have an internal structure that is specific to the attestation mechanism.

3.15**redactable attestation process**

process which takes as inputs the *message* (3.12), the *private attestation key* (3.2), the *admissible changes* (3.1) and the *domain parameters* (3.9), and which outputs a *redactable attestation* (3.14)

3.16**redactable attestation scheme**

set of processes that achieves *digital attestation* (3.7) and supports the creation and verification of *redactable attestations* (3.14) together with a *redaction process* (3.23)

3.17**redacted admissible changes**

admissible changes (3.1) that are the output of the *redaction process* (3.23)

Note 1 to entry: The redacted admissible changes are derived during the redaction process from the given admissible changes by applying modification instructions.

3.18**redacted attestation
redacted digital attestation**

attestation resulting from applying the *redaction process* (3.23) at least once with some *modification instructions* (3.13)

Note 1 to entry: This string of bits may have an internal structure that is specific to the attestation mechanism.

3.19**redacted attested message**

set of data items resulting from the *redaction process* (3.23) which consists of the *redacted attestation* (3.18), the *redacted admissible changes* (3.17) and the *redacted message* (3.20) composed from those *fields* (3.10) that have not been subject to any redaction

Note 1 to entry: Depending on the instantiation, if not all redacted admissible changes are part of the redacted attested message, then at least those redacted admissible changes that are relevant for the verification process can be reconstructed from the redacted attestation in combination with the redacted message and the verification key.

3.20**redacted message**

message (3.12) that is the output from the *redaction process* (3.23)

3.21**redaction**

removal of a *field* (3.10) such that it results in the irreversible and permanent removal of information contained within that field from the *message* (3.12)

Note 1 to entry: The removal of a field only removes the information contained within that field. Information that can be derived from other fields of the message or from other sources is not removed.

3.22

redaction key

set of public data elements which is related to an attester's (3.4) *private attestation key* (3.2) and which is used by the *redactor* (3.24) in the *redaction process* (3.23)

Note 1 to entry: Depending on the instantiation, the redaction key may be private or public. In any case, knowledge of the redaction key does not result in information about the attester's private attestation key.

3.23

redaction process

process which takes as inputs the *attested message* (3.3), the *domain parameters* (3.9), the *redaction key* (3.22) and the *modification instructions* (3.13), and which outputs a *redacted attested message* (3.19) by applying the given modification instructions

Note 1 to entry: The input to the redaction process may be an attested message or a redacted attested message obtained by one (or potentially multiple) previous application(s) of a redaction process.

Note 2 to entry: The admissible changes are implicitly provided as inputs as part of the attested message.

Note 3 to entry: It is only possible to create a redacted attestation which will be verifiable using the attester's verification key, if a given set of modification instructions are in accordance with the attester-specified admissible changes.

3.24

redactor

entity that carries out the *redaction process* (3.23)

3.25

verification key

set of data elements which is related to an attester's *private attestation key* (3.2) and which is used by the *verifier* (3.27) in the *verification process* (3.26)

Note 1 to entry: Depending on the instantiation, the verification key may be private or public. In the case of a public verification key, knowledge of the verification key cannot be used to deduce information about the attester's private attestation key.

3.26

verification process

process which:

- takes as input the *attested* (potentially redacted) *message* (3.13), consisting of the (potentially redacted) *message* (3.12), the (potentially redacted) *admissible changes* (3.1) and the (potentially redacted) *redactable attestation* (3.14), the *verification key* (3.25) and the *domain parameters* (3.9);
- checks whether the given attestation is a valid attestation for the given message under the given verification key; and
- gives as output the result of the attestation verification: valid or invalid

Note 1 to entry: It is only possible to output valid if the modification instructions that have been applied in one (or potentially many) application (s) of the redaction process are in accordance with the attester-specified admissible changes.

Note 2 to entry: Depending on the instantiation, if not all the (potentially redacted) admissible changes are part of the attested (potentially redacted) message, then at least those (potentially redacted) admissible changes that are relevant for the verification process can be reconstructed from the (potentially redacted) attestation in combination with the (potentially redacted) message and the verification key.

3.27

verifier

entity that performs the *verification process* (3.26)