# INTERNATIONAL STANDARD



First edition 2021-10

# Road vehicles — Vehicle interface for electronic Periodic Technical Inspection (ePTI) —

Part 3: Data definitions

iTeh STVéhicules routiers — Interface de véhicule pour le contrôle technique périodique électronique (ePTI) — Stante 3: Définition des données

<u>ISO 20730-3:2021</u> https://standards.iteh.ai/catalog/standards/sist/87b4f6e9-a14c-4366-b8a4ceee8398a028/iso-20730-3-2021



Reference number ISO 20730-3:2021(E)

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 20730-3:2021</u> https://standards.iteh.ai/catalog/standards/sist/87b4f6e9-a14c-4366-b8a4ceee8398a028/iso-20730-3-2021



#### **COPYRIGHT PROTECTED DOCUMENT**

#### © ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Page

# Contents

Forev	word	iv
Intro	duction	<b>v</b>
1	Scope	1
2	Normative references	
3	Terms and definitions	
4	Symbols and abbreviated terms4.1Symbols4.2Abbreviated terms	
5	Informative guidance for considering ePTI relevance	2
6	ePTI-relevant system list, DIDs and RIDs	3
Anne	x A (normative) ePTI-relevant system list	4
Anne	<b>x B</b> (normative) <b>DID definitions</b>	9
Anne	x C (normative) Routine definitions	
Anne	x D (normative) Templates for proposed identifiers and names	
Biblic	ography	

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 20730-3:2021</u> https://standards.iteh.ai/catalog/standards/sist/87b4f6e9-a14c-4366-b8a4ceee8398a028/iso-20730-3-2021

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="https://www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. (standards.iteh.ai)

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 31, *Data communication*.

https://standards.iteh.ai/catalog/standards/sist/87b4f6e9-a14c-4366-b8a4-

A list of all parts in the ISO 20730 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

## Introduction

Roadworthiness testing is a part of a wider regime designed to ensure that vehicles are kept in a safe and environmentally acceptable condition during their use. This regime covers periodic roadworthiness testing of vehicles and technical roadside inspections of vehicles used for commercial road transport activities and provides a vehicle registration procedure allowing for the suspension of a vehicle's authorization to be used in road traffic where the vehicle constitutes an immediate risk to road safety. Periodic testing is the main tool to ensure roadworthiness. Technical roadside inspections of commercial vehicles are merely complementary to periodic testing.

An ePTI system list, which is defined in this document, summarizes ePTI-relevant systems and specifies a defined name (system), a unique identifier (ePTI system identifier) and a description for each ePTI system. All the definitions in this document refer to this ePTI system list.

The ISO 20730 series is based on the Open Systems Interconnection (OSI) basic reference model specified in ISO/IEC 7498-1<sup>[1]</sup> and ISO/IEC 10731,<sup>[3]</sup> which structures communication systems into seven layers. When mapped on this model, the application protocol and data link framework requirements specified/ referenced in the ISO 20730 series are structured according to Figure 1.

Figure 1 illustrates a standard-based documentation concept, which consists of the following main clusters:

- vehicle diagnostic communication framework: covers all relevant basic vehicle diagnostic communication specifications of OSI layers 7, 6, and 5;
- vehicle diagnostic communication use case framework: covers the master specification, which specifies use cases und requirements of subject matter of OSI layer 7;
- presentation layer framework: covers all data relevant specifications of OSI layer 6;
- conformance tests planacoversi, the conformance tests planacoversi, tests planacoversi,
- lower OSI layer framework: covers all vehicle diagnostic protocol standards of OSI layers 4, 3, 2, and 1, which are relevant and referenced by the use case specific standard.



Figure 1 — ePTI document reference according to OSI model

# Road vehicles — Vehicle interface for electronic Periodic Technical Inspection (ePTI) —

# Part 3: Data definitions

#### 1 Scope

This document specifies ePTI-relevant system identifiers, data identifiers, routine identifiers, input/ output control identifiers, data types, CompuMethods (computations), and units.

This document describes ePTI systems' data definitions and associated technical requirements. The technical requirements of data definitions of emissions-related systems are specified in other standards, e.g. the ISO 15031 series<sup>[4]</sup>, the ISO 27145 series<sup>[5]</sup>, and SAE J1979DA.

The ePTI system list defined in this document summarizes ePTI-relevant systems and specifies a defined name (system), a unique identifier (ePTI system identifier) and a description for each ePTI-relevant system.

This document does not specify any type of test method or pass/fail criteria of the ePTI-relevant system during a PTI. (standards.iteh.ai)

#### 2 Normative references ISO 20730-3:2021

https://standards.iteh.ai/catalog/standards/sist/87b4f6e9-a14c-4366-b8a4-The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3779, Road vehicles — Vehicle identification number (VIN) — Content and structure

ISO 14229-1, Road vehicles — Unified diagnostic services (UDS) — Part 1: Application layer

ISO 20730-1, Road vehicles — Vehicle interface for electronic Periodic Technical Inspection (ePTI) — Part 1: Application and communication requirements

SAE J1979DA, Digital Annex of E/E Diagnostic Test Modes

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 14229-1, ISO 20730-1 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <a href="https://www.iso.org/obp">https://www.iso.org/obp</a>
- IEC Electropedia: available at <u>https://www.electropedia.org/</u>

**3.1** error indicates an erroneous status

#### 3.2

#### currently not available

information cannot be reported at time of request

#### 3.3

not installed

information cannot be reported because the source is physically not available

#### 4 Symbols and abbreviated terms

#### 4.1 Symbols

--- empty table cell or feature undefined

#### 4.2 Abbreviated terms

- Cvt convention
- DID data identifier
- IOID input output identifier
- IOCT input output control ITeh STANDARD PREVIEW
- LSB least significant byte
- M mandatory

# MI malfunction indicator/standards.iteh.ai/catalog/standards/sist/87b4f6e9-a14c-4366-b8a4-

(standards.iteh.ai)

- MSB most significant byte ceee8398a028/iso-20730-3-2021
- 0 optional
- RCTP routineControlType
- RCOR routineControlOptionRecord
- RID routine identifier
- SPN suspect parameter number
- TP tyre pressure
- U user optional

#### 5 Informative guidance for considering ePTI relevance

ePTI-relevant systems are all vehicle systems and components, that when not operating to their design criteria, affect the safety of the vehicle. These are vehicle systems that perform at least one of the following functions:

- a) deceleration of the vehicle;
- b) longitudinal, lateral and yaw stabilization of vehicle movements;
- c) hold the vehicle stationary;
- d) change of angle >3° on any steered wheel, while vehicle speed is  $\geq$ 15 km/h;

- e) adjustment of the intensity and/or direction of the road illumination;
- f) change of the signal image of the vehicle lighting devices, while vehicle speed is  $\geq$ 15 km/h;
- g) protecting the survival space of road users;
- h) adjustment of the behaviour of the suspension and shock absorbers;
- i) monitoring and control of tyre air pressure;
- j) adjustment of the aerodynamic devices;
- k) high voltage electrical propulsion  $\geq 60$  V;
- l) changes in visibility;
- m) hazard warning and emergency related communication;
- n) generation of external warning for, e.g. pedestrian attention in regard to electric vehicle;
- o) adjustment of the vehicle height or tilt;
- p) automatically controlled acceleration.

The criteria and definition should be updated as technology progresses.

EXAMPLE The "automatic emergency brake" vehicle system can perform the "deceleration" function and is therefore an ePTI-relevant vehicle system. NDARD PREVIEW

# 6 ePTI-relevant system list, DIDs and RIDs

The ePTI-relevant system list shall be in <u>accordance with Annex A</u>. The status of <u>Annex A</u> is normative. https://standards.iteh.ai/catalog/standards/sist/87b4f6e9-a14c-4366-b8a4-The DID definitions shall be in accordance with <u>Annex B</u>. The status of <u>Annex B</u> is normative.

The RID definitions shall be in accordance with <u>Annex C</u>. The status of <u>Annex C</u> is normative.

The templates for identifier definitions shall be in accordance with <u>Annex D</u>. The status of <u>Annex D</u> is normative.

### Annex A

(normative)

## ePTI-relevant system list

The ePTI-relevant systems are identified based on the functional criteria in <u>Clause 5</u>. <u>Table A.1</u> specifies ePTI-relevantSystemIdentifier, ePTI-relevant system name, symbolic name and ePTI system description. The symbolic names provide the possibility , for example, to make a unique reference to diagnostic description information in case a diagnostic service is not yet implemented using the ePTI-relevantSystemIdentifier as specified in this document. Symbolic names use the character set ISO 8859-1<sup>[2]</sup> in the range of  $30_{16}$  to  $39_{16}$  (0, 1, ... 9),  $41_{16}$  to  $5A_{16}$  (A, B, ... Z), and  $5F_{16}$  (\_).

ePTISys- tem-Identi- fier	ePTI-relevant system name	Symbolic name	ePTI system description
0000 <sub>16</sub>	Reserved	RESRVD	Reserved by this document for future standardization.
0001 <sub>16</sub>	Generic ePTI information	sys generic info <b>I eh STANDA</b> (standard	This "virtual" (non-safety) system can be used to report standardized information as specified in this document, e.g. VIN or the mileage of the vehicle, which may not be supported by any of the other systems in this system list.
	https:/	<u>ISO 207:</u> /standards.iteh.ai/catalog/standa ceee8398a028/is	This system is conditional. It is mandatory if standardized information, as specified in this doc- ument, is not provided by any of the other systems in this system list.
0002 <sub>16</sub>	Cornering light	SYS_CORN_LI	During cornering, an extra headlamp is activated. Operates up to 40 km/h, e.g. in accordance with ECE-R 48 <sup>[21]</sup> ; ECE-R 119 <sup>[31]</sup> .
0003 <sub>16</sub>	Adaptive cruise control	SYS_ADP_CRUISE_CTRL	The system maintains the vehicle's speed, depend- ing on the preferred speed and distance to the vehicle in front.
0004 <sub>16</sub>	Adaptive deflec- tors	SYS_ADP_DEFLECTOR	Depending on the vehicle's speed, the air deflec- tors are adjusted in order to improve driving stability.
0005 <sub>16</sub>	Airbag	SYS_AIRBAG	In case of an accident, inflatable airbags reduce the risk of injury by their absorbing effect, e.g. in accordance with ECE-R 12 <sup>[13]</sup> ; ECE-R 14 <sup>[15]</sup> ; ECE-R 16 <sup>[16]</sup> .
0006 <sub>16</sub>	Active headrest	SYS_ACT_HEADREST	The system reduces the danger of a whiplash injury in the event of a rear end collision by changing the position of the headrest towards the head.
0007 <sub>16</sub>	Active hood	SYS_ACT_HOOD	By automatically lifting the bonnet, the system ensures a larger collapsible zone in the event of an accident involving a pedestrian.
0008 <sub>16</sub>	Automatic hold function	SYS_AUTO_HOLD_FCT	The system independently holds the vehicle after stopping using the service brake and/or park- ing brake and automatically releases them when starting.
NOTE The me system.	entioned UN/ECE re	gulations are solely stated t	to clarify and/or help to understand each ePTI-relevant

#### Table A.1 — Definition of ePTI-relevant system identifiers and names

Table A.1 (	(continued)
-------------	-------------

ePTISys- tem-Identi- fier	ePTI-relevant system name	Symbolic name	ePTI system description
0009 <sub>16</sub>	Automatic head- lamp levelling	SYS_AUTO_HL_LEVEL	Depending on the load and (optional) pitch angle, the system regulates the headlamp's vertical aim, e.g. in accordance with ECE-R 121 <sup>[32]</sup> .
000A <sub>16</sub>	Automatic emer- gency brake	SYS_AUTO_EM_BRAKE	The system independently starts braking in order to avoid a collision with an obstacle or to reduce the consequences of an inevitable impact.
000B <sub>16</sub>	Anti-lock brake	SYS_ANTI_L_BRAKE	The system automatically prevents wheel-locking during braking by selective reduction of the wheel brake force, e.g. in accordance with ECE-R 13 <sup>[14]</sup> ; 71/320/EEC.
000C <sub>16</sub>	Automatic light	SYS_AUTO_LI	Depending on the ambient brightness, the system automatically switches on and off the driving light.
000D <sub>16</sub>	Electric drive	SYS_ELEC_DRIVE	Includes all propulsion systems which can propel the vehicle using electrical power, e.g. in accord- ance with ECE-R 100 <sup>[29]</sup> .
000E <sub>16</sub>	Electro mechan- ic power steering	SYS_ELEC_MECH_PWR_ STER	The supporting power for steering is generated by an electric motor.
000F <sub>16</sub>	Electronic four- wheel steering	SYS_ELEC_4 W_STER	Two axles are steered, with a steering angle greater than 3° on all steered wheels, e.g. in accordance with ECE-R 79 <sup>[22]</sup> ; ECE-R 83 <sup>[23]</sup> ; 70/311/EEC <sup>[35]</sup> .
0010 <sub>16</sub>	Electronic damping	<b>SYS_ELEC_DAMPIS.IU</b> ISO 20730-3:2021	Depending on the driving situation, the rebound and compression stage of the shock absorbers is adjusted by the system.
0011 <sub>16</sub>	Elec <b>tronic brake</b> system	SYS_aELECOBRAKE ds/sist/8 ceee8398a028/iso-20730-	A brake bedal sensor and/or pressure sensor records the braking request and calculates the optimal brake force for each wheel, so that there is optimal activation of all wheel brakes.
0012 <sub>16</sub>	Electronic sta- bility program	SYS_ELEC_STAB_PRG	The system stabilizes the vehicle or the complete vehicle train in critical, dynamic driving situa- tions, e.g. in accordance with Regulation (EC) No. 661/2009 <sup>[9]</sup> .
0013 <sub>16</sub>	High beam assist	SYS_HIGH_BEAM_AST	The system automatically activates and deac- tivates the high beam according to the driving situation and lighting conditions.
0014 <sub>16</sub>	Speed limiter	SYS_SPEED_LIM	While driving, the system prevents exceeding a defined maximum speed. Relevant, if mandatory, e.g. in accordance with ECE-R 89 <sup>[25]</sup> ; §57c German Road Traffic Act <sup>[39]</sup> ; 92/24/EEC <sup>[38]</sup> .
0015 <sub>16</sub>	Belt tensioner and belt force limiter	SYS_TENS_BELT_LIM	In the event of an accident, the seat belt is tensioned to place the passengers in a setpoint position and/or limits the belt force, electrically controlled and, thus, limits the forces acting on the persons e.g. in accordance with ECE-R 16 <sup>[16]</sup> ; ECE-R 94 <sup>[2Z]</sup> .
0016 <sub>16</sub>	Tail light switch- ing	SYS_TAIL_LI	Depending on operating status and/or failure of the illuminants, lighting functions are taken over by other luminaires.
0017 <sub>16</sub>	Reserved	RESRVD	Reserved by this document for future standardization.
NOTE The me system.	entioned UN/ECE re	gulations are solely stated t	o clarify and/or help to understand each ePTI-relevant

ePTISys- tem-Identi- fier	ePTI-relevant system name	Symbolic name	ePTI system description
0018 <sub>16</sub>	Bending light	SYS_BEND_LI	During cornering and depending on the steer- ing angle and speed, the light beam is swivelled and/or an additional headlight is activated, e.g. in accordance with ECE-R 48 <sup>[21]</sup> ; ECE-R 98 <sup>[28]</sup> ; ECE-R 112 <sup>[30]</sup> ; ECE-R 123 <sup>[33]</sup> .
0019 <sub>16</sub>	Steering assist	SYS_STER_AST	Depending on the driving situation, the steering angle is automatically changed, without interven- tion by the driver. Relevant if the steering inter- vention occurs at a speed of more than 15 km/h, e.g. in accordance with ECE-R 79 <sup>[22]</sup> .
001A <sub>16</sub>	Height levelling	SYS_HEIGHT_LEVEL	The system changes the clearance between vehicle chassis and the road.
001B <sub>16</sub>	Emergency braking signal	SYS_EM_BRAKE_SIG	During strong deceleration, hazard warning lights and/or additional luminous surfaces are activated and/or the following traffic is warned by flashing brake lights, e.g. in accordance with ECE-R 48 <sup>[21]</sup> ; ECE-R 13 <sup>[14]</sup> .
001C <sub>16</sub>	Pre-crash sys- tem	SYS_PRE_CRASH	In a critical driving situation, the vehicle is pre- pared for the crash so that the risk of injury to the passengers and/or other road users is reduced.
001D <sub>16</sub>	Tyre pressure warning	sys_tyre_pres_war (standard	The system detects loss of tyre pressure through integrated sensors and/or by implausible values for wheel speed, e.g. in accordance with Regulation (EC) No. 661/2009 <sup>[9]</sup> .
001E <sub>16</sub>	Traction control	SYS_TRACT_CTRLSO 20/3 (standards.iteh.ai/catalog/standa	The system prevents the drive wheels spinning during acceleration by applying brake force.
001F <sub>16</sub>	Superimposed steering	SYS_SU_IMP_STER	Depending on the driving situation, the system varies the transmission ratio of the steering.
0020 <sub>16</sub>	Roll over protec- tion (active)	SYS_ACT_R_O_PROTECT	In the event of an imminent rollover, support ele- ments are extended to secure the survival space, e.g. in accordance with 74/60/EEC <sup>[37]</sup> .
0021 <sub>16</sub>	Hydrogen instal- lation	SYS_HYD_INST	The hydrogen is stored in the vehicle and is used to propel the vehicle, either by combustion in an internal combustion engine or by conversion in a fuel cell with an additional electric engine.
0022 <sub>16</sub>	Start-up aid	SYS_START_UP_AID	Aids start-up, e.g. by raising the lift axle or by mo- mentarily applying brake pressure or by automatic release of the parking brake.
0023 <sub>16</sub>	Trailer stabili- zation	SYS_TRAILER_STAB	Through selective braking of the trailer by the service brakes, the complete vehicle train is stabilized.
0024 <sub>16</sub>	Endurance brake	SYS_END_BRAKE	Is an additional braking system that can maintain braking over a period of time without a significant reduction in performance, e.g. in accordance with ECE-R 13 <sup>[14]</sup> ; 71/320/EEC <sup>[36]</sup> ; 92/24/EEC <sup>[38]</sup> .
0025 <sub>16</sub>	Differential lock deactivation	SYS_DIF_LOCK_DACT	If this system is activated, the differential locks are unlocked depending on parameters (e.g. wheel slip, steering angle, speed).
NOTE The me	ntioned UN/ECE re	gulations are solely stated t	o clarify and/or help to understand each ePTI-relevant

#### Table A.1 (continued)

ePTISys- tem-Identi- fier	ePTI-relevant system name	Symbolic name	ePTI system description	
0026 <sub>16</sub>	Electronically controlled lead- ing and trailing axle	SYS_ELEC_CTRL_LT_AX	The steered axles are additional axles with elec- tronically controlled steering. The steering force is generated by a hydraulic pump or by the lateral force on the wheels.	
0027 <sub>16</sub>	Electronic steer- ing damper	SYS_ELEC_STER_DAMP	Steering damping is controlled electronically.	
0028 <sub>16</sub>	Bus stop brake	SYS_BUS_STOP_BRAKE	The system ensures the application of brake pres- sure when stationary, independent of the brake pedal activation. Buses can only start moving when the doors are closed.	
0029 <sub>16</sub>	Kneeling	SYS_KNEELING	The system allows a road vehicle to be lowered to make it easier for passengers to board and disembark.	
002A <sub>16</sub>	Steering brake	SYS_STER_BRAKE	During cornering, dosed braking is applied to one or more wheels.	
002B <sub>16</sub>	Tyre pressure control	SYS_TYRE_PRE_CTRL	According to the requirement of the driver, the system regulates the tyre pressure.	
002C <sub>16</sub>	Sliding joint stabilization	SYS_SLID_J_STAB	The articulated joint is stabilized by damping, dependent on vehicle speed, cylinder pressure of the articulated dampers, steering and articula- tion-angle.	
002D <sub>16</sub>	Reserved	RESEVPICIATOS.IU	Reserved by this document for future standardi- zation.	
002E <sub>16</sub>	Four-wheel parkingsbrakelard	SYS_4_W_PARR2BRARE2 s.iteh.ai/catalog/standards/sist/8	The system applies the maximum brake pressure in the wheel cylinders at all four wheels.	
002F <sub>16</sub>	Front-wheel locking device	SYS_FRONT_W_LOCK <sup>730-</sup>	Front wheel suspension, which permits lateral inclination of the motorbike, can be locked and unlocked by an electric actuator. Above a certain speed, it is automatically unlocked.	
0030 <sub>16</sub>	Adaptive head- lights	SYS_ADAP_HEAD_LI	The illumination of the surrounding road area and/or the direct illumination of road users in the danger area in front of the vehicle is optimized by dynamic adaption of the light beams.	
0031 <sub>16</sub>	Electrically-ac- tuated parking brake	SYS_ELEC_PARK_ BRAKE	The parking brake function is triggered or trans- mitted electronically or electromechanically.	
0032 <sub>16</sub>	Lane change assist	SYS_LANE_CH_AST	At a lane change, the system warns the driver about vehicles in the next lane and steers the vehi- cle back.	
0033 <sub>16</sub>	Lane keep assist	SYS_LANE_KEEP_AST	The system warns the driver when the vehicle is unintentionally leaving its lane and steers the vehicle back.	
0034 <sub>16</sub>	Automatic eCall	SYS_AUTO_ECALL	The system is triggered automatically by in-vehicle sensors or manually, it transmits a minimum set of data (EN 15722) via mobile communication net- work and establishes an audio connection based on the (emergency) number between the vehicle passengers and the public safety answering point, see Regulation (EU) 2015/758 <sup>[10]</sup> .	
NOTE The mentioned UN/ECE regulations are solely stated to clarify and/or help to understand each ePTI-relevant system.				

ePTISys- tem-Identi- fier	ePTI-relevant system name	Symbolic name	ePTI system description	
0035 <sub>16</sub>	Active roll stabi- lization	SYS_ACT_ROLL_STAB	Via appropriate actuators the system produces a roll moment which encounters the vehicle roll movement depending on the current driving situ- ation.	
0036 <sub>16</sub>	Camera monitor	SYS_CAM_MONITOR	The system which generates at least a part of the indirect field of vision by a camera monitor combination (e.g. in accordance with ECE-R $46^{[20]}$ ).	
0037 <sub>16</sub>	Acoustic vehicle alerting	SYS_ACO_VE_ALERTING	At low speed, the system generates an external, specific sound in order to warn, e.g. pedestrians.	
0038 <sub>16</sub>	Basic exterior lights	SYS_EXTER_LI	The system switches on/switches off the basic lighting devices (e.g. indicators).	
0039 <sub>16</sub>	Automated lane keeping system (ALKS)	SYS_AUTO_LANE_KEEP	A system which is activated by the driver and which keeps the vehicle within its lane by con- trolling the lateral and longitudinal movements of the vehicle for extended periods without the need for further driver input.	
003A <sub>16</sub>	Turning assis- tant	SYS_TURN_ASSIST	A system to inform the driver of a possible colli- sion with a traffic participant (e.g. bicycle) near side (e.g. in accordance with ECE-R 151 <sup>[34]</sup> ).	
003B <sub>16</sub>	Tachograph I	SystachographDA (standard	A system to record the driving time, breaks, rest periods as well as periods of other work undertak- en by a driver, for example, required by Regulation (EU) No 165/2014 <sup>[8]</sup> .	
003C <sub>16</sub> to EFFF <sub>16</sub>	Reserved https:/	RESRVD ISO 2073 (standards.iteh.ai/catalog/standa	Reserved by this document for future standardi- Reserved by the stand	
F000 <sub>16</sub> to FFFE <sub>16</sub>	Reserved for vehicle manufac- turer use	RESRVD_VM	Reserved for vehicle manufacturer use.	
FFFF <sub>16</sub>	Reserved	RESRVD	Reserved by this document, not available for ePTI system identifier assignment.	
NOTE The mentioned UN/ECE regulations are solely stated to clarify and/or help to understand each ePTI-relevant system.				

#### Table A.1 (continued)

## Annex B (normative)

## **DID definitions**

#### **B.1 Definition of DIDs and names**

<u>Table B.1</u> specifies the DID #, DID name, symbolic name, and definition. The symbolic names provide the possibility, e.g. to make a unique reference to diagnostic description information in case a diagnostic service is not yet implemented using the DIDs and computation methods specified in this document. Symbolic names use the character set ISO  $8859 \cdot 1^{[2]}$  in the range of  $30_{16}$  to  $39_{16}$  (0, 1, ... 9),  $41_{16}$  to  $5A_{16}$  (A, B, ... Z), and  $5F_{16}$  (\_).

REQ	7.1 Definition of DIDs and names
DID im	plementation in ePTI-relevant ECU(s) shall be in accordance with <u>Table B.1</u> .

The accuracy of the sensor values identified by the DID might have a different resolution as specified in this document.

DID #	DID name	St Symbolic name it (	h.ai) Definition	Cvt <sup>a</sup>	
FA19 <sub>16</sub>	ISO edition number	DID_ISO_ED_NUM ISO 20730-3:2021	Description, definition and requirements are specified in <u>B.3</u> .	М	
FA20 <sub>16</sub>	Supported PFI/dataards.i identifiers	DID <u>SUPE</u> DIDlards/sist/8 ceee8398a028/iso-20730-	<b>DÍDS are specified in t</b> his table. 3-2021	М	
FA21 <sub>16</sub>	Supported ePTI systems	DID_SUPP_SYS	Description, definition and requirements for the ePTISystem identifiers are specified in <u>B.4</u> and <u>Annex A</u> .	М	
FA22 <sub>16</sub>	Supported ePTI routine identifiers	DID_SUPP_RID	Routine identifiers are specified in <u>Annex C</u> .	М	
FA23 <sub>16</sub>	Supported ePTI input/ output control identifi- ers	DID_SUPP_IOCT_DID	Input/output identifiers are specified in <u>Annex D</u> .	М	
FA24 <sub>16</sub>	ePTI system status	DID_SYS_STATUS	Description, definition and requirements are specified in <u>B.10</u> .	М	
FA25 <sub>16</sub>	Seat belt buckle	DID_SEAT_BELT_BUC	Description, definition and requirements are specified in <u>B.11</u> .	0	
FA26 <sub>16</sub>	Hydraulic brake pres- sure	DID_HYD_BRK	Description, definition and requirements are specified in <u>B.12</u> .	0	
FA27 <sub>16</sub>	Air brake pressure	DID_AIR_BRK	Description, definition and requirements are specified in <u>B.13</u> .	0	
FA28 <sub>16</sub>	Tyre pressure	DID_TYRE_PRESS	Description, definition and requirements are specified in <u>B.14</u> .	0	
FA29 <sub>16</sub>	Wheel speed	DID_WHEEL_SPD	Description, definition and requirements are specified in <u>B.15</u> .	0	
FA2A <sub>16</sub>	Dynamic driving values	DID_DYN_DRIVING	Description, definition and requirements of are specified in <u>B.16</u> .	0	
<sup>a</sup> See ISO 20730-1, BP7 for the condition of implementation.					

# iTebrable B.1 Definition of DIDs and names