

# DRAFT INTERNATIONAL STANDARD

## ISO/DIS 14132-3

ISO/TC 172/SC 4

Secretariat: DIN

Voting begins on:  
2020-03-13

Voting terminates on:  
2020-06-05

---

---

## Optics and photonics — Vocabulary for telescopic systems —

### Part 3: Terms for telescopic sights

*Optique et photonique — Vocabulaire relatif aux systèmes télescopiques —  
Partie 3: Termes pour lunettes de pointage*

ICS: 01.040.37; 37.020

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/b52e30f3-79ba-4fda-b19f-6e9e3ba4d67a/iso-dis-14132-3>

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.



Reference number  
ISO/DIS 14132-3:2020(E)

© ISO 2020

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/b52e30f3-79ba-4fda-b19f-6e9ef3a4d67a/iso-dis-14132-3>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Fax: +41 22 749 09 47  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
Foreword .....	iv
1 Scope .....	1
2 Normative references .....	1
3 Terms and definitions .....	1
Bibliography .....	4

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/b52e30f3-79ba-4fda-b19f-6e9e3a4d67a/iso-dis-14132-3>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 172, *Optics and photonics*, Subcommittee SC 4, *Telescopic systems*.

This third edition cancels and replaces the second edition (ISO 14132-3:2014), which has been technically revised.

The main changes compared to the previous edition are as follows:

- the term and definition "critical eye relief" was added and harmonised with "eye relief" and "eye relief range".

A list of all parts in the ISO 14132 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

# Optics and photonics — Vocabulary for telescopic systems —

## Part 3: Terms for telescopic sights

### 1 Scope

This part of ISO 14132 applies to telescopic sights used on hand-held firearms and airguns and gives terms and definitions for telescopic sights only.

The alphabetical indexes of terms that are common for all published parts of ISO 14132 are published in ISO 14132-1.

The definitions can be changed, if required, by introducing derivative attributes into them, revealing the meanings of the terms used, showing the objects covered by the scope of the notion being defined. These changes will not affect the scope and contents of this part of ISO 14132.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 14490-3, *Optics and photonics — Test methods for telescopic systems — Part 3: Test methods for telescopic sights*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <http://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

#### 3.1

##### **telescopic sight**

telescopic observational instrument which is mounted on hand-held firearms and airguns and used for sighting

#### 3.2

##### **main tube**

main body of a *telescopic sight* (3.1)

#### 3.3

##### **central tube**

in most cases slimmest part of a *telescopic sight* (3.1) located between eyepiece and objective cell

#### 3.4

##### **objective tube**

straight, mostly cylindrical part of the *main tube* (3.2) in which the objective housing is mounted

**3.5**

**parallax**

angular deviation between the *aiming points* (3.12) for on-axis and off-axis observation

**3.6**

**parallax-free distance**

object distance for which the shift between the image of an object and the axial position of the reticle becomes imperceptible for on-axis and off-axis observations

Note 1 to entry: In the above case, the angular deviation for off-axis observation is zero.

**3.7**

**elevation adjustment**

system to adjust the relative position of the object image and the reticle in vertical direction

**3.8**

**windage adjustment**

system to adjust the relative position of the object image and the reticle in horizontal direction

**3.9**

**reticle adjustment range**

independent adjustment range for the relative position of object image and the reticle in each of the two perpendicular directions for windage and elevation corrections

**3.10**

**reticle tracking**

angular deviation between the reticle adjustment axes (elevation and windage) and the axes that are defined by the reticle lines

**3.11**

**aiming mark**

structural part of the reticle which is used for aiming

Note 1 to entry: Note that besides the term "aiming mark" in some languages (but not in English) there exists a special term for the hunting style type of aiming mark, e.g. in German "Absehen", "Abkommen".

**3.12**

**aiming point**

point on an object which corresponds with the *aiming mark* (3.11)

**3.13**

**first image plane**

image plane of the objective

**3.14**

**second image plane**

image plane of the erecting system

**3.15**

**subtension value**

**subtension measure**

equivalent of a measure of the *aiming mark* (3.11) in the object plane

**3.16**

**point of impact**

point where the bullet actually hits the target

**3.17**

**shift of point of impact**

**sighting in**

action to eliminate the deviation of *point of impact* (3.16) from line of sight

**3.18****line of sight shift**

displacement of the line of sight due to zooming or focusing

**3.19****image jump**

shift of the *aiming point* (3.12) due to a toggle of the position or change in the movement direction of the magnification changer

**3.20****zoom riflescope**

*telescopic sight* (3.1) with continuously changeable magnification

**3.21****eye relief range**

distance range from the vertex of the last optical surface to the eye's pupil over that the full field of view can be seen without noticeable vignetting

Note 1 to entry: For telescopic sights an eye pupil diameter of 3 mm (representing daylight conditions) is assumed.

**3.22****eye relief**

$d_{\max}$

maximum distance from the vertex of the last optical surface to the eye's pupil at which the full field of view can still be seen without noticeable vignetting

Note 1 to entry: See ISO 14490-3:- Figure 4 .

**3.23****critical eye relief**

$d_{\text{rim}}$

minimum distance from the rim of the rifle scope's eyecup to the eye's pupil at which the full field of view can still be seen without noticeable vignetting

Note 1 to entry: See ISO 14490-3:- Figure 4 .

Note 2 to entry: The critical eye relief-distance is a significant information to ensure that the shooter's eye is far enough from the rifle scope to protect themselves from recoil injuries. This is particularly important when using high calibre rifles with a large recoil.

## Bibliography

- [1] ISO 14132-1, *Optics and photonics — Vocabulary for telescopic systems — Part 1: General terms and alphabetical indexes of terms in ISO 14132*

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/b52e30f3-79ba-4fda-b19f-6e9e3a4d67a/iso-dis-14132-3>