



SLOVENSKI STANDARD

SIST EN 300 167 V1.2.1:2003

01-december-2003

Prenos in multipleksiranje (TM) – Funkcijske karakteristike vmesnikov s hitrostjo 2048 kbit/s

Transmission and Multiplexing (TM); Functional characteristics of 2 048 kbit/s interfaces

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: EN 300 167 Version 1.2.1

<https://standards.iteh.ai/catalog/standards/sist/d095acee-5d00-4a96-953b-561e4361b58e/sist-en-300-167-v1-2-1-2003>

ICS:

33.040.20	Prenosni sistem	Transmission systems
35.200	Vmesniška in povezovalna oprema	Interface and interconnection equipment

SIST EN 300 167 V1.2.1:2003

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 167 V1.2.1:2003](https://standards.iteh.ai/catalog/standards/sist/d095acee-5d00-4a96-953b-561e4361b58e/sist-en-300-167-v1-2-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/d095acee-5d00-4a96-953b-561e4361b58e/sist-en-300-167-v1-2-1-2003>

ETSI EN 300 167 V1.2.1 (2001-09)

European Standard (Telecommunications series)

Transmission and Multiplexing (TM); Functional characteristics of 2 048 kbit/s interfaces

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 167 V1.2.1:2003](https://standards.iteh.ai/catalog/standards/sist/d095acee-5d00-4a96-953b-561e4361b58e/sist-en-300-167-v1-2-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/d095acee-5d00-4a96-953b-561e4361b58e/sist-en-300-167-v1-2-1-2003>



Reference

REN/TM-01062

Keywords

interface, transmission

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 167 V1.2.1:2003

<https://standards.iteh.ai/catalog/standards/sist/d095acee-5d00-4a96-953b-561e4361b58e/sist-en-300-167-v1-2-1-2003>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:

editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2001.
All rights reserved.

Contents

Intellectual Property Rights	4
Foreword	4
1 Scope.....	5
2 References	5
3 Definitions and abbreviations.....	5
3.1 Definitions	5
3.2 Abbreviations.....	5
4 Requirements.....	6
History	7

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 167 V1.2.1:2003](https://standards.iteh.ai/catalog/standards/sist/d095acee-5d00-4a96-953b-561e4361b58e/sist-en-300-167-v1-2-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/d095acee-5d00-4a96-953b-561e4361b58e/sist-en-300-167-v1-2-1-2003>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Transmission and Multiplexing (TM).

The present document aims at providing inter-vendor and inter-operator compatibility for synchronous frame structures based on ITU-T Recommendations G.704 [1] used at primary hierarchical levels and G.706 [2] on frame alignment and Cyclic Redundancy Check (CRC) procedures relating to basic frame structures defined in ITU-T Recommendation G.704 [1].

The conformance testing requirements corresponding to the specifications contained in the present document are to be specified in a different EN.

iTeh STANDARD PREVIEW

(standards.iteh.ai)

National transposition dates

Date of adoption of this EN:	SIST EN 300 167 V1.2.1:2003	31 August 2001
Date of latest announcement of this EN (doa):	https://standards.iteh.ai/catalog/standards/sist/d095acee-5d00-4a96-953b-36c4931b58e/sist-en-300-167-v1-2-1-2003	30 November 2001
Date of latest publication of new National Standard or endorsement of this EN (dop/e):		31 May 2002
Date of withdrawal of any conflicting National Standard (dow):		31 May 2002

1 Scope

The present document describes the synchronous frame structures and Cyclic Redundancy Check (CRC) relevant to 2 048 kbit/s interfaces based on ITU-T Recommendation G.704 [1].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

- [1] ITU-T Recommendation G.704 (1998): "Synchronous frame structures used at 1544, 6312, 2048, 8448 and 44 736 kbit/s hierarchical levels".
- [2] ITU-T Recommendation G.706 (1991): "Frame alignment and cyclic redundancy check (CRC) procedures relating to basic frame structures defined in Recommendation G.704"
- [3] ITU-T Recommendation G. 703: "Physical/electrical characteristics of hierarchical digital interfaces".

(standards.iteh.ai)

3 Definitions and abbreviations

<https://standards.iteh.ai/catalog/standards/sist/d095acee-5d00-4a96-953b-561e4361b58e/sist-en-300-167-v1-2-1-2003>

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

N = normative: requirements with which it is necessary to comply in order to be able to claim compliance with the present document

NOTE Therefore, functions and features in clauses of ITU-T Recommendation G. 703 [3], stated as being normative in the present document, shall be implemented and followed even if the text is given as a recommendation or an example.

I = informative: text provided for information only

NOTE: Titles for clauses are marked as informative when the requirements are given in further clauses.

N/R = not relevant: clause which is not relevant to the present document

3.2 Abbreviations

For the purposes of the present document, the following abbreviation applies:

CRC Cyclic Redundancy Check

4 Requirements

Table 1: Modifications and statements to ITU-T Recommendation G.704 [1]

Clause	Title	Statement
1	General	N
2	Basic frame structures	I
2.1	Basic frame structure at 1 544 kbit/s	N/R
2.2	Basic frame structure at 6 312 kbit/s	N/R
2.3	Basic frame structure at 2 048 kbit/s	N
2.4	Basic frame structure at 8 448 kbit/s	N/R
2.5	Basic frame structure at 44 736 kbit/s	N/R
3	Characteristics of frame structures carrying channels at various bit rates in 1 544 kbit/s	N/R
4	Characteristics of frame structures carrying channels at various bit rates in 6 312 kbit/s	N/R
5	Characteristics of frame structures carrying channels at various bit rates in 2 048 kbit/s interfaces	N
5.1	Interface at 2 048 kbit/s carrying 64 kbit/s channels	I
5.1.1	Frame structure	N
5.1.2	Use of other 64 kbit/s channel time slots	N
5.1.3	Signalling	N
5.2	Interface at 2 048 kbit/s carrying $n \times 64$ kbit/s	N
5.2.1	One $n \times 64$ kbit/s signal on the tributary side of a multiplex equipment	N (note)
5.2.2	One or more $n \times 64$ kbit/s signals on the multiplexed signal side of a multiplexing equipment	N (note)
6	Characteristics of frame structures carrying channels at various bit rates in 8 448 kbit/s interface	N/R
Annex A	Examples of CRC implementations using shift registers	
A.1	CRC-6 procedure for interface at 1 544 kbit/s	N/R
A.2	CRC-5 procedure for interface at 6 312 kbit/s	N/R
A.3	CRC-4 procedure for interface at 2 048 kbit/s	I
Annex B	Alphabetical list of abbreviations used in this Recommendation.	I
NOTE:	Inside the network of a network operator the time slots composing an $n \times 64$ kbit/s signal need not be contiguous.	