



Designation: D3130-03

~~Standard Specification for~~ Designation: D3130 – 11

Standard Specification for *n*-Propyl Acetate (96 % Grade)¹

This standard is issued under the fixed designation D3130; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This specification covers *n*-propyl acetate (96 % grade).

1.2 The values stated in SI units are to be regarded as the standard. ~~The values given in parentheses~~ No other units of measurement are for information only included in this standard.

1.3 The following applies to all specified limits in this standard; for purposes of determining conformance with this standard, an observed value or a calculated value shall be rounded off “to the nearest unit” in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E29.

1.4 For specific hazard information and guidance, see the supplier’s Material Safety Data Sheet for material listed in this specification.

2. Referenced Documents

2.1 *ASTM Standards*:²

D268 [Guide for Sampling and Testing Volatile Solvents and Chemical Intermediates for Use in Paint and Related Coatings and Material](#)

D1078 [Test Method for Distillation Range of Volatile Organic Liquids](#)

D1209 [Test Method for Color of Clear Liquids \(Platinum-Cobalt Scale\)](#)

D1353 [Test Method for Nonvolatile Matter in Volatile Solvents for Use in Paint, Varnish, Lacquer, and Related Products](#)

D1364 [Test Method for Water in Volatile Solvents \(Karl Fischer Reagent Titration Method\)](#)

D1476 [Test Method for Heptane Miscibility of Lacquer Solvents](#)

D1613 [Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish, Lacquer, and Related Products](#)

D3545 [Test Method for Alcohol Content and Purity of Acetate Esters by Gas Chromatography](#)

D4052 [Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter](#) ~~E1 Specification for ASTM Liquid-in-Glass Thermometers~~

D5386 [Test Method for Color of Liquids Using Tristimulus Colorimetry](#)

E29 [Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications](#)

E300 [Practice for Sampling Industrial Chemicals](#)

2.2 *U.S. Federal Specification*:³

PPP-C-2020 [Chemicals, Liquid, Dry, and Paste: Packaging of](#)

3. Properties

3.1 *n*-Propyl acetate shall conform to the following requirements:

¹ This specification is under the jurisdiction of ASTM Committee D01 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.35 on Solvents, Plasticizers, and Chemical Intermediates.

Current edition approved Oct. Nov. 1, 2003-2011. Published October 2003-December 2011. Originally approved in 1972. Last previous edition approved in 1995-2003 as D3130-95(2000)-D3130-03. DOI: 10.1520/D3130-03-10.1520/D3130-11.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard’s Document Summary page on the ASTM website.

³ Available from Standardization Documents Order Desk, DODSSP, Bldg. 4, Section D, 700 Robbins Ave., Philadelphia, PA 19111-5098, http://www.dodssp.daps.mil.

*A Summary of Changes section appears at the end of this standard.