

DRAFT INTERNATIONAL STANDARD

ISO/DIS 4000-1

ISO/TC 31/SC 3

Secretariat: **AFNOR**

Voting begins on:
2020-05-22

Voting terminates on:
2020-08-14

Passenger car tyres and rims —

Part 1: Tyres (metric series)

Pneus et jantes pour voitures particulières —

Partie 1: Pneumatiques (série millimétrique)

ICS: 83.160.10

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/DIS 4000-1](https://standards.iteh.ai/catalog/standards/sist/ec64218c-17b1-40e4-b4b1-7b59ac20e47c/iso-dis-4000-1)

<https://standards.iteh.ai/catalog/standards/sist/ec64218c-17b1-40e4-b4b1-7b59ac20e47c/iso-dis-4000-1>

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.



Reference number
ISO/DIS 4000-1:2020(E)

© ISO 2020

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/DIS 4000-1](https://standards.iteh.ai/catalog/standards/sist/ec64218c-17b1-40e4-b4b1-7b59ac20e47c/iso-dis-4000-1)
<https://standards.iteh.ai/catalog/standards/sist/ec64218c-17b1-40e4-b4b1-7b59ac20e47c/iso-dis-4000-1>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Designation.....	1
4.1 Size and construction.....	1
4.1.1 Characteristics.....	1
4.1.2 Nominal section width.....	2
4.1.3 Nominal aspect ratio.....	2
4.1.4 Tyre construction code.....	2
4.1.5 Nominal rim diameter code.....	2
4.2 Service description.....	3
4.2.1 General.....	3
4.2.2 Load index.....	3
4.2.3 Speed categories.....	3
4.3 Other service characteristics.....	3
5 Marking.....	6
6 Tyre dimensions.....	6
6.1 Rounding values.....	6
6.2 Calculation of design tyre dimensions.....	7
6.2.1 Theoretical rim width, R_{th}	7
6.2.2 Measuring rim width code, R_{mc}	7
6.2.3 Design tyre section width, S	7
6.2.4 Design tyre section height, H	8
6.2.5 Design tyre overall diameter, D_0	8
6.2.6 Guidelines.....	8
6.3 Calculation of maximum overall (grown) tyre dimensions in service tyre mounted on their measuring rims.....	8
6.3.1 General.....	8
6.3.2 Maximum overall (grown) width in service, W_{max}	8
6.3.3 Maximum overall (grown) diameter in service, D_{0max}	9
6.4 Calculation of minimum tyre dimensions for radial tyres mounted on their measuring rims.....	9
6.4.1 Minimum tyre section width, S_{min}	9
6.4.2 Minimum tyre overall diameter, D_{0min}	9
6.5 Range of approved rims.....	9
7 Tyre dimension measurement procedure.....	10
8 Inflation pressures.....	10
9 Load capacities.....	11
10 Choice of tyre sizes.....	11
11 Camber angle.....	12
Annex A (normative) Guideline values for metric-series tyres.....	14
Annex B (normative) Load indices for passenger car tyres.....	21
Annex C (normative) Minimum inflation pressure for intermediate load.....	40
Annex D (normative) Other existing size markings.....	48
Bibliography.....	50

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html. (standards.iteh.ai)

The committee responsible for this document is ISO/TC 31, Tyres, rims and valves, Subcommittee SC 3, Passenger car tyres and rims. ISO/DIS 4000-1

<https://standards.iteh.ai/catalog/standards/sist/ec64218c-17b1-40e4-b4b1-715d-201478-8-4000-1>

This eleventh edition of ISO 4000-1 cancels and replaces the tenth edition (ISO 4000-1:2013), which has been technically revised.

ISO 4000 consists of the following parts, under the general title *Passenger car tyres and rims*:

- Part 1: Tyres (*metric series*)
- Part 2: Rims

Passenger car tyres and rims —

Part 1: Tyres (metric series)

1 Scope

This part of ISO 4000 specifies the designation, dimensions, and load ratings of metric-series tyres primarily intended for passenger cars.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3877-1, *Tyres, valves and tubes — List of equivalent terms — Part 1: Tyres*

ISO 4223-1, *Definitions of some terms used in the tyre industry — Part 1: Pneumatic tyres*

ISO 16992, *Passenger car tyres — Spare unit substitutive equipment (SUSE)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 4223-1, ISO 3877-1¹⁾, and the following apply.

3.1

rim protector

feature incorporated into the lower sidewall area of the tyre which is intended to protect the rim flange from damage

EXAMPLE protruding circumferential rubber rib.

4 Designation

4.1 Size and construction

4.1.1 Characteristics

The tyre characteristics shall be designated as follows:

Nominal section width / Nominal aspect ratio Tyre construction code Nominal rim diameter code

EXAMPLE 235/45 R 17.

1) ISO 3877-1 gives other terms used in this field, together with their equivalents in other languages.

4.1.2 Nominal section width

The nominal section width of the tyre shall be indicated in millimetres, and this part of the designation shall end in either the numeral of zero or five, so that in any single series of tyres with the same nominal aspect ratio, the values shall all end in 0 or all end in 5.

For sizes mounted on 5° tapered (code-designated) rims, the nominal section width shall end in 5.

4.1.3 Nominal aspect ratio

The nominal aspect ratio (H/S) shall be expressed as a percentage and shall be a multiple of 5.

4.1.4 Tyre construction code

The tyre construction code shall be as follows:

- B for bias-belted construction;
- D for diagonal construction;
- R for radial construction;
- RF for radial run-flat construction (only applicable to run-flat or self-supporting tyres as defined in ISO 16992; radial extended mobility tyres as defined in ISO 16992 shall have the construction code R)

In the case of tyres having a maximum speed capability exceeding 240 km/h, the tyre construction code R can be replaced by ZR and the tyre construction code RF can be replaced by ZRF.

In the case of tyres having a maximum speed capability exceeding 300 km/h, the tyre construction code R shall be replaced by ZR and the tyre construction code RF shall be replaced by ZRF.

For maximum speed capability and load capacity of the tyre over 300 km/h consult the manufacturer.

Use of any other code-letter (for example, in the case of a new construction type) should first be submitted to ISO for acceptance.

4.1.5 Nominal rim diameter code

For tyres mounted on 5° tapered (code-designated) rims, the code shall be as given in [Table 1](#).

Table 1 — Nominal rim diameter code

Nominal rim diameter code	Nominal rim diameter Dr
	mm
10	254
12	305
13	330
14	356
15	381
16	406
17	432
18	457
19	483
20	508
21	533
22	559

Table 1 (continued)

Nominal rim diameter code	Nominal rim diameter D_r
	mm
23	584
24	610
25	635
26	660
28	711
30	762

In the case of tyres requiring new-concept rims, for safety reasons, especially concerning mounting, as an example, A-metric tyre, the code-number shall be equal to the nominal rim diameter (D_r) expressed as a whole number in millimetres.

4.2 Service description

4.2.1 General

The service description shall be as follows:

Load index Speed symbol

In the case of tyres having a maximum speed capability exceeding 300 km/h, the speed symbol Y and the load index shall be both placed within parentheses, to identify performance up to 300 km/h.

EXAMPLE 235/45 ZR 17 (97Y).

For maximum speed capability and load capacity of the tyre over 300 km/h, consult the manufacturer.

4.2.2 Load index

The maximum tyre load-carrying capacity corresponding to the service conditions specified by the tyre manufacturer shall be indicated by a load index taken from [Table 2](#), per tyre for a single mounting.

4.2.3 Speed categories

A speed category is assigned to a tyre according to the maximum speed for which its use is rated. The speed for each category shall be indicated by a letter-symbol, in accordance with [Table 3](#).

4.3 Other service characteristics

4.3.1 The word “TUBELESS” shall appear on tyres without tubes.

4.3.2 The letters “XL”, close to the tyre size designation, or the words “REINFORCED” or “EXTRA LOAD” shall appear on tyres designed for loads and inflation pressures higher than the standard version.

4.3.3 The letters “LL”, close to the tyre size designation, or the words “LIGHT LOAD” shall appear on the sidewalls of tyres designed for loads lower than the standard version.

4.3.4 The letter “T”, immediately preceding the tyre size designation, shall be used to identify T-type temporary-use spare tyres.

4.3.5 Specific indications, if required, can be added to indicate:

- the type of vehicle for which the tyre is primarily designed, using the symbol “P” for passenger cars (see 4.3.6);
- temporary use of certain spare tyres, using indications such as “TEMPORARY USE ONLY”;
- bias-belted construction, with the words “BIAS-BELTED”;
- radial construction, with the word “RADIAL”;
- direction of mounting;
- direction of rotation;
- type of tread pattern; — other characteristics.

4.3.6 The optional marking “P” can be used where there could be ambiguity regarding the tyre type. It should be positioned such that confusion cannot result from its proximity to any other service condition marking.

EXAMPLE P295/45 R 17.

Table 2 — Equivalence between load index (LI) and tyre load-carrying capacity (TLCC)

LI	TLCC kg	LI	TLCC kg	LI	TLCC kg	LI	TLCC kg
50	190	70	335	90	600	110	1 060
51	195	71	345	91	615	111	1 090
52	200	72	355	92	630	112	1 120
53	206	73	365	93	650	113	1 150
54	212	74	375	94	670	114	1 180
55	218	75	387	95	690	115	1 215

^a ISO tyre loads have a 116 load index maximum: some existing tyres can have a higher load index number.

The maximum tyre load capacity corresponding to the load index shall apply for speeds up to and including 210 km/h.

For tyres in the speed category V (between 210 km/h and 240 km/h), the maximum load capacity per tyre shall be reduced to 100 % at 210 km/h, 97 % at 220 km/h, 94 % at 230 km/h and 91 % at 240 km/h; linear interpolation is permitted.

In the case of speed categories W and Y, the maximum load capacity per tyre corresponding to the load index shall apply for speeds up to and including 240 km/h for W and 270 km/h for Y.

For tyres in the speed category W (between 240 km/h and 270 km/h), the maximum load capacity per tyre shall be reduced to 100 % at 240 km/h, 95 % at 250 km/h, 90 % at 260 km/h and 85 % at 270 km/h; linear interpolation is permitted.

For tyres in the speed category Y (between 270 km/h and 300 km/h), the maximum load capacity per tyre shall be reduced to 100 % at 270 km/h, 95 % at 280 km/h, 90 % at 290 km/h and 85 % at 300 km/h; linear interpolation is permitted.

See 4.2.3 and Table 3 for speed categories and their symbols.

For speeds of over 300 km/h or ZR-marked tyres or both, consult the tyre manufacturer for the maximum tyre load capacity permitted in relation to the maximum speed allowed for the tyre.

For vehicles with a design maximum speed capability of up to 60 km/h, the maximum load capacity corresponding to the load index can be exceeded, as shown below. However, an increase in the reference inflation pressure is necessary and should be determined in consultation with the tyre manufacturer. In the absence of such agreement, the following pressure increases are recommended:

- for 60 km/h, a 10 % load increase with a 10 kPa inflation pressure increase;
- for 50 km/h, a 15 % load increase with a 20 kPa inflation pressure increase;
- for 40 km/h, a 25 % load increase with a 30 kPa inflation pressure increase;
- for 30 km/h, a 35 % load increase with a 40 kPa inflation pressure increase;
- for 25 km/h, a 42 % load increase with a 50 kPa inflation pressure increase.

Table 2 (continued)

LI	TLCC kg	LI	TLCC kg	LI	TLCC kg	LI	TLCC kg
56	224	76	400	96	710	116	1 250
57	230	77	412	97	730	117 ^a	1 285
58	236	78	425	98	750	118 ^a	1 320
59	243	79	437	99	775	119 ^a	1 360
60	250	80	450	100	800	120 ^a	1 400
61	257	81	462	101	825	—	—
62	265	82	475	102	850	—	—
63	272	83	487	103	875	—	—
64	280	84	500	104	900	—	—
65	290	85	515	105	925	—	—
66	300	86	530	106	950	—	—
67	307	87	545	107	975	—	—
68	315	88	560	108	1 000	—	—
69	325	89	580	109	1 030	—	—

^a ISO tyre loads have a 116 load index maximum: some existing tyres can have a higher load index number.

The maximum tyre load capacity corresponding to the load index shall apply for speeds up to and including 210 km/h.

For tyres in the speed category V (between 210 km/h and 240 km/h), the maximum load capacity per tyre shall be reduced to 100 % at 210 km/h, 97 % at 220 km/h, 94 % at 230 km/h and 91 % at 240 km/h; linear interpolation is permitted.

In the case of speed categories W and Y, the maximum load capacity per tyre corresponding to the load index shall apply for speeds up to and including 240 km/h for W and 270 km/h for Y.

For tyres in the speed category W (between 240 km/h and 270 km/h), the maximum load capacity per tyre shall be reduced to 100 % at 240 km/h, 95 % at 250 km/h, 90 % at 260 km/h and 85 % at 270 km/h; linear interpolation is permitted.

For tyres in the speed category Y (between 270 km/h and 300 km/h), the maximum load capacity per tyre shall be reduced to 100 % at 270 km/h, 95 % at 280 km/h, 90 % at 290 km/h and 85 % at 300 km/h; linear interpolation is permitted.

See 4.2.3 and Table 3 for speed categories and their symbols.

For speeds of over 300 km/h or ZR-marked tyres or both, consult the tyre manufacturer for the maximum tyre load capacity permitted in relation to the maximum speed allowed for the tyre.

For vehicles with a design maximum speed capability of up to 60 km/h, the maximum load capacity corresponding to the load index can be exceeded, as shown below. However, an increase in the reference inflation pressure is necessary and should be determined in consultation with the tyre manufacturer. In the absence of such agreement, the following pressure increases are recommended:

- for 60 km/h, a 10 % load increase with a 10 kPa inflation pressure increase;
- for 50 km/h, a 15 % load increase with a 20 kPa inflation pressure increase;
- for 40 km/h, a 25 % load increase with a 30 kPa inflation pressure increase;
- for 30 km/h, a 35 % load increase with a 40 kPa inflation pressure increase;
- for 25 km/h, a 42 % load increase with a 50 kPa inflation pressure increase.

Table 3 — Speed symbols

Symbol	Speed km/h
J	100
K	110
L	120

NOTE This list is not exhaustive, and other categories and symbols might be added later.

^a For tyres designed for speeds exceeding 300 km/h, see 4.2.1.

Table 3 (continued)

Symbol	Speed km/h
M	130
N	140
P	150
Q	160
R	170
S	180
T	190
U	200
H	210
V	240
W	270
Y ^a	300

NOTE This list is not exhaustive, and other categories and symbols might be added later.

^a For tyres designed for speeds exceeding 300 km/h, see 4.2.1.

5 Marking

The marking shall include designations of the following:

- a) size and construction;
- b) service description (see 4.2.1);
- c) any other service characteristics.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/DIS 4000-1

[https://standards.iteh.ai/catalog/standards/sist/ec64218c-17b1-40e4-b4b1-](https://standards.iteh.ai/catalog/standards/sist/ec64218c-17b1-40e4-b4b1-7b59ac20e47c/iso-dis-4000-1)

[7b59ac20e47c/iso-dis-4000-1](https://standards.iteh.ai/catalog/standards/sist/ec64218c-17b1-40e4-b4b1-7b59ac20e47c/iso-dis-4000-1)

The location of the marking of the load and speed characteristics shall be distinct, but near the marking of the size and construction.

No location is specified for the markings related to other service characteristics (see 4.3).

EXAMPLE A tubeless tyre having a nominal section width of 165 mm, a nominal aspect ratio of 80, a radial construction and a nominal rim diameter code of 15, whose service description consists of a load index (LI) of 87 corresponding to a tyre load-carrying capacity of 545 kg, and which falls into the speed symbol H (210 km/h), is marked:

165/80 R 15 87 H 92

TUBELESS

NOTE See Annex D for other existing size markings.

6 Tyre dimensions

6.1 Rounding values

Except in the cases given in 6.2.1 and 6.2.2, round the formula-derived values for tyre dimensions to the nearest millimetre (see ISO 80000-1, section B3, rule B).

6.2 Calculation of design tyre dimensions

6.2.1 Theoretical rim width, R_{th}

See [Formula \(1\)](#):

$$R_{th} = K_1 \times SN \quad (1)$$

where

K_1 is the rim/section width ratio;

SN is the nominal section width.

For tyres mounted on 5° rims (code-designated) with nominal rim diameter expressed by a two-figure code:

- $K_1 = 0,7$ where the tyres have a nominal aspect ratio of 50 to 95;
- $K_1 = 0,85$ where this ratio is 20 to 45.

NOTE K_1 values for other tyre and rim types will be defined in a future revision.

6.2.2 Measuring rim width code, R_{mc}

See [Formula \(2\)](#):

$$R_{mc} = \frac{K_2 \times SN}{25,4} \quad (2)$$

rounded to the nearest 0,5 rim width code, where K_2 is the rim/section width ratio coefficient.

For tyres mounted on 5° drop-centre rims with a nominal diameter expressed by a two-figure code:

- $K_2 = 0,7$ for nominal aspect ratios 95 to 75;
- $K_2 = 0,75$ for nominal aspect ratios 70 to 60;
- $K_2 = 0,8$ for nominal aspect ratios 55 and 50;
- $K_2 = 0,85$ for nominal aspect ratio 45;
- $K_2 = 0,9$ for nominal aspect ratios 40 to 30;
- $K_2 = 0,92$ for nominal aspect ratios 20 and 25.

NOTE Other values of K_2 for other tyre and rim types will be defined in a future revision.

6.2.3 Design tyre section width, S

The design tyre section width, S , is the nominal section width, SN , transferred from the theoretical rim, R_{th} , to the measuring rim width code, R_{mc} , as shown in [Formula \(3\)](#):

$$S = SN + 0,4 \times (25,4R_{mc} - R_{th}) \quad (3)$$

with R_{th} expressed in millimetres.

EXAMPLE **265/40 R17.**

$K_1 = 0,85$ (see 6.2.1) and $K_2 = 0,9$ (see 6.2.2).

$$R_{th} = K_1 \times SN = 265 \times 0,85 = 225,25 \text{ mm.}$$

$$R_{mc} = K_2 \times SN/25,4 = 0,9 \times 265/25,4 = 9,39, \text{ rounded to } 9,5.$$

$$25,4 \times R_{mc} = 25,4 \times 9,5 = 241,3 \text{ mm.}$$

$$S = SN + 0,4 (25,4 R_{mc} - R_{th}) = 265 + 0,4 (241,3 - 225,25) = 271,42, \text{ rounded to } 271 \text{ mm.}$$

6.2.4 Design tyre section height, H

The design tyre section height, H, is calculated using [Formula \(4\)](#):

$$H = SN \times \frac{H/S}{100} \frac{H/S}{100} \tag{4}$$

6.2.5 Design tyre overall diameter, D₀

The design tyre overall diameter, D₀, is calculated using [Formula \(5\)](#):

$$D_0 = D_r + 2 \times H \tag{5}$$

For those tyres having a nominal rim diameter code, use the corresponding value of D_r given in [Table 1](#).

6.2.6 Guidelines

See [Annex A](#) for general guidelines on the tyre design dimensions for the metric series of passenger car tyres mounted on 5° rims (code-designated).

6.3 Calculation of maximum overall (grown) tyre dimensions in service tyre mounted on their measuring rims

6.3.1 General

The calculation of maximum overall (grown) tyre dimensions in service for tyres mounted on their measuring rims is for use by vehicle manufacturers in designing for tyre clearance.

Calculate these dimensions with the coefficient appropriate to the design tyre section width and design tyre section height (see [Table 4](#)).

Table 4 — Coefficients for calculation of tyre dimensions

Structure	Construction code	Coefficient			
		a	b	c	d
Diagonal	D	1,1	1,08	—	—
Bias-belted	B			—	—
Radial	R	1,04	1,04	0,96	0,97
Radial run-flat					

6.3.2 Maximum overall (grown) width in service, W_{max}

The maximum overall (grown) width in service, W_{max}, includes elevation due to labelling, decorations, protective ribs or bands and rim protectors and is equal to the greater of the following values:

- the product of the design tyre section width, S, and the appropriate coefficient, a (see [Table 4](#)):

$$W_{\max} = S \times a \quad (6)$$

— the addition of 8 mm to the design tyre section width, S :

$$W_{\max} = S + 8 \quad (7)$$

If the overall (grown) width is measured at the rim protectors, an additional 8 mm is allowed. In this case, W_{\max} equals to the greater of the following values $Sa + 8$ or $S + 16$.

6.3.3 Maximum overall (grown) diameter in service, $D_{0 \max}$

See [Formula \(8\)](#):

$$D_{0 \max} = D_r + 2H \times b \quad (8)$$

See [Table 4](#) for the value of coefficient b . Hb shall be first rounded to the nearest integer before calculating the maximum overall diameter in service.

6.4 Calculation of minimum tyre dimensions for radial tyres mounted on their measuring rims

6.4.1 Minimum tyre section width, S_{\min}

See [Formula \(9\)](#):

$$S_{\min} = S \times c \quad (9)$$

See [Table 4](#) for the value of coefficient c . <https://standards.iteh.ai/catalog/standards/sist/ec64218c-17b1-40e4-b4b1-7b59ac20e47c/iso-dis-4000-1>

6.4.2 Minimum tyre overall diameter, $D_{0 \min}$

See [Formula \(10\)](#):

$$D_{0 \min} = D_r + 2H \times b \quad (10)$$

See [Table 4](#) for the value of coefficient d . Hd shall be first rounded to the nearest integer before calculating the minimum overall diameter.

6.5 Range of approved rims

The range of approved rim width codes for the nominal aspect ratio of 35 and above is calculated as the product of the nominal section width, SN , and the coefficients shown in [Table 5](#), divided by 25,4. Round the values obtained to the nearest 0,5 rim width code. For tyre sizes with a nominal aspect ratio of 30 and below, the range of approved rim width codes is the measuring rim width code $\pm 0,5$.

The maximum overall (grown) width in service, W_{\max} , and the minimum tyre section width, S_{\min} , will change by 40 % of the change in rim width code multiplied by 25,4, rounded to the nearest millimetre. However, this is not applicable to tyres which overall width is measured at the rim protectors, in which case, the change will be greater than 40 %.

Table 5 — Approved rim width codes for passenger car tyres as a function of nominal aspect ratio

Nominal aspect ratio H/S	Coefficients for calculation of approved rim width	
	min.	max.
$70 \leq H/S \leq 95$	0,65	0,85

Table 5 (continued)

Nominal aspect ratio H/S	Coefficients for calculation of approved rim width	
	min.	max.
$50 \leq H/S \leq 65$	0,7	0,9
$H/S = 45$	0,8	0,95
$35 \leq H/S \leq 40$	0,85	1
$H/S \leq 30$	measuring rim width code -0,5	measuring rim width code +0,5

7 Tyre dimension measurement procedure

The tyre dimension measurement procedure shall be as described below of the following:

- prior to measurement, mount the tyre on an approved rim, inflated to the recommended pressure given in [Table 6](#), and allow it to stand for a minimum of 24 h at normal room temperature;
- readjust the inflation pressure to the original value;
- calliper the section width and the overall width of the tyre at six points approximately equally spaced around the tyre circumference. Record the average of these measurements as section width and overall width;
- determine the tyre overall diameter by measuring its maximum circumference and dividing this by π (where $\pi = 3,141\ 6$).

STANDARD PREVIEW

Table 6 — Recommended pressures for measurement of tyre dimensions

Tyre	Pressure
Standard load and P-type light load (LL) version	180
Extra load/reinforced version	220
T-type temporary-use spare type	420

8 Inflation pressures

Correct inflation pressures are of the highest importance for driving safety.

Over-inflation causes the tyre to be more susceptible to impact damage.

Under-inflation causes over-heating and can greatly shorten the life of a tyre. It affects vehicle stability and can cause irregular wear, internal damage and, ultimately, even tyre disablement.

The effects of under-inflation are not necessarily immediate. It may be a considerable time before they occur. The pressures (cold) recommended by the tyre manufacturers in their technical documents should be regarded as a minima.

The recommended cold tyre inflation pressure for each tyre position specified by the vehicle and/or the tyre manufacturer for the intended service condition of the given vehicle shall be equal or higher than the minimum cold tyre inflation pressure, given by the tyre manufacturer or the tyre standardization body for the given service conditions.

The recommended cold tyre inflation pressure should take into account not only the tyre load-carrying capacity (see [Annex C](#)) and the high speed capability, but also the operating conditions such as maximum speed capability of the vehicle, camber angle, as well as the construction and characteristics of the vehicle.

Unless otherwise specified by the tyre manufacturer, it is recommended that the cold inflation pressure of radialtyres be limited in normal application to 350 kPa for all standard load, extra load or light load version sizes on code designated rims, irrespective of the speed symbol (see [Table 3](#)).

For normal road applications, the specified inflation pressure cannot be less than

- 140 kPa for vehicle operating speeds ≤ 160 km/h, and
- 180 kPa for vehicle operating speeds > 160 km/h.

For special applications, consult the tyre manufacturer.

NOTE Cold inflation pressure is the pressure of the tyre at ambient temperature, and does not include pressure build-up due to tyre usage.

9 Load capacities

Load indices for passenger car tyres are given in [Annex B](#).

NOTE For sizes not included in [Annex B](#), consult the National Standardization Organization.

See [Annex C](#) for tyre load-carrying capacity at various inflation pressures.

10 Choice of tyre sizes

In selecting tyres for a vehicle, the vehicle maximum load on the tyre shall not be greater than the applicable maximum load-carrying capacity of the tyre. Vehicle maximum load on the tyre is the load on an individual tyre that is determined by distributing to each axle its share of the maximum loaded vehicle mass and dividing by the number of tyres on the axle.

The vehicle normal load on the tyre shall not be greater than 88 % of the maximum load-carrying capacity of the tyre. Vehicle normal load on the tyre is the load on an individual tyre that is determined by distributing (in accordance with [Table 7](#)) to each axle its share of the curb mass, accessory mass and normal occupant mass and dividing by the number of tyres on the axle. These, and other relevant masses, are defined below.

In specific local regulations, the vehicle normal load on the tyre shall not be greater than 94 % of the load rating at the vehicle manufacturer's recommended cold inflation pressure for the tyre.

The vehicle manufacturer can specify an inflation pressure less than that corresponding to the maximum tyre load. In this case, the load on the tyre (at the corresponding vehicle loading condition) shall not exceed the tyre load capacity at the specified inflation pressure.

Maximum loaded vehicle mass is the sum of the following:

- a) curb mass;
- b) accessory mass;
- c) vehicle capacity mass; and
- d) production option mass.

Curb mass is the mass of a motor vehicle with standard equipment, including the maximum capacity of fuel, oil and coolant, and, if so equipped, of air conditioning and the additional mass of an optional engine.

Accessory mass is the combined mass (in excess of those standard items that can be replaced) of automatic transmission, power steering, power brakes, power windows, power seats, radio and heater, to the extent that these items are available as factory-installed equipment (whether installed or not).