

FINAL
DRAFT

INTERNATIONAL
STANDARD

ISO/FDIS
22932-3

ISO/TC 82

Secretariat: DIN

Voting begins on:
2023-03-03

Voting terminates on:
2023-04-28

Mining – Vocabulary —
Part 3:
Rock mechanics

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/FDIS 22932-3](https://standards.iteh.ai/catalog/standards/sist/1e783dec-1671-43dd-82da-2b622d173d7c/iso-fdis-22932-3)

<https://standards.iteh.ai/catalog/standards/sist/1e783dec-1671-43dd-82da-2b622d173d7c/iso-fdis-22932-3>

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number
ISO/FDIS 22932-3:2023(E)

© ISO 2023

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/FDIS 22932-3

<https://standards.iteh.ai/catalog/standards/sist/1e783dec-1671-43dd-82da-2b622d173d7c/iso-fdis-22932-3>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
3.1 General terms.....	1
3.2 Stress.....	2
3.3 Strain.....	7
3.4 Both stress and strain.....	9
3.5 Rock mass.....	12
3.6 Discontinuity.....	16
3.7 Anisotropy and inhomogeneity.....	25
3.8 Mechanical behaviour of rock.....	26
3.9 Physical properties of rock.....	31
Bibliography	37
Index	38

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 22932-3

<https://standards.iteh.ai/catalog/standards/sist/1e783dec-1671-43dd-82da-2b622d173d7c/iso-fdis-22932-3>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 82, *Mining*.

A list of all parts in the ISO 22932 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The ISO 22932 series has been prepared in order to standardize and to coordinate the global use of technical terms and definitions in mining, for the benefit of the experts working on different types of mining activities.

The need for the ISO 22932 series arose from the widely varying interpretation of terms used within the industry and the prevalent use of more than one synonym.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/FDIS 22932-3](https://standards.iteh.ai/catalog/standards/sist/1e783dec-1671-43dd-82da-2b622d173d7c/iso-fdis-22932-3)

<https://standards.iteh.ai/catalog/standards/sist/1e783dec-1671-43dd-82da-2b622d173d7c/iso-fdis-22932-3>

Mining – Vocabulary —

Part 3: Rock mechanics

1 Scope

This document specifies the rock-mechanics terms commonly used in mining. Only those terms that have a specific meaning in this field are included.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1 General terms

3.1.1 abrasion <https://standards.iteh.ai/catalog/standards/sist/1e783dec-1671-43dd-82da-2b622d173d7c/iso-fdis-22932-3>
rubbing and wearing away

[SOURCE: Reference [1], 235]

3.1.2 angle of repose

maximum angle with respect to the horizontal plane that the surface of a pile of a loose material will assume

[SOURCE: Reference [1], 3]

3.1.3 erosion

process whereby soil or *rock mass* (3.5.25) is loosened or dissolved and removed from any part of the earth's surface

Note 1 to entry: It includes *weathering* (3.1.8), solution and transportation.

[SOURCE: IS 11358:1987, 2.109, modified — Note 1 to entry was originally part of the definition]

3.1.4 incompetent rock

rock (3.1.5) incapable of standing in underground opening or steep slopes at the surface without support

[SOURCE: IS 11358:1987, 2.155]

3.1.5

rock

solid material forming as part of the earths' crust

3.1.6

rock material

smallest element of *rocks* (3.1.5) not cut by any *fracture* (3.6.20)

Note 1 to entry: There are always some micro-fractures in the *rocks* (3.1.5) material.

[SOURCE: IS 11358:1987, 2.253, modified — Note 1 to entry was originally part of the definition.]

3.1.7

rock mechanics

theoretical and applied science of the mechanical behaviour of *rock* (3.1.5)

[SOURCE: Reference [1], 9]

3.1.8

weathering

process of disintegration and decomposition as a consequence of exposure to the atmosphere, to chemical action, and to the action of frost, water, and heat

[SOURCE: Reference [1], 99]

3.2 Stress

iTeh STANDARD PREVIEW
(standards.iteh.ai)

3.2.1

biaxial compression

compression caused by the application of *normal stresses* (3.2.20) in two perpendicular directions

[SOURCE: Reference [1], 20]

ISO/FDIS 22932-3

<https://standards.iteh.ai/catalog/standards/sist/1e783dec-1671-43dd-82da-2b622d173d7c/iso-fdis-22932-3>

3.2.2

biaxial state of stress

state of *stress* (3.2.29) in which one of the three principal *stresses* (3.2.29) is zero

[SOURCE: Reference [1], 33]

3.2.3

coefficient of friction

μ

relating *normal stress* (3.2.20) and the corresponding critical *shear stress* (3.2.27) at which *sliding* (3.8.36) starts between two surfaces as follows:

$$\tau = \mu \cdot \sigma$$

where

τ is the shear stress;

μ is the coefficient of friction;

σ is the normal stress.

[SOURCE: Reference [1], 1]

3.2.4**cohesion**

<stress> shear resistance at zero *normal stress* (3.2.20)

Note 1 to entry: An equivalent term in *rock mechanics* (3.1.7) is intrinsic shear *strength* (3.9.31).

Note 2 to entry: Compare with *cohesion* (3.9.8).

[SOURCE: Reference [1], 72, modified — Note 1 to entry was originally part of the definition.]

3.2.5**competent ground**

rock mass (3.5.25) *strength* (3.9.31) which is higher than the ground *stresses* (3.2.29) imposed

Note 1 to entry: See Reference [4].

3.2.6**compressive stress**

normal stress (3.2.20) tending to shorten the body in the direction in which it acts

[SOURCE: Reference [1], 50]

3.2.7**critical stress**

maximum and minimum *compressive stress* (3.2.6) on the boundary of an opening

[SOURCE: IS 11358:1987, 2.75]

3.2.8**cyclical stress**

stress (3.2.29) produced by repeated stressing and de-stressing

[SOURCE: IS 11358:1987, 2.82, modified — The phrase "stress produced" has been added and "of material" was originally part of the definition.]

3.2.9**dilatancy**

property of volume increase under loading

[SOURCE: Reference [1], 75]

3.2.10**effective stress**

pore water pressure (3.9.20) in *rock* (3.1.5) as a factor affecting *rock* (3.1.5) *strength* (3.9.31)

Note 1 to entry: The effective *normal stress* (3.2.20) is generally taken equal to the difference between normal stress and the pore water pressure.

Note 2 to entry: This is strictly valid only where pores, *cracks* (3.6.11) and *fractures* (3.6.20) are interconnected.

[SOURCE: IS 11358:1987, 2.107, modified — Notes 1 and 2 to entry were originally part of the definition.]

3.2.11**finite element**

one of the regular geometrical shapes into which a figure is subdivided for the purpose of numerical *stress* (3.2.29) analysis

[SOURCE: Reference [1], 17]

3.2.12

hydraulic fracturing

method to measure the principal *stress* (3.2.29) situation by fracturing of the *rock* (3.1.5) surrounding a section of a drill hole

Note 1 to entry: The *fracture* (3.6.20) is obtained using increasing water pressure.

Note 2 to entry: See Reference [4].

3.2.13

hydrostatic pressure

state of *stress* (3.2.29) in which all the principal *stresses* (3.2.29) are equal (and there is no *shear stress* (3.2.27))

[SOURCE: Reference [1], 48]

3.2.14

incompetent ground

overstressed *rock masses* (3.5.25)

Note 1 to entry: See Reference [4].

3.2.15

inelastic deformation

portion of *deformation* (3.8.13) under *stress* (3.2.29) that is not annulled by removal of *stress* (3.2.29)

[SOURCE: Reference [1], 67]

3.2.16

keelformed overbreak

characteristic shape of overbreak caused by high, anisotropic *rock* (3.1.5) *stress* (3.2.29)

Note 1 to entry: See Reference [4].

3.2.17

Kirsch's equation

equation, which may be used for evaluating the tangential *stresses* (3.2.29) around tunnels and other underground openings

Note 1 to entry: See Reference [4].

3.2.18

k-value

ratio between horizontal and vertical *stresses* (3.2.29) within the *rock mass* (3.5.25)

Note 1 to entry: See Reference [4].

3.2.19

Mohr's envelope

envelope of a sequence of Mohr's circles representing *stress* (3.2.29) conditions at *failure* (3.6.15) for a given material

[SOURCE: Reference [1], 12]

3.2.19.1

angle of internal friction

angle of shear resistance

angle, ϕ , (degrees) between the axis of *normal stress* (3.2.20) and the tangent to the *Mohr's envelope* (3.2.19) at a point representing a given *failure* (3.6.15)-*stress* (3.2.29) condition for solid material

[SOURCE: Reference [1], 2]

3.2.20**normal stress**

stress (3.2.29) in a *rock* (3.1.5) perpendicular to the *shear stress* (3.2.27)

[SOURCE: IS 11358:1987, 2.203, modified — The phrase "(normal)" was removed of the definition]

3.2.21**primary state of stress**

state of *stress* (3.2.29) in a geological formation before it is disturbed by an opening

Note 1 to entry: Adapted from Reference [1], 46.

3.2.22**primitive stress**

virgin rock stress

ground which is in a state of equilibrium before excavation of a tunnel or any underground opening

Note 1 to entry: At this stage, the *stresses* (3.2.29) at any point within the ground are termed as "primitive", "primary" or "pre-excavation" *stresses* (3.2.29).

[SOURCE: IS 11358:1987, 2.234, modified — Note 1 to entry was originally part of the definition.]

3.2.23**plasticity**

property of a material to continue to deform indefinitely while sustaining a constant *stress* (3.2.29)

[SOURCE: Reference [1], 94]

3.2.24**relaxation**

rate of reduction of *stress* (3.2.29) in a material due to *creep* (3.8.10)

Note 1 to entry: An alternate term is *stress* (3.2.29) relaxation.

[SOURCE: IS 11358:1987, 2.240, modified — Note 1 to entry was originally part of the definition.]

3.2.25**residual stress**

stress (3.2.29) remaining in a solid under zero external *stress* (3.2.29) after some process that causes the dimensions of the various parts of the solid to be incompatible under zero *stress* (3.2.29)

EXAMPLE 1 *Deformation* (3.8.13) under the action of external *stress* (3.2.29) when some parts of the body suffer *permanent strain* (3.3.7).

EXAMPLE 2 Heating or cooling of a body in which the thermal expansion coefficient is not uniform throughout the body.

[SOURCE: Reference [1], 49, modified — EXAMPLES 1 and 2 to entry were originally part of the definition.]

3.2.26**secondary state of stress**

resulting state of *stress* (3.2.29) in the *rock* (3.1.5) around an opening

[SOURCE: Reference [1], 47, adapted]

3.2.27**shear stress**

stress (3.2.29) directed parallel to the surface element across which it acts

[SOURCE: Reference [1], 51]

**3.2.28
stability**

condition of a structure or a mass of material when it is able to support the applied *stress* (3.2.29) for a long time without suffering any significant *deformation* (3.8.13) or movement that is not reversed by the release of stress

[SOURCE: Reference [1], 15]

**3.2.29
stress**

force acting across a given surface element, divided by the area of the element as follows:

$$\sigma = \frac{F_v}{A}$$

$$\tau = \frac{F_h}{A}$$

where

σ is the *normal stress* (3.2.20);

τ is the *shear stress* (3.2.27);

F_v is the vertical force;

F_h is the horizontal force;

A is the area of element.

[SOURCE: Reference [1], 66]

**3.2.30
stress concentration factor**

ratio of tangential *stress* (3.2.29) at a particular point along the periphery and the initial stress before excavation at that point

Note 1 to entry: Stress concentration takes place when a cavity is excavated in a *rock mass* (3.5.25).

Note 2 to entry: The higher the stress concentration factor, the greater are the chances of *failure* (3.6.15) of the rock mass or *rock burst* (3.8.30).

[SOURCE: IS 11358:1987, 2.311, modified — Notes 1 and 2 to entry were originally part of the definition.]

**3.2.31
stress ellipsoid**

representation of the state of *stress* (3.2.29) in the form of an ellipsoid whose semi-axes are proportional to the magnitudes of the principal stresses and lie in the principal directions

Note 1 to entry: The coordinates of a point P on this ellipse are proportional to the magnitudes of the respective components of the stress across the plane normal to the direction OP , where O is the centre of the ellipsoid.

[SOURCE: Reference [1], 5, modified — Note 1 to entry was originally part of the definition.]

**3.2.32
tensile stress**

normal stress (3.2.20) tending to lengthen the body in the direction in which it acts

[SOURCE: Reference [1], 52]

3.2.33**thermal stress**

internal *stress* (3.2.29), caused in part by uneven heating

[SOURCE: IS 11358:1987, 2.327]

3.2.34**triaxial compression**

compression caused by the application of *normal stresses* (3.2.20) in three perpendicular directions

[SOURCE: Reference [1], 21]

3.2.35**triaxial state of stress**

state of *stress* (3.2.29) in which none of the three principal stresses is zero

[SOURCE: Reference [1], 24]

3.2.36**uniaxial compression**

unconfined compression

compression caused by the application of *normal stress* (3.2.20) in a single direction

[SOURCE: Reference [1], 19]

3.2.37**uniaxial state of stress**

state of *stress* (3.2.29) in which two of the three principal stresses are zero

[SOURCE: Reference [1], 22]

3.2.38**yield stress**

stress (3.2.29) beyond which the induced *deformation* (3.8.13) is not fully annulled after complete distressing

[SOURCE: Reference [1], 68]

3.3 Strain**3.3.1****brittleness**

material condition characterised by reduced ability to carry load as the *strain* (3.3.11) increases

Note 1 to entry: See Reference [4].

3.3.2**contraction**

linear *strain* (3.3.11) associated with a decrease in length

[SOURCE: Reference [1], 25]

3.3.3**ductility**

condition in which material can sustain permanent *deformation* (3.8.13) without losing its ability to resist load, or on the other hand for a known or particular *stress* (3.2.29) state (existing or imposed) to which a material can sustain *plastic deformation* (3.8.26) without *breaking* (3.6.7) or *rupture* (3.6.30)

Note 1 to entry: Elongation and reduction of area are common indices of ductility.