INTERNATIONAL STANDARD



INTERNATIONAL ORGANIZATION FOR STANDARDIZATION •МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ •ORGANISATION INTERNATIONALE DE NORMALISATION

Surface active agents — Detergents — Anionic-active matter hydrolyzable under alkaline conditions — Determination of hydrolyzable and non-hydrolyzable anionic-active matter

iTeh STANDARD PREVIEW (standards.iteh.ai)

First edition - 1973-12-01

ISO 2869:1973 https://standards.iteh.ai/catalog/standards/sist/e48a8c2a-c44e-4332-9402-214a8ff5f9fc/iso-2869-1973

UDC 661.185 : 543 Ref. No. ISO 2869-1973 (E)

Descriptors: surfactants, detergents, chemical analysis, determination of content, anionic-active matter, volumetric analysis, alkaline conditions.

FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO Member Bodies). The work of developing International Standards is carried out through ISO Technical Committees. Every Member Body interested in a subject for which a Technical Committee has been set up has the right to be represented on that Committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the Technical Committees are circulated to the Member Bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 2869 was drawn up by Technical Committee ISO/TC 91, Surface active agents, and circulated to the Member Bodies in August 1972.

It has been approved by the Member Bodies of the following countries 973

https://standards.iteh.ai/catalog/standards/sist/e48a8c2a-c44e-4332-9402-

Austria Ireland Belgium Japan

eland 214a Spanic/iso-2869-1973 pan Switzerland

Belgium Egypt, Arab Rep. of France

Mexico New Zealand

Turkey United Kingdom

Germany Hungary Poland Romania

U.S.S.R.

Thailand

India South Africa, Rep. of

This International Standard has also been approved by the International Union of Pure and Applied Chemistry (IUPAC).

No Member Body expressed disapproval of the document.

© International Organization for Standardization, 1973 •

Printed in Switzerland

Surface active agents — Detergents — Anionic-active matter hydrolyzable under alkaline conditions - Determination of hydrolyzable and non-hydrolyzable anionic-active matter

1 SCOPE AND FIELD OF APPLICATION

This International Standard specifies a method for the determination, in detergents, of anionic-active matter hydrolyzable under alkaline conditions.

This active matter includes dialkylsulphosuccinates and fatty acid glyceride sulphates. The method is applicable to the analysis of mixtures containing hydrolyzable and non-hydrolyzable anionic-active matter.

The molar mass of the two types of active matter must be known or previously determined, if their content is expressed as a percentage by mass.

- 4.2 Sulphuric acid, 5 N solution.
- 4.3 Sulphuric acid, 1,0 N solution.
- 4.4 Sodium hydroxide, 1,0 N standard volumetric solution.
- 4.5 Sodium lauryl sulphate, 0,004 M standard volumetric solution.
- **4.6** Benzethonium chloride, 0,004 M standard volumetric solution.

iTeh STANDARI

4.7 Phenolphthalein solution. (standards.iteh.ai)

4.8 Mixed indicator solution.

2 REFERENCE

Detergents 2869:1973 the following reagents are necessary : ISO 2271. Surface active agents -Determination of anionic-actives matters (direct atwo-phase ards/sist/e titration procedure).

- 214a8ff5f9fc/iso-284.9 1 Sodium hydroxide, 10 N solution.
 - 4.10 Sulphuric acid, 10 N solution.

3 PRINCIPLE

Titration of an aliquot portion of a sample solution with benzethonium chloride solution according to the direct two-phase titration procedure described in ISO 2271.

Hydrolysis, by refluxing under alkaline conditions of a second aliquot portion of the sample solution.

Titration of unhydrolyzed anionic-active matter with benzethonium chloride solution as before.

Calculation of the contents of hydrolyzable and non-hydrolyzable anionic-active matter from the results obtained.

4 REAGENTS

The water used shall be distilled water or water of a least equivalent purity.

In addition to the reagents mentioned in ISO 2271 and given below as a reminder:

4.1 Chloroform, ρ_{20} 1,48 g/ml, distilling between 59,5 and 61,5 $^{\circ}$ C.

5 APPARATUS

Ordinary laboratory apparatus, and

- 5.1 Conical flask, 250 ml, with a conical ground glass
- 5.2 Reflux condenser, water-cooled, with a conical ground glass joint at the bottom.

6 PROCEDURE

6.1 Determination of total anionic-active matter

Carry out the determination of total anionic-active matter present in the sample by the procedure described in ISO 2271.

6.2 Determination of hydrolyzable anionic-active matter

By means of a pipette, transfer a second aliquot portion of 25 ml of the anionic-active matter solution to the conical flask (5.1). Add, by means of a pipette, 5 ml of the sodium hydroxide solution (4.9) and a few anti-bumping granules. Attach the water-cooled reflux condenser (5.2), well washed with water, to the conical flask and reflux for 30 min. Apply heat cautiously at the start to avoid excessive foaming.

At the end of the reflux period of 30 min, allow to cool, wash down the water-cooled reflux condenser well with at least 5 ml of water, detach the conical flask, and the ground glass joints with a little water, collecting the washings in the conical flask.

Add a few drops of the phenolphthalein solution (4.7) and neutralize with the sulphuric acid solution (4.10); add most of the sulphuric acid at once and then complete the neutralization drop by drop with the sulphuric acid solution (4.3) until the solution is just colourless.

Transfer 15 ml of the chloroform (4.1) and 10 ml of the mixed indicator solution (4.8) to the conical flask, stopper and shake well.

Titrate with the benzethonium chloride solution (4.6) as described in ISO 2271.

The amount, expressed in milli-equivalents per gram, is equal to

$$\frac{V_1 \times T \times 1000}{25 \times m} = \frac{V_1 \times T \times 40}{m}$$

where

 M_1 is the molar mass of the anionic-active matter hydrolyzable under alkaline conditions;

 M_2 is the molar mass of the anionic-active matter non-hydrolyzable under alkaline conditions;

m is the mass, in grams, of the test portion;

T is the normality or the molarity of the benzethonium chloride solution (4.6);

 V_0 is the volume, in millilitres, of the benzethonium chloride solution (4.6) used for the titration of total anionic-active matter:

 V_1 is the volume, in millilitres, of the benzethonium chloride solution (4.6) used for the titration of anionic-active matter after alkaline hydrolysis.

7 EXPRESSION OF RESULTS

7.1 Calculations

iTeh STAND A.2 Repeatability VIF.W

conditions

The content, as a percentage by mass, is equal to the ai/catalog/stanmean vialue8a8c2a-c44e-4332-9402-

$$\frac{(v_0 - v_1) \times \tau \times 1000 \times M_1 \times 100}{1000 \times 25 \times m} = \frac{(v_0 - v_1) \times \tau \times M_1^{21} \times 4^{18} \text{ff5 f9fc/iso-} 2869-1973}{m}$$
7.3 Reproduc

The amount, expressed in milli-equivalents per gram, is equal to

$$\frac{(V_0 - V_1) \times T \times 1000}{25 \times m} = \frac{(V_0 - V_1) \times T \times 40}{m}$$

where the symbols have the meanings given in 7.1.2.

7.1.2 Anionic-active matter non-hydrolyzable under alkaline conditions

The content, as a percentage by mass, is equal to

$$\frac{V_1 \times T \times 1000 \times M_2 \times 100}{1000 \times 25 \times m} = \frac{V_1 \times T \times M_2 \times 4}{m}$$

7.1.1 Anionic-active matter hydrolyzable under alkaline determinations carried out on the same sample simultaneously or in rapid succession by the same analyst ISO 20sing 9the same apparatus should not exceed 2 % of the

7.3 Reproducibility

The difference between the results obtained on the same sample in two different laboratories should not exceed 4 % of the mean value.

8 TEST REPORT

The test report shall include the following particulars:

- a) the reference of the method used:
- b) the results and the method of expression used;
- c) anv unusual features noted during the determination;
- d) any operation not included in this International Standard, or regarded as optional.