



Designation: D4511 – 11

Standard Test Method for Hydraulic Conductivity of Essentially Saturated Peat¹

This standard is issued under the fixed designation D4511; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This test method covers the determination of the hydraulic conductivity (permeability) of essentially saturated, intact cylindrical specimens of peat when the hydraulic conductivity is greater than 1×10^{-7} m/s (1×10^{-5} cm/s). During the test, the specimens are contained in the core holder, or in right, regular cylindrical sections cut from the sampling tube in which they were originally obtained in the field.

1.2 Hydraulic conductivity is calculated on the basis of the measured constant flow rate through the specimen under constant head.² For verification, flow rate determinations may be made at two or more values of constant head with corresponding calculations of hydraulic conductivity.

1.3 *Units*—The values stated in SI units are to be regarded as the standard. The inch-pound units given in parentheses are mathematical conversions, which are provided for information purposes only and are not considered standard.

1.3.1 The converted inch-pound units use the gravitational system of units. In this system, the pound (lbf) represents a unit of force (weight), while the unit for mass is slugs. The converted slug unit is not given, unless dynamic ($F = ma$) calculations are involved.

1.4 All observed and calculated values shall conform to the guide for significant digits and rounding established in Practice D6026.

1.4.1 The procedures used to specify how data are collected/recorded and calculated in this standard are regarded as the industry standard. In addition, they are representative of the significant digits that should generally be retained. The procedures used do not consider material variation, purpose for obtaining the data, special purpose studies, or any considerations for the user's objectives, and it is common practice to increase or reduce significant digits of reported data to be commensurate with these considerations. It is beyond the scope

¹ This test method is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.04 on Hydrologic Properties and Hydraulic Barriers.

Current edition approved Nov. 1, 2011. Published January 2012. Originally approved in 1992. Last previous edition approved in 2006 as D4511–00(2006). DOI: 10.1520/D4511-11.

² For further information, see "Methods for Measurement of Saturated Hydraulic Conductivity," *Peat Testing Manual*, Technical Memorandum No. 125, NRC Canada, pp. 80–84.

of this standard to consider significant digits used in analysis methods for engineering design.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards*:³

D653 Terminology Relating to Soil, Rock, and Contained Fluids

D1587 Practice for Thin-Walled Tube Sampling of Soils for Geotechnical Purposes

D2434 Test Method for Permeability of Granular Soils (Constant Head)

D2974 Test Methods for Moisture, Ash, and Organic Matter of Peat and Other Organic Soils

D3740 Practice for Minimum Requirements for Agencies Engaged in Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction

D4220 Practices for Preserving and Transporting Soil Samples

D4753 Guide for Evaluating, Selecting, and Specifying Balances and Standard Masses for Use in Soil, Rock, and Construction Materials Testing

D6026 Practice for Using Significant Digits in Geotechnical Data

2.2 *NRC Document*:

Peat Testing Manual⁴

3. Terminology

3.1 *Definitions*—For common definitions of terms in this standard, refer to Terminology D653.

3.2 *Definitions of Terms Specific to This Standard*:

3.2.1 *deaerated (de-aired) water*—water in which the amount of dissolved gas (air) has been reduced.

³ For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

⁴ National Research Council of Canada, Publications Section, Building R-88, Ottawa, Canada K1A 0R6. Out of print.

*A Summary of Changes section appears at the end of this standard

3.2.2 *flow rate*—the quantity of water flowing through the test specimen in a given period of time, when subjected to a certain constant head differential.

3.2.3 *soaking*—placement of a specimen in water for the purpose of removing gas contained in the pore space, through buoyancy, and replacement with water to cause saturation of the specimen. This method of saturation does not effectively remove all the gas contained in the specimen and does not prevent the continuous slow formation of gas from decomposition under anaerobic conditions.

4. Significance and Use

4.1 Values of hydraulic conductivity determined by this test method may be useful in making rough preliminary estimates of the initial rates of drainage and compression of peat deposits when the only effective stress increase on the deposit is that resulting from a moderate, gradual lowering of the water table.

4.2 Even under light, sustained loads, peat will undergo dramatic volume changes that influence (decrease) the hydraulic conductivity of the deposit by several orders of magnitude. This test method does not offer provisions for the determination of the relationship between hydraulic conductivity and the void ratios corresponding to increasing stress levels. Therefore, this test method is not suitable for applications involving grade increases, such as embankment construction or placement of access berms alongside drainage ditches.

4.3 Undisturbed specimens from apparently homogeneous peat deposits at the same location often exhibit significantly different hydraulic conductivity properties due to variations in material composition and sampling procedure.

NOTE 1—The quality of the result produced by this standard is dependent on the competence of the personnel performing it, and the suitability of the equipment and facilities used. Agencies that meet the criteria of Practice D3740 are generally considered capable of competent and objective testing/sampling/inspection/etc. Users of this standard are cautioned that compliance with Practice D3740 does not in itself ensure reliable results. Reliable results depend on many factors; Practice D3740 provides a means of evaluating some of those factors.

5. Interferences

5.1 Due to the generally fibrous texture and extremely high compressibility of peat, present sampling technologies may not be able to obtain samples truly representative of the in situ conditions. Disturbance caused by sampling and specimen preparation as well as heterogeneity existing in situ may cause the hydraulic conductivity determined using this method to be significantly different than the in situ hydraulic conductivity.

5.2 There are no provisions in this test method for verification of compliance with the fundamental test conditions listed in 6.1.1 and 6.1.2. The assumption is made that these conditions are satisfied if the flow rate, with time, is a linear relationship.

5.3 The result of the test may be influenced by flow through open passages between the specimen and the rigid wall of the specimen container. If such a condition is suspected or visually verified, notice thereof should be made in the test report.

6. Fundamental Test Conditions

6.1 The following ideal test conditions are prerequisite for laminar flow of water through porous media under constant-head conditions:

6.1.1 Continuity of flow with no volume change during a test,

6.1.2 Flow with the void space saturated with water and no air bubbles in the voids,

6.1.3 Flow in the steady state with no changes in hydraulic gradient, and

6.1.4 Direct proportionality of flow velocity with hydraulic gradients below certain values, after which flow becomes turbulent.

6.2 All other types of flow involving partial saturation of void space, turbulent flow, and unsteady state of flow are transient in character and yield variable and time-dependent values of hydraulic conductivity; therefore, they require special test conditions and procedures.

7. Apparatus

7.1 *Flow Device*—The flow device shall be as shown in Fig. 1, fitted with the following components:

7.1.1 *Constant-Head Filter Tank*, as shown in Fig. 1 of Test Method D2434, to supply water and to remove most of the air from the water. The tank shall be fitted with a suitable siphon.

NOTE 2—Alternatively, deaerated water may be used, supplied from a self-siphoning burette with attached inverted flask (minimum 750-mL capacity), filled with deaerated water, and closed with a rubber stopper holding a tube, 150 cm (6 in.) long with the end cut diagonally.

7.1.2 *Upper Reservoir*, of the same diameter as the sampling cylinder and approximately 150 cm (6 in.) high.

7.1.3 *Wire-Screen Support*, fabricated from a ring clamp, with an inside diameter greater than the specimen cylinder and covered with 425- μm (No. 40) wire mesh screening.

7.1.4 *Circular Disk*, cut from 425- μm (No. 40) wire mesh screening, with a diameter 1 mm smaller than that of the specimen.

7.1.5 *Funnel*, with a head diameter at least 10 % larger than that of the specimen cylinder.

7.1.6 *Two 400-mL Beakers*.

7.2 *Balance*—A balance or scale conforming to the requirements of Specification D4753, readable (with no estimate) to 0.1 % of the test mass, or better.

7.3 *Miscellaneous Apparatus and Materials*, such as thermometers, timer reading to nearest second, soaking pan, pipe cutters, trimming knife, cheese cloth, rubber bands, vinyl electrical tape, and micro-crystalline wax.

8. Specimen Preparation and Set Up

8.1 Specimens shall have a minimum diameter of 73 mm (2.87 in.). The height-to-diameter ratio shall be between 1 and 2.

8.2 Prepare specimens from tube samples secured in accordance with Practice D1587, or other acceptable undisturbed sampling procedure, yielding cylindrical samples obtained in tight-fitting, rigid-metal core holders (Note 3). Preserve and