

DRAFT INTERNATIONAL STANDARD

ISO/DIS 8611-2

ISO/TC 51

Secretariat: **BSI**

Voting begins on:
2021-03-16

Voting terminates on:
2021-06-08

Pallets for materials handling — Flat pallets —

Part 2: Performance requirements and selection of tests

Palettes pour la manutention — Palettes plates —

Partie 2: Exigences de performance et sélection des essais

ICS: 55.180.20

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/DIS 8611-2](https://standards.iteh.ai/catalog/standards/sist/71858c7a-2791-42c6-a464-b2785571f721/iso-dis-8611-2)

<https://standards.iteh.ai/catalog/standards/sist/71858c7a-2791-42c6-a464-b2785571f721/iso-dis-8611-2>

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.

ISO/CEN PARALLEL PROCESSING



Reference number
ISO/DIS 8611-2:2021(E)

© ISO 2021

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/DIS 8611-2
<https://standards.iteh.ai/catalog/standards/sist/71858c7a-2791-42c6-a464-b2785571f721/iso-dis-8611-2>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Test conditions	3
4.1 General.....	3
4.2 Wooden pallets.....	3
4.3 Metal pallets.....	3
4.4 Plastic pallets.....	3
4.5 Paper pallets.....	4
4.6 Wood-based composite pallets.....	4
5 Number of replicates	4
6 Performance requirements	4
7 Selection of the tests	7
7.1 Intended use.....	7
7.2 Handling of goods with racking and stacking.....	8
7.3 Handling of goods with stacking without racking.....	8
7.4 Handling of goods without racking or stacking.....	8
7.5 Special applications.....	9
7.5.1 General.....	9
7.5.2 Automatic handling or conveyors.....	9
7.5.3 Lifting with slings.....	9
7.5.4 Resistance to impact.....	9
7.5.5 Friction tests.....	9
8 Test load — Nominal load	9
8.1 Strength tests.....	9
8.2 Ultimate load, <i>U</i>	9
8.3 Stiffness tests.....	9
8.4 Nominal load.....	9
9 Duration for static stiffness tests	10
10 Number of impacts for dynamic tests	10
11 Test report	10
Annex A (informative) Plots of typical force versus deformation from pallet testsshowing the deformation of ultimate load, <i>U</i>	11
Bibliography	13

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 51, *Pallets for unit load method of materials handling*.

ISO/DIS 8611-2
<https://standards.iteh.ai/catalog/standards/sist/71858c7a-2791-42c6-a464-b278571d110e/iso-8611-2>

This second edition cancels and replaces the first edition (ISO 8611-2:2011), which has been technically revised.

The main changes compared to the previous edition are as follows:

- Separate performance/deflection limits for the internal and external spans were defined for test 2a and 2b.
- It was clarified that test 5 applies for both twin track conveyors and narrow span beam racking.
- It was clarified in [Table 2](#), that test 4a,b should be conducted for a pallet without racking or stacking but only on the top deck.
- The determination of nominal load was clarified in [Table 3](#).

A list of all parts in the ISO 8611 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The forces to which pallets are exposed during use vary significantly. The test procedures described in ISO 8611-1 are approximate simulations of pallet use. These tests help the pallet designer to establish an initial acceptable balance between the cost and the performance of a pallet design. It is intended that all results of tests performed using this protocol be confirmed and verified using field trials before publication of performance or the commercial implementation of a new pallet design.

The nominal load, determined according to this test protocol, does not represent a payload and cannot be verified using field trials. The nominal load is a minimum payload level for use in determining maximum working load according to the procedures in ISO 8611-3. The maximum working load can be verified for a specified payload and intended use, using field trials. It is intended that the publication of the maximum working load include a description of the payload and the intended modes of use of the pallet.

It is essential to exercise care when comparing the results of tests with historic experience using existing pallet designs. User expectations of pallet performance vary. Some require greater and some accept lower levels of performance. Users are accepting different levels of risk when using pallets. Because of the varied performance expectations of pallet users, the results of tests might not always reflect the user's perception of pallet performance in use.

The nominal load might not reflect users' perception of pallet performance because the nominal load does not represent a payload. It is intended that maximum working loads be used to compare with the historic performance of existing pallet designs.

Regarding the use of the ISO 8611 series,

- ISO 8611-1 describes the test methods,
- this part of ISO 8611 describes the performance requirements and selection of tests, and
- ISO 8611-3 describes tests for determining maximum working loads for known payloads.

ISO 8611-1 and this part of ISO 8611 are required for determining nominal load. The nominal load is the lowest safe load value for the specified support conditions, independent of the type of load (excluding concentrated loads).

ISO 8611-1, this part of ISO 8611 and ISO 8611-3 are required for determining maximum working loads for known payloads.

The nominal load for the intended use is established by the selection of tests in ISO 8611-1 and the performance requirement is established from criteria in this part of ISO 8611.

The following three types of intended use with specified support conditions are defined:

- handling of loaded pallets with racking and stacking;
- handling of loaded pallets without racking;
- handling of loaded pallets without racking or stacking.

To determine the maximum working load through testing given in ISO 8611-3, the deflection under the known payload cannot exceed the limiting deflection (see 4.2, 4.3 and 4.4 of ISO 8611-3:2011) established in ISO 8611-1 and this part of ISO 8611. The maximum working load is the greatest payload that a pallet can be permitted to carry in a specific loading and support condition.

Guidance is given in Annex A of ISO 8611-3:2011 as to the general effect on performance of different load types and stabilization methods. These can only give guidance as to the likely result from tests with the known payload.

Other tests for durability evaluation are specified in ISO 8611-1.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/DIS 8611-2

<https://standards.iteh.ai/catalog/standards/sist/71858c7a-2791-42c6-a464-b2785571f721/iso-dis-8611-2>

Pallets for materials handling — Flat pallets —

Part 2: Performance requirements and selection of tests

1 Scope

This part of ISO 8611 specifies the performance requirements to establish nominal loads for new flat pallets.

It also specifies the tests required for new flat pallets in various handling environments and the performance requirements for tests with payloads. It is not intended to apply to pallets with a fixed superstructure or a rigid, self-supporting container that can be mechanically attached to the pallet and which contributes to the strength of the pallet.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 445, *Pallets for materials handling — Vocabulary*

ISO 8611-1, *Pallets for materials handling — Flat pallets — Part 1: Test methods*

<https://standards.iteh.ai/catalog/standards/sist/71858c7a-2791-42c6-a464-027955717219/iso-8611-1>

ISO 8611-3, *Pallets for materials handling — Flat pallets — Part 3: Maximum working loads*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 445 and the following apply.

3.1

breaking of one component

fracture of a structural element which significantly affects the strength, stiffness or functionality of a pallet

3.2

concentrated load

load concentrated over an area of less than 50 % of the pallet top deck

[SOURCE: ISO 445:2008, definition 2.3]

3.3

maximum working load

greatest payload that a pallet is permitted to carry in a specific loading and support condition

Note 1 to entry: This varies according to the type, distribution, arrangement and means of stabilization of the load and the system of support, and can be lower or higher than the nominal load (see, for example, [Clauses 4](#) and [6](#) and see also ISO 8611-3).

Note 2 to entry: Adapted from ISO 445:2008, definition 2.7.

**3.4
nominal load**

R

lowest test load value for the specified support conditions, independent of the type of load (excluding concentrated loads)

Note 1 to entry: "Specified support conditions" refers to the range of conditions of use in [7.1](#) of this part of ISO 8611.

Note 2 to entry: Nominal load does not represent an actual payload on a pallet in use. The nominal load is used for comparing the performance of different pallets.

Note 3 to entry: Adapted from ISO 445:2008, definition 2.2.

**3.5
payload**

Q

load carried by the pallet in use

[SOURCE: ISO 445:2008, definition 2.8]

Note 1 to entry: This can be above, identical to or below the nominal load.

**3.6
platen**

solid, rigid surface on a test machine used for applying a load to test a sample pallet

**3.7
racking**

storage of unit loads in drive-in or beam racks with free, unsupported spans

[SOURCE: ISO 445:2008, definition A.3.1]

[ISO/DIS 8611-2](#)

<https://standards.iteh.ai/catalog/standards/sist/71858c7a-2791-42c6-a464-b2785571f721/iso-dis-8611-2>

**3.8
safety factor**

ratio of the ultimate load to the nominal load

Note 1 to entry: In ISO 8611 (all parts), this ratio is at least 2,0.

**3.9
solid load**

single, compact, rigid, homogeneous load, supported by all the blocks and/or stringers (bearers) of the pallet

Note 1 to entry: Adapted from ISO 445:2008, definition 2.6.

**3.10
stacking**

placing of pallets with unit loads one upon the other without recourse to intermediate shelves or racking

Note 1 to entry: Adapted from ISO 445:2008, definition A.2.1.

**3.11
stiffness**

relative deformation of a pallet or component under load

Note 1 to entry: High stiffness means small displacement, deflection or deformation for a given load.

**3.12
test load**

P

load applicators, the load board or load box and the applied load itself including the datum load (1,5% of Ultimate Load)

3.13 ultimate load

U

load at which compression, displacement or deflection is no longer contained, resulting in the destruction of the specimen or breaking of one component, or when displacement, deformation or deflection becomes excessive

Note 1 to entry: See [Table 1](#).

3.14 uniformly distributed bonded load

load spread evenly across the full surface of the pallet top deck, where the pattern of each single layer changes, so that the packages are interlocked

3.15 uniformly distributed unbonded load

load spread evenly across the full surface of the pallet top deck where the packages are not interlocked, bound or connected

4 Test conditions

4.1 General

Test conditions shall be determined based on the pallet material in accordance with [4.2](#) to [4.6](#) and shall be maintained throughout the test. If the pallet comprises several different types of material, the moisture and temperature conditions shall be in accordance with the material that is most sensitive to changes in conditions.

4.2 Wooden pallets

[ISO/DIS 8611-2](#)

<https://standards.iteh.ai/catalog/standards/sist/71858c7a-2791-42c6-a464-207855707216/iso-dis-8611-2>

The reference moisture content is (20 ± 2) %. If the pallets are used at a higher moisture content, they shall be tested at this higher moisture content and the moisture content shall be recorded in the test results.

NOTE The measurement can be carried out in accordance with EN 13183-2^[2].

4.3 Metal pallets

Conditioning shall not be used for metal pallets.

4.4 Plastic pallets

The test conditions for nominal load, maximum working load and durability tests for plastic pallets shall be the following:

- tests 1a, 1b, 2a, 2b, 3a, 3b, 4a, 4b, 5a, 5b, 6a, 6b, 8, 9, 10, 11, 12 and 13: (23 ± 2) °C
- maximum working load tests supporting the payload: (40 ± 2) °C
- test 9: (23 ± 2) °C and (-10 ± 2) °C

For maximum working loads and test 9, wherever plastic pallets are used in controlled or more extreme conditions, the test conditions shall be agreed between the supplier and purchaser.