INTERNATIONAL **STANDARD**



First edition 1990-12-15

Corrected and reprinted 1991-12-15

Surface active agents — Detergents — **Determination of cationic-active matter** content -

iTeh STANDARD PREVIEW

Cationic-active matter of low molecular mass (between 200 and 500) ISO 2871-2:1990

https://standards.iteh.ai/catalog/standards/sist/71fle040-2050-4a55-bc8d-

4afe8a0a5d7f/iso-2871-2-1990 Agents de surface — Détergents — Détermination de la teneur en matière active cationique -

Partie 2: Matière active cationique à faible masse moléculaire (entre 200 et 500)



Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75% of the member VIEW bodies casting a vote.

International Standard ISO 2871-2 was prepared by Technical Committee ISO/TC 91, Surface active agents.

ISO 2871 consists of the following parts, under the general title Surface-2050-4a55-bc8dactive agents — Detergents — Determination of cationic-active matter content:

- Part 1: High-molecular-mass cationic-active matter
- Part 2: Cationic-active matter of low molecular mass (between 200 and 500)

© ISO 1990

International Organization for Standardization

Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Surface active agents — Detergents — Determination of cationic-active matter content —

Part 2:

Cationic-active matter of low molecular mass (between 200 and 500)

1 Scope

shall be destroyed before the analysis, and the This part of ISO 2871 specifies a method for the desample shall be completely soluble in water. termination of low-molecular-mass cationic-active materials such as monoamines, amine loxides IS. 11 this part of ISO 2871 should be read in conjunction quaternary ammonium compounds and alkylwith ISO 2271. pyridinium salts which have a main chain of 10_{210} 22 carbon atoms and not more than 6 other carbon atoms and not more than 6 other carbon atoms and not more than 6 other carbon atoms itely at a standards/sist/71f1e040-2050-4a55-bc8d-

atoms in the cation. 4afe8a0a5d7f/iso-2871-2-1990

The method is also suitable for other cationic-active materials.

The method is applicable to solids or to aqueous solutions of the active material. The relative molecular mass of the cationic-active matter shall be known or previously determined if its content is expressed as a percentage by mass. If more than one type of cationic-active material is present, an estimate of average relative molecular mass may be used.

The method is not applicable if anionic and/or amphoteric surface active agents are present.

NOTE 1 Low relative molecular mass sulfonates of toluene and xylene present as hydrotropes do not interfere when present in concentrations up to and including 15 % (m/m) with respect to the active material. At higher levels, their influence should be evaluated in each particular case.

Non-ionic surface active agents, soap, urea and the salts of (ethylenedinitrilo)tetraacetic acid do not interfere.

Typical inorganic components of detergent formulations, such as sodium chloride, sulfate, borate,

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 2871. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 2871 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

tripolyphosphate, perborate, silicate, etc., do not in-

terfere, but bleaching agents other than perborate

ISO 385-1:1984, Laboratory glassware - Burettes -Part 1: General requirements.

ISO 607:1980, Surface active agents and detergents Methods of sample division.

ISO 1042:1983, Laboratory glassware — One-mark volumetric flasks.

ISO 2271:1989, Surface active agents – Detergents - Determination of anionic-active matter by manual or mechanical direct two-phase titration procedure.

ISO 3696:1987, Water for analytical laboratory use ---Specification and test methods.

Principle 3

The cationic-active matter in a sample is titrated in a two-phase (aqueous chloroform) system against a standard anionic surface-active agent in the presence of an indicator consisting of mixed anionic and cationic dyes. The cationic surface-active agent present in the sample initially reacts with the anionic dye to form a salt which dissolves in the chloroform layer, imparting a blue colour to this layer. During the titration, the anionic surface-active agent displaces the anionic dye and, at the end point, forms a salt with the cationic dye, imparting a greyish-pink colour to the chloroform layer.

Reagents 4

During the analysis, use only reagents of recognized analytical grade and only distilled water or water of at least equivalent purity complying with the specifications for grade 3 of ISO 3696.

4.1 Chloroform, ρ_{20} 1,48 g/ml, distilling between 59,5 °C and 61.5 °C.

[CH₃(CH₂)₁₁OSO₃Na], standard volumetric solution,

Add a few drops of ethanolic phenolphthalein solution (concentration 10 g/l), and titrate the solution with sodium hydroxide solution c(NaOH) = 1 mol/l.

Carry out a blank test by titrating 25 ml of the 1 mol/l sulfuric acid solution with the 1 mol/l sodium hydroxide solution.

Calculate the purity, τ , expressed as a percentage by mass, of the sodium lauryl sulfate using the formula

$$\frac{28,84(V_1 - V_0)c_0}{m_1}$$

where

- V_0 is the volume, in millilitres, of the 1 mol/l sodium hydroxide solution used for the blank test;
- V_1 is the volume, in millilitres, of the 1 mol/l sodium hydroxide solution used for the test portion of sodium lauryl sulfate taken;
- is the exact concentration, expressed in C_0 4.2 Sodium lauryl sulfate (Sodium dode v sulfate) DARD moles of NaOH per litre, of sodium hy-Р droxide solution used;

 $c(C_{12}H_{25}NaO_4S) = 0,004 \text{ mol/l}.$ (standards.mehisthe mass, in grams, of the test portion of sodium lauryl sulfate taken. While preparing the standard volumetric solution as

described in 4.2.2, check the purity of the solid_{SO 2871-2:1990} sodium lauryl sulfate used as described in it 2al catalog/standards/sist/71f1e040-2050-4a55-bc8d-

4afe8a0a5d7f/iso-2871-2-1990

Determination of purity of sodium lauryl sul-4.2.1 fate.

Weigh, to the nearest 1 mg, 5 g \pm 0,2 g of the solid product into a 250 ml round bottom flask with ground-glass neck. Add exactly 25 ml of a standard volumetric sulfuric acid solution, $c(0.5H_2SO_4)$ = 1 mol/l, and reflux using a water condenser. During the first 5 min to 10 min, the solution will thicken and tend to foam strongly; control this by removing the source of heat and swirling the contents of the flask.

In order to avoid excessive foaming, instead of refluxing, the solution may be left on a boiling water bath for 60 min.

After a further 10 min, the solution will become clear and foaming will cease. Reflux for a further 90 min.

Remove the source of heat, cool the flask and carefully rinse the condenser with 30 ml of ethanol followed by water.

4.2.2 Preparation of standard volumetric sodium lauryl sulfate solution.

Weigh, to the nearest 1 mg, between 1,14 g and 1,16 g of sodium lauryl sulfate and dissolve in 200 ml of water. Transfer the solution quantitatively to a 1 000 ml one-mark volumetric flask (5.3) fitted with a ground-glass stopper, and dilute to the mark with water.

Calculate the exact concentration c_2 , expressed in moles of C₁₂H₂₅NaO₄S per litre, of the solution thus obtained, using the formula

$$\frac{m_2\tau}{288,4\times100}$$

where

- is the mass, in grams, of sodium lauryl m_2 sulfate used to prepare the solution;
- has the same meaning as in 4.2.1. τ

4.3 Mixed indicator solution¹⁾.

4.3.1 Stock solution.

This solution shall be prepared from acid blue 1 and dimidium bromide.

4.3.1.1 Acid blue 1²⁾ (Colour Index 42045) (disodium-4',4''-dinitrilodiethyltriphenylmethane-2,4-disulfonate).



4.3.1.2 Dimidium bromide (3,8-diamino-5-methyl-6-phenylphenanthridinium bromide).

mix and dilute to the mark with water. Store in the dark.

5 Apparatus

Ordinary laboratory apparatus, and

5.1 Flask or **measuring cylinder**, 250 ml capacity, with ground-glass stopper.

5.2 Burette, 25 ml capacity, complying with the specifications for class A of ISO 385-1.

5.3 One-mark volumetric flask, 1 000 ml capacity, with ground-glass stopper, complying with ISO 1042.

6 Sampling

The laboratory sample of the detergent shall be prepared and stored in accordance with instructions given in ISO 607.



4.3.1.3 **Preparation of the stock solution**.

Weigh, to the nearest 1 mg, 0.5 g \pm 0.005 g of dimidium bromide (4.3.1.2) into a 50 ml beaker, and 0.25 g \pm 0.005 g of acid blue 1 (4.3.1.1) into a second 50 ml beaker.

Add between 20 ml and 30 ml of hot 10 % (V/V) ethanol to each beaker.

Stir until dissolved and transfer the solutions to a 250 ml one-mark volumetric flask. Rinse the beakers into the volumetric flask with the ethanol and dilute to the mark with the ethanol.

4.3.2 Acid solution.

Add 200 ml of water to 20 ml of the stock solution (4.3.1) in a 500 ml one-mark volumetric flask. Add 20 ml of approximately 245 g/l sulfuric acid solution,

| Expected cationic-active % (<i>m/m</i>) | Mass of test portion g |
|---|---------------------------|
| 10 | 10 |
| 20 | 5 |
| 100 | 1 |

Table 1 - Guide to mass of test portion

7.2 Determination

Dissolve the test portion (7.1) in water and transfer to the 1 000 ml one-mark volumetric flask (5.3). Dilute to the mark with water and mix well.

By means of a pipette, transfer 25 ml of this solution to the 250 ml flask or measuring cylinder (5.1).

¹⁾ This mixed indicator is available commercially in the form of a basic solution, which should be acidified and diluted before use.

²⁾ Acid blue 1, VS blue and disulfine blue VN 150 are examples of suitable products available commercially. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by ISO of these products.

Using measuring cylinders, add 10 ml of the mixed indicator solution (4.3), 15 ml of chloroform (4.1) and 25 ml of water. Mix well.

Fill the burette (5.2) with the sodium lauryl sulfate solution (4.2) and titrate; stopper the flask or measuring cylinder after each addition and shake well.

NOTE 3 The lower (chloroform) layer will be coloured blue.

Continue the titration, drop by drop, with repeated vigorous shaking, until at the end point the blue colour is discharged and the lower (chloroform) layer turns greyish-pink.

8 Expression of results

8.1 Calculation

The content, expressed as a percentage by mass, of cationic-active matter is given by the formula

 $\frac{VcM_{\rm r} \times 1\ 000 \times 100}{25 \times 1\ 000m_{\rm 0}}$

$$=\frac{4V cM}{m_0}$$

where

8.2.1 Repeatability

8.2 Precision

1,6 % of the mean value.

In the normal and correct operation of the method, the difference between two individual results obtained within the shortest feasible time interval by the same operator using the same apparatus and identical test material will exceed the repeatability value on average not more than once in 20 cases.

8.2.2 Reproducibility

4% of the mean value.

In the normal and correct operation of the method, the difference between individual results obtained by two different laboratories using identical test material will exceed the reproducibility value on average not more than once in 20 cases.

9 Test report

The test report shall include the following particuiTeh STANDA lars: PREVIEW

(standard) all the indications necessary for the complete identification of the sample;

- V is the volume, in millilitres, of the sodiumso 2871-2:1990 lauryl sulfate solution (4.2) used for the b) the method used (reference to this part of titration;
- c is the actual concentration, expressed in moles of $C_{12}H_{25}NaO_4S$ per litre, of the sodium lauryl sulfate solution (4.2);
- $M_{\rm r}$ is the mean relative molecular mass of the cationic-active matter;
- m_0 is the mass, in grams, of the test portion (7.1).
- c) the results and the way in which they have been expressed;
- d) any unusual features noted during the determination;
- e) any operation not specified in this part of ISO 2871 or in the International Standard to which reference is made, as well as any operation regarded as optional.

iTeh STANDARD PREVIEW (This page intentionally left blank

<u>ISO 2871-2:1990</u> https://standards.iteh.ai/catalog/standards/sist/71f1e040-2050-4a55-bc8d-4afe8a0a5d7f/iso-2871-2-1990

iTeh STANDARD PREVIEW (standards.iteh.ai)

.

<u>ISO 2871-2:1990</u> https://standards.iteh.ai/catalog/standards/sist/71f1e040-2050-4a55-bc8d-4afe8a0a5d7f/iso-2871-2-1990

UDC 661.185:543.24

Descriptors: surfactants, detergents, chemical analysis, determination of content, cationic active matter, volumetric analysis.

Price based on 4 pages