



**SLOVENSKI STANDARD**  
**oSIST prEN 3646-006:2024**  
**01-maj-2024**

---

**Aeronavtika - Konektorji, električni, okrogli, bajonetno sklapljanje, stalna delovna temperatura 175 °C ali 200 °C - 006. del: Podloga, hermetična, pritrjena z matico - Standard za proizvod**

Aerospace series - Connectors, electrical, circular, bayonet coupling, operating temperature 175 °C or 200 °C continuous - Part 006: Receptacle, hermetic, jam-nut mounting - Product standard

Luft- und Raumfahrt - Elektrische Rundsteckverbinder mit Bajonettkupplung, Betriebstemperatur 175 °C oder 200 °C konstant - Teil 006: Hermetischer fester Steckverbinder mit Mutterbefestigung - Produktnorm

Série aérospatiale - Connecteurs électriques circulaires à accouplement par baïonnettes, température d'utilisation 175 °C ou 200 °C continu - Partie 006: Embasse hermétique à fixation par écrou - Norme de produit

<https://standards.iteh.ai/catalog/standards/sist/7abc214d-57b4-46a6-963b-13e56f525f80/osist-pren-3646-006-2024>

**Ta slovenski standard je istoveten z: prEN 3646-006**

---

**ICS:**

31.220.10	Vtiči in vtičnice, konektorji	Plug-and-socket devices. Connectors
49.060	Letalska in vesoljska električna oprema in sistemi	Aerospace electric equipment and systems

**oSIST prEN 3646-006:2024**

**en,fr,de**



EUROPEAN STANDARD  
NORME EUROPÉENNE  
EUROPÄISCHE NORM

**DRAFT**  
**prEN 3646-006**

March 2024

ICS 49.060

Will supersede EN 3646-006:2018

English Version

**Aerospace series - Connectors, electrical, circular, bayonet  
coupling, operating temperature 175 °C or 200 °C  
continuous - Part 006: Receptacle, hermetic, jam-nut  
mounting - Product standard**

Série aérospatiale - Connecteurs électriques circulaires  
à accouplement par baïonnettes, température  
d'utilisation 175 °C ou 200 °C continu - Partie 006:  
Embase hermétique à fixation par écrou - Norme de  
produit

Luft- und Raumfahrt - Elektrische Rundsteckverbinder  
mit Bajonettkupplung, Betriebstemperatur 175 °C oder  
200 °C konstant - Teil 006: Hermetischer fester  
Steckverbinder mit Mutterbefestigung - Produktnorm

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee ASD-STAN.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

**Warning** : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels**

<b>Contents</b>	<b>Page</b>
<b>European foreword</b> .....	<b>3</b>
<b>1 Scope</b> .....	<b>4</b>
<b>2 Normative references</b> .....	<b>4</b>
<b>3 Terms and definitions</b> .....	<b>4</b>
<b>4 Required characteristics</b> .....	<b>4</b>
<b>4.1 Dimensions and mass</b> .....	<b>4</b>
<b>4.2 Tightening torque of attachment nut</b> .....	<b>6</b>
<b>4.3 Panel cut-out</b> .....	<b>6</b>
<b>4.4 Material and surface treatment</b> .....	<b>7</b>
<b>4.5 Main general characteristics</b> .....	<b>7</b>
<b>4.6 Possible combinations of plugs and receptacles</b> .....	<b>7</b>
<b>5 Designation</b> .....	<b>8</b>
<b>6 Marking</b> .....	<b>8</b>
<b>6.1 General</b> .....	<b>8</b>
<b>6.2 Marking on the product</b> .....	<b>8</b>
<b>6.3 Marking on the individual packaging</b> .....	<b>8</b>
<b>7 Technical specification</b> .....	<b>9</b>
<b>Bibliography</b> .....	<b>10</b>

iTeh Standards  
(<https://standards.iteh.ai>)  
Document Preview

[oSIST prEN 3646-006:2024](https://standards.iteh.ai/catalog/standards/sist/7a6c214d-57b4-46a6-963b-13e56f525f80/osist-pren-3646-006-2024)

<https://standards.iteh.ai/catalog/standards/sist/7a6c214d-57b4-46a6-963b-13e56f525f80/osist-pren-3646-006-2024>

## **European foreword**

This document (prEN 3646-006:2024) has been prepared by ASD-STAN.

After enquiries and votes carried out in accordance with the rules of this Association, this document has received the approval of the National Associations and the Official Services of the member countries of ASD-STAN, prior to its presentation to CEN.

This document is currently submitted to the CEN Enquiry.

This document will supersede EN 3646-006:2018.

prEN 3646-006:2024 includes the following significant technical changes with respect to EN 3646-006:2018:

- possibility to have six equally spaced holes in the jam nut for locking wire added and Figure 1 updated;

**iTeh Standards**  
**(<https://standards.iteh.ai>)**  
**Document Preview**

[oSIST prEN 3646-006:2024](https://standards.iteh.ai/catalog/standards/sist/7a6c214d-57b4-46a6-963b-13e56f525f80/osist-pren-3646-006-2024)

<https://standards.iteh.ai/catalog/standards/sist/7a6c214d-57b4-46a6-963b-13e56f525f80/osist-pren-3646-006-2024>

## prEN 3646-006:2024 (E)

### 1 Scope

This document specifies the characteristics of hermetic jam-nut mounted receptacles in the family of bayonet coupling circular connectors, intended for use in an operating temperature range of – 65 °C to 175 °C or 200 °C continuous.

It applies to models specified in Table 4.

For plugs and protective covers, see EN 3646-008 and EN 3646-009 respectively.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 3646-001, *Aerospace series — Connectors, electrical, circular, bayonet coupling, operating temperature 175 °C or 200 °C continuous — Part 001: Technical specification*

EN 3646-002, *Aerospace series — Connectors, electrical, circular, bayonet coupling, operating temperature 175 °C or 200 °C continuous — Part 002: Specification of performance and contact arrangements*

ISO 3161, *Aerospace — UNJ threads — General requirements and limit dimensions*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 3646-001 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp/>

— IEC Electropedia: available at <https://www.electropedia.org/>

### 4 Required characteristics

#### 4.1 Dimensions and mass

Dimensions and mass shall be according to Figure 1 and Table 1.

Dimensions and tolerances are in millimetres, they apply after surface treatment.

Interface mating dimensions shall be according to EN 3646-001.