2022-12-07

ISO/FDIS 17401:2021(E)

ISO/TC 20/SC 14<del>/WG</del>

Secretariat: ANS

Date: 2023-01-20

## Space systems — Spacecraft interface requirements document for launch vehicle services

 $Syst\`emes\ spatiaux - Document\ d'exigences\ d'interface\ du\ v\'ehicule\ spatial\ vis-\`a-vis\ du\ service\ de\ lancement$ 

ICS: 49.140

# iTeh STANDARD PREVIEW (standards.iteh.ai)

#### **ISO/FDIS 17401**

Error! Reference source not found.

# FDIS stage

# iTeh STANDARD PREVIEW (standards.iteh.ai)

#### **ISO/FDIS 17401**

#### ISO/FDIS 17401:2021(E)

© ISO 2021 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: + 41 22 749 01 11 EmailE-mail: copyright@iso.org Website: www.iso.org

Published in Switzerland

## iTeh STANDARD PREV**IEW** (standards.iteh.ai)

**ISO/FDIS 17401** 

### ISO/FDIS 17401:<del>2022<u>2</u>023</del>(E) Contents—<del>Page</del>

Forew	vord	vii
Introd	luctionv	riii
1	Scope	1
2	Normative references	1
3	Terms, definitions and abbreviated terms	1
3.1	Terms and definitions	1
3.2	Abbreviated terms	2
4	Spacecraft mission description	2
4.1	Mission description	2
4.2	SC description (optional)	2
5	Mechanical interfaces	2
5.1	Mechanical configuration	2
5.2	SC fundamental frequencies	2
5.3	Usable volume	3
5.4	Spacecraft (or SC adapter) mechanical interface	3
5.5	Connectors and microswitches (SC side of the interface)	3
5.6	Purges and fluid connection interface	4
5.7	Encapsulated spacecraft access	4
6	Electrical interfaces	4
6.1	Umbilical wiring diagram	4
6.2	Umbilical connectors	4
6.3	Umbilical wiring links (for each connector pin)	5 36d5-4713-b01b-
6.4	Electrical commands dedicated to spacecraft	5
6.4.1	Pyrotechnic commands	5
6.4.2	Dry loop commands	6
6.4.3	Electrical commands	6
6.5	Separation status transmission	7
6.6	SC in-flight telemetry	7
6.7	Power supply required from LV	7
6.8	Earth potential continuity	7
7	Radio-frequency and electromagnetic interface	8
7.1	Characteristics of radio-electrical systems	8
7.2	RF telemetry and command link	9
7.2.1	SC RF-link definition for ground operations	9
7.2.2	SC antenna coordinates	9
7.2.3	RF-link implementation	9
7.2.4	RF-link budget	9
7.2.5	Base band signal characteristics	10
iv		

	ISO/FDIS 17401: <del>2022</del> 2023(E)			
3	Spacecraft mission characteristics			
3.1	SC input data for mission analyses	1		
3.1.1				
3.1.2	S (F			
3.1.3				
3.2	SC orbit parameters (with tolerances)			
3.3	Launch window1			
3.3.1	Launch window constraints (when applicable)1	3		
3.3.2				
8.4	SC pointing and separation	3		
9	Environment requirements			
9.1	General	3		
9.2	Mechanical environment1	3		
9.3	Thermal environment	4		
9.4	Static pressure			
9.5	Contamination and cleanliness control	5		
9.6	Radio frequency and electromagnetic environment			
9.7	Environment monitoring	5		
9.8	Exposure to sun1			
10	SC Development and test programme1	5		
11	Launch range operations: facilities and support requirements			
11.1	General logistics requirements			
11.1.1				
11.1.2	Judy 1 Judy			
11.1.3	3 Material handling equipment	7		
11.1.4	4 Electrical power for SC and ground station	7		
11.1.5	5 Umbilical lines and ground lines 1	7		
11.1.6	6 Gas and fluid lines 1	7		
11.1.7	7 Clean room 1	7		
11.1.8				
11.1.9	, and the second			
11.1.1	10 Area 1	8		
11.1.1				
11.1.1	12 SC pre-launch activities calendar 1	9		
11.1.1	13 Special technical support equipment	9		
11.1.1	14 Other	9		
11.2 Specific requirements for solid propellant motor facilities (Y/N, to specify)20				
11.2.1				
11.2.2	2 Pyrotechnics storage	0		
ര സ	2.2022 All vights vacawad			

#### ISO/FDIS 17401:20222023(E) Gases 20 11.4.1 11.4.2 Liquid propellant......21 11.4.3 11.4.4 Payload handling and transport requirements......21 11.5 11.7 11.8

Bibliography.......23

# iTeh STANDARD PREVIEW (standards.iteh.ai)

#### ISO/FDIS 17401

ISO/FDIS 17401:20222023(E)

1

#### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

This document was prepared by Technical Committee ISO/TC 20, Aircraft and space vehicles, Subcommittee SC 14, Space systems and operations.

This second edition cancels and replaces the first edition (ISO 17401:2004), which has been technically revised.

The main changes compared to the previous edition are as follows: 688 / 150 - 1740

- upgrade orbit definition parameters
- upgrade SC environment description
- upgrade SC description (interface, thermal aspects, EMC)

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org/members.html">www.iso.org/members.html</a>.

Field Code Changed

© ISO 2023 - All rights reserved

\_v

vii

## ISO/FDIS 17401:<del>20222023</del>(E) **Introduction**

This document gives guidelines for writing an interface requirements document (IRD) for launch vehicle (LV) services. The application of this document is intended to facilitate the technical exchanges between spacecraft (SC) and launch vehicle agencies. By reducing the amount of work necessary for requesting launch services, this document will minimize spacecraft contractor's and spacecraft manufacturer's costs.

In some cases, drawings are explicitly requested in order to provide comprehensive information. Explicit international system units are specified for all items. The corresponding scale may be adjusted if not appropriate.

SC organizations may include additional topics if required. Some sections of the IRD may refer to specificities that are not applicable to the launch services of interest, in which case they should be ignored.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 17401

## Space systems — Spacecraft interface requirements document for launch vehicle services

#### 1 Scope

This document provides spacecraft (SC) organizations with the general format for presenting the interface requirement document (IRD) for launch vehicle services. The IRD provides a list of the major technical requirements spacecraft agencies provide to launch vehicle (LV) agencies when submitting an application for launch services.

The IRD addresses the definition of the SC mission, the mechanical and electrical interfaces, the overall environment requirements (mechanical, thermal, cleanliness, radio-electrical), the SC development and test programme and, finally, launch range facilities and support requirements.

This document is applicable to all existing commercial LV and related launch facilities so as to permit SC contractors to prepare a single interface requirement document for a given SC mission, independently of the LV contractor to be selected.

The IRD, as defined in this document, includes the basic SC input data needed by LV agencies to prepare the interface control document defined in the ISO 15863.

#### 2 Normative references

There are no normative references in this document.

## 3 Terms, definitions and abbreviated terms 10 2 10 5 11 2 11

#### 3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <a href="https://www.iso.org/obp">https://www.iso.org/obp</a>
- IEC Electropedia: available at <a href="https://www.electropedia.org/">https://www.electropedia.org/</a>

And, if required, terminology databases of national space agencies are used

#### 3.1.1

#### usable volume

volume available to the payload within the LV fairing or carrying structure that the static envelope of the SC may not exceed in order to ensure that there is no physical contact between the SC and the LV in a dynamic environment

#### 3.1.2

#### spacecraft adapter (SC adapter)

#### **SC** adapter

structure that mates the SC to the LV and includes the separation system for SC/LV separation

Note 1 to entry: The SC adapter is a part of the LV and does not separate with the SC.

#### ISO/FDIS 17401:2023(E)

#### 3.2 Abbreviated terms

EIRP equivalent isotropic radiated power

EMC electromagnetic compatibility

IRD interface requirement document

LV launch vehicle RF radio frequency

SC spacecraft

Y/N yes/no response

#### 4 Spacecraft mission description

#### 4.1 Mission description

The IRD shall describe the following items:

- a) a) purpose of the mission;
- b) b) orbital characteristics;
- c) e—in orbit view of SC, with drawing

### 4.2 SC description (optional)

The IRD may describe the following items:

a) a)—SC platform

b) b) SC payload

#### SO/FDIS 17401

### 5 Mechanical interfaces/standards iteh ai/catalog/standards/sist/5cea679e-36d5-4713-b01b

#### 5.1 Mechanical configuration

The IRD shall provide the following information:

- a) a)—SC mechanical drawing (launch configuration);
- b) b)—SC coordinate system, with drawing;
- c) e)—maximum height above interface plane, in metres;
- d) d)-SC overall dimensions (maximum diameter, maximum height, ...), in metres;
- e) e)—SC/LV interface diameter, in metres. SC/LV interface geometrical definition.
- f) available volumes of SC, in cubic meters
- g) g)—SC mass center position relative to the reference frame which is centered in the adapter plane;
- h) h) mean-square deviation of SC mass center position along SC axis

#### 5.2 SC fundamental frequencies

The IRD shall provide the fundamental natural frequencies of SC (specify boundary conditions):

- a) a) axial frequencies, in hertz;
- b) b) lateral frequencies, in hertz.

2

© ISO 2023 – All rights reserved

#### 5.3 Usable volume

The IRD shall provide the following information:

- a) a) static envelope, with drawing;
- b) b) SC protrusions below interface plane, with dimensioned drawings;
- c) c)—SC volumetric displacement, in cubic metres;
- d) d)—SC free air volume, in cubic metres;
- e) e) special clearance requirements, with drawing.

#### 5.4 Spacecraft (or SC adapter) mechanical interface

The IRD shall provide the following information:

- a) a) mechanical interface, with drawing;
- b) b) diameter, in metres;
- c) e)-attachments at SC interface;
- d) d)-material;
- e) e)—Young's modulus, in newtons per square metre;
- f) f) coating:
  - 1) 1) surfaces in contact,
  - 2) 2) other surfaces;

#### ISO/FDIS 17401

- g) g) roughness, in micrometers of surfaces in contact; at a log/standards/sist/5cea679e-1645-4713-b01b
- h) h) flatness/perpendicularity of surfaces in contact; 7 be 1
- i) i) stiffness (for clampband mating system):
  - 1) 1) applicable length (height), in meters,
  - 2) 2) section area, in square millimeters,
  - inertia (with respect to centre of gravity of section), in millimeters to the power of (mm<sup>4</sup>);
- j) stiffness (except for clampband mating systems):
  - 1) 1) radial direction, in newtons per metre,
  - 2) 2) tangent direction, in newtons per metre.

NOTE This section of the IRD applies to the lower adapter interface ring for a SC provided adapter.

### 5.5 Connectors and microswitches (SC side of the interface)

The IRD shall provide the following information:

- a) a) manufacturer and part number;
- b) <del>b)</del>-quantity;

© ISO 2023 - All rights reserved

\_;

#### ISO/FDIS 17401:2023(E)

- c) e) location and mechanical interface, with drawing:
  - 1) 1) angular position, in degrees,
  - 2) 2) radial position, in metres,
  - 3) 3) height from separation plane, in metres;
- d) d)-push-on and push-off loads, in newtons;
- e) energy released, in joules;
- f) f)—keying index.

#### Purges and fluid connection interface 5.6

The IRD shall provide the following information:

- a) definition;
- b) b)—location and mechanical interface, with drawing:
  - 1) 1) angular position, in degrees,
  - 2) 2) radial position, in metres,
  - 3) 3)—height from separation plane, in metres.

#### 5.7 Encapsulated spacecraft access

For each access requirement to payload, the IRD shall specify the following items:

- a) location in SC coordinates, in metres, with drawing:

  - 2) <del>2)</del> Y<sub>s</sub>,
  - 3)  $\frac{3}{2}$   $Z_{S}$
- b) b) minimum size of access door, length and height in metres;
- c) <del>c)</del> purpose.

NOTE The symbols X<sub>5</sub>, Y<sub>5</sub>, Z<sub>5</sub> are the generic coordinates of any point in SC axes (or in axes parallel to the SC axes).

#### 6 **Electrical interfaces**

#### 6.1 Umbilical wiring diagram

Drawings for SC to LV and SC to ground facilities wiring shall be provided.

#### 6.2 Umbilical connectors

The IRD shall provide the following information:

- a) number of connectors required;
- b)\_LV supplied (Y/N, to specify); b)
- e) manufacturer;

© ISO 2023 - All rights reserved