

TECHNICAL REPORT

**Information technology – Generic cabling for customer premises –
Part 9906: Balanced 1-pair cabling channels up to 600 MHz for single pair
Ethernet (SPE)**

(standards.iteh.ai)

[ISO/IEC TR 11801-9906:2020](https://standards.iteh.ai/catalog/standards/sist/ce9af1b2-c021-4fc8-8549-8b77d311f72f/iso-iec-tr-11801-9906-2020)

<https://standards.iteh.ai/catalog/standards/sist/ce9af1b2-c021-4fc8-8549-8b77d311f72f/iso-iec-tr-11801-9906-2020>





THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2020 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

[ISO/IEC TR 11801-9906:2020](https://standards.iteh.ai/catalog/standards/sist/ce9afb2-c021-4fc8-8549-8b77d311f72f/iso-iec-tr-11801-9906-2020)

<https://standards.iteh.ai/catalog/standards/sist/ce9afb2-c021-4fc8-8549-8b77d311f72f/iso-iec-tr-11801-9906-2020>

iTeh STANDARDS (Standards.iteh.ai)



TECHNICAL REPORT

Information technology – Generic cabling for customer premises –
Part 9906: Balanced 1-pair cabling channels up to 600 MHz for single pair
Ethernet (SPE)

[ISO/IEC TR 11801-9906:2020](https://standards.iteh.ai/catalog/standards/sist/cc9af1b2-c021-4fc8-8549-8b77d311f72f/iso-iec-tr-11801-9906-2020)

<https://standards.iteh.ai/catalog/standards/sist/cc9af1b2-c021-4fc8-8549-8b77d311f72f/iso-iec-tr-11801-9906-2020>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.200

ISBN 978-2-8322-7843-7

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	6
INTRODUCTION.....	8
1 Scope.....	9
2 Normative references	9
3 Terms, definitions and symbols.....	9
3.1 Terms and definitions.....	9
3.2 Symbols.....	10
4 Balanced 1-pair cabling channels	10
4.1 General.....	10
4.2 Component specifications	11
4.3 Environmental classifications	11
4.4 Channel reference implementations	12
4.5 Balanced 1-pair cabling channel signal transmission specifications.....	12
4.5.1 Return loss (RL)	12
4.5.2 Insertion loss (IL).....	12
4.5.3 Unbalance attenuation and coupling attenuation	13
4.5.4 Alien (exogenous) crosstalk.....	15
4.5.5 DC loop resistance.....	16
4.5.6 Propagation delay.....	16
Annex A (informative) Balanced 1-pair cable specifications.....	17
A.1 General.....	17
A.2 Cables using alternative conductor sizes.....	17
A.3 Balanced 1-pair cable specifications.....	17
A.3.1 Return loss (RL).....	17
A.3.2 Insertion loss (IL).....	18
A.3.3 Unbalance attenuation and coupling attenuation	18
A.3.4 Alien (exogenous) crosstalk.....	20
A.3.5 DC resistance.....	21
A.3.6 Propagation delay.....	21
Annex B (informative) Balanced 1-pair connector specifications.....	22
B.1 General.....	22
B.2 Balanced 1-pair connector specifications	22
B.2.1 Return loss (RL)	22
B.2.2 Insertion loss (IL).....	22
B.2.3 Unbalance attenuation and coupling attenuation	23
B.2.4 Alien (exogenous) crosstalk.....	24
B.2.5 DC resistance (DCR)	25
B.2.6 Propagation delay (delay).....	25
Annex C (informative) Link segment specifications	26
C.1 General.....	26
C.2 Return loss (RL).....	26
C.2.1 1000BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD4	26
C.2.2 100BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD1	26
C.2.3 10BASE-T1S, IEEE 802.3cg	26
C.2.4 10BASE-T1L, IEEE 802.3cg	27

C.3	Insertion loss (IL).....	27
C.3.1	1000BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD4	27
C.3.2	100BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD1	27
C.4	TCL - 10BASE-T1L, IEEE 802.3cg	28
C.5	ELTCTL - 10BASE-T1L, IEEE 802.3cg	29
C.6	PS ANEXT	29
C.6.1	1000BASE-T1, Type A, ISO/IEC/IEEE 8802-3:2017/AMD4	29
C.6.2	1000BASE-T1, Type B, ISO/IEC/IEEE 8802-3:2017/AMD4	29
C.6.3	100BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD1	29
C.6.4	10BASE-T1S, IEEE 802.3cg	30
C.6.5	10BASE-T1L, IEEE 802.3cg	30
C.7	PS AACR-F	30
C.7.1	1000BASE-T1, Type A, ISO/IEC/IEEE 8802-3:2017/AMD4	30
C.7.2	1000BASE-T1, Type B, ISO/IEC/IEEE 8802-3:2017/AMD4	30
C.7.3	100BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD1	31
C.7.4	10BASE-T1S, IEEE 802.3cg	31
C.7.5	10BASE-T1L, IEEE 802.3cg	31
C.8	Coupling attenuation	31
C.8.1	1000BASE-T1, Type A, ISO/IEC/IEEE 8802-3:2017/AMD4	31
C.8.2	1000BASE-T1, Type B, ISO/IEC/IEEE 8802-3:2017/AMD4	32
C.8.3	100BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD1	32
C.8.4	10BASE-T1S, IEEE 802.3cg	32
C.8.5	10BASE-T1L, IEEE 802.3cg	32
C.9	Delay	33
C.9.1	1000BASE-T1, Type A, ISO/IEC/IEEE 8802-3:2017/AMD4	33
C.9.2	1000BASE-T1, Type B, ISO/IEC/IEEE 8802-3:2017/AMD4	33
C.9.3	10BASE-T1L, IEEE 802.3cg	33
Annex D (informative)	Considerations for balanced 1-pair channels bundled in a 4-pair cabling channel.....	34
Annex E (informative)	Conductor size effects for reduced insertion loss.....	35
E.1	Channel parameters affected by conductor size and AWG	35
E.2	IL parameter variation due to conductor size variation	36
E.3	AWG.....	36
Bibliography	37
Table 1	– SPE signal transmission functional space.....	11
Table 2	– Balanced 1-pair cabling channel return loss (RL).....	12
Table 3	– Balanced 1-pair cabling channel IL.....	13
Table 4	– Balanced 1-pair cabling channel TCL	14
Table 5	– Balanced 1-pair cabling channel ELTCTL	14
Table 6	– Balanced 1-pair cabling channel coupling attenuation	15
Table 7	– Balanced 1-pair cabling channel PS ANEXT	15
Table 8	– Balanced 1-pair cabling channel PS AACR-F	16
Table 9	– Balanced 1-pair cabling channel DC loop resistance	16
Table 10	– Balanced 1-pair cabling channel propagation delay	16
Table A.1	– Balanced 1-pair cable standards	17
Table A.2	– Balanced 1-pair cable RL	18

Table A.3 – Balanced 1-pair cable IL	18
Table A.4 – Balanced 1-pair cable TCL	19
Table A.5 – Balanced 1-pair cable ELTCTL	19
Table A.6 – Balanced 1-pair cable coupling attenuation	20
Table A.7 – Balanced 1-pair cable PS ANEXT	20
Table A.8 – Balanced 1-pair cable PS AACR-F	21
Table A.9 – Balanced 1-pair cable DC resistance	21
Table A.10 – Balanced 1-pair cable propagation delay	21
Table B.1 – Balanced 1-pair connector standards	22
Table B.2 – Balanced 1-pair connector RL	22
Table B.3 – Balanced 1-pair connector IL	23
Table B.4 – Balanced 1-pair connector TCL	23
Table B.5 – Balanced 1-pair connector TCTL	23
Table B.6 – Balanced 1-pair connector coupling attenuation	24
Table B.7 – Balanced 1-pair connector PS ANEXT	24
Table B.8 – Balanced 1-pair connector PS AACR-F	24
Table B.9 – Balanced 1-pair connector DCR	25
Table B.10 – Balanced 1-pair connector delay	25
Table C.1 – Return loss limits for 15 m and 40 m link segment	26
Table C.2 – Return loss limits for 15 m link segment	26
Table C.3 – Return loss limits for 15 m link segment	26
Table C.4 – Return loss limits for 1 000 m link segment	27
Table C.5 – Insertion loss limits of a 15 m and 40 m link segment	27
Table C.6 – Insertion loss limits for a 15 m link segment	27
Table C.7 – Insertion loss limits for a 15 m link segment	28
Table C.8 – Insertion loss limits for a 1 000 m link segment	28
Table C.9 – TCL for a 1 000 m link segment	28
Table C.10 – ELTCTL for a 1 000 m link segment	29
Table C.11 – PS ANEXT for a 15 m link segment	29
Table C.12 – PS ANEXT for a 40 m link segment	29
Table C.13 – PS ANEXT for a 15 m link segment	29
Table C.14 – PS ANEXT for a 15 m link segment	30
Table C.15 – PS ANEXT for a 1 000 m link segment	30
Table C.16 – PS AACR-F for a 15 m link segment	30
Table C.17 – PS AACR-F for a 40 m link segment	30
Table C.18 – PS AACR-F for a 15 m link segment	31
Table C.19 – PS AACR-F for a 15 m link segment	31
Table C.20 – PS AACR-F for a 1 000 m link segment	31
Table C.21 – Coupling attenuation for a 15 m link segment	31
Table C.22 – Coupling attenuation for a 40 m link segment	32
Table C.23 – Coupling attenuation for a 15 m link segment	32
Table C.24 – Coupling attenuation for a 15 m link segment	32
Table C.25 – Coupling attenuation for a 1 000 m link segment	32

Table C.26 – Delay for a 15 m link segment.....	33
Table C.27 – Delay for a 40 m link segment.....	33
Table C.28 – Delay for a 1 000 m link segment.....	33
Table E.1 – Conductor diameter IL factors to be used with example 24 AWG cable with 1,8 conductor IL coefficient.....	35

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC TR 11801-9906:2020](https://standards.iteh.ai/catalog/standards/sist/ce9af1b2-c021-4fc8-8549-8b77d311f72f/iso-iec-tr-11801-9906-2020)

<https://standards.iteh.ai/catalog/standards/sist/ce9af1b2-c021-4fc8-8549-8b77d311f72f/iso-iec-tr-11801-9906-2020>

INFORMATION TECHNOLOGY – GENERIC CABLING FOR CUSTOMER PREMISES –

Part 9906 – Balanced 1-pair cabling channels up to 600 MHz for single pair Ethernet (SPE)

FOREWORD

- 1) ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.
- 2) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees and ISO member bodies.
- 3) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC National Committees and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO, IEC or ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 5) ISO and IEC do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. ISO or IEC are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC National Committees or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this ISO/IEC publication may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC and ISO technical committees is to prepare International Standards. However, a technical committee may propose the publication of a Technical Report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

ISO/IEC TR 11801-9906, which is a Technical Report, was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 11801 series, under the general title *Information technology – Generic cabling for customer premises*, can be found on the IEC and ISO websites.

The text of this Technical Report is based on the following documents:

Draft TR	Report on voting
JTC1-SC25/2888/DTR	JTC1-SC25/2913/RVDTR

Full information on the voting for the approval of this Technical Report can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

[ISO/IEC TR 11801-9906:2020](https://standards.iteh.ai/catalog/standards/sist/ce9af1b2-c021-4fc8-8549-8b77d311f72f/iso-iec-tr-11801-9906-2020)
<https://standards.iteh.ai/catalog/standards/sist/ce9af1b2-c021-4fc8-8549-8b77d311f72f/iso-iec-tr-11801-9906-2020>

INTRODUCTION

This document is a compendium of balanced 1-pair cabling channels specifications related to specific applications.

The balanced 1-pair cabling channels support single-pair Ethernet (SPE) applications, according to ISO/IEC/IEEE 8802-3:2017/AMD4, 1000BASE-T1; ISO/IEC/IEEE 8802-3:2017/AMD1, 100BASE-T1; and IEEE 802.3cg, 10BASE-T1.

While the original use case for SPE was automotive applications, this document describes balanced 1-pair cabling channels intended for use in non-automotive, SPE applications – for example:

- industrial automation applications, Industrial Internet of Things (IIoT), Industry 4.0;
- enterprise building applications, Internet of Things (IoT), smart lighting, energy management, and access control;
- other IoT applications, smart building and home automation applications.

SPE cabling channels support bidirectional signal transmission, using one balanced pair, for 1 000 Mbit/s (ISO/IEC/IEEE 8802-3:2017/AMD4) up to 40 m, 100 Mbit/s (ISO/IEC/IEEE 8802-3:2017/AMD1) up to 15 m, or 10 Mbit/s (IEEE 802.3cg) up to 1 000 m, where reach is influenced by cabling channel capacity limitations from signal loss and electromagnetic interference.

iTeh STANDARD PREVIEW

SPE channels optionally support power delivery together with the signal delivery over a single balanced pair. Remote powering over balanced 1-pair cabling is addressed in ISO/IEC TS 29125:2017/AMD11.

[ISO/IEC TR 11801-9906:2020](https://standards.itih.ai/catalog/standards/sist/ce9af1b2-c021-4fc8-8549-8b77d311f72f/iso-iec-tr-11801-9906-2020)

<https://standards.itih.ai/catalog/standards/sist/ce9af1b2-c021-4fc8-8549-8b77d311f72f/iso-iec-tr-11801-9906-2020>

¹ To be published. Stage at the time of publication: ISO/IEC DTS 29125:2017/AMD1:2019.

INFORMATION TECHNOLOGY – GENERIC CABLING FOR CUSTOMER PREMISES –

Part 9906 – Balanced 1-pair cabling channels up to 600 MHz for single pair Ethernet (SPE)

1 Scope

This document covers channel specifications, for channels constructed from balanced 1-pair cabling components, primarily intended for use in industrial automation and process control applications.

The channel specifications are consistent with corresponding IEEE 802.3 single-pair Ethernet (SPE) applications and are referenced from link segment specifications in the following IEEE SPE physical layer specifications:

- ISO/IEC/IEEE 8802-3:2017/AMD4, 1 000 Mb/s: 1000BASE-T1 Type A, ≤ 15 m, 1000BASE-T1 Type B, ≤ 40 m;
- ISO/IEC/IEEE 8802-3:2017/AMD1, 100 Mb/s: 100BASE-T1, ≤ 15 m;
- IEEE 802.3cg, 10 Mb/s: 10BASE-T1S, ≤ 15 m; 10BASE-T1L, ≤ 1 000 m.

The channel component specifications are referenced according to corresponding IEC balanced 1-pair cable and connector specifications.

Channel specifications include IL, RL, TCL, coupling attenuation, and alien crosstalk parameters specifications.

Channel EMC related specifications include electromagnetic isolation levels E_1 , E_2 and E_3 , which are defined according to the MICE standard environmental characterization system specified in ISO/IEC 11801-1.

2 Normative references

ISO/IEC 11801-1, *Information technology – Generic cabling for customer premises – Part 1: General requirements*

3 Terms, definitions and symbols

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 11801-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1.1

balanced 1-pair cabling channel

cabling channel constructed from balanced 1-pair cables, balanced 1-pair connectors and balanced 1-pair cord to form a cabling channel intended for use in differential-mode signal transmission and power delivery applications

3.1.2

balanced 1-pair cable

cable consisting of a single pair of conductors, optional screen, and overall jacket, primarily intended for use in differential-mode signal transmission and power delivery applications

3.1.3

balanced 1-pair connector

connector intended for use with balanced 1-pair cable in differential-mode signal transmission and power delivery applications

3.1.4

balanced 1-pair cord

cable assembly constructed from a 1-pair cable and 1-pair connectors

3.2 Symbols

V_{pp} peak-to-peak voltage

4 Balanced 1-pair cabling channels

4.1 General

Channel signal transmission specifications for balanced 1-pair cabling are referenced from three physical layer specifications: ISO/IEC/IEEE 8802-3:2017/AMD1, ISO/IEC/IEEE 8802-3:2017/AMD4 and IEEE802.3cg. These cover five link segment specifications: 1000BASE-T1 Type A, 1000BASE-T1 Type B, 100BASE-T1, 10BASE-T1S, and 10BASE-T1L. IEEE SPE link segment specifications and physical layer standards are summarized in Annex C.

The SPE link segment specifications are identified by their corresponding upper frequency specification, i.e. 600 MHz, 66 MHz, and 20 MHz.

The SPE signal transmission functional space covered by the five link segment specifications is given in Table 1.

Table 1 – SPE signal transmission functional space

Upper frequency	Frequency range	Reach	Screen	Data rate	SPE link segment	IEEE physical layer
MHz	MHz	m	Type	Mb/s	Specification	Standard
600	$1 \leq f \leq 600$	15	Screened and unshielded	1 000	1000BASE-T1 Type A	ISO/IEC/IEEE 8802-3:2017/AMD4
600	$1 \leq f \leq 600$	40	Screened	1 000	1000BASE-T1 Type B	ISO/IEC/IEEE 8802-3:2017/AMD4
66	$0,3 \leq f \leq 66$	15	Unshielded	100	100BASE-T1	ISO/IEC/IEEE 8802-3:2017/AMD1
20	$0,1 \leq f \leq 20$	15	Screened and unshielded	10	10BASE-T1S	802.3cg
20	$0,1 \leq f \leq 20$	1 000	Screened and unshielded	10	10BASE-T1L	802.3cg

NOTE Limits involving more than 1 pair within a channel; the following parameters are not applicable to balanced 1-pair cabling channels: NEXT, PS NEXT, ACR-F, PS ACR-F, ACR-N, PS ACR-N, delay skew and pair-to-pair resistance unbalance.

4.2 Component specifications

Balanced 1-pair cabling channel characteristics are specified using balanced 1-pair cabling component specifications. Balanced 1-pair cable and connector component specification references are given in Annex A and Annex B, respectively.

The characteristics of a channel are specified between connections to active equipment. The channel comprises only passive sections of cable, connecting hardware and cords. The connections at the hardware interface to active equipment are not taken into account.

Application support depends on channel performance, which in turn depends on cable length, number of connections, connector termination practices, workmanship and performance. It is possible to achieve equivalent channel performance over greater lengths by the use of fewer connections or by using components with higher performance.

Considerations for balanced 1-pair channels bundled in a 4-pair cabling channel are given in Annex D.

4.3 Environmental classifications

ISO/IEC 11801-1 classifies the environments for generic cabling according to three "MICE" levels.

The balanced 1-pair cabling specifications referenced in ISO/IEC/IEEE 8802-3:2017/AMD1, ISO/IEC/IEEE 8802-3:2017/AMD4 and IEEE 802.3cg include channel EMC related specifications for electromagnetic isolation levels E_1 , E_2 and E_3 , which are defined according to the MICE standard environmental characterization system specified in ISO/IEC 11801-1.

The channel EMC related specifications are unbalance attenuation, coupling attenuation, and alien (exogenous) crosstalk, which are specified for channels and components per E_1 , E_2 and E_3 .