

International **Standard**

ISO 22760-6

Road vehicles — Dimethyl ether (DME) fuel system components —

Part 6:

Pressure relief valve (PRV) h Standards

Véhicules routiers — Composants des systèmes de combustible Diméthyle Ether (DME) —

Partie 6: vannes de contrôle de la surpression UMENT Preview

First edition

https://standards.iteh.ai/catalog/standards/iso/1e9f625c-d6bf-44/c-a39d-9cf42fb143d7/iso-prf-22760-6

PROOF/ÉPREUVE

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/PRF 22760-6

https://standards.iteh.ai/catalog/standards/iso/1e9f625c-d6bf-447c-a39d-9cf42fb143d7/iso-prf-22760-6



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

PROOF/ÉPREUVE © ISO 2024 – All rights reserved

ISO 22760-6:2024(en)

Contents			Page
Fore	word		iv
1	Scope		1
2	Normative references		1
3	Terms and definitions		1
4	Marking		2
5	Design and assembly		2
6	Tests		2
	6.1 6.2 6.3 6.4 6.5	Applicability Hydrostatic strength Leakage Continued operation Operational test 6.5.1 General 6.5.2 Test procedure	4
7	Pro	duction batch inspection and acceptance testing	
Ribl	iogran	ihv	5

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/PRF 22760-6

https://standards.iteh.ai/catalog/standards/iso/1e9f625c-d6bf-44/c-a39d-9cf42fb143d//iso-prf-22/60-6

ISO 22760-6:2024(en)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 41, *Specific aspects for gaseous fuels*.

A list of all parts in the ISO 22760 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

https://standards.iteh.ai/catalog/standards/iso/1e9f625c-d6bf-44/c-a39d-9cf42fb143d//iso-prf-22/60-6

Road vehicles — Dimethyl ether (DME) fuel system components —

Part 6:

Pressure relief valve (PRV)

1 Scope

This document specifies definitions of and general requirements to a pressure relief valve for limiting internal pressure of DME fuel containers intended for use on the types of motor vehicles as defined in ISO 3833. It also provides general design principles and specifies requirements for instructions and marking.

This document is applicable to vehicles using gaseous fuels in accordance with ISO 16861. It is not applicable to the following:

- a) fuel containers for any application other than as noted above;
- b) stationary, ship, railroad vehicle or aircraft DME engine installations;
- c) fuel container mounting hardware; en significant and signif
- d) parts of vehicle fuel systems other than the fuel container;
- e) electronic fuel management;
- f) refuelling receptacles.

NOTE 1 It is recognized that miscellaneous component properties not specifically addressed herein can be examined for compliance with the criteria of any applicable part of the ISO 22760 series, including subjecting the component to appropriate functional tests.

NOTE 2 All pressures referred to in this document are gauge pressures unless otherwise specified.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies:

ISO 22760-1, Road vehicles — Dimethyl ether (DME) fuel system components — Part 1: General requirements and definitions

ISO 22760-2, Road vehicles — Dimethyl ether (DME) fuel system components — Part 2: Performance and general test methods

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 22760-1 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

ISO 22760-6:2024(en)

IEC Electropedia: available at https://www.electropedia.org/

3.1

discharge pressure

pressure at which the pressure relief valve begins to open to relieve pressure upstream of valve

Note 1 to entry: This concept is also sometimes referred to as "cracking" or "opening" pressure.

4 Marking

Marking of the component shall provide sufficient information to allow the following to be traced:

- a) the manufacturer's or agent's name, trademark or symbol;
- b) the model designation (part number);
- c) the working pressure or working pressure and temperature range;
- d) the discharge pressure.

The following additional marking entries are recommended:

- the direction of flow (when necessary for correct installation);
- the type of fuel;
- the electrical rating (if applicable);
- the symbol of the certification agency;
- the type approval number;
 the type approval number;
- the serial number or date code;
- a reference to this document.

NOTE This information can be provided by a suitable identification code on at least one part of the component when it consists of more than one part.

5 Design and assembly

The pressure relief valve (PRV) shall comply with the applicable provisions of ISO 22760-1 and ISO 22760-2, and pass the tests specified in Clause 6.

Additional requirements to the design of the PRV and to its assembly with other fuel system components are as follows:

- mounting location of the PRV relative to the fuel container geometry and positioning in use is such that the contact of the PRV inlet with the liquid phase of the fuel is avoided as much as possible;
- discharge pressure is not greater than the working pressure of the DME fuel container.

6 Tests

6.1 Applicability

The required tests are indicated in <u>Table 1</u>.