
**Information technology — Multimedia
application format (MPEG-A) —**

**Part 19:
Common media application format
(CMAF) for segmented media**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

*Technologies de l'information — Format pour application multimédia
(MPEG-A) —*

*Partie 19: Format CMAF (Common Media Application Format) pour
médias segmentés*

ISO/IEC 23000-19:2020

<https://standards.iteh.ai/catalog/standards/sist/38819e8e-0a94-48b9-aff6-08dc035d7bd4/iso-iec-23000-19-2020>



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 23000-19:2020

<https://standards.iteh.ai/catalog/standards/sist/38819e8e-0a94-48b9-aff6-08dc035d7bd4/iso-iec-23000-19-2020>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	vii
Introduction	viii
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
3.1 Media objects.....	3
3.2 Logical structure.....	3
3.3 Application model.....	4
4 Abbreviated terms	6
5 Document organization	8
6 CMAF hypothetical application model, media object model and profiles	10
6.1 Overview of the hypothetical application model and media object model.....	10
6.2 CMAF content processing model.....	11
6.3 Late binding CMAF track synchronization.....	12
6.4 Adaptive switching of CMAF tracks in CMAF switching sets.....	13
6.5 CMAF specified objects and profiles.....	14
6.5.1 Object derivation and interoperability code points.....	14
6.5.2 Encoded media objects.....	14
6.5.3 Logical media object sets.....	14
6.5.4 Addressable media objects.....	14
6.5.5 CMAF profiles, brand and identifiers.....	15
6.6 CMAF media object model.....	16
6.6.1 CMAF fragments.....	16
6.6.2 CMAF tracks.....	17
6.6.3 CMAF track files.....	17
6.6.4 CMAF segments.....	18
6.6.5 CMAF chunks.....	18
6.6.6 CMAF switching sets and adaptive switching.....	19
6.6.7 CMAF selection sets and late binding.....	22
6.6.8 CMAF presentation timing model.....	23
6.6.9 Manifest information.....	26
6.6.10 CMAF addressable media objects, resources, and resource identifiers.....	26
7 CMAF track format	27
7.1 Overview.....	27
7.2 CMAF brands.....	27
7.3 CMAF media objects.....	28
7.3.1 CMAF boxes.....	28
7.3.2 CMAF track media objects.....	30
7.3.3 CMAF addressable media objects.....	34
7.3.4 CMAF switching sets.....	36
7.3.5 CMAF selection sets.....	39
7.3.6 CMAF presentations.....	39
7.4 Additional boxes, not defined in the ISO Base Media File Format.....	40
7.4.1 Track Encryption Box ('tenc').....	40
7.4.2 Sample Encryption Box ('senc').....	40
7.4.3 Protection System Specific Header Box ('pssh').....	40
7.4.4 Media profile specific boxes.....	40
7.4.5 Event Message Box ('emsg').....	40
7.5 Constraints on ISO Base Media File Format boxes.....	41
7.5.1 Movie Header Box ('mvhd').....	41
7.5.2 Metadata Boxes.....	41
7.5.3 Kind Box ('kind').....	41

7.5.4	Track Header Box ('tkhd')	42
7.5.5	Media Header Box ('mdhd')	42
7.5.6	Video Media Header Box ('vmhd')	42
7.5.7	Sound Media Header Box ('smhd')	43
7.5.8	Subtitle Media Header Box ('sthd')	43
7.5.9	Data Reference Box ('dref')	43
7.5.10	Sample Description Box ('stsd')	43
7.5.11	Protection Scheme Information Box ('sinf')	43
7.5.12	Track contained media sample information boxes	43
7.5.13	Edit List Box ('elst')	44
7.5.14	Track Extends Box ('trex')	44
7.5.15	Movie Fragment Header Box ('mfhd')	44
7.5.16	Track Fragment Header Box ('tfhd')	44
7.5.17	Track Run Box ('trun')	45
7.5.18	Sample Group Description Box ('sgpd')	45
7.5.19	Media Data Box ('mdat')	45
7.5.20	Sub-sample Information Box ('subs')	46
7.6	The Structural CMAF Brand 'cmfc'	46
7.7	The structural CMAF Brand 'cmf2'	46
7.7.1	General	46
7.7.2	Edit List Box ('elst')	46
7.7.3	Track Run Box ('trun')	46
8	Common encryption of CMAF tracks	46
8.1	Multiple DRM system support	46
8.2	Track encryption	47
8.2.1	General requirements	47
8.2.2	CMAF track constraints	48
8.2.3	Encryption constraints	49
8.2.4	CMAF presentation encryption	50
9	Video CMAF tracks	50
9.1	Overview	50
9.2	General video CMAF track format	51
9.2.1	General video CMAF track structure and constraints	51
9.2.2	Video Media Header ('vmhd')	51
9.2.3	Track Header Box ('tkhd')	52
9.2.4	Sample Description Box ('stsd')	52
9.2.5	Video CMAF fragment presentation time	53
9.2.6	Video media sample dependencies	53
9.2.7	Video edit lists	53
9.2.8	General video CMAF fragment random access constraints	53
9.2.9	Additional random access pictures within CMAF video fragments	53
9.2.10	Image framing and encoding constraints	54
9.2.11	General video CMAF switching set constraints	54
9.3	NAL structured video CMAF tracks	55
9.3.1	Overview	55
9.3.2	CMAF track format constraints for NAL structured video	56
9.3.3	NAL structured video access units contained in media samples	57
9.3.4	NAL structured video coding sequences corresponding to CMAF fragments	57
9.3.5	Elementary stream constraints	58
9.3.6	General CMAF switching set constraints for NAL structured video	58
9.3.7	Single initialization CMAF switching set constraints for NAL structured video tracks and media profiles	58
9.4	AVC video CMAF tracks	59
9.4.1	Storage of AVC elementary streams	59
9.4.2	Constraints on AVC elementary streams	60
9.5	AVC video Internet Media Type parameters	61
9.5.1	AVC signalling of "codecs" parameters	61

10	Audio CMAF tracks	62
10.1	Overview.....	62
10.2	General audio CMAF track format.....	62
10.2.1	Derivation.....	62
10.2.2	Track Header Box (' <i>tkhd</i> ').....	62
10.2.3	Sound Media Header Box (' <i>smhd</i> ').....	63
10.2.4	Sample Description Box (' <i>stsd</i> ').....	63
10.2.5	AudioSampleEntry.....	63
10.2.6	Audio offset edit list.....	63
10.3	AAC audio CMAF tracks.....	63
10.3.1	Overview.....	63
10.3.2	" <i>codecs</i> " parameter signalling.....	63
10.3.3	Considerations for AAC audio encoding.....	64
10.3.4	AAC track constraints.....	65
10.3.5	AAC elementary stream constraints.....	66
10.4	AAC core audio CMAF media profile.....	67
10.5	AAC adaptive switching audio CMAF media profile.....	67
10.5.1	General constraints.....	67
10.5.2	CMAF fragment encoding constraints.....	68
10.5.3	General considerations and requirements.....	68
10.5.4	Constraints for AAC-LC.....	68
10.5.5	Constraints for HE-AAC.....	69
10.5.6	Constraints for HE-AACv2.....	70
11	Subtitles and captions	71
11.1	Overview.....	71
11.2	WebVTT.....	71
11.3	IMSC text and image tracks.....	72
11.3.1	General.....	72
11.3.2	Common constraints.....	72
11.3.3	IMSC1 text track constraints.....	73
11.3.4	IMSC1 image track constraints.....	73
11.4	CTA-608 and CTA-708.....	73
11.5	Metadata for subtitles.....	74
12	CMAF media profiles and CMAF presentation profiles	74
12.1	CMAF media profiles.....	74
12.1.1	General guidelines for specifying CMAF media profiles.....	74
12.1.2	Guidelines for audio CMAF media profiles.....	75
12.1.3	Guidelines for video CMAF media profiles.....	75
12.2	CMAF presentation profiles.....	76
12.2.1	General.....	76
12.2.2	CMAF profile conformance.....	76
	Annex A (normative) CMAF presentation profiles, media profiles and supplemental data	79
	Annex B (normative) HEVC video CMAF track format and CMAF media profiles	83
	Annex C (informative) Subsampling of NAL structured video tracks in CMAF switching sets	88
	Annex D (informative) Hypothetical player model	98
	Annex E (informative) Event messages	101
	Annex F (informative) Error handling for missing media	102
	Annex G (informative) Recommendations for AAC CMAF switching set encoding	103
	Annex H (normative) Scalable HEVC media profile and track format	106
	Annex I (normative) AAC multichannel CMAF media profiles and track format	112
	Annex J (normative) MPEG-H 3D audio track format and CMAF media profile	115
	Annex K (normative) MPEG-D USAC track format and CMAF media profile	120

Annex L (normative) IMSC 1.1 media profiles	122
Bibliography	124

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 23000-19:2020

<https://standards.iteh.ai/catalog/standards/sist/38819e8e-0a94-48b9-aff6-08dc035d7bd4/iso-iec-23000-19-2020>

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see <http://patents.iec.ch>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

This second edition cancels and replaces the first edition (ISO/IEC 23000-19:2018), which has been technically revised. It also incorporates the Amendments ISO/IEC 23000-19:2018/Amd.1:2018 and ISO/IEC 23000-19:2018/Amd.2:2019.

The main changes compared to the previous edition are as follows:

- addition of supplemental data brands;
- modification to the structural brand $cmfc$ for compatibility with DASH segments;
- definition of a stricter brand ' $cmf2$ ' for legacy devices;
- refinements and updates to HEVC media profiles for SDR and HDR;
- definition of the scalable HEVC media profile;
- definition of AAC multichannel media profiles;
- definition of MPEG-H 3D audio track format and CMAF media profile;
- definition of MPEG-D USAC track format and CMAF media profile;
- definition of IMSC1.1 media profile.

A list of all parts in the ISO/IEC 23000 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Common media application format (CMAF) combines and constrains several MPEG specifications to define a multimedia format that is optimized for delivery of a single adaptive multimedia presentation to a variety of devices, using a variety of adaptive streaming, broadcast, download and storage methods.

Several MPEG specifications have been adopted for much of the video delivered over the internet and other IP networks (cellular, cable, broadcast, etc.). Various organizations have taken MPEG's core coding, file format and system standards and combined them into their own specifications for their specific application. While these specifications are similar, their differences result in unnecessary duplication of engineering effort and duplication of identical content in slightly different formats, which results in increased storage and delivery costs.

CMAF provides a common media specification that application specifications, such as MPEG dynamic adaptive streaming over HTTP (DASH), can reference and a common media format that allows a single encoded multimedia presentation to be used by many applications.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 23000-19:2020](https://standards.iteh.ai/catalog/standards/sist/38819e8e-0a94-48b9-aff6-08dc035d7bd4/iso-iec-23000-19-2020)

<https://standards.iteh.ai/catalog/standards/sist/38819e8e-0a94-48b9-aff6-08dc035d7bd4/iso-iec-23000-19-2020>

Information technology — Multimedia application format (MPEG-A) —

Part 19: Common media application format (CMAF) for segmented media

1 Scope

This document specifies the CMAF multimedia format, which contains segmented media objects optimized for streaming delivery and decoding on end user devices in adaptive multimedia presentations.

CMAF specifies a track format derived from the ISO base media file format, then derives addressable media objects from CMAF tracks that can be used for storage and delivery.

CMAF specifies sets of tracks that share encoding and packaging constraints that enable the selection of multiple tracks to form a multimedia presentation and allow seamless switching of alternative encodings of the same content at different bit rates, frame rates, resolution, etc.

CMAF specifies a hypothetical application model that determines how tracks in a CMAF presentation are intended to be combined and synchronized to form a multimedia presentation. The model abstracts delivery to allow any delivery method. The hypothetical application model assumes a manifest and player, but CMAF does not specify a manifest, player, or delivery protocol, with the intent that any that support the hypothetical application model can be used.

CMAF specifies media profiles and brands that constrain media encoding and packaging of CMAF tracks to enable seamless adaptive switching of tracks and allow devices to identify compatible content by its brand.

CMAF specifies presentation profiles that conditionally require sets of CMAF tracks conforming to specified media profiles and allow content creators and devices to identify compatible multimedia presentations.

CMAF enables extensibility by specifying how new media profiles and presentation profiles can be specified and identified and includes guidelines for those specifications.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 14496-1, *Information technology — Coding of audio-visual objects — Part 1: Systems*

ISO/IEC 14496-3, *Information technology — Coding of audio-visual objects — Part 3: Audio*

ISO/IEC 14496-10, *Information technology — Coding of audio-visual objects — Part 10: Advanced video coding*

ISO/IEC 14496-12, *Information technology — Coding of audio-visual objects — Part 12: ISO base media file format*

ISO/IEC 14496-14, *Information technology — Coding of audio-visual objects — Part 14: MP4 file format*

ISO/IEC 23000-19:2020(E)

ISO/IEC 14496-15, *Information technology — Coding of audio-visual objects — Part 15: Carriage of network abstraction layer (NAL) unit structured video in the ISO base media file format*

ISO/IEC 14496-30, *Information technology — Coding of audio-visual objects — Part 30: Timed text and other visual overlays in ISO base media file format*

ISO/IEC 23001-7, *Information technology — MPEG systems technologies — Part 7: Common encryption in ISO base media file format files*

ISO/IEC 23008-2, *Information technology — High efficiency coding and media delivery in heterogeneous environments — Part 2: High efficiency video coding*

ISO/IEC 23009-1, *Information technology — Dynamic adaptive streaming over HTTP (DASH) — Part 1: Media presentation description and segment formats*

ISO/IEC 23008-3:2019, *Information technology — High efficiency coding and media delivery in heterogeneous environments — Part 3: 3D audio*

ISO/IEC 23091-3, *Information technology — Coding-independent code points — Part 3: Audio*

ISO/IEC 23003-4:2015, *MPEG audio technologies — Part 4: Dynamic range control*

ISO/IEC 23003-3:2012, *Information technology — MPEG audio technologies — Part 3: Unified speech and audio coding*

IETF RFC 5234, *Augmented BNF for Syntax Specifications: ABNF*, <https://tools.ietf.org/html/rfc5234>

IETF RFC 6381:2011, *The 'Codecs' and 'Profiles' Parameters for "Bucket" Media Types*, <https://tools.ietf.org/html/rfc6381>

ITU-R Recommendation BT.709, *Parameter values for the HDTV standards for production and international programme exchange*

ITU-R Recommendation BT.1886, *Reference electro-optical transfer function for flat panel displays used in HDTV studio production*

ITU-R Recommendation BT.2035, *A reference viewing environment for evaluation of HDTV program material or completed programmes*

ITU-T Recommendation X.667:2014, *Information technology — Open Systems Interconnection — Procedures for the operation of OSI Registration Authorities: Generation and registration of Universally Unique Identifiers (UUIDs) and their use as ASN.1 object identifier components*, <https://www.itu.int/rec/T-REC-X.667>

ANSI/CTA-608-E R-2014, *Line 21 Data Services*, http://www.techstreet.com/standards/cta-608-e-r2014?product_id=1815447

ANSI/CTA-708-E, *Digital Television (DTV) Closed Captioning*, http://www.techstreet.com/standards/cta-708-e?product_id=1860354

W3C IMSC1, *TTML Profiles for Internet Media Subtitles and Captions 1.0*, <http://www.w3.org/TR/ttml-imscl>

W3C IMSC1.1, *TTML Profiles for Internet Media Subtitles and Captions 1.1*, <http://www.w3.org/TR/ttml-imscl1>

W3C, *TTML Media Type Definition and Profile Registry*, *W3C Working Group Note*, <https://www.w3.org/TR/ttml-profile-registry>

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1 Media objects

3.1.1

CMAF fragment

encoded ISO BMFF media segment conforming to CMAF constraints

3.1.2

CMAF header

sequence of CMAF constrained ISO BMFF boxes that do not reference any *media samples* (3.3.15), but are associated with a *CMAF track* (3.2.1) and necessary for the decoding of its *CMAF fragments* (3.1.1)

3.1.3

CMAF addressable media object

CMAF media object packaged for storage or delivery

Note 1 to entry: Examples include a *CMAF track file* (3.1.6) containing a *CMAF header* (3.1.2) and *CMAF fragments* (3.1.1), or a *CMAF segment* (3.1.5) containing one or more CMAF fragments, or a *CMAF chunk* (3.1.4) containing a partial sequence of the *media samples* (3.3.15) of a CMAF fragment.

3.1.4

CMAF chunk

CMAF media object that contains a consecutive subset of the *media samples* (3.3.15) of a *CMAF fragment* (3.1.1), where only the first CMAF chunk of a CMAF fragment is constrained to be an adaptive *switching* (3.3.9) point

iTeh STANDARD PREVIEW

(standards.iteh.ai)

ISO/IEC 23000-19:2020

3.1.5

CMAF segment

CMAF addressable media object (3.1.3) consisting of one or more consecutive *CMAF fragments* (3.1.1) from the same *CMAF track* (3.2.1)

<https://standards.iteh.ai/catalog/standards/sist/38819e8e-0a94-48b9-aff6-08dc035d7bd4/iso-iec-23000-19-2020>

Note 1 to entry: A “CMAF segment” is conformant to an “ISO BMFF segment” and a “DASH segment”.

3.1.6

CMAF track file

one *CMAF track* (3.2.1) stored consecutively in a single ISO BMFF file with the earliest *CMAF fragment* (3.1.1) constrained to start at decode time zero

3.2 Logical structure

3.2.1

CMAF track

sequence of *CMAF fragments* (3.1.1) that are consecutive in presentation time, contain one media stream, conform to at least one structural CMAF brand, together with an associated *CMAF header* (3.1.2) that can initialize playback

3.2.2

CMAF switching set

set of one or more *CMAF tracks* (3.2.1), where each track is an alternative encoding of the same source content, and are constrained to enable seamless *track switching* (3.3.9)

3.2.3

aligned CMAF switching set

set of *CMAF switching sets* (3.2.2), the *CMAF tracks* (3.2.1) of which all contain alternative encodings of the same source content in time-aligned *CMAF fragments* (3.1.1), but all CMAF tracks do not conform to a single CMAF switching set

3.2.4

CMAF selection set

set of one or more *CMAF switching sets* (3.2.2), where each CMAF switching set encodes an alternative aspect of the same presentation over the same time period, only one of which is intended to be played at a time, e.g., an alternative language or codec

3.2.5

CMAF presentation

set of one or more *CMAF selection sets* (3.2.4) that can be simultaneously decoded to produce a multimedia user experience, potentially including synchronized audio, video, and subtitles

3.2.6

CMAF media profile

encoding constraint on a *CMAF track* (3.2.1) and its contained *media samples* (3.3.15) associated with a CMAF structural brand

3.2.7

CMAF presentation profile

requirement on the *CMAF media profiles* (3.2.6) contained in a *CMAF presentation* (3.2.5)

3.2.8

required media profile

CMAF media profile (3.2.6) conditionally required by a *CMAF presentation profile* (3.2.7)

3.2.9

manifest

document describing one or more *CMAF presentations* (3.2.5)

Note 1 to entry: Manifest formats are not specified in this document.

3.2.10

audio programme

complete collection of all audio programme components and, if present, a set of accompanying presets

3.2.11

audio programme component

smallest addressable unit of an audio programme

3.2.12

CMAF supplemental data

data that can be present in a *CMAF track* (3.2.1) and its contained *media samples* (3.3.15) conformant to a set of requirements identified by a brand

3.2.13

CMAF structural brand

four-character code used in brand-signaling boxes to indicate compliance to box-level constraints as opposed to media-level constraints

3.3 Application model

3.3.1

CMAF hypothetical application model

CMAF presentation (3.2.5) application model based on *late binding* (3.3.3) and synchronization of *CMAF tracks* (3.2.1) that partly determines the CMAF track encoding constraints necessary for an intended CMAF presentation

3.3.2

player

component of the *CMAF hypothetical application model* (3.3.1) responsible for interpreting a *manifest* (3.2.9), requesting resources, and rendering a *CMAF presentation* (3.2.5)

3.3.3**late binding**

selection (3.3.8) and synchronization of separately stored *CMAF tracks* (3.2.1) by a *player* (3.3.2) resulting in a synchronized multimedia presentation

3.3.4**CMAF presentation timeline**

timeline shared by all *CMAF tracks* (3.2.1) in a *CMAF presentation* (3.2.5), starting at CMAF presentation time zero, which is coincident with the earliest *media samples* (3.3.15) intended for presentation

3.3.5**presentation time offset**

earliest presentation time of each *CMAF track* (3.2.1) at the start of a *CMAF presentation* (3.2.5)

Note 1 to entry: Presentation time offset is an encoded property of tracks in a presentation, but it can also refer to that value stored in a *manifest* (3.2.9).

3.3.6**CMAF fragment duration**

sum of the *media sample* (3.3.15) durations documented in the `TrackFragmentRunBox` of all `MovieFragmentHeaderBoxes` in the *CMAF fragment* (3.1.1)

3.3.7**CMAF presentation duration**

sum of the *CMAF fragment durations* (3.3.6) of the longest *CMAF track* (3.2.1) in a *CMAF presentation* (3.2.5), starting from its earliest presentation time on the *CMAF presentation timeline* (3.3.4)

3.3.8**selection**

choice of a *CMAF track* (3.2.1) from alternatives in a selection set (e.g., selecting an audio track by language), possibly by user action or stored user preference

3.3.9**switching**

changing to a different *CMAF track* (3.2.1) during presentation, including adaptively switching between *CMAF fragments* (3.1.1) in a *CMAF switching set* (3.2.2)

3.3.10**seamless switching**

switching (3.3.9) between *CMAF tracks* (3.2.1) without interrupting presentation of the media content, i.e., decoding *media samples* (3.3.15), at the same time and quality as though their containing CMAF track was decoded without switching

3.3.11**CMAF switching set constraints**

CMAF media profile (3.2.6) constraints that enable seamless *switching* (3.3.9) between *CMAF tracks* (3.2.1) in a *CMAF switching set* (3.2.2) conforming to that media profile

3.3.12**single initialization CMAF switching set constraints**

additional *CMAF switching set constraints* (3.3.11) so *CMAF fragments* (3.1.1) do not depend on a different *CMAF header* (3.1.2) when *switching* (3.3.9)

3.3.13**resource identifier**

externally specified identifier that identifies a *CMAF addressable media object* (3.1.3)

Note 1 to entry: An example is a URI or other object identifier specified by a delivery protocol and *manifest* (3.2.9).

3.3.14

stream access point

media sample (3.3.15) random access property

Note 1 to entry: This is numbered as in ISO/IEC 14496-12:2015, Annex I.

3.3.15

media sample

media data in a *CMAF fragment* (3.1.1) associated with a single decode start time and duration

Note 1 to entry: The term “sample” is often used in the context of video to refer to the spatial samples of an image and in the context of audio to refer to PCM waveform samples. In this document, each type of sample is identified by a defined term. A media sample defined by ISO BMFF is always identified by the term “media sample”. The word “sample” is frequently used in ISO BMFF to refer to objects and parameters such as a “sample entry”, “sample size”, etc., and those terms are used without modification in this document.

3.3.16

audio PCM sample

digital sample quantizing the amplitude of an audio waveform at regular and frequent intervals, e.g., 48 kHz

3.3.17

video spatial sample

quantized values representing the colour and brightness of an area of an image corresponding to a two-dimensional spatial tessellation of the image

3.3.18

subsampling

video encoding using a smaller number of video spatial samples (3.3.17) than the source video, that number being an integer submultiple that can be scaled to the source video size based on video stream parameters without position shift or picture aspect ratio distortion

<https://standards.iteh.ai/catalog/standards/sist/38819e8e-0a94-48b9-aff6-08dc035d7bd4/iso-iec-23000-19-2020>

iTeh STANDARD PREVIEW

(standards.iteh.ai)

4 Abbreviated terms

AAC	advanced audio coding
ABNF	augmented backus-naur form
ADIF	audio data interchange format
ADTS	audio data transport stream
AOT	audio object type
ASC	audio specific configuration
AU	access unit
AVC	advanced video coding
CCE	coupling channel element
CDN	content delivery network
CMAF	common media application format
CPE	channel pair element

CVS	coded video sequence [A sequence of media samples (coded video frames), starting with a SAP type 1 or 2, and including all media samples prior to the next SAP type 1 or 2 in decoding order.]
DASH	dynamic adaptive streaming over HTTP
DRC	dynamic range control
DRM	digital rights management
DSE	data stream element
DTV	digital television
EBU	European Broadcast Union
EOTF	electro-optical transfer function
GOP	group of pictures
HDMI	high-definition multimedia interface
HDR	high dynamic range
HDTV	high definition television
HEVC	high efficiency video coding
HLG	hybrid log-gamma
HRD	hypothetical reference decoder
IDR	instantaneous decoding refresh
IMDCT	inverse modified discrete cosine transform
IPF	immediate playout frames
ISO BMFF	ISO base media file format, defined in ISO/IEC 14496-12
KID	key identifier, defined in ISO/IEC 23001-7
LFE	low frequency enhancement
LKFS	loudness, K-weighted, relative to nominal full scale
MAE	MPEG-H audio metadata information
MHAS	MPEG-H audio stream
MIME	multipurpose internet mail extensions
MPD	media presentation description
MPEG	moving picture experts group
MSE	media source extension
NAL	network adaptation layer
NTSC	National Television System Committee