

ISO/TC 70/SC 8

Secretariat: DIN

Voting begins on:
2020-03-23

Voting terminates on:
2020-05-18

Reciprocating internal combustion engines — Exhaust emission measurement —

Part 4: Steady-state and transient test cycles for different engine applications

Moteurs alternatifs à combustion interne — Mesurage des émissions de gaz d'échappement —

Partie 4: Cycles d'essai en régimes permanent et transitoire pour différentes applications des moteurs

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number
ISO/FDIS 8178-4:2020(E)

© ISO 2020

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/1023745-25d7-4a14-bb53-9de43a7f054c/iso-fdis-8178-4>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	vi
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	11
4.1 General symbols.....	11
4.2 Symbols and abbreviated terms for fuel composition.....	13
4.3 Symbols and abbreviated terms for chemical components.....	14
4.4 Abbreviated terms.....	14
5 Test conditions	15
5.1 Engine test conditions.....	15
5.1.1 Laboratory test conditions.....	15
5.1.2 Test validity.....	16
5.2 Engine power.....	16
5.2.1 Auxiliaries to be fitted.....	16
5.2.2 Auxiliaries to be removed.....	16
5.2.3 Determination of auxiliary power.....	17
5.2.4 Engine cycle work.....	17
5.3 Engine intake air.....	17
5.3.1 General.....	17
5.3.2 Intake air restriction.....	17
5.3.3 Engines with charge air cooling.....	18
5.4 Engine exhaust system.....	18
5.4.1 General.....	18
5.4.2 Exhaust restriction.....	18
5.4.3 Engine with exhaust after-treatment system.....	18
5.5 Specific test conditions.....	19
5.5.1 Engine with exhaust after-treatment system.....	19
5.5.2 Crankcase emissions.....	22
5.6 Cooling system.....	23
5.7 Lubricating oil.....	23
6 Test fuels	23
7 Test cycles	24
7.1 General.....	24
7.2 Test speeds.....	24
7.2.1 Maximum test speed (MTS).....	24
7.2.2 Rated speed.....	25
7.2.3 Intermediate speed.....	25
7.2.4 Idle speed.....	26
7.2.5 Test speed for constant-speed engines.....	26
7.3 Torque and power.....	27
7.3.1 Torque.....	27
7.3.2 Power.....	28
7.4 Engine mapping.....	28
7.4.1 Engine mapping for transient cycles.....	29
7.4.2 Engine mapping for variable-speed steady-state cycles.....	30
7.4.3 Engine mapping for constant-speed engines.....	30
7.5 Steady-state test cycles.....	31
7.5.1 Discrete mode test cycles.....	31
7.5.2 Ramped-modal test cycles.....	33
7.5.3 Cycle types and applicability.....	33

7.6	Transient cycles.....	37
7.6.1	General.....	37
7.6.2	Non-road transient cycle (NRTC).....	37
7.6.3	Large spark-ignition non-road transient cycle.....	38
7.7	Test cycle generation.....	38
7.7.1	Generation of steady-state discrete-mode or RMC test cycles.....	38
7.7.2	Generation of NRTC and LSI-NRTC.....	39
8	Test run.....	42
8.1	General test sequence.....	42
8.2	Instrument validation for test.....	44
8.2.1	Validation of proportional flow control for batch sampling and minimum dilution ratio for PM batch sampling.....	44
8.2.2	Gas analyser range validation, drift validation and drift correction.....	45
8.2.3	PM sampling media (e.g. filters) preconditioning and tare weighing.....	45
8.3	Sample system decontamination and preconditioning.....	47
8.3.1	Verification of HC contamination.....	48
8.4	Pre-test procedures.....	49
8.4.1	Preparation of the sampling filters.....	49
8.4.2	General requirements for preconditioning the sampling system and the engine.....	49
8.4.3	Engine cool down (NRTC).....	50
8.4.4	Preparation of measurement equipment for sampling.....	50
8.4.5	Calibration of gas analysers.....	51
8.4.6	Adjustment of the dilution system.....	51
8.5	Engine starting and restarting.....	51
8.5.1	Engine start.....	51
8.5.2	Engine stalling.....	51
8.6	Test cycle running procedure.....	52
8.6.1	Test sequence for discrete steady-state test cycles.....	52
8.6.2	Ramped-modal test cycles.....	53
8.6.3	Transient test cycle (NRTC and LSI-NRTC).....	54
8.7	Post-test procedures.....	57
8.7.1	Verification of proportional sampling.....	57
8.7.2	Post-test PM conditioning and weighing.....	57
8.7.3	Analysis of gaseous batch sampling.....	58
8.7.4	Drift verification.....	59
9	Data evaluation and calculation.....	59
9.1	Gaseous emissions.....	59
9.1.1	General.....	59
9.1.2	Sampling for gaseous emissions.....	59
9.1.3	Data evaluation.....	61
9.1.4	Calculation of mass emission.....	61
9.1.5	Dry/wet correction.....	67
9.1.6	NO _x correction for humidity and temperature.....	71
9.1.7	Cycle work and specific emissions.....	71
9.1.8	NH ₃ data evaluation.....	73
9.2	Particulate mass emission.....	74
9.2.1	General.....	74
9.2.2	Particulate sampling.....	74
9.2.3	Data evaluation.....	74
9.2.4	Calculation of mass emission.....	75
9.2.5	Effective weighting factor (steady-state discrete cycles only).....	80
9.3	Adjustment for emission controls that are regenerated on an infrequent (periodic) basis.....	80
9.4	Particle number emission.....	81
9.4.1	Time alignment.....	81
9.4.2	Determination of particle numbers for transient and ramped-modal cycles (RMC) with a partial flow dilution or raw gas sampling system.....	81

9.4.3	Determination of particle numbers for transient and ramped-modal cycles (RMC) with a full flow dilution system	82
9.4.4	Determination of particles numbers for discrete-mode cycles with partial flow dilution or raw gas sampling system	83
9.4.5	Determination of particle numbers for discrete-mode cycles with a full flow dilution system	85
9.4.6	Test result	85
9.4.7	Determination of particle number background	87
9.5	Specific requirements for dual-fuel engines	87
9.5.1	Emission test procedure requirements for dual-fuel engines	87
9.5.2	Determination of molar component ratios and u_{gas} values for dual-fuel engines	91
10	Engine control area	93
10.1	General remarks	93
10.2	Control area for engines tested to cycles C1, C2, E1 and H	93
10.3	Control area for engines tested to cycles D1, D2, E2, G1, G2 and G3	95
10.4	Control area for engines tested to test cycle I	95
10.5	Control area for engines tested to E3 and E5 test cycle	96
10.5.1	Control area for CI marine engines	96
10.5.2	Control area for engines tested to the E4 test cycle	99
10.5.3	Control area for engines tested to the F cycle	100
Annex A	(normative) Steady-state discrete-mode test-cycles	102
Annex B	(normative) Steady-state ramped-modal test cycles (RMCs)	107
Annex C	(normative) Transient test cycles	113
Annex D	(informative) Calculation of the exhaust gas mass flow and/or of the combustion air mass flow	171
Annex E	(informative) Example programme for calculation of exhaust mass flows	192
Annex F	(informative) Example of calculation procedure (raw/partial flow)	194
Annex G	(normative) Installation requirements for equipment and auxiliaries	197
Annex H	(normative) Molar based emission calculations	199
Bibliography	239

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/TC 70, *Reciprocating internal combustion engines*, Subcommittee SC 8, *Exhaust gas emission measurement*.

This fourth edition cancels and replaces the third edition (ISO 8178-4:2017), which has been technically revised.

The main changes compared to the previous edition are as follows:

- amendment of the information regarding the determination of the background concentration;
- revision of particle number emission evaluation;
- addition of electrical equipment in the auxiliary table;

A list of all the parts in the ISO 8178 series, can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

In comparison with engines for on-road applications, engines for non-road use are made in a much wider range of power output and configuration and are used in a great number of different applications.

The objective of this document is to rationalize the test procedures for non-road engines in order to simplify and make more cost effective the drafting of legislation, the development of engine specifications and the certification of engines to control gaseous and particulate emissions.

This document embraces three concepts in order to achieve the objectives.

The first principle is to group applications with similar engine operating characteristics in order to reduce the number of test cycles to a minimum, but ensure that the test cycles are representative of actual engine operation.

The second principle is to express the emissions results on the basis of brake power as defined in ISO 8178-1. This ensures that alternative engine applications do not result in a multiplicity of tests.

The third principle is the incorporation of an engine family concept in which engines with similar emission characteristics and of similar design may be represented by the highest emitting engine within the group.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/1023745-25d7-4a14-bb53-9de43a7f054c/iso-fdis-8178-4>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/1023745-25d7-4a14-bb53-9de43a7f054c/iso-fdis-8178-4>

Reciprocating internal combustion engines — Exhaust emission measurement —

Part 4: Steady-state and transient test cycles for different engine applications

1 Scope

This document specifies the test cycles, the test procedures and the evaluation of gaseous and particulate exhaust emissions from reciprocating internal combustion (RIC) engines coupled to a dynamometer. With certain restrictions, this document can also be used for measurements at site. The tests are carried out under steady-state and transient operation using test cycles which are representative of given applications.

This document is applicable to RIC engines for mobile, transportable and stationary use, excluding engines for on-road transport of passengers and goods. It can be applied to engines for non-road use, e.g. for earth-moving machines, generating sets and for other applications. For engines used in machinery covered by additional requirements (e.g. occupational health and safety regulations, regulations for power plants), additional test conditions and special evaluation methods can apply.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8178-1:—, *Reciprocating internal combustion engines — Exhaust emission measurement — Part 1: Test-bed measurement of gaseous and particulate exhaust emissions*

ISO 8178-5, *Reciprocating internal combustion engines — Exhaust emission measurement — Part 5: Test fuels*

ASTM E29–06b, *Standard Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

adjustment factors

additive (upward adjustment factor and downward adjustment factor) or multiplicative factors to be used for engines equipped with emission controls, that are regenerated on an infrequent (periodic) basis

**3.2
applicable emission limit**

emission limit to which an engine is subject

**3.3
aqueous condensation**

precipitation of water-containing constituents from a gas phase to a liquid phase

Note 1 to entry: Aqueous condensation is a function of humidity, pressure, temperature, and concentrations of other constituents such as sulphuric acid. These parameters vary as a function of engine intake-air humidity, dilution-air humidity, engine air-to-fuel ratio, and fuel composition — including the amount of hydrogen and sulphur in the fuel.

**3.4
atmospheric pressure**

wet, absolute, atmospheric static pressure

Note 1 to entry: If the atmospheric pressure is measured in a duct, negligible pressure losses shall be ensured between the atmosphere and the measurement location, and changes in the duct's static pressure resulting from the flow shall be accounted for.

**3.5
calibration**

process of setting a measurement system's response so that its output agrees with a range of reference signals

Note 1 to entry: Contrast with *verification* (3.78).

**3.6
calibration gas**

purified gas mixture used to calibrate gas analysers meeting the specifications of ISO 8178-1:—, 9.2

Note 1 to entry: Calibration gases and *span gases* (3.65) are qualitatively the same, but differ in terms of their primary function. Various performance *verification* (3.78) checks for gas analysers and sample handling components might refer to either calibration gases or span gases.

**3.7
certification**

process of obtaining a certificate of conformity

**3.8
compression ignition engine
CI engine**

engine that works on the compression-ignition principle

**3.9
constant-speed engine**

engine whose *type approval* (3.76) or *certification* (3.7) is limited to *constant-speed operation* (3.10)

Note 1 to entry: Engines whose constant-speed *governor* (3.29) function is removed or disabled are no longer constant-speed engines.

**3.10
constant-speed operation**

engine operation with a *governor* (3.29) that automatically controls the *operator demand* (3.47) to maintain engine speed, even under changing load

Note 1 to entry: Governors do not always maintain speed exactly constant. Typically, speed can decrease (0,1 to 10) % below the speed at zero load, such that the minimum speed occurs near the engine's point of *maximum power* (3.39).

3.11 continuous regeneration

regeneration (3.59) process of an *exhaust after-treatment system* (3.22) that occurs either in a sustained manner or at least once over the applicable *transient test cycle* (3.75) or ramped-modal cycle; in contrast to *infrequent (periodic) regeneration* (3.33)

3.12 conversion efficiency of non-methane cutter conversion efficiency of NMC

E

efficiency of the conversion of an NMC that is used for the removal of the *non-methane hydrocarbons* (3.44) from the sample gas by oxidizing all *hydrocarbons* (3.30) except methane

Note 1 to entry: Ideally, the conversion for methane is 0 % ($E_{\text{CH}_4} = 0$) and for the other hydrocarbons represented by ethane 100 % ($E_{\text{C}_2\text{H}_6} = 100$ %). For the accurate measurement of NMHC (3.44), the two efficiencies shall be determined and used for the calculation of the NMHC emission mass flow rate for methane and ethane. Contrast with *penetration fraction* (3.52).

3.13 delay time

difference in time between the change of the component to be measured at the reference point and a system response of 10 % of the final reading (t_{10}) with the sampling *probe* (3.54) being defined as the reference point

Note 1 to entry: For the gaseous components, this is the transport time of the measured component from the sampling probe to the detector (see [Figure 1](#)).

3.14 deNO_x system

exhaust after-treatment system (3.22) designed to reduce emissions of *oxides of nitrogen (NO_x)* (3.48)

EXAMPLE Passive and active lean NO_x catalysts, NO_x adsorbers and selective catalytic reduction (SCR) systems.

3.15 dew point

measure of humidity stated as the equilibrium temperature at which water condenses under a given pressure from moist air with a given absolute humidity

Note 1 to entry: Dew point is specified as a temperature in °C or K, and is valid only for the pressure at which it is measured.

3.16 drift

difference between a zero or calibration (3.5) signal and the respective value reported by a measurement instrument immediately after it was used in an emission test, as long as the instrument was *zeroed* (3.79) and *spanned* (3.64) just before the test

3.17 dual-fuel engine

engine system that is designed to simultaneously operate with *liquid fuel* (3.36) and a *gaseous fuel* (3.26), both fuels being metered separately, where the consumed amount of one of the fuels relative to the other one may vary depending on the operation

3.18 emission-control system

device, system, or element of design that controls or reduces the emissions of regulated pollutants from an engine

3.19

engine family

manufacturers grouping of engines which, through their design as defined in ISO 8178-7, have similar exhaust emission characteristics

Note 1 to entry: All members of the family shall comply with the *applicable emission limit* (3.2) values.

3.20

engine governed speed

engine operating speed when it is controlled by the installed *governor* (3.29)

3.21

engine type

category of engines which do not differ in essential engine characteristics

3.22

exhaust after-treatment system

catalyst, particulate filter, *deNO_x system* (3.14), combined deNO_x particulate filter or any other emission-reducing device that is installed downstream of the engine

Note 1 to entry: This definition excludes *exhaust-gas recirculation (EGR)* (3.23) and turbochargers, which are considered an integral part of the engine.

3.23

exhaust-gas recirculation

EGR

technology that reduces emissions by routing exhaust gases that had been exhausted from the combustion chamber(s) back into the engine to be mixed with incoming air before or during combustion

Note 1 to entry: The use of valve timing to increase the amount of residual exhaust gas in the combustion chamber(s) that is mixed with incoming air before or during combustion is not considered exhaust-gas recirculation for the purposes of this document.

3.24

full flow dilution

method of mixing the exhaust gas flow with dilution air prior to separating a fraction of the diluted exhaust gas flow for analysis

3.25

gas energy ratio

GER

value of the energy content (for a *dual-fuel engine* (3.17)) of the *gaseous fuel* (3.26) divided by the energy content of both fuels (liquid and gaseous), the energy content of the fuels being defined as the lower heating value

3.26

gaseous fuel

fuel which is wholly gaseous at standard ambient conditions

Note 1 to entry: Ambient temperature 298 K (25 °C), absolute ambient pressure 101,3 kPa.

3.27

gaseous pollutants

exhaust gas emissions of carbon monoxide, *NO_x* (3.48), expressed in NO₂ equivalent, *hydrocarbons* (3.30) (i.e. total hydrocarbons, *non-methane hydrocarbons* (3.44) and methane)

3.28

good engineering judgement

judgement made consistent with generally accepted scientific and engineering principles and available relevant information

3.29**governor**

device or control strategy that automatically controls engine speed or load that is not an over-speed limiter

3.30**hydrocarbon****HC**

hydrocarbon group on which the emission standards are based for each type of fuel and engine

EXAMPLE THC (3.73), NMHC (3.44) as applicable

3.31**high speed**

n_{hi}
highest engine speed where 70 % of the *maximum power* (3.39) occurs

3.32**idle speed**

engine speed declared by the manufacturer that conforms to the requirements of 7.2.4

3.33**infrequent regeneration****periodic regeneration**

regeneration (3.59) process of an *exhaust after-treatment system* (3.22) that occurs periodically in typically less than 100 hours of normal engine operation

Note 1 to entry: During cycles where regeneration occurs, emission standards may be exceeded.

3.34**intermediate speed**

engine speed declared by the manufacturer that conforms to the requirements of 7.2.3

3.35**linearity**

degree to which measured values agree with respective reference values quantified using a linear regression of pairs of measured values and reference values over a range of values expected or observed during testing

3.36**liquid fuel**

fuel which exists in the liquid state under standard ambient conditions (298 K, absolute ambient pressure 101,3 kPa)

3.37**low speed**

n_{lo}
lowest engine speed where 50 % of the *maximum power* (3.39) occurs

3.38**maximum no load speed**

engine speed at which an engine *governor* (3.29) function controls engine speed with *operator demand* (3.47) at maximum and with zero load applied

3.39**maximum power**

maximum power in kW as designed by the manufacturer

3.40**maximum test speed**

engine speed determined from the curve of engine speed versus power according to 7.2.1