



**SLOVENSKI STANDARD**  
**oSIST prEN ISO 24478:2024**  
**01-junij-2024**

---

**Železniške naprave - Zavore - Slovar (ISO 24478:2023)**

Railway applications - Braking - General vocabulary (ISO 24478:2023)

Bahnanwendungen - Bremsen - Fachbegriffe (ISO 24478:2023)

Applications ferroviaires - Freinage - Vocabulaire général (ISO 24478:2023)

**Ta slovenski standard je istoveten z: prEN ISO 24478**

---

**ICS:**

01.040.45	Železniška tehnika (Slovarji)	Railway engineering (Vocabularies)
45.040	Materiali in deli za železniško tehniko	Materials and components for railway engineering

**oSIST prEN ISO 24478:2024**

**en,fr,de**





# International Standard

**ISO 24478**

## Railway applications — Braking — General vocabulary

*Applications ferroviaires — Freinage — Vocabulaire général*

**First edition  
2023-08**

**Corrected version  
2024-04**

iTeh Standards  
(<https://standards.iteh.ai>)  
Document Preview

[oSIST prEN ISO 24478:2024](https://standards.iteh.ai/catalog/standards/sist/ff684072-ff56-40fe-b9c3-99717fae6ba7/osist-pren-iso-24478-2024)

<https://standards.iteh.ai/catalog/standards/sist/ff684072-ff56-40fe-b9c3-99717fae6ba7/osist-pren-iso-24478-2024>

## ISO 24478:2023(en)

# iTeh Standards (<https://standards.iteh.ai>) Document Preview

[oSIST prEN ISO 24478:2024](https://standards.iteh.ai/catalog/standards/sist/ff684072-ff56-40fe-b9c3-99717fae6ba7/osist-pren-iso-24478-2024)

<https://standards.iteh.ai/catalog/standards/sist/ff684072-ff56-40fe-b9c3-99717fae6ba7/osist-pren-iso-24478-2024>



### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

## ISO 24478:2023(en)

## Contents

	Page
<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
3.1 Basic definitions.....	1
3.2 Brake system compatibility.....	1
3.3 Performance.....	2
3.4 Purposes of braking.....	2
3.5 Mechanics of braking.....	2
3.6 Kinematics and dynamics of braking.....	4
3.7 Types and characteristics of brakes.....	9
3.8 Brake application and release.....	11
3.9 Brake control.....	12
3.9.1 General definitions.....	12
3.9.2 Types of control.....	13
3.9.3 Types of combined control.....	14
3.10 Brake system components.....	14
3.10.1 Components used for the command and control of braking.....	14
3.10.2 Sensors/indicators.....	16
3.10.3 Control assemblies.....	16
3.10.4 Brake control and/or system energy lines.....	17
3.10.5 Friction brake system components.....	18
3.10.6 Brake system energy storage.....	20
3.10.7 Compressed air supply.....	21
3.10.8 Ancillary air system equipment.....	21
3.10.9 Hydraulic pressure supply.....	21
3.10.10 Hand brake equipment.....	22
3.10.11 Parking brake equipment.....	22
3.11 Wheel slide protection (WSP).....	22
3.12 Types of brake test.....	23
<b>4 Symbols and abbreviated terms</b> .....	<b>23</b>
<b>Annex A (informative) Delay time and build-up time for brake application</b> .....	<b>24</b>
<b>Annex B (informative) Delay time and release time for brake release</b> .....	<b>25</b>
<b>Annex C (informative) Brake chart</b> .....	<b>26</b>
<b>Annex D (informative) Overview of relationship between brake devices and signals</b> .....	<b>29</b>
<b>Annex E (informative) System set up and components</b> .....	<b>30</b>
<b>Bibliography</b> .....	<b>33</b>

## ISO 24478:2023(en)

### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at [www.iso.org/patents](http://www.iso.org/patents). ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 269, *Railway applications*, Subcommittee SC 2, *Rolling stock*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

This corrected version of ISO 24478:2023 incorporates the following correction: footnotes "a" and "b" have been replaced with the symbols "c" and "d", respectively, in Figure B.1.

[oSIST prEN ISO 24478:2024](https://standards.iteh.ai/catalog/standards/sist/ff684072-ff56-40fe-b9c3-99717fae6ba7/osist-pren-iso-24478-2024)

<https://standards.iteh.ai/catalog/standards/sist/ff684072-ff56-40fe-b9c3-99717fae6ba7/osist-pren-iso-24478-2024>

**ISO 24478:2023(en)****Introduction**

This document provides unambiguous definitions of generic terminology used in the field of railway braking. The terms and definitions reflect those used in numerous published International Standards.

The braking includes all factors that have a bearing on the stopping, slowing or immobilization performance of the train (e.g. train resistance, gradient) and may involve the conversion and dissipation of braking energy.

**iTeh Standards**  
**(<https://standards.iteh.ai>)**  
**Document Preview**

[oSIST prEN ISO 24478:2024](https://standards.iteh.ai/catalog/standards/sist/ff684072-ff56-40fe-b9c3-99717fae6ba7/osist-pren-iso-24478-2024)

<https://standards.iteh.ai/catalog/standards/sist/ff684072-ff56-40fe-b9c3-99717fae6ba7/osist-pren-iso-24478-2024>





# Railway applications — Braking — General vocabulary

## 1 Scope

This document defines terms for brakes and braking in rolling stock.

## 2 Normative references

There are no normative references in this document.

## 3 Terms and definitions

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

### 3.1 Basic definitions

#### 3.1.1

##### **braking**

process generating controlled forces which result in the deceleration of the train, or maintaining a constant speed on a falling gradient, or preventing a stationary train from moving

#### 3.1.2

##### **brake**

brake system

combination of *brake unit(s)* (3.1.3) with their trainwide/local control device(s) ensuring one or more braking function(s)

oSIST prEN ISO 24478:2024

<https://standards.iteh.ai/catalog/standards/sist/ff684072-ff56-40fe-b9c3-99717fae6ba7/osist-pren-iso-24478-2024>

Note 1 to entry: Brakes and brake systems can also be used for other functions e.g. shunting, de-icing of friction brake units.

#### 3.1.3

##### **brake unit**

device or assembly of components, that generates a braking force

Note 1 to entry: See [Annex E](#).

Note 2 to entry: For tread brake and disc brake, it consists of the brake actuator, the friction material (pads or block) and the disc (for disc brake units).

Note 3 to entry: The *magnetic track brake* (3.7.3.3) unit includes two magnet assemblies (one per rail).

Note 4 to entry: The primary purpose of the brake unit might not be to generate a braking force, for example elements of the traction system can also function as a brake unit.

### 3.2 Brake system compatibility

#### 3.2.1

##### **brake system compatibility**

ability of the brake systems of coupled rail vehicles/trains to achieve the specified levels of braking performance, functionality and safety

## ISO 24478:2023(en)

### 3.3 Performance

#### 3.3.1

##### **braking performance**

parameters and their values used to quantify braking as described in applicable braking standards

#### 3.3.2

##### **deceleration**

result of a force acting contrary to the direction of movement

### 3.4 Purposes of braking

#### 3.4.1

##### **stopping**

braking from an initial speed to a standstill

#### 3.4.2

##### **slowing**

braking from an initial speed to a final speed, but not standstill

#### 3.4.3

##### **drag braking**

##### **continuous brake application**

braking on a falling gradient to maintain a substantially constant speed value

#### 3.4.4

##### **stationary braking**

braking used to prevent a stationary train from moving, using the holding, *immobilizing* (3.4.6) or *parking* (3.4.7) functions

#### 3.4.5

##### **holding**

braking which is used to prevent a stationary train from moving, under the specified conditions and for a specified time, when the brake system energy used is being replenished

Note 1 to entry: Holding is usually achieved by the application of the service brake.

#### 3.4.6

##### **immobilizing**

braking which is used to prevent a stationary train from moving, under the specified conditions and for a specified time, using just the brake system energy stored on the train

Note 1 to entry: Immobilizing is usually achieved by the application of the service brake or parking brake equipment.

#### 3.4.7

##### **parking**

braking which is used to prevent a stationary train from moving, under the specified conditions and for an indefinite period of time, without the need for any brake system energy replenishment following application

Note 1 to entry: Parking is usually achieved by the application of the parking brake equipment.

### 3.5 Mechanics of braking

#### 3.5.1

##### **braking force**

force generated by the brake system to stop, slow or hold the rail vehicle/unit/train stationary, or when drag braking the train

Note 1 to entry: It does not include external forces which contribute to the overall deceleration of the rail vehicle, unit or train (e.g. train resistance, gradient).

## ISO 24478:2023(en)

### 3.5.2

#### **retarding force**

force transmitted between the rail vehicle/unit/train and the external environment in reaction to an applied braking force

Note 1 to entry: For wheel/rail adhesion dependent brakes, the retarding force can be lower than or equal to the braking force depending on the available wheel/rail adhesion.

Note 2 to entry: The retarding force can be calculated for a single brake equipment type.

### 3.5.3

#### **decelerating force**

sum of longitudinal forces acting on a moving train during braking (combination of retarding forces with all other external and internal forces acting on a moving train)

Note 1 to entry: External forces can be caused by, for example, aerodynamic resistance, rising gradient or head wind.

Note 2 to entry: Internal forces can be caused by, for example, rolling resistance.

Note 3 to entry: External forces can also provide an accelerating effect (negative deceleration) in certain circumstances (e.g. falling gradient, tail wind).

Note 4 to entry: The general assessment is usually done on straight and level track to reduce the number of variables.

### 3.5.4

#### **retention force**

force transmitted between the rail vehicle/unit/train and the external environment in reaction to an applied braking force, used to hold the rail vehicle/unit/train stationary against the external forces (e.g. due to gradient or wind loads)

Note 1 to entry: For wheel/rail adhesion dependent brakes, the retention force can be lower than or equal to the braking force depending on the available wheel/rail adhesion.

### 3.5.5

#### **static mass**

mass of the rail vehicle/unit/train in a stationary condition

Note 1 to entry: Static mass is usually determined at the wheel-rail interface.

### 3.5.6

#### **equivalent rotating mass**

equivalent mass resulting from the moment of inertia of the wheels including coupled rotating parts

### 3.5.7

#### **dynamic mass**

sum of the static mass and the equivalent rotating mass

### 3.5.8

#### **wheel/rail adhesion**

physical phenomenon at the wheel-rail interface used to generate a retarding force

### 3.5.9

#### **coefficient of wheel/rail adhesion**

ratio of the tangential force at the wheel-rail interface and the force at this interface acting perpendicular to the surface of the rail

Note 1 to entry: Usually the term “required adhesion” or “demanded adhesion” defines the minimum level of adhesion to transmit the applied braking force (retarding force equal to braking force).

Note 2 to entry: Usually the term “available adhesion” defines the level of adhesion for which the effort that can be transmitted from the wheel to the rail according to the actual conditions is maximum.

## ISO 24478:2023(en)

### 3.6 Kinematics and dynamics of braking

#### 3.6.1

##### **fully-established brake**

state in which all relevant brake units are assumed to be generating their braking force corresponding to the brake demand

Note 1 to entry: The brake demand will be determined by the driver or the train control system.

Note 2 to entry: The term “fully-established brake” is not to be confused with the term “*full service brake application*” (3.8.3).

#### 3.6.2

##### **free running distance**

$s_a$   
distance travelled during the *delay time* (3.6.12)

#### 3.6.3

##### **build-up distance**

$s_{ab}$   
distance travelled during the *build-up time* (3.6.14)

#### 3.6.4

##### **braking distance with a fully-established brake**

$s_f$   
distance travelled with a fully-established brake to a point when achieving standstill or the final speed

#### 3.6.5

##### **braking distance**

$s_g$   
distance travelled from the commencement of the brake application until achieving standstill or the final speed

#### 3.6.6

##### **distance during release time**

$s_{cd}$   
distance travelled during the *release time* (3.6.15)

#### 3.6.7

##### **slowing distance**

$s_{sl}$   
distance travelled from the initiation of brake demand until achieving the final speed

#### 3.6.8

##### **stopping distance**

$s$   
distance travelled from the initiation of brake demand until standstill

#### 3.6.9

##### **equivalent free running distance**

$s_{a,e}$   
distance travelled during *equivalent response time* (3.6.22)

Note 1 to entry: During the equivalent response time, it is assumed that there is no braking force applied.

#### 3.6.10

##### **equivalent braking distance**

$s_{f,e}$   
distance travelled during the *equivalent braking time* (3.6.23)

Note 1 to entry: During the equivalent braking time it is assumed that the fully established braking force is applied.