



SLOVENSKI STANDARD
oSIST prEN IEC 62680-1-3:2024
01-julij-2024

**Vmesniki univerzalnega serijskega vodila za prenos podatkov in napajanje - 1-3.
del: Skupne komponente - Specifikacija za kable in priključke univerzalnega
serijskega vodila tipa C®**

Universal serial bus interfaces for data and power - Part 1-3: Common components -
USB type-c® cable and connector specification

iTeh Standards

Interfaces de bus universel en série pour les données et l'alimentation électrique - Partie
1-3: Composants communs - Spécification des câbles et des connecteurs USB type-c®

Ta slovenski standard je istoveten z: prEN IEC 62680-1-3:2024

[oSIST prEN IEC 62680-1-3:2024](https://standards.itih.ai/catalog/standards/sist/4bc1adaf-902f-4a77-a635-defcbeb5e520/osist-pr-en-iec-62680-1-3-2024)

<https://standards.itih.ai/catalog/standards/sist/4bc1adaf-902f-4a77-a635-defcbeb5e520/osist-pr-en-iec-62680-1-3-2024>

ICS:

35.200	Vmesniška in povezovalna oprema	Interface and interconnection equipment
--------	------------------------------------	--

oSIST prEN IEC 62680-1-3:2024 **en,fr,de**



100/4139/CDV

COMMITTEE DRAFT FOR VOTE (CDV)

PROJECT NUMBER: IEC 62680-1-3 ED6	
DATE OF CIRCULATION: 2024-05-10	CLOSING DATE FOR VOTING: 2024-08-02
SUPERSEDES DOCUMENTS: 100/4107/RR	

IEC TA 18 : MULTIMEDIA HOME SYSTEMS AND APPLICATIONS FOR END-USER NETWORKS	
SECRETARIAT: Japan	SECRETARY: Mr Keisuke Koide
OF INTEREST TO THE FOLLOWING COMMITTEES:	PROPOSED HORIZONTAL STANDARD: <input type="checkbox"/> Other TC/SCs are requested to indicate their interest, if any, in this CDV to the secretary.
FUNCTIONS CONCERNED: <input type="checkbox"/> EMC <input type="checkbox"/> ENVIRONMENT <input type="checkbox"/> QUALITY ASSURANCE <input type="checkbox"/> SAFETY	
<input checked="" type="checkbox"/> SUBMITTED FOR CENELEC PARALLEL VOTING Attention IEC-CENELEC parallel voting The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Committee Draft for Vote (CDV) is submitted for parallel voting. The CENELEC members are invited to vote through the CENELEC online voting system.	<input type="checkbox"/> NOT SUBMITTED FOR CENELEC PARALLEL VOTING

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Recipients of this document are invited to submit, with their comments, notification of any relevant "In Some Countries" clauses to be included should this proposal proceed. Recipients are reminded that the CDV stage is the final stage for submitting ISC clauses. (SEE [AC/22/2007](#) OR [NEW GUIDANCE DOC](#)).

TITLE:

Universal serial bus interfaces for data and power - Part 1-3: Common components - USB Type-C® cable and connector specification

PROPOSED STABILITY DATE: 2030

Copyright © 2024 International Electrotechnical Commission, IEC. All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

NOTE FROM TC/SC OFFICERS:

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[oSIST prEN IEC 62680-1-3:2024](https://standards.iteh.ai/catalog/standards/sist/4bc1adaf-902f-4a77-a635-defcbeb5e520/osist-pren-iec-62680-1-3-2024)

<https://standards.iteh.ai/catalog/standards/sist/4bc1adaf-902f-4a77-a635-defcbeb5e520/osist-pren-iec-62680-1-3-2024>

1
2
3
4
5
6
7
8
9
10
11
12

Universal Serial Bus Type-C Cable and Connector Specification

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

Release 2.3
October 2023

[oSIST prEN IEC 62680-1-3:2024](https://standards.iteh.ai/catalog/standards/sist/4bc1adaf-902f-4a77-a635-defcbeb5e520/osist-pren-iec-62680-1-3-2024)

<https://standards.iteh.ai/catalog/standards/sist/4bc1adaf-902f-4a77-a635-defcbeb5e520/osist-pren-iec-62680-1-3-2024>

13 **Copyright © 2014-2023, USB3.0 Promoter Group:**
14 **Apple Inc., HP Inc., Intel Corporation, Microsoft Corporation,**
15 **Renesas, STMicroelectronics, and Texas Instruments**

16 **All rights reserved.**

17
18 NOTE: Adopters may only use the USB Type-C® cable and connector to implement USB or third-party
19 functionality as expressly described in this Specification; all other uses are prohibited.

20 LIMITED COPYRIGHT LICENSE: The USB 3.0 Promoters grant a conditional copyright license under the
21 copyrights embodied in the USB Type-C Cable and Connector Specification to use and reproduce the
22 Specification for the sole purpose of, and solely to the extent necessary for, evaluating whether to implement
23 the Specification in products that would comply with the specification. Without limiting the foregoing, use of
24 the Specification for the purpose of filing or modifying any patent application to target the Specification or
25 USB compliant products is not authorized. Except for this express copyright license, no other rights or
26 licenses are granted, including without limitation any patent licenses. In order to obtain any additional
27 intellectual property licenses or licensing commitments associated with the Specification a party must
28 execute the USB 3.0 Adopters Agreement. NOTE: By using the Specification, you accept these license terms on
29 your own behalf and, in the case where you are doing this as an employee, on behalf of your employer.

30

31

32 INTELLECTUAL PROPERTY DISCLAIMER

33 THIS SPECIFICATION IS PROVIDED TO YOU "AS IS" WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY
34 WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE.
35 THE AUTHORS OF THIS SPECIFICATION DISCLAIM ALL LIABILITY, INCLUDING LIABILITY FOR
36 INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATING TO USE OR IMPLEMENTATION OF
37 INFORMATION IN THIS SPECIFICATION. THE PROVISION OF THIS SPECIFICATION TO YOU DOES NOT
38 PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY
39 INTELLECTUAL PROPERTY RIGHTS.

40 All implementation examples and reference designs contained within this Specification are included as part of
41 the limited patent license for those companies that execute the USB 3.0 Adopters Agreement.

42

43

44 USB Type-C®, USB-C® and USB4® are trademarks of the Universal Serial Bus Implementers Forum (USB-IF).
45 DisplayPort™ is a trademark of VESA. All product names are trademarks, registered trademarks, or service
46 marks of their respective owners.

47 Thunderbolt™ is a trademark of Intel Corporation. You may only use the Thunderbolt™ trademark or logo in
48 conjunction with products designed to this specification that complete proper certification and executing a
49 Thunderbolt™ trademark license – see <https://www.usb.org/compliance> for further information.

50

Contents	
51	
52	Specification Work Group Chairs / Specification Editors.....20
53	Specification Work Group Contributors.....20
54	Pre-Release Draft Industry Reviewing Companies That Provided Feedback.....28
55	Revision History.....28
56	1 Introduction.....29
57	1.1 Purpose.....29
58	1.2 Scope.....29
59	1.3 Related Documents.....29
60	1.4 Conventions.....30
61	1.4.1 Precedence.....30
62	1.4.2 Keywords.....30
63	1.4.3 Numbering.....31
64	1.5 Terms and Abbreviations.....31
65	2 Overview.....36
66	2.1 Introduction.....36
67	2.2 USB Type-C Receptacles, Plugs and Cables.....37
68	2.3 Configuration Process.....38
69	2.3.1 Source-to-Sink Attach/Detach Detection.....38
70	2.3.2 Plug Orientation/Cable Twist Detection.....39
71	2.3.3 Initial Power (Source-to-Sink) Detection and Establishing the Data (Host-to-Device) Relationship
72	39
73	2.3.4 USB Type-C VBUS Current Detection and Usage.....40
74	2.3.5 USB PD Communications.....40
75	2.3.6 Functional Extensions.....41
76	2.4 VBUS.....41
77	2.5 VCONN.....41
78	2.6 Hubs.....42
79	3 Mechanical.....43
80	3.1 Overview.....43
81	3.1.1 Compliant Connectors.....43
82	3.1.2 Compliant Cable Assemblies.....43
83	3.1.3 Compliant USB Type-C to Legacy Cable Assemblies.....44
84	3.1.4 Compliant USB Type-C to Legacy Adapter Assemblies.....45
85	3.2 USB Type-C Connector Mating Interfaces.....45
86	3.2.1 Interface Definition.....45
87	3.2.2 Reference Designs.....66

88	3.2.3	Pin Assignments and Descriptions	73
89	3.3	Cable Construction and Wire Assignments	74
90	3.3.1	Cable Construction (<i>Informative</i>).....	74
91	3.3.2	Wire Assignments	76
92	3.3.3	Wire Gauges and Cable Diameters (<i>Informative</i>).....	77
93	3.4	Standard USB Type-C Cable Assemblies.....	79
94	3.4.1	USB Full-Featured Type-C Cable Assembly.....	79
95	3.4.2	USB 2.0 Type-C Cable Assembly	81
96	3.4.3	USB Type-C Captive Cable Assembly	81
97	3.4.4	USB Type-C Thumb Drive Assembly	82
98	3.5	Legacy Cable Assemblies.....	82
99	3.5.1	USB Type-C to USB 3.1 Standard-A Cable Assembly	83
100	3.5.2	USB Type-C to USB 2.0 Standard-A Cable Assembly	84
101	3.5.3	USB Type-C to USB 3.1 Standard-B Cable Assembly	85
102	3.5.4	USB Type-C to USB 2.0 Standard-B Cable Assembly	86
103	3.5.5	USB Type-C to USB 2.0 Mini-B Cable Assembly.....	87
104	3.5.6	USB Type-C to USB 3.1 Micro-B Cable Assembly.....	88
105	3.5.7	USB Type-C to USB 2.0 Micro-B Cable Assembly.....	89
106	3.6	Legacy Adapter Assemblies.....	89
107	3.6.1	USB Type-C to USB 3.1 Standard-A Receptacle Adapter Assembly	89
108	3.6.2	USB Type-C to USB 2.0 Micro-B Receptacle Adapter Assembly	91
109	3.7	Electrical Characteristics.....	91
110	3.7.1	Raw Cable (<i>Informative</i>).....	92
111	3.7.2	USB Type-C to USB Type-C Passive Cable Assemblies	93
112	3.7.3	Mated Connector (<i>Informative – USB 3.2 Gen2 and USB4 Gen2</i>).....	115
113	3.7.4	Receptacle Connector SI Requirements and Testing (<i>Normative – USB4 Gen3/Gen4</i>).....	119
114	3.7.5	USB Type-C to USB Legacy Cable Assemblies (<i>Normative</i>)	121
115	3.7.6	USB Type-C to USB Legacy Adapter Assemblies (<i>Normative</i>)	125
116	3.7.7	Shielding Effectiveness Requirements (<i>Normative</i>)	128
117	3.7.8	DC Electrical Requirements (<i>Normative</i>).....	130
118	3.8	Mechanical and Environmental Requirements (<i>Normative</i>).....	132
119	3.8.1	Mechanical Requirements	133
120	3.8.2	Environmental Requirements.....	138
121	3.9	Docking Applications (<i>Informative</i>)	139
122	3.10	Implementation Notes and Design Guides	140
123	3.10.1	EMC Management (<i>Informative</i>)	140
124	3.10.2	Stacked and Side-by-Side Connector Physical Spacing (<i>Informative</i>)	143

125	3.10.3	Cable Mating Considerations (<i>Informative</i>)	143
126	3.11	Extended Power Range (EPR) Cables	144
127	3.11.1	Electrical Requirements.....	144
128	3.11.2	EPR Cable Identification Requirements.....	144
129	4	Functional	145
130	4.1	Signal Summary.....	145
131	4.2	Signal Pin Descriptions	145
132	4.2.1	USB 3.2/USB4 Pins	145
133	4.2.2	USB 2.0 Pins.....	146
134	4.2.3	Auxiliary Signal Pins	146
135	4.2.4	Power and Ground Pins.....	146
136	4.2.5	Configuration Pins	146
137	4.3	Sideband Use (SBU).....	146
138	4.4	Power and Ground.....	146
139	4.4.1	IR Drop.....	146
140	4.4.2	VBUS	147
141	4.4.3	VCONN.....	149
142	4.5	Configuration Channel (CC)	153
143	4.5.1	Architectural Overview.....	153
144	4.5.2	CC Functional and Behavioral Requirements	165
145	4.5.3	USB Port Interoperability Behavior	201
146	4.6	Power	218
147	4.6.1	Power Requirements during USB Suspend.....	219
148	4.6.2	VBUS Power Provided Over a USB Type-C Cable	220
149	4.7	USB Hubs	225
150	4.8	Power Sourcing and Charging.....	226
151	4.8.1	DFP as a Power Source.....	226
152	4.8.2	Non-USB Charging Methods	228
153	4.8.3	Sinking Host.....	229
154	4.8.4	Sourcing Device.....	229
155	4.8.5	Charging a System with a Dead Battery	229
156	4.8.6	USB Type-C Multi-Port Chargers	229
157	4.9	Electronically Marked Cables	233
158	4.9.1	Parameter Values.....	234
159	4.9.2	Active Cables.....	234
160	4.10	VCONN-Powered Accessories (VPAs) and VCONN-Powered USB Devices (VPDs).....	235
161	4.10.1	VCONN-Powered Accessories (VPAs).....	235

162	4.10.2	VCONN-Powered Devices (VPDs).....	235
163	4.11	Parameter Values	237
164	4.11.1	Termination Parameters	237
165	4.11.2	Timing Parameters.....	239
166	4.11.3	Voltage Parameters	242
167	5	<i>USB4</i> Discovery and Entry	244
168	5.1	Overview of the Discovery and Entry Process	244
169	5.2	<i>USB4</i> Functional Requirements.....	245
170	5.2.1	<i>USB4</i> Host Functional Requirements.....	245
171	5.2.2	USB Device Functional Requirements.....	245
172	5.2.3	<i>USB4</i> Alternate Mode Support.....	245
173	5.3	<i>USB4</i> Power Requirements.....	246
174	5.3.1	Source Power Requirements	246
175	5.3.2	Sink Power Requirements	246
176	5.3.3	Device Power Management Requirements	246
177	5.4	<i>USB4</i> Discovery and Entry Flow Requirements	247
178	5.4.1	USB Type-C Initial Connection	247
179	5.4.2	USB Power Delivery Contract.....	247
180	5.4.3	<i>USB4</i> Discovery and Entry Flow	247
181	5.4.4	<i>USB4</i> Post-Entry Operation.....	252
182	5.5	<i>USB4</i> Hub Connection Requirements.....	253
183	5.5.1	<i>USB4</i> Hub Port Initial Connection Requirements.....	253
184	5.5.2	<i>USB4</i> Hub UFP and Host Capabilities Discovery.....	253
185	5.5.3	Hub DFP Connection Requirements	254
186	5.5.4	Hub Ports Connection Behavior Flow Examples.....	254
187	5.5.5	Connecting to Downstream <i>USB4</i> Hubs	260
188	5.5.6	Fallback Functional Requirements for <i>USB4</i> Hubs.....	260
189	5.6	<i>USB4</i> Device Connection Requirements	260
190	5.6.1	Fallback Mapping of <i>USB4</i> Peripheral Functions of USB Device Class Types	260
191	5.7	Parameter Values	262
192	5.7.1	Timing Parameters	262
193	6	Active Cables.....	263
194	6.1	General Specifications for All Active Cables.....	263
195	6.1.1	Discovering Active Cable Characteristics.....	263
196	6.1.2	Electrical Requirements	265
197	6.1.3	Mechanical Requirements	297
198	6.2	Additional Specifications for Copper and Hybrid-Optical Active Cables.....	298

199	6.2.1	Active Cable Block Diagram	299
200	6.2.2	USB4 Asymmetric Mode Support	299
201	6.2.3	Active Cable USB PD Requirements	299
202	6.2.4	Active Cable Behaviors in Response to USB PD Events	299
203	6.2.5	Active Cable Power Requirements	300
204	6.3	Additional Specifications for Optically Isolated Active Cables	300
205	6.3.1	OIAC Block Diagrams	301
206	6.3.2	OIAC Limitations and General Requirements	303
207	6.3.3	OIAC Cable Power Requirements	304
208	6.3.4	OIAC USB PD Requirements	304
209	6.3.5	OIAC Connection Flow and State Diagrams	314
210	6.3.6	Additional Electrical Requirements for OIAC	332
211	6.3.7	Additional Mechanical Requirements for OIAC	335
212	A	Liquid Corrosion Mitigation Mode	336
213	A.1	Overview	336
214	A.2	Detail	336
215	A.3	Liquid Detection Methods	338
216	A.3.1	Liquid Measurement Method	338
217	A.3.2	Pulsed Measurement Method	338
218	A.3.3	Impedance Measurement Method	339
219	A.4	Liquid Detection Pins in the Connector	342
220	B	Debug Accessory Mode	345
221	B.1	Overview	345
222	B.2	Functional	345
223	B.2.1	Signal Summary	345
224	B.2.2	Port Interoperability	346
225	B.2.3	Debug Accessory Mode Entry	346
226	B.2.4	Connection State Diagrams	346
227	B.2.5	DTS Port Interoperability Behaviors	355
228	B.2.6	Orientation Detection	364
229	B.3	Security/Privacy Requirements	364
230	C	USB Type-C Digital Audio	365
231	C.1	Overview	365
232	C.2	USB Type-C Digital Audio Specifications	365
233	D	Thermal Design Considerations for Active Cables	366
234	D.1	Introduction	366
235	D.2	Model	366

236	D.2.1	Assumptions	366
237	D.2.2	Model Architecture	367
238	D.2.3	Heat Sources	367
239	D.2.4	Heat Flow	368
240	D.3	<i>USB 3.2</i> Single-Lane Active Cable	369
241	D.3.1	<i>USB 3.2</i> Single-Lane Active Cable Design Considerations.....	369
242	D.4	Dual-Lane Active Cables.....	372
243	D.4.1	<i>USB 3.2</i> Dual-Lane Active Cable Design Considerations.....	372
244	D.4.2	<i>USB 3.2</i> Dual-Lane Active Cable in a Multiple Port Configuration	374
245	D.5	<i>USB 3.2</i> Host and Device Design Considerations	375
246	D.5.1	Heat Spreading or Heat Sinking from Host or Device	375
247	D.5.2	Motherboard Temperature Control.....	376
248	D.5.3	Wider Port Spacing for Multi-Port Applications.....	376
249	D.5.4	Power Policies.....	376
250	E	Alternate Modes	377
251	E.1	Alternate Mode Architecture	377
252	E.2	Alternate Mode Requirements.....	377
253	E.2.1	Alternate Mode Pin Reassignment.....	378
254	E.2.2	Alternate Mode Electrical Requirements.....	378
255	E.3	Parameter Values	381
256	E.4	Example Alternate Mode – USB DisplayPort™ Dock	382
257	E.4.1	USB DisplayPort™ Dock Example	382
258	E.4.2	Functional Overview	382
259	E.4.3	Operational Summary	383
260	E.5	Example Alternate Mode Entry Flow with Cable Warnings.....	384
261	E.5.1	Operational Summary	385
262	F	Thunderbolt™ 3 Compatibility Discovery and Entry	386
263	F.1	<i>TBT3</i> Compatibility Mode Functional Requirements	386
264	F.1.1	<i>TBT3</i> -Compatible Power Requirements.....	386
265	F.1.2	<i>TBT3</i> -Compatible Host Requirements	386
266	F.1.3	<i>TBT3</i> -Compatible Device Upstream Requirements.....	386
267	F.1.4	<i>TBT3</i> -Compatible Device Downstream Requirements	386
268	F.1.5	<i>TBT3</i> -Compatible Self-Powered Device Without Predefined Upstream Port Rules	387
269	F.1.6	<i>TBT3</i> -Compatible Devices with a Captive Cable	387
270	F.2	<i>TBT3</i> Discovery and Entry Flow.....	387
271	F.2.1	<i>TBT3</i> Passive Cable Discover Identity Responses	388
272	F.2.2	<i>TBT3</i> Active Cable Discover Identity Responses.....	391

273	F.2.3	<i>TBT3</i> Device Discover Identity Responses.....	394
274	F.2.4	<i>TBT3</i> Discover SVID Responses.....	395
275	F.2.5	<i>TBT3</i> Device Discover Mode Responses.....	396
276	F.2.6	<i>TBT3</i> Cable Discover Mode Responses.....	397
277	F.2.7	<i>TBT3</i> Cable Enter Mode Command.....	398
278	F.2.8	<i>TBT3</i> Device Enter Mode Command.....	399
279	F.2.9	<i>TBT3</i> Cable Functional Difference Summary.....	401
280	G	Extracting Pulse Response from Sampled Data and Calculating Non-Linearity Noise.....	402
281	H	<i>USB PD</i> High-Voltage Design Considerations.....	404
282	H.1	Potential for Arcing Damage During Cable Withdrawal.....	404
283	H.2	Arcing During USB Type-C Cable Withdrawal.....	404
284	H.3	Mitigating Arcing Damage During Cable Withdrawal Due to Sink Discharge.....	406
285	H.3.1	Limiting Sink Discharge Rate.....	407
286	H.3.2	Load Removal.....	408
287	H.3.3	Limiting Source Current Capability.....	411
288	I	<i>USB PD</i> Encoding Guidelines for USB Type-C Product Types.....	412
289	I.1	USB Type-C Product Type Definitions and <i>USB PD</i> Encodings.....	412
290	I.2	<i>USB PD</i> Encoding Guidelines Tables.....	413
291	I.3	Detailed Examples.....	420
292	I.3.1	<i>USB 3.2</i> Host – no DC – Power Consumer : DRP (Source or Sink) / Not DRD (DFP).....	420
293	I.3.2	<i>USB 3.2</i> Peripheral – Power Provider : DRP (Source or Sink) / Not DRD (UFP).....	420
294	I.3.3	<i>USB4</i> Host – Power Consumer : DRP (Source or Sink) / Not DRD (DFP).....	421
295	I.3.4	<i>USB4</i> Host – <i>USB4</i> DC – Partial or no USB Equivalent : DRP (Source or Sink) / DRD.....	421
296	I.3.5	<i>USB4</i> Peripheral : UFP (Sink).....	422
297	I.3.6	<i>USB4</i> Dock (Upstream) – Power Provider : DRP (Source or Sink) / Not DRD (UFP).....	423
298	I.3.7	<i>USB4</i> Hub (Downstream) – DFP (Source).....	423
299	J	Design Assumptions for the <i>USB4</i> Gen4 LRD Cable Specification.....	425

300

301

Figures

302	Figure 2-1	USB Type-C Receptacle Interface (Front View).....	36
303	Figure 2-2	USB Full-Featured Type-C Plug Interface (Front View).....	37
304	Figure 3-1	USB Type-C Receptacle Interface Dimensions.....	48
305	Figure 3-2	Reference Design USB Type-C Plug External EMC Spring Contact Zones.....	51
306	Figure 3-3	USB Full-Featured Type-C Plug Interface Dimensions.....	52
307	Figure 3-4	Reference Footprint for a USB Type-C Vertical Mount Receptacle (<i>Informative</i>).....	55
308	Figure 3-5	Reference Footprint for a USB Type-C Dual-Row SMT Right-Angle Receptacle (<i>Informative</i>).....	56
309	Figure 3-6	Reference Footprint for a USB Type-C Hybrid Right-Angle Receptacle (<i>Informative</i>).....	57
310	Figure 3-7	Reference Footprint for a USB Type-C Mid-Mount Dual-Row SMT Receptacle (<i>Informative</i>).....	58
311	Figure 3-8	Reference Footprint for a USB Type-C Mid-Mount Hybrid Receptacle (<i>Informative</i>).....	59
312	Figure 3-9	Reference Footprint for a <i>USB 2.0</i> Type-C Through Hole Right Angle Receptacle (<i>Informative</i>).....	60

313	Figure 3-10 Reference Footprint for a <i>USB 2.0</i> Type-C Single Row Right Angle Receptacle (<i>Informative</i>)	61
314	Figure 3-11 <i>USB 2.0</i> Type-C Plug Interface Dimensions	62
315	Figure 3-12 USB Type-C Plug EMC Shielding Spring Tip Requirements	65
316	Figure 3-13 Reference Design of Receptacle Mid-Plate.....	66
317	Figure 3-14 Reference Design of Retention Latch	67
318	Figure 3-15 Illustration of the Latch Soldered to the Paddle Card Ground.....	67
319	Figure 3-16 Reference Design of the USB Full-Featured Type-C Plug Internal EMC Spring.....	68
320	Figure 3-17 Reference Design of the <i>USB 2.0</i> Type-C Plug Internal EMC Spring	69
321	Figure 3-18 Reference Design of Internal EMC Pad.....	70
322	Figure 3-19 Reference Design of a USB Type-C Receptacle with External EMC Springs.....	71
323	Figure 3-20 Reference Design of a USB Full-Featured Type-C Plug Paddle Card.....	72
324	Figure 3-21 Illustration of a USB Full-Featured Type-C Cable Cross Section, a Coaxial Wire Example with	
325	VCONN.....	75
326	Figure 3-22 Illustration of a USB Full-Featured Type-C Cable Cross Section, a Coaxial Wire Example without	
327	VCONN.....	75
328	Figure 3-23 USB Full-Featured Type-C Standard Cable Assembly.....	79
329	Figure 3-24 USB Type-C to <i>USB 3.1</i> Standard-A Cable Assembly.....	83
330	Figure 3-25 USB Type-C to <i>USB 2.0</i> Standard-A Cable Assembly.....	84
331	Figure 3-26 USB Type-C to <i>USB 3.1</i> Standard-B Cable Assembly.....	85
332	Figure 3-27 USB Type-C to <i>USB 2.0</i> Standard-B Cable Assembly.....	86
333	Figure 3-28 USB Type-C to <i>USB 2.0</i> Mini-B Cable Assembly.....	87
334	Figure 3-29 USB Type-C to <i>USB 3.1</i> Micro-B Cable Assembly.....	88
335	Figure 3-30 USB Type-C to <i>USB 2.0</i> Micro-B Cable Assembly.....	89
336	Figure 3-31 USB Type-C to <i>USB 3.1</i> Standard-A Receptacle Adapter Assembly.....	90
337	Figure 3-32 USB Type-C to <i>USB 2.0</i> Micro-B Receptacle Adapter Assembly.....	91
338	Figure 3-33 Illustration of Test Points for a Mated Cable Assembly.....	93
339	Figure 3-34 Recommended Differential Insertion Loss Requirement (<i>USB 3.2</i> Gen2 and <i>USB4</i> Gen2)	94
340	Figure 3-35 Recommended Differential Return Loss Requirement	94
341	Figure 3-36 Recommended Differential Crosstalk Requirement.....	95
342	Figure 3-37 Recommended Differential Near-End and Far-End Crosstalk Requirement between USB D+/D-	
343	Pair and TX/RX Pair	96
344	Figure 3-38 Recommended Differential Insertion Loss Requirement (<i>USB4</i> Gen3/Gen4).....	96
345	Figure 3-39 Illustration of Insertion Loss Fit at Nyquist Frequency	97
346	Figure 3-40 Input Pulse Spectrum.....	98
347	Figure 3-41 IMR Limit as Function of ILfitatNq.....	99
348	Figure 3-42 IRL Limit as Function of ILfitatNq.....	101
349	Figure 3-43 Differential-to-Common Mode Conversion Requirement.....	101
350	Figure 3-44 IMR Limit as Function of ILfit at 10 GHz (<i>USB4</i> Gen3/Gen4).....	105
351	Figure 3-45 Definition of Port, Victim, and Aggressor.....	106
352	Figure 3-46 IXT_DP and IXT_USB Limit as Function of ILfit at 10 GHz (<i>USB4</i> Gen3/Gen4)	106
353	Figure 3-47 IRL Limit as Function of ILfit at 10 GHz (<i>USB4</i> Gen3/Gen4).....	107
354	Figure 3-48 Differential-to-Common Mode Conversion Requirement (<i>USB4</i> Gen3/Gen4).....	107
355	Figure 3-49 Cable Assembly in System.....	108
356	Figure 3-50 Requirement for Differential Coupling between CC and D+/D-	111
357	Figure 3-51 Requirement for Single-Ended Coupling between CC and D- in <i>USB 2.0</i> Type-C Cables.....	111
358	Figure 3-52 Requirement for Single-Ended Coupling between CC and D- in USB Full-Featured Type-C Cables	
359	112
360	Figure 3-53 Requirement for Differential Coupling between VBUS and D+/D-	112
361	Figure 3-54 Requirement for Single-Ended Coupling between SBU_A and SBU_B.....	113
362	Figure 3-55 Requirement for Single-Ended Coupling between SBU_A/SBU_B and CC.....	114