
**Test methods for machine readable
travel documents (MRTD) and
associated devices —**

**Part 2:
Test methods for the contactless
interface**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

*Méthodes d'essai pour les documents de voyage lisibles par machine
(MRTD) et dispositifs associés —*

Partie 2: Méthodes d'essai de l'interface sans contact

<https://standards.iteh.ai/catalog/standards/sist/4b8a6a57-08c7-4e32-bfde-1d181787f7ee/iso-iec-18745-2-2021>



iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 18745-2:2021](https://standards.iteh.ai/catalog/standards/sist/4b8a6a57-08c7-4e32-bfde-1d181787f7ee/iso-iec-18745-2-2021)
<https://standards.iteh.ai/catalog/standards/sist/4b8a6a57-08c7-4e32-bfde-1d181787f7ee/iso-iec-18745-2-2021>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols and abbreviated terms	2
5 Test methods for eMRTD	3
5.1 General test conditions	3
5.1.1 General	3
5.1.2 Test environment	3
5.1.3 Test conditions for PICC	3
5.1.4 Applicant information	5
5.1.5 Test report	6
5.2 Test of ISO/IEC 14443-1 parameters	7
5.2.1 Antenna size and PICC Class 1 verification (optional)	7
5.2.2 Static electricity	7
5.2.3 Alternating magnetic field	7
5.3 Test of ISO/IEC 14443-2 parameters	8
5.3.1 eMRTD transmission	8
5.3.2 Operating field strength	8
5.3.3 eMRTD reception	9
5.3.4 eMRTD maximum loading effect	9
5.3.5 eMRTD resonance frequency (optional)	9
5.3.6 eMRTD EMD level and low EMD time test (optional)	10
5.4 Test of ISO/IEC 14443-3 and ISO/IEC 14443-4 parameters	10
5.5 List of the test command sequences	11
5.5.1 General	11
5.5.2 Test commands for eMRTD supporting only BAC	11
5.5.3 Test commands for eMRTD supporting PACE	13
5.6 Functionality check test	16
5.6.1 General	16
5.6.2 Optional procedure 1: Application functionality check test	16
5.6.3 Optional procedure 2: Electrical functionality check test	17
6 Test methods for eMRTD reader	17
6.1 General test conditions	17
6.1.1 General	17
6.1.2 Test environment	18
6.1.3 Test conditions for PCD	18
6.1.4 Applicant information	18
6.1.5 Test report	19
6.1.6 Definition of test positions	19
6.2 Test of ISO/IEC 14443-1 parameters	20
6.2.1 Alternating magnetic field	20
6.3 Test of ISO/IEC 14443-2 parameters	20
6.3.1 Carrier frequency	20
6.3.2 eMRTD reader field strength	20
6.3.3 Modulation index and waveform	21
6.3.4 Load modulation reception	21
6.3.5 eMRTD reader EMD immunity test (optional)	22
6.3.6 eMRTD reader EMD recovery test (optional)	22
6.4 Test of ISO/IEC 14443-3 and ISO/IEC 14443-4 parameters	23
6.5 List of test command sequences	24

6.5.1	General.....	24
6.5.2	Test commands.....	24
6.5.3	Default test command sequence.....	24
6.5.4	Test_command_sequence_1.....	25
6.5.5	Test_command_sequence_2.....	25
6.6	Measurement positions.....	25
7	Specific access control test sequences.....	27
7.1	General.....	27
7.2	List of the test command sequences with EAC for eMRTD	27
7.2.1	General.....	27
7.2.2	Test commands for eMRTD supporting EAC.....	28
7.2.3	Test commands for eMRTD supporting PACE and EAC	29

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC 18745-2:2021
<https://standards.iteh.ai/catalog/standards/sist/4b8a6a57-08c7-4e32-bfde-1d181787f7ee/iso-iec-18745-2-2021>

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by ISO/IEC JTC 1, *Information technology, SC 17, Cards and security devices for personal identification*.

This second edition cancels and replaces the first edition (ISO/IEC 18745-2:2016), which has been technically revised.

The main changes compared to the previous edition are as follows:

- simplification of the test conditions for PCD in terms of temperature;
- modification of the loading effect required for eMRTD.

A list of all parts in the ISO/IEC 18745 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document represents a necessary step in a process designed to ensure contactless communications interoperability between inspection systems and machine-readable travel documents to be accepted by them. The purpose of this document is to provide the conformance test plan that needs to be performed to ensure conformity of inspection systems and any machine-readable travel documents in accordance with ICAO Doc 9303.

This conformance test plan is not designed to repeat or duplicate the referenced specifications and associated test method [essentially ISO/IEC 14443 (all parts) and ISO/IEC 10373-6] but to list the test conditions to be performed in addition to the ones already described in the ISO/IEC 10373-6 and to define their testing and use conditions.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 18745-2:2021](https://standards.iteh.ai/catalog/standards/sist/4b8a6a57-08c7-4e32-bfde-1d181787f7ee/iso-iec-18745-2-2021)

<https://standards.iteh.ai/catalog/standards/sist/4b8a6a57-08c7-4e32-bfde-1d181787f7ee/iso-iec-18745-2-2021>

Test methods for machine readable travel documents (MRTD) and associated devices —

Part 2: Test methods for the contactless interface

1 Scope

This document defines the conformance test plan, based on ISO/IEC 10373-6, for the contactless interface of eMRTDs and eMRTD associated readers compliant with ICAO Doc 9303.

Application requirements for eMRTD and eMRTD reader are outside of the scope of this document and are defined in ICAO Doc 9303-10.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 10373-6:2016¹⁾, *Identification cards — Test methods — Part 6: Proximity cards*

ISO/IEC 10373-6:2016/Amd.3:2018¹⁾, *Identification cards — Test methods — Part 6: Proximity cards, AMENDMENT 3: PICC loading effect*

ISO/IEC 14443-1:2018¹⁾, *Identification cards — Contactless integrated circuit cards — Proximity cards — Part 1: Physical characteristics*

ISO/IEC 14443-2, *Identification cards — Contactless integrated circuit cards — Proximity cards — Part 2: Radio frequency power and signal interface*¹⁾

ISO/IEC 14443-3, *Identification cards — Contactless integrated circuit cards — Proximity cards — Part 3: Initialization and anticollision*¹⁾

ISO/IEC 14443-4:2018¹⁾, *Identification cards — Contactless integrated circuit cards — Proximity cards — Part 4: Transmission protocol*

Doc ICAO 9303-2, *Machine Readable Travel Documents, Eighth Edition — Part 2: Specifications for the Security of the Design, Manufacture and Issuance of MRTDs*

Doc ICAO 9303-9, *Machine Readable Travel Documents, Eighth Edition — Part 9: Deployment of Biometric Identification and Electronic Storage of Data in MRTDs*

Doc ICAO 9303-10, *Machine Readable Travel Documents, Eighth Edition — Part 10: Logical Data Structure (LDS) for Storage of Biometrics and Other Data in the Contactless Integrated Circuit (IC)*

Doc ICAO 9303-11, *Machine Readable Travel Documents, Eighth Edition — Part 11: Security Mechanisms for MRTDs*

1) When ISO/IEC 10373-6 or ISO/IEC 14443 (all parts) are referred to, PICC represents the eMRTD and PCD represents eMRTD associated reader.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1 test method

method for testing the characteristics of eMRTDs and eMRTD associated readers for the purpose of assessing their conformance with International Standards

3.2 sample

piece of the total number of eMRTDs or eMRTD associated readers required and presented for testing according to this document

3.3 PICC eMRTD object

3.4 PCD eMRTD associated reader

iTeh STANDARD PREVIEW
(standards.iteh.ai)

4 Symbols and abbreviated terms

For the purposes of this document, the following abbreviations apply.
ISO/IEC 18745-2:2021
<https://standards.iteh.ai/catalog/standards/sist/4b8a0a57-08c7-4e32-bfde-1d181787f7ee/iso-iec-18745-2-2021>

AA	active authentication
BAC	basic access control
CVCA	country verifying certification authority
DUT	device under test
DV	document verifier
EAC	extended access control (throughout this document, the term EAC refers to EAC v1)
eMRTD	electronic machine-readable travel document
f_c	frequency of operating field as defined in ISO/IEC 14443-2
f_s	frequency of subcarrier as defined in ISO/IEC 14443-2
$H_{\min}$	minimum field strength as defined in ISO/IEC 14443-2
$H_{\max}$	maximum field strength as defined in ISO/IEC 14443-2
IS	inspection system
LDS	logical data structure
PACE	password authenticated connection establishment

"XY"	hexadecimal notation, equal to XY in base 16
REQA	REQuest command, Type A as defined in ISO/IEC 14443-3
REQB	REQuest command, Type B as defined in ISO/IEC 14443-3
$t_{E,PCD}$	low EMD time, PCD as defined in ISO/IEC 14443-3
$V_{E,PCD}$	EMD limit, PCD as defined in ISO/IEC 14443-2

5 Test methods for eMRTD

5.1 General test conditions

5.1.1 General

Test conditions and procedures in this clause are based on ISO/IEC 10373-6 taking into account specific needs of eMRTD application.

This clause addresses the test of the mandatory and optional features of eMRTD's contactless interface.

[5.1.2](#) to [5.1.5](#) specify the different test setups, the values used for the tests, and a recommendation for the format of the test report.

Depending on the implementation statement of the applicant, Type A or Type B tests shall be performed.

All the tests defined in this document and relevant to eMRTD are applied in accordance to PICC Class 1.

For tests of ISO/IEC 14443-1 and ISO/IEC 14443-2 parameters, the minimum number of samples provided for testing is three, unless explicitly defined otherwise. The applicant may request that a larger number of samples be tested. The samples provided by the applicant shall be personalized and should be marked each with a unique serial number.

It is not mandatory to use the same samples to run all the tests defined in this document. It's recommended to provide to the test laboratory at least:

- 3 samples for static electricity test;
- 3 samples for alternating magnetic field test;
- 3 samples for ISO/IEC 14443-2 parameters;
- 1 sample for ISO/IEC 14443-3 and ISO/IEC 14443-4 parameters.

5.1.2 Test environment

Unless otherwise specified, testing shall take place at room temperature $23\text{ °C} \pm 3\text{ °C}$ ($73\text{ °F} \pm 5\text{ °F}$) and in an environment of relative humidity 25 % to 75 %.

5.1.3 Test conditions for PICC

Unless otherwise specified, the test conditions defined in [Table 1](#) shall be applied.

Table 1 — Test conditions for PICC

Conditions	Temperature	Values
Field strength	At room temperature and -10 °C	1,5 A/m, 2,5 A/m, 3,5 A/m, 4,5 A/m and 7,5 A/m ^a
	At + 50 °C	1,5 A/m, 2,5 A/m, 3,5 A/m, 4,5 A/m and 6,0 A/m ^b
^a Optional values 5,5 A/m and 6,5 A/m may be applied in addition.		
^b Optional value 5,5 A/m may be applied in addition.		

NOTE Optional and mandatory field strength values are chosen in line with the following reasons:

- most of eMRTD associated readers operate between 1,5 A/m(rms) and 4,5 A/m(rms);
- check that there is no potential communication hole between 1,5 A/m(rms) and 4,5 A/m(rms) or more.

Unless otherwise specified, the values defined in [Table 2](#) shall be used to adjust PICC-test-apparatus parameters.

Table 2 — Values of the PICC-test-apparatus parameters unless otherwise specified

Parameter	Value	To be applied to
Parameters applicable for all bit rates		
FSDI	8	Type A
Start Of Frame (SOF) timing	10 etu "0" followed by 2 etu "1"	Type B
End Of Frame (EOF) timing	10 etu "0"	Type B
Extra Guard Time (EGT) timing	0 etu	Type B
Maximum Frame Size Code in ATTRIB	8	Type B
Parameters applicable for PCD to PICC bit rate $f_c/128$		
PCD field envelope during 60 % of t_2	0,5 %	Type A
t_1	$40/f_c$	Type A
t_2	$7/f_c$	Type A
t_3	$12/f_c$	Type A
t_4	$6/f_c$	Type A
Overshoot	0 %	Type A and Type B
Modulation index m	12 %	Type B
Rise time, t_r , fall time, t_f	$12/f_c$	Type B
Parameters applicable for PCD to PICC bit rate $f_c/64$ (optional)		
a	0,1	Type A
t_1	$18/f_c$	Type A
t_5	$15/f_c$	Type A
t_6	$9/f_c$	Type A
Overshoot	0	Type A and Type B
Modulation index m	12 %	Type B
Rise time t_r , fall time t_f	$10/f_c$	Type B
Parameters applicable for PCD to PICC bit rate $f_c/32$		
a	0,2	Type A
t_1	$9/f_c$	Type A
t_5	$7/f_c$	Type A
t_6	$8/f_c$	Type A
Overshoot	0	Type A and Type B

Table 2 (continued)

Parameter	Value	To be applied to
Modulation index m	12 %	Type B
Rise time t_r , fall time t_f	$8/f_c$	Type B
Parameters applicable for PCD to PICC bit rate $f_c/16$ (Optional)		
a	0,4	Type A
t_1	$5/f_c$	Type A
t_5	$4/f_c$	Type A
t_6	$5/f_c$	Type A
Overshoot	0	Type A and Type B
Modulation index m	12 %	Type B
Rise time t_r , fall time t_f	$6/f_c$	Type B
Parameters applicable for PCD to PICC bit rate $f_c/8$ (Optional)		
Overshoot	0	Type A and Type B
Modulation index m	8 % for short modulation pulses	Type A and Type B
Rise time t_r , fall time t_f	$5/f_c$	Type A and Type B
Parameters applicable for PCD to PICC bit rate $f_c/4$ (Optional)		
Overshoot	0	Type A and Type B
Modulation index m	8 % for short modulation pulses	Type A and Type B
Rise time t_r , fall time t_f	$4/f_c$	Type A and Type B
Parameters applicable for PCD to PICC bit rate $f_c/2$ (Optional)		
Overshoot	0	Type A and Type B
Modulation index m	8 % for short modulation pulses	Type A and Type B
Rise time t_r , fall time t_f	$2/f_c$	Type A and Type B
Parameters applicable for PCD to PICC bit rate $3f_c/4$ and $3f_c/2$ (Optional)		
PR	56°	Type A and Type B
ISI _d	0	Type A and Type B
ISI _m	1	Type A and Type B
Phase noise	0,03	Type A and Type B
Parameters applicable for PCD to PICC bit rate f_c and $2f_c$ (Optional)		
PR	60°	Type A and Type B
ISI _d	0	Type A and Type B
ISI _m	1	Type A and Type B
Phase noise	0,012 5	Type A and Type B

5.1.4 Applicant information

In order to set up the tests properly, the information specified in Table 3 shall be known by the laboratory. The information not accessible to the laboratory from the sample itself shall be provided by the applicant.

Table 3 — Applicant information on eMRTD product

Product characteristic	Standard reference	Applicant declaration
Physical size of product	ICAO Doc 9303-2	TD1/TD2/TD3
Location of antenna within eMRTD	ICAO Doc 9303-10, B.1	Data page/Centre of booklet/Cover/ Separate sewn-in page/Back cover
PICC class 1 ^a	ICAO Doc 9303-10, B.1	YES/NO
Shielding of eMRTD	ICAO Doc 9303-10, B.7	YES/NO If yes, precise where shielding is applied
(Optional) eMRTD resonance frequency range ^b	ICAO Doc 9303-10, B.9	Minimum and maximum resonance frequency in MHz
Communication signal interface	ICAO Doc 9303-10, B.9	Type A/Type B
Random or fixed UID (Type A) or PUI (Type B)	ICAO Doc 9303-10, B.8	Fixed / Random
(Optional) PCD to PICC supported bit rates	ICAO Doc 9303-10, B.4	List of supported optional PCD to PICC bit rates
(Optional) PICC to PCD supported bit rates	ICAO Doc 9303-10, B.4	List of supported optional PICC to PCD bit rates
(Optional) Support of exchange of additional parameters	ICAO Doc 9303-10, B.6	YES/NO
(Optional) Frames with error corrections supported	ICAO Doc 9303-10, B.6	YES/NO
Maximum frame size supported	ICAO Doc 9303-10, B.10	Declare the maximum frame size integer in reception supported by the eMRTD
Frame waiting time integer	ICAO Doc 9303-10, B.11	Declare the frame waiting time integer supported by the eMRTD
Supported access control ^c	ICAO Doc 9303-11	BAC: YES/NO PACE: YES/NO EAC: YES/NO
Active authentication supported	ICAO Doc 9303-11	YES/NO ^d

^a If PICC Class 1 is claimed, the Class 1 verification test is performed.

^b If the range is provided, the optional resonance frequency test is performed.

^c Information required to perform authentication is provided by the applicant (machine readable zone (MRZ), EAC certificates chain with IS private key, static/dynamic binding). If no access control is selected by the applicant, eMRTD supports plaintext access. If PACE is supported, PACE is applied during operating field strength test. If EAC is supported, EAC is applied during operating field strength test in addition to BAC or PACE.

^d If supported, active authentication is applied during operating field strength.

5.1.5 Test report

The test report shall include the number of successful evaluations versus the total number of evaluations for each sample and for each test. A description of each test, the information whether the result was a pass or a fail, and the date of the tests shall be included.

For all functionality check tests, the report shall state what tools and methods have been used to verify the functionality of the eMRTD.

The test report shall include the information on eMRTD product as defined in 5.1.4.