

SLOVENSKI STANDARD kSIST-TS FprCEN ISO/TS 18683:2024

01-september-2024

[Not translated]

Guidelines for safety and risk assessment of LNG fuel bunkering operations (ISO/TS 18683:2021)

Leitlinien für die Sicherheits- und Risikobewertung beim Bunkern von LNG-Kraftstoff (ISO/TS 18683:2021)

Lignes directrices pour la sécurité et l'évaluation des risques des opérations de soutage de GNL (ISO/TS 18683:2021)

Ta slovenski standard je istoveten z: FprCEN ISO/TS 18683

ICS:

75.200

Oprema za skladiščenje nafte, naftnih proizvodov in

zemeljskega plina

Petroleum products and natural gas handling

equipment

kSIST-TS FprCEN ISO/TS 18683:2024 en,fr,de

kSIST-TS FprCEN ISO/TS 18683:2024

iTeh Standards (https://standards.iteh.ai) Document Preview

kSIST-TS FprCEN ISO/TS 18683:2024

https://standards.iteh.ai/catalog/standards/sist/555fdf0e-7959-4b5c-a143-042425f95313/ksist-ts-fprcen-iso-ts-18683-2024

TECHNICAL SPECIFICATION

ISO/TS 18683

Second edition 2021-11

Guidelines for safety and risk assessment of LNG fuel bunkering operations

Lignes directrices pour la sécurité et l'évaluation des risques des opérations de soutage de GNL

iTeh Standards (https://standards.iteh.ai) Document Preview

kSIST-TS FprCEN ISO/TS 18683:2024

023-1868/https://standards.iteh.ai/catalog/standards/sist/555fdf0e- /959-4b5c-a143-042425f95313/ksist-ts-fprcen



iTeh Standards (https://standards.iteh.ai) Document Preview

kSIST-TS ForCEN ISO/TS 18683:2024

https://standards.iteh.ai/catalog/standards/sist/555fdf0e-7959-4b5c-a143-042425f95313/ksist-ts-fprcen-iso-ts-18683-2024



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org Published in Switzerland

ii

Contents					
Forev	vord	iv			
Intro	duction	vi			
1	Scope	1			
2	Normative references				
3	Terms, definitions and abbreviated terms 3.1 Terms and definitions 3.2 Abbreviated terms	1			
4	Bunkering supply scenarios	5			
5	Properties and behaviour of LNG 5.1 General 5.2 Description and hazards of LNG 5.3 Potential hazardous situations associated with LNG bunker transfer 5.4 Composition of LNG as a bunker fuel	6 6 7			
6	Safety 6.1 Objectives 6.2 General safety principles 6.3 Approach	 8			
7	Risk assessment 7.1 General 7.2 Types of risk assessment 7.3 Roles and responsibilities of stakeholders 7.4 Approach, scope and basis 7.5 Mitigation measures 7.6 Reporting 7.7 Safety Zone and controlled areas 7.8 Safety zone determination 7.9 Determination of monitoring and security areas 7.10 Simultaneous Operations (SIMOPs)	8 9 10 11 14 15 16 17 17 18 18 18 18 18 18 18 18 18 18 18 18 18			
8	Functional requirements for LNG bunker transfer system 8.1 General 8.2 Functional requirements	19			
9	Training	22			
Anne	x A (informative) Risk acceptance criteria	23			
	x B (informative) Examples of safety zone calculations				
	ography				

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 67, *Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries*, Subcommittee SC 9, *Liquefied natural gas installations and equipment*.

This second edition cancels and replaces the first edition (ISO/TS 18683:2015), which has been technically revised. In the control of the con

The main changes are as follows:

- title and scope restricted to Guidelines for safety and risk assessment of LNG fuel bunkering operations;
- list of bunkering supply scenarios updated with experience gained since 2015 in Clause 4;
- addition of concept of design stage risk assessment and operational risk assessment in 7.1;
- addition of Quantitative Consequence Assessment in 7.2;
- addition of roles and responsibilities of stakeholders in 7.3;
- design requirements removed from Clause 8 to avoid duplication with ISO 20519;
- individual Risk Criteria added in Annex A;
- three methods added to determine safety zone in <u>Annex B</u>;
- to avoid duplication with ISO 20519, the following clauses and annexes have been removed:
 - Clause 9 Requirements to components and systems;
 - Clause 11 Requirements for documentation;
 - Annex C Functional requirements;

- Annex D Sample Ship supplier checklist;
- Annex E Sample LNG delivery note;
- Annex F Arrangement and types of presenting connection;
- Annex G Dry disconnect coupling.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

iTeh Standards (https://standards.iteh.ai) Document Preview

kSIST-TS FprCEN ISO/TS 18683:2024

https://standards.jteh.aj/catalog/standards/sjst/555fdf0e-7959-4b5c-a143-042425f95313/ksjst-ts-fprcen-jso-ts-18683-2024

Introduction

The properties, characteristics, and behaviour of LNG differ significantly from conventional marine fuels, such as heavy fuel oils and distillate fuels as marine diesel oil (MDO) or marine gas oil (MGO).

For these reasons, it is essential that all LNG bunkering operations are undertaken with diligence and due attention is paid to prevent leakage of LNG liquid or vapour and to control all sources of ignition. Therefore, it is important that throughout the LNG bunkering chain, each element is carefully designed and has dedicated safety and operational procedures executed by trained personnel.

It is important that the basic requirements laid down in this document are understood and applied to each operation in order to ensure the safe, secure, and efficient transfer of LNG as a fuel to the ship.

The objective of this document is to provide guidance for the risk assessment of LNG fuel bunkering operations and thereby ensuring that an LNG fuelled vessel and bunkering supply facilities are operating with a high level of safety, integrity, and reliability regardless of the type of bunkering supply scenario.

The LNG bunkering interface comprises the area of LNG transfer and includes manifold, valves, safety and security systems and other equipment, and the personnel involved in the LNG bunkering operations.

This document is based on the assumption that the receiving ships and LNG bunkering supply facilities are designed according to the relevant and applicable codes, regulations, and guidelines such as the International Maritime Organization (IMO), ISO, EN, and NFPA standards and the Society for Gas as a Marine Fuel (SGMF) and other recognized documents during LNG bunkering. Relevant publications by these and other organizations are listed in the Bibliography.

This document should be combined with the requirements set on ISO 20519.

In cases where the distance to third parties is too close and the risk exceeds acceptance criteria, the bunkering location should not to be considered.

kSIST-TS FprCEN ISO/TS 18683:2024

https://standards.iteh.ai/catalog/standards/sist/555fdf0e-7959-4b5c-a143-042425f95313/ksist-ts-fprcen-iso-ts-18683-202

Guidelines for safety and risk assessment of LNG fuel bunkering operations

1 Scope

This document gives guidance on the risk-based approach to follow for the design and operation of the LNG bunker transfer system, including the interface between the LNG bunkering supply facilities and receiving LNG fuelled vessels.

This document provides requirements and recommendations for the development of a bunkering site and facility and the LNG bunker transfer system, providing the minimum functional requirements qualified by a structured risk assessment approach taking into consideration LNG properties and behaviour, simultaneous operations and all parties involved in the operation.

This document is applicable to bunkering of both seagoing and inland trading vessels. It covers LNG bunkering from shore or ship, mobile to ship and ship to ship LNG supply scenarios, as described in Clause 4.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC Guide 73, Risk management — Vocabulary

ISO 31010, Risk management — Guidelines on principles and implementation of risk management

ISO 20519, Ships and marine technology — Specification for bunkering of liquefied natural gas fuelled vessels

IMO, IGF Code of Safety for Ships using Gases or other Low flashpoint fuels

IMO, IGC International Code for the Construction and Equipment of Ships Carrying Liquefied Gases in Bulk

IMO, International Convention on Standards of Training, Certification and Watchkeeping for Seafarers

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC Guide 73 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at https://www.electropedia.org/

3.1.1

as low as reasonably practical

ALARP

reducing a risk to a level that represents the point, objectively assessed, at which the time, trouble, difficulty, and cost of further reduction measures become unreasonably disproportionate to the additional risk reduction obtained

3.1.2

boiling liquid expanding vapour explosion

BLEVE

sudden release of the content of a vessel containing a pressurized flammable liquid followed by a fireball

3.1.3

bunkering

process of transferring fuel to a ship

3.1.4

bunkering facility

system designed to be used to transfer/bunker liquefied gas as fuel to a gas-fuelled vessel

Note 1 to entry: It may consist of a floating, shore-based, fixed or mobile fuel-supply facility, such as a bunker vessel, terminal or road tanker.

3.1.5

bunkering site

location dedicated for bunkering comprising the bunkering installations, port and jetty, and other facilities and equipment that should be considered in the planning of bunkering

3.1.6

competent authority

organization or organizations that implement the requirements of legislation and regulate installations that must comply with the requirements of legislation

3.1.7

kSIST-TS FprCEN ISO/TS 18683:2024

consequence

outcome of an event

outcome of all eveni

3.1.8

drip tray

spill containment manufactured of material that can tolerate cryogenic temperatures

3.1.9

emergency shut-down

ESD

method that safely and effectively stops the bunker/transfer of natural gas and vapour between the supply facilities and receiving ship

3.1.10

gas-fuelled vessel

GFV

vessel using gas as marine fuel

3.1.11

hazard

potential source of harm

3.1.12

hazard identification

HAZID

brainstorming exercise using checklists where the potential hazards in a project are identified and gathered in a risk register for follow up in the project

3.1.13

impact assessment

assessment of how consequences (fires, explosions, etc.) affect people, structures the environment, etc.

3.1.14

individual risk

probability on an annual basis for an individual to be killed due to accidental events arising from the activity

3.1.15

mist

fog

cloud that will be generated by condensing humidity in air when in contact with cold surfaces during bunkering

Note 1 to entry: This mist will reduce visibility and can mask minor leaks.

3.1.16

monitoring and security area

area around the bunkering facility and ship where ship traffic and other activities are monitored (and controlled) to mitigate harmful effects

3.1.17

probability

extent to which an event is likely to occur

3.1.18

rapid phase transition

RPT

shock wave forces generated by instantaneous vaporization of LNG upon coming in contact with water

3.1.19

receiver

one or more organizations with ownership, operational and/or legal interests in a gas-fuelled vessel

Note 1 to entry: The receiver can be the vessel owner(s), the charterer or the operator.

[SOURCE: Reference [24]]

3.1.20

risk

combination of the probability of occurrence of harm and the severity of that harm

3.1.21

risk analysis

systematic use of information to identify sources and to estimate the risk

3.1.22

risk assessment

overall process of risk analysis and risk evaluation

3.1.23

risk contour

two-dimensional representation of risk (e.g. individual risk on a map)

3.1.24

risk evaluation

procedure based on the risk analysis to determine whether the tolerable risk has been achieved

3.1.25

safety

freedom from unacceptable risk

3.1.26

safety zone

area around the bunkering station where only dedicated and essential personnel and activities are allowed during bunkering

3.1.27

stakeholder

individual, group, or organization that can affect, be affected by, or perceive itself to be affected by a risk

3.28

supplier

one or more organizations with ownership, operational and/or legal interests in a bunkering facility

Note 1 to entry: The supplier can be the bunker vessel owner, charterer or operator; the LNG bunkering terminal owner or operator; the road tanker fleet manager; the LNG producer; and so on.

[SOURCE: Reference [24]]

3.1.29

tolerable risk

risk that is accepted in a given context based on the current values of society

3.1.30

topping up

final sequence of LNG transfer to ensure correct filling level in receiving tank

3.1.31

water curtain

sprinkler arrangement to protect steel surfaces from direct contact with LNG

3.2 Abbreviated terms

BASiL	bunkering area safety information for LNG
ERC/standards/	emergency release coupling 3-042423195313
ERS	emergency release system
HFO	heavy fuel oil
HSE	health, safety, and environment
IMO	international maritime organization
LNG	liquefied natural gas
MGO	marine gas oil
PPE	personal protective equipment
QualRA	qualitative risk assessment
QCA	quantitative consequence assessment
QRA	quantitative risk assessment
SGMF	society for gas as marine fuel
SIMOPS	simultaneous operations
STCW	seafarers' training, certification and watch- keeping

NOTE LNG is defined in ISO 16903.