

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Short-circuit temperature limits of electric cables with rated voltages above
30 kV ($U_m = 36$ kV)**

**Limites de température de court-circuit des câbles électriques de tension
assignée supérieure à 30 kV ($U_m = 36$ kV)**

IEC 61443:1999

<https://standards.iteh.ai/catalog/standards/iec/4b1ed9e4-56d1-4326-a070-cb2d5f555fcb/iec-61443-1999>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2008 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 15 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

65 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.



IEC 61443

Edition 1.1 2008-11
CONSOLIDATED VERSION

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Short-circuit temperature limits of electric cables with rated voltages above 30 kV ($U_m = 36$ kV)

Limites de température de court-circuit des câbles électriques de tension assignée supérieure à 30 kV ($U_m = 36$ kV)

[IEC 61443:1999](https://standards.iteh.ai/standards/iec/4b1ed9e4-56d1-4326-a070-cb2d5f555fcb/iec-61443-1999)

<https://standards.iteh.ai/catalog/standards/iec/4b1ed9e4-56d1-4326-a070-cb2d5f555fcb/iec-61443-1999>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.060.20

ISBN 978-2-8891-0518-2

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	6
2 Normative references.....	6
3 Factors governing the application of the temperature limits	6
4 Maximum permissible short-circuit temperatures for cables with rated voltages above 30 kV ($U_m = 36$ kV).....	8
Table 1 – Temperature limits for insulation materials	9
Table 2 – Temperature limits for oversheath materials.....	9
Table 3 – Temperature limits for current-carrying components	10

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[IEC 61443:1999](#)

<https://standards.iteh.ai/catalog/standards/iec/4b1ed9e4-56d1-4326-a070-cb2d5f555fcb/iec-61443-1999>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**SHORT-CIRCUIT TEMPERATURE LIMITS OF ELECTRIC CABLES
WITH RATED VOLTAGES ABOVE 30 kV ($U_m = 36$ kV)**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 61443 edition 1.1 contains the first edition (1999) [documents 20A/409/FDIS and 20A/411/RVD] and its amendment 1 (2008) [documents 20/953/FDIS and 20/976/RVD].

A vertical line in the margin shows where the base publication has been modified by amendment 1.

International Standard IEC 61443 has been prepared by subcommittee 20A: High-voltage cables, of IEC technical committee 20: Electric cables.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[IEC 61443:1999](#)

<https://standards.iteh.ai/catalog/standards/iec/4b1ed9e4-56d1-4326-a070-cb2d5f555fcb/iec-61443-1999>

INTRODUCTION

The following four aspects may be applicable when selecting the short-circuit rating of a cable system.

- a) The permissible maximum temperature limits for cable components (e.g. conductor, insulation, screen or metallic sheath, bedding, armour and oversheath). For the range of voltages covered by this standard, dielectric integrity is the major limitation. For practical uses, the energy producing the temperature rise is usually expressed by an equivalent (I^2t) value so that the permitted maximum duration for a given short-circuit current can be calculated.
- b) The maximum value of current which will not cause mechanical failure (such as bursting) due to electromagnetic forces. Irrespective of any temperature limitations, this determines a maximum current which should not be exceeded.
- c) The thermal performance of joints and terminations at the limits of current and duration specified for the associated cable. Accessories should also withstand the thermo-mechanical and electromagnetic forces produced by the short-circuit current in the cable.
- d) The influence of installation conditions on the above three aspects.

Aspect a) is dealt with in detail, and the limits given are based on a consideration of the cable only. A single short-circuit application is not expected to produce any significant damage to the cable, but repeated short-circuits may cause cumulative damage. Guidance is given, where appropriate, on aspects c) and d) mainly as they concern thermo-mechanical forces in the conductors and metallic sheath. Aspect b) is not covered in this standard.

The limits recommended in this standard should be used for guidance only. There is little scientific evidence available on the behaviour of actual cables under short-circuit conditions, most of the information being based on tests on the constituent materials themselves. It has been necessary to exercise considerable judgement in setting these recommended limits, and, in general, especially for the dielectric, the best average of present usage has been suggested.

It is not possible to provide complete limits for joints and terminations because their construction is not standardized and performance varies. Where the full short-circuit capability of the cable is needed, the accessories should be designed appropriately, but this is not always economically justified and the short-circuit capability of a cable system may be determined by the performance of its joints and terminations. Where possible, guidance has been included on the performance of accessories when they are installed on cables subject to the short-circuit limits given in this standard.

SHORT-CIRCUIT TEMPERATURE LIMITS OF ELECTRIC CABLES WITH RATED VOLTAGES ABOVE 30 kV ($U_m = 36$ kV)

1 Scope

This International Standard gives guidance on the short-circuit maximum temperature limits of electric cables having rated voltages above 30 kV ($U_m = 36$ kV) up to the voltage limits given in IEC 60141 and IEC 62067, with regard to the following:

- insulating materials;
- oversheath and bedding materials;
- conductor and metallic sheath materials and methods of connection.

The design of accessories and the influence of the installation conditions on the temperature limits are taken into consideration.

The calculation of the permissible short-circuit current in the current-carrying components of the cable should be carried out in accordance with IEC 60949.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60141 (all parts), *Tests on oil-filled and gas-pressure cables and their accessories*

IEC 60840:1999, *Power cables with extruded insulation and their accessories for rated voltages above 30 kV ($U_m = 36$ kV) up to 150 kV ($U_m = 170$ kV) – Test methods and requirements*

IEC 60949:1988, *Calculation of thermally permissible short-circuit currents, taking into account the non-adiabatic heating effects*

IEC 62067, *Power cables with extruded insulation and their accessories for rated voltages above 150 kV ($U_m = 170$ kV) up to 500 kV ($U_m = 550$ kV) – Test methods and requirements*

3 Factors governing the application of the temperature limits

3.1 General

The short-circuit temperatures given in clause 4 are the actual temperatures of the current-carrying component as limited by the adjacent material in the cable and are valid for short-circuit durations of up to 5 s. When calculating the allowable short-circuit current, these temperatures will be obtained if heat loss into the insulation during the short circuit is taken into account (non-adiabatic heating). If heat loss during the short-circuit is neglected (adiabatic heating), the calculations give short-circuit currents that are on the safe side.

NOTE The temperature limits given in clause 4 should also not be exceeded with repeated short-circuits occurring in a short time.

The 5 s time period mentioned is the limit for the temperatures quoted to be valid and not for the application of the adiabatic calculation method. The time limit for the use of the adiabatic method has a different definition, being a function of both the short-circuit duration and the cross-sectional area of the current-carrying component. This is dealt with in IEC 60949.

The short-circuit temperature limits recommended in this standard are based on the consideration of the range of limits used by various authorities. They are not necessarily the ideal values as very little applicable experimental data are available on actual cables. The values are, however, considered to be on the safe side.

The limits for cables in this standard are selected so that the dielectric properties are not impaired. The impairment of dielectric properties will be very dependent on the type of cable, e.g. adhesion of the semi-conducting screens will most likely set the limits for polymeric insulated cables, whereas the properties of the dielectric itself are of more importance in paper cables (both oil-filled and gas-pressure cables).

Caution may be needed when using the conductor temperatures specified when the cables are sheathed with a lower temperature material, especially for cables with conductor cross-sectional areas of 1 000 mm² and above. This is because the high thermal time constant of these cables will cause the oversheath to attain high temperatures for longer times. In addition, the high mechanical forces could result in insulation deformation. Nevertheless, it should be stressed that for conductor cross-sectional areas above 1 000 mm² the permissible short-circuit current is so high that it is not normally attained in common systems.

Where other temperature limits are known with certainty to be more appropriate for the materials or the cable design, then these may be used.

3.2 Cables

3.2.1 Paper-insulated cables (both oil-filled and gas-pressure cables, according to IEC 60141)

The temperature limits for paper-insulated cables are imposed by thermal degradation of the cable components and by possible tearing of paper tapes due to movement of the cores.

In addition, the temperature limits for gas-pressure cables are imposed by the tendency to compound migration whereas oil-filled cables may be limited by the maximum applicable transient oil pressure.

3.2.2 Polymeric insulated cables (according to IEC 60840 and IEC 62067)

The temperature limits for polymeric insulated cables are imposed by the dielectric properties of the insulation. The high temperatures, electromagnetic forces and expansion forces produced under short-circuit conditions could have a marked effect on the physical condition of the cable. Thus, the integrity of the bond between the semi-conducting screens and the insulation and deformation of the insulation are two important considerations for polymeric insulated cables. In addition, the high temperatures may change the properties of the semi-conducting and sheathing materials.

For thermoplastic insulating materials, the temperature limits should be applied with caution when the cables are either directly buried or securely clamped when in air. Local pressure due to clamping or the use of an installation radius less than that specified for the cable, especially for cables that are rigidly restrained, can lead to high deforming forces under short-circuit conditions. Where these conditions cannot be avoided it is suggested that the limit be reduced by 10 °C.

3.3 Accessories

Attention should be given to the design and installation of joints and terminations if the short-circuit limits set out in this standard are to be safely used. The following aspects are not exclusive and are provided for guidance only. It is desirable that the performance of an accessory be considered in the context of the particular installation.

- a) Longitudinal thrust in cable conductors can be considerable, depending on the degree of lateral restraint imposed on the cable. Conductor stresses as high as 50 N/mm² can easily occur. These forces may cause buckling of conductors and other damage in a joint or termination.
- b) Longitudinal tension in cable conductors is also to be expected after a short-circuit. This tension may exist for a very long period, particularly if the cable is only partly loaded after the short-circuit. A minimum conductor stress of 40 N/mm² should be used for design purposes.
- c) The use of a temperature limit only implies that any combination of current and time which produces temperatures not exceeding that limit is permissible. For short-circuit currents this is not sufficient. An additional limit should be set for the peak value of the current in order to avoid excessive electromagnetic forces. These forces are of particular importance at terminations and proper support is necessary to avoid undesirable movement and damage.
- d) Soldered joints should not be used if conductor temperatures greater than 160 °C are contemplated.
- e) Attention is drawn to the need to examine the design for short-circuit stability of the electrical contact of all connectors used for jointing conductors and connecting armour and metallic sheath bonds.
- f) Screen and/or armour wires, when gathered together at a joint or termination, may have a lower short-circuit performance than when in the cable. At such connections the expected temperature rise should not be excessive for the materials involved and adequate mechanical support should be provided.
- g) Account should be taken of the risk of longitudinal shrinkage of polymeric components at the cut ends of cables at short-circuit temperatures.

3.4 Installation conditions

When it is intended to make full use of the short-circuit limit of a cable, consideration should be given to the influence of the installation conditions. An important aspect concerns the extent and nature of the mechanical restraint imposed on the cable. Longitudinal expansion of a cable during a short-circuit can be significant and when this expansion is restrained the resultant forces are considerable.

For cables in air, it is advisable to install them so that expansion is absorbed uniformly along the cable length. When snaking, fixings should be spaced sufficiently far apart to permit lateral movement of the cables.

Where cables are installed directly in the ground, or are restrained by frequent fixing, then provision should be made to accommodate the resulting longitudinal forces on accessories. Sharp bends should be avoided because the longitudinal forces are translated into radial pressures at bends in the cable route, and these may damage thermoplastic components of the cable. Attention is drawn to the minimum radius of installed bend recommended by the appropriate installation regulations.

4 Maximum permissible short-circuit temperatures for cables with rated voltages above 30 kV ($U_m = 36$ kV)

Tables should be read in conjunction with the comments in clause 3. Values given are actual temperatures of the current-carrying components. Limits are for short-circuits of up to 5 s in duration.