

## SLOVENSKI STANDARD SIST ISO 2950:1998

01-februar-1998

Rjavi premogi in lig	niti - Razvrstitev v	vrste po deleži	u celotne vlage	e in deležu
katrana				

Brown coals and lignites -- Classification by types on the basis of total moisture content and tar yield

### iTeh STANDARD PREVIEW

Charbons bruns et lignites -- Classification en types d'après la teneur en humidité totale et le rendement en goudron

SIST ISO 2950:1998

Ta slovenski standard je istoveten z: dobolov standard sistem z: dobolov sistem z: dobolov standard sistem z: dobolov standard sistem z: dobolov sistem z: d

ICS:

73.040 Premogi Coals

SIST ISO 2950:1998 en

SIST ISO 2950:1998

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 2950:1998

https://standards.iteh.ai/catalog/standards/sist/e5cf732c-2029-49db-93dd-9f8520a6b50d/sist-iso-2950-1998



INTERNATIONAL ORGANIZATION FOR STANDARDIZATION •МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ •ORGANISATION INTERNATIONALE DE NORMALISATION

## Brown coals and lignites — Classification by types on the basis of total moisture content and tar yield

Charbons bruns et lignites — Classification en types, d'après la teneur en humidité totale et le rendement en goudron

First edition – 1974-02-01

(standards.iteh.ai)

SIST ISO 2950:1998

https://standards.iteh.ai/catalog/standards/sist/e5cf732c-2029-49db-93dd-9f8520a6b50d/sist-iso-2950-1998

UDC 662.642.001.3

Descriptors: coal, lignite, classification, moisture content, tars, yield.

Ref. No. ISO 2950-1974 (E)

O 2950-1974 (E

#### **FOREWORD**

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO Member Bodies). The work of developing International Standards is carried out through ISO Technical Committees. Every Member Body interested in a subject for which a Technical Committee has been set up has the right to be represented on that Committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the Technical Committees are circulated to the Member Bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 2950 was edrawn up by Technical Committee VIEW ISO/TC 27, Solid mineral fuels, and circulated to the Member Bodies in November 1972.

Standards.iten.al)

It has been approved by the Member Bodies of the following countries: 1998

https://standards.iteh.ai/catalog/standards/sist/e5cf732c-2029-49db-93dd-

Belgium Bulgaria Iran

9f8520a6bfailland-iso-2950-1998

Canada

Italy New Zealand Turkey

Czechoslovakia

Poland

U.S.A. U.S.S.R.

Denmark

Portugal

Yugoslavia

France

South Africa, Rep. of

India

Sweden

The Member Body of the following country expressed disapproval of the document on technical grounds:

Australia

© International Organization for Standardization, 1974 •

Printed in Switzerland

## Brown coals and lignites — Classification by types on the basis of total moisture content and tar yield

#### 1 SCOPE AND FIELD OF APPLICATION

This International Standard establishes a classification of brown coals and lignites by types on the basis of total moisture content and tar yield.

Until reliable parameters for differentiation of browns and 950:1 hard coals are worked outpandsconfirmed coals donsideredds/sist/e5cf732c-4ABLEAD-Class numbers of brown coal types in each country as brown, on the basis of agrumber of other-iso-2950-1998 characteristics, should be classified as brown coals regardless of their calorific value, i.e. including the cases when the gross calorific value of the coal in equilibrium with air at 30 °C and 96 % relative humidity is more than 24 000 kJ/kg on the ash-free basis.

#### 2 REFERENCES

ISO/R 647, Determination of the yields of tar, water, gas and coke residue by low temperature distillation of brown coal and lignite.

ISO/R 1015, Determination of moisture in brown coals and lignites by the direct volumetric method.

ISO/R 1171, Determination of ash of solid mineral fuels.

#### 3 PRINCIPLE

Brown coals are classified in this International Standard according to the following properties:

- a) total moisture content calculated on the ash-free basis:
- b) tar yield calculated on the dry, ash-free basis.

#### 4 CLASSIFICATION INDICES

4.1 Division of brown coals into classes

The brown coals are first divided according to their total moisture content, calculated on the ash-free basis, into the classes shown in table 1.

Class number	Total moisture content of run-of-mine coals on the ash-free basis %		
1	< 20		
2	> 20 to 30		
3	> 30 to 40		
4	> 40 to 50		
5	> 50 to 60		
6	> 60 to 70		

#### 4.2 Division of brown coals into groups

The brown coals, divided into classes as described in 4.1, are then sub-divided according to their tar yield, calculated on the dry, ash-free basis, into the groups shown in table 2.

TABLE 2 - Group numbers of brown coal types

Group number	Tar yield on the dry, ash-free basis $\%$		
0	≤ 10		
1	> 10 to 15		
2	> 15 to 20		
3	> 20 to 25		
4	> 25		

#### ISO 2950-1974 (E)

#### 4.3 Code numbers

The type of brown coal is indicated by a two-digit code number in which

the first digit indicates the class of coal;

the second digit indicates the group of coal.

#### 4.4 Classification of brown coals by types

The resulting code numbers for the classification of brown coals by types are shown in table 3.

#### 5 METHODS OF TESTING

#### 5.1 Determination of total moisture content

ISO/R 1015 shall be used.

#### 5.2 Determination of tar yield

ISO/R 647 shall be used.

#### 5.3 Determination of ash

ISO/R 1171 shall be used.

TABLE 3 -Code numbers of brown coal types

Group parameter : tar yield on the dry, ash-free basis %	Group number	Code numbers					
> 25	4	14	24	34	44	54	64
> 20 to 25	3	13 C	<b>73</b>	D 133 DD	EV43EV	7 53	63
> 15 to 20	2					52	62
> 10 to 15	1	11	standar	ds.iteh.	ai) 41	51	61
≤ 10	0	10	20	30	40	50	60
Class number		1 cps://standards.ite	-	) <u>2950:1998</u> dards/sist/e5cf73	<b>4</b> 2c 2020 40db (	5	6
Class parameter: to content of run-of-m ash-free basis, %	otal moisture		_	sist-iso-2950-19 > 30 to 40		> 50 to 60	> 60 to 70