

## SLOVENSKI STANDARD SIST ISO 4382-1:2022

01-marec-2022

## Drsni ležaji - Bakrove zlitine - 1. del: Bakrove zlitine za masivne in večslojne debelostene drsne ležaje

Plain bearings - Copper alloys - Part 1: Cast copper alloys for solid and multilayer thick-walled plain bearings

# iTeh STANDARD

Paliers lisses - Alliages de cuivre PREVIEW

(standards.iteh.ai)

Ta slovenski standard je istoveten z: ISO 438

SIST ISO 4382-1:2022

https://standards.iteh.ai/catalog/standards/sist/0814a645-35be-4690-b0a0-4f101dfe8f12/sist-iso-4382-1-2022

ICS:

21.100.10 Drsni ležaji Plain bearings 77.150.30 Bakreni izdelki Copper products

SIST ISO 4382-1:2022 en,fr,de

SIST ISO 4382-1:2022

# iTeh STANDARD **PREVIEW** (standards.iteh.ai)

SIST ISO 4382-1:2022 https://standards.iteh.ai/catalog/standards/sist/0814a645-35be-4690-b0a0-4f101dfe8f12/sist-iso-4382-1-2022

SIST ISO 4382-1:2022

# INTERNATIONAL STANDARD

ISO 4382-1

Third edition 2021-11

## Plain bearings — Copper alloys —

Part 1:

Cast copper alloys for solid and multilayer thick-walled plain bearings

Paliers lisses — Alliages de cuivre —

Partie 1: Alliages de cuivre moulés pour paliers lisses à paroi épaisse, massifs et multicouches

(standards.iteh.ai)

SIST ISO 4382-1:2022

https://standards.iteh.ai/catalog/standards/sist/0814a645-35be-4690-b0a0-4f101dfe8f12/sist-iso-4382-1-2022



# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 4382-1:2022

https://standards.iteh.ai/catalog/standards/sist/0814a645-35be-4690-b0a0-4f101dfe8f12/sist-iso-4382-1-2022



#### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Cor	itent		Page
Fore	word		iv
1	Scop	e	1
2	Norn	native references	1
3	Term	s and definitions	1
4	Requ 4.1 4.2 4.3	irements General Chemical composition Analysis	1 2
5	<b>Mate</b> 5.1 5.2	rial properties General Test methods 5.2.1 Hardness test 5.2.2 Tensile test	2 5 5
6	Desig	gnation and ordering information	5
Anne		formative) Guidance for uses of bearing metals and for the hardness of the ng bearing part (shaft)	7
Bibli	ograph	y iTeh STANDARD	8
		PREVIEW	
		(standards.iteh.ai)	

SIST ISO 4382-1:2022 https://standards.iteh.ai/catalog/standards/sist/0814a645-35be-4690-b0a0-4f101dfe8f12/sist-iso-4382-1-2022

#### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

This document was prepared by Technical Committee ISO/TC 123 *Plain bearings*, Subcommittee SC 2, *Materials and lubricants, their properties, characteristics, test methods and testing conditions.* 

This third edition cancels and replaces the second edition (ISO 4382-1:1991), which has been technically revised. https://standards.iteh.ai/catalog/standards/sist/0814a645-

The main changes compared to the previous edition are as follows:

- Clause 2 "Normative references" has been updated;
- Clause 3 "Terms and definitions" has been implemented;
- <u>Table 1</u> and <u>Table 2</u> have been updated.

A list of all parts in the ISO 4382 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org/members.html">www.iso.org/members.html</a>.

### Plain bearings — Copper alloys —

#### Part 1:

## Cast copper alloys for solid and multilayer thick-walled plain bearings

#### 1 Scope

This document specifies requirements for cast copper alloys for use in solid and multilayer thick-walled plain bearings. It gives a limited selection of alloys currently available for general purposes.

#### Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4384-1, Plain bearings — Hardness testing of bearing metals — Part 1: Multilayer bearings materials

ISO 4384-2, Plain bearings — Hardness testing of bearing metals — Part 2: Solid materials

ISO 6892-1, Metallic materials — Tensile testing — Part 1: Method of test at room temperature

#### Terms and definitions

SIST ISO 4382-1:2022

No terms and definitions/are listed in this document tandards/sist/0814a645-

35be-4690-b0a0-4f101dfe8f12/sist-iso-4382-1-2022 ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <a href="https://www.iso.org/obp">https://www.iso.org/obp</a>
- IEC Electropedia: available at <a href="https://www.electropedia.org/">https://www.electropedia.org/</a>

#### 4 Requirements

#### 4.1 General

If the purchaser's requirements necessitate limits for any element not specified, or limits different from those already specified, these should be agreed upon between supplier and purchaser.

WARNING — Lead's (Pb) toxicity has been recognized, and its use has since been phased out of many applications. However, many countries still allow the sale of products that expose humans to lead. Lead is a neurotoxin (see Figure 1).







**GHS 09** 

Figure 1 — Reach compliance symbols

#### 4.2 Chemical composition

The chemical composition shall be within the limits specified in <u>Table 1</u> and <u>Table 2</u>, where single figures denote maximum values.

#### 4.3 Analysis

Methods of analysis for alloying elements or impurities shall either be as specified in relevant International Standards or as mutually agreed between supplier, purchaser and any mutually acceptable arbitrator.

#### 5 Material properties

## **PREVIEW**

#### 5.1 General

## (standards.iteh.ai)

The minimum tensile strength and elongation values quoted in Table 1 and Table 2 are included as properties which may assist designers. Brinell hardness is the mandatory quality control check. If tensile strength and elongation tests are required, this should be stated by the purchaser at the time of ordering.

35be-4690-b0a0-4f101dfe8f12/sist-iso-4382-1-2022

For finished bearings, Brinell hardness will normally be checked.

Table 1 — Copper/lead/tin and copper/aluminium casting alloys for solid and multilayer thick-walled plain bearings

	Chemical composition						
Chemical elements and properties	mass fraction %						
und properties	CuPb9Sn5	CuPb10Sn10a	CuPb15Sn8	CuPb20Sn5	CuAl10Fe5Ni5		
Cu	Remainder	Remainder	Remainder	Remainder	Remainder		
Sn	4 to 6	9 to 11	7 to 9	4 to 6	0,2		
Pb	8 to 10	8 to 11	13 to 17	18 to 23	0,1		
Zn	2	2	2	2	0,5		
Fe	0,25	0,25	0,25	0,25	3,5 to 5,5		
Ni	2	2	2	2,5	3,5 to 6,5		
Sb	0,5	0,5	0,5	0,75	_		
P	0,1 <sup>b</sup>	0,05 <sup>b</sup>	0,1 <sup>b</sup>	0,1 <sup>b</sup>	_		
Al	0,01	0,01	0,01	0,01	8 to 11		
Mn	0,2	0,2	0,2	0,2	3		
Si	0,01	0,01	0,01	0,01	0,1		
S	0,1	0,1	0,1	0,1	_		

Table 1 (continued)

Chemical elements and properties		Chemical composition						
		mass fraction %						
		CuPb9Sn5	CuPb10Sn10a	CuPb15Sn8	CuPb20Sn5	CuAl10Fe5Ni5		
Cu+ Fe+ Ni+ Al+	Cu+ Fe+ Ni+ Al+ Mn		_	_	_	> 99,2		
		Material properties of test bar						
Brinell	GS	55	65	60	45	140		
<b>hardness</b> <sup>c</sup> HBW	GM	60	65	60	50	140		
2,5/62,5/10,	GZ	60	70	65	50	140		
min.	GC	60	70	65	50	140		
Tensile	GS	160	180	170	150	600		
strength	GM	200	220	200	170	600		
$R_{\rm m}$	GZ	220	220	220	180	680		
N/mm <sup>2</sup> , min.	GC	230	220	220	180	680		
Elongation	GS	7	7	5	5	10		
after fracture	GM	5	3	3	5	12		
A	GZ	6	6	8	7	12		
%, min.	GC	9	6	8	7	12		
0,2 % proof	GS	60 <b>1 e</b> n	80	JA 80	60	250		
stress	GM	80	140	7 100	80	250		
$R_{\text{p0,2}}$	GZ	80	RE <sub>110</sub> /IE	100	80	280		
N/mm <sup>2</sup> , min.	GC	130	do 110	100	80	280		
Elastic modul	us	85 85	iuai us.i	ten.ai)				
<i>E</i> kN/mm² ≈	E		90	85	75	120		
	l ov-	<u>S</u>	ST ISO 4382-1	2022				
Linear thermal experient		ps://standards.it	eh.ai/catalog/sta	ndards/sist/0814	a645- 022 19	16		
$\alpha_{\rm l}$ $10^{-6}/{\rm K} \approx$		35be-4 <b>49</b> U-bUat	-4f101 <b>48</b> e8f12/s	1ST-1SO-4 <b>0</b> 82-1-2	022 19	10		
Thermal conductivity λ, at 15°C W/(m·K) ≈		71	47	47	59	60		
<b>Density</b> , $\rho$ kg/dm <sup>3</sup> ≈		9	9	9,1	9,3	7,6		

GS: Sand

GM: Permanent mould

GZ: Centrifugal

GC: Continuous

NOTE <u>Table A.1</u> gives some general guidance on the characteristics and principal uses of the different bearing alloys.

 $<sup>^{\</sup>rm a}$  The chemical composition of this alloy differs from that of thin-walled multilayer plain bearings (see ISO 4383).

 $<sup>^{\</sup>rm b}$   $\,$  For continuous casting, the phosphorus content may be increased to a maximum of 1,5 % by agreement.

For hardness testing, see ISO 4384-1 and ISO 4384-2.

Table 2 — Copper/tin/zinc casting alloys for solid plain bearings

Chemical elements		Chemical composition					
and propertie		mass fraction %					
		CuSn8Pb2	CuSn10P	CuSn12Pb2	CuPb5Sn5Zn5	CuSn7Pb7Zn3	
Cu		Remainder	Remainder	Remainder	Remainder	Remainder	
Sn		6 to 9	10 to 11,5	11 to 13 <sup>a</sup>	4 to 6	6 to 8	
Pb		0,5 to 4	0,25	1 to 2,5	4 to 6	5 to 8	
Zn		3	0,05	2	4 to 6	2 to 5	
Fe		0,2	0,1	0,2	0,3	0,2	
Ni		2,5	0,1	2	2,5	2	
Sb		0,25	0,05	0,2	0,25	0,35	
P		0,05 <sup>b</sup>	0,5 to 1	0,05 to 0,4 <sup>b,c</sup>	0,05 <sup>b</sup>	0,1 <sup>b</sup>	
Al		0,01	0,01	0,01	0,01	0,01	
Mn		_	0,5	0,2	_		
Si		0,01	0,02	0,01	0,01	0,01	
S		0,1	0,05	0,05	0,1	0,1	
		Ma	terial properties	of test bar			
Brinell	GS	60	70	80	60	65	
hardness <sup>d</sup>	GM	85	en 95 IA	NDAR	60	65	
HBW 2,5/62,5/10,	GZ	85	D95 TX	90, 7	65	70	
min.	GC	85	1 95 L V	11 90 V	65	70	
	GS	250	ta n <sup>220</sup> a rd	240	200	210	
Tensile strength	GM	220	1411 <sub>310</sub> 41 U	3.11 <u>C</u> 11.6	200	210	
R <sub>m</sub> N/mm², min.	GZ	230	330	280	250	260	
, ,	GC	270	SIST <sub>0</sub> ISO 43	82-1:2822	250	260	
Elongation after	GS	https://standa	irds.iteh_ai/catalo	)g/standards/si	1.3	12	
fracture	GM	35be-4690 2	-b0a0-4f101dfe8	f12/sis <u>t-</u> iso-43	82-1- <u>2022</u> 13	12	
A	GZ	4	4	5	13	12	
%, min.	GC	5	6	7	13	12	
0,2 % proof	GS	130	130	130	90	100	
stress	GM	130	170	_	90	100	
R <sub>p0,2</sub> N/mm2, min.	GZ	130	170	150	100	120	
N/mm2, min.	GC	130	170	150	100	120	
Elastic moduli	ıs						
$E$ kN/mm <sup>2</sup> $\approx$		75	95	95	90	85	
Linear thermal expansion coefficient $\alpha_l \ 10^{-6}/\mathrm{K} \approx$		18	18	18	18	18	
Thermal conductivity λ, at 15 °C W/(m·K) ≈		47	50	54	71	59	
<b>Density</b> $\rho$ kg/dm <sup>3</sup> $\approx$		8,8	8,8	8,7	8,7	8,8	