# INTERNATIONAL STANDARD

First edition 2023-03

# Industrial furnaces and associated processing equipment — Secondary steelmaking — Machinery and equipment for treatment of liquid steel

Fours industriels et équipements associés — Sidérurgie secondaire — Machines et équipements pour le traitement de l'acier liquide

# (standards.iteh.ai)

<u>ISO 4529:2023</u> https://standards.iteh.ai/catalog/standards/sist/c324c1a1-6b7c-41dd-aef7-535c5e1fb32e/iso-4529-2023



Reference number ISO 4529:2023(E)

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 4529:2023

https://standards.iteh.ai/catalog/standards/sist/c324c1a1-6b7c-41dd-aef7-535c5e1fb32e/iso-4529-2023



### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

# Contents

Foreword			
Intro	ductio		vi
1	Scope		1
2	Norm	tive references	2
2	Torm	and definitions	2
5			
4	Signi	cant nazards and risk assessment	7
5	Safet	requirements	7
	5.1	General	7
	5.2	General requirements for design and risk assessment	8
		5.2.1 General	8
		5.2.2 Design requirements	9
		5.2.3 Structural assembly	9
		5.2.4 Safety davices and protective measures	9
		5.2.6 Warning devices and cafety labelling	10
		5.2.7 Personal protective equipment (PDF)	11 11
		5.2.8 Loss of operative equipment (FFE)	11 11
		5.2.9 Operating stations for the SSME	11
		5.2.10 Portable wired /wireless control hox	12
		5.2.10 Fortable wheely wheless control box	12
		5.2.12 Access to and presence in danger zone	13
		5.2.13 Safety related control system	14
		5.2.14 Electrical power supply	14
		5.2.15 Electrical low voltage supply	
		5.2.16 Fluid systems carrying or containing fluids	
		5.2.17 Harmful areas	
		5.2.18 Exchange of lances 4529-2023	
		5.2.19 Surface temperatures, heat radiation	16
		5.2.20 Temperature measurement and sampling equipment	16
		5.2.21 Electrode clamp	
		5.2.22 Electrode exchange	16
		5.2.23 Grounding of mechanical ladle furnace parts	16
		5.2.24 Emergency stop	
		5.2.25 Fire protection	
		5.2.26 Special requirements for explosion prevention and protection	17
		5.2.27 Ergonomics	18
		5.2.28 Vibrations	18
		5.2.29 Noise reduction as a safety requirement	19
	5.3	List of significant hazards, hazardous situations, safety requirements and/or	
		protective/risk reduction measures	19
6	Vorif	ation of safety requirements and protective/risk reduction measures	40
U	61	General	40
	6.2	Required verification D	40
	63	Required verification V M and T	40
-	0.5		
7	Infor	ation for use	
	7.1	General requirements	41
	7.2	Warning devices and safety labelling	42
	7.3	Marking and labelling.	42
	7.4	Accompanying documents	42
		V.4.1 INSTRUCTIONS	42
Anne	x A (no	native) <b>Noise test code</b>	46

Annex B (normative) Safety requirements for electrical equipment and for safety related	
control systems	50
Annex C (informative) Examples for secondary steelmaking equipment	52
Bibliography	54

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 4529:202</u>

https://standards.iteh.ai/catalog/standards/sist/c324c1a1-6b7c-41dd-aef7-535c5e1fb32e/iso-4529-2023

### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="https://www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 244, *Industrial furnaces and associated processing equipment*.

<u>ISO 4529:2023</u>

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

### Introduction

This document is a type-C standard as stated in ISO 12100.

This document is of relevance, in particular, for the following stakeholder groups representing the market players with regard to machinery safety:

- machine manufacturers (small, medium and large enterprises);
- health and safety bodies (regulators, accident prevention organisations, market surveillance etc.).

Others can be affected by the level of machinery safety achieved with the means of the document by the above-mentioned stakeholder groups:

- machine users/employers (small, medium and large enterprises);
- machine users/employees (e.g. trade unions, organizations for people with special needs);
- service providers, e.g. for maintenance (small, medium and large enterprises);
- consumers (in case of machinery intended for use by consumers).

The above-mentioned stakeholder groups have been given the possibility to participate at the drafting process of this document.

The machinery concerned and the extent to which hazards, hazardous situations or hazardous events are covered are indicated in the Scope of this document.

When requirements of this type-C standard are different from those which are stated in type-A or type-B standards, the requirements of this type-C standard take precedence over the requirements of the other standards for machines that have been designed and built according to the requirements of this type-C standard.

https://standards.iteh.ai/catalog/standards/sist/c324c1a1-6b7c-41dd-aef7-535c5e1fb32e/iso-4529-2023

## Industrial furnaces and associated processing equipment — Secondary steelmaking — Machinery and equipment for treatment of liquid steel

### **1** Scope

This document:

- pecifies the general safety requirements for secondary steelmaking machinery and equipment (SSME) as defined in 3.1 to treat liquid steel;
- deals with all significant hazards, hazardous situations and events pertinent to SSME, when used as intended and under conditions foreseen by the manufacturer, but also includes foreseeable misuse, faults and malfunctions:
- specifies the requirements to ensure the safety of persons which are to be met during the design, pre-assembly, transport, sites assembly, commissioning, operation, maintenance, decommissioning and dismantling/ disassembling of the equipment;
- assumes that SSMEs are operated and maintained by adequately trained and competent personnel. Manual intervention for setting, adjustment and maintenance is accepted as part of the normal use of the equipment.

This document applies to SSME involved in the treatment process of liquid steel under vacuum or atmospheric pressure and covers:

- VD, vacuum degassing,
- VOD, vacuum oxygen decarburization,
- RH (OB), Ruhrstahl Heraeus (oxygen blowing),
- process related interfaces/interactions (e.g. according to design, controls) to:
  - a) process media,
  - b) primary and secondary gas cleaning plant,
  - c) material handling systems,
  - d) transfer cars for steel ladle, and
  - e) crane and ladle.

NOTE 1 Due to the variety of secondary metallurgical processes, there are other variants (e.g. VODC - vacuum oxygen decarburization converter, CAS, CAS - OB) in addition to the main processes discussed in this document. Most countries require that applicable safety requirements, specific to this equipment be implemented.

This document does not cover safety requirements for the following equipment:

- cranes;
- transfer cars, e.g. ladle transfer cars, tank cars, maintenance cars;
- fork lift trucks or other transporting equipment;

- ladles;
- equipment for relining and preheating in the relining area;
- burners according to ISO 13577-2 (the burner lances for RH vessels are covered by ISO 13577-2 except for maximum main burner ignition time, see <u>5.2.26.2</u>);
- cleaning and treatment of dust and fume exhaust systems;
- process media (e.g. air separation, boiler house, steam generation system);
- material handling systems.

NOTE 2 Significant hazards and hazardous situations due to transporting/positioning of heavy components, e.g. by cranes (e.g. ladles, vessels, covers) are considered in this document (see <u>5.2.3</u>).

This document is not applicable to SSMEs and associated equipment manufactured before the date of its publication.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3864-1, Graphical symbols — Safety colours and safety signs — Part 1: Design principles for safety signs and safety markings

ISO 3864-3, Graphical symbols — Safety colours and safety signs — Part 3: Design principles for graphical symbols for use in safety signs

ISO 4413, Hydraulic fluid power — General rules and safety requirements for systems and their components ISO 4414, Pneumatic fluid power — General rules and safety requirements for systems and their components

ISO 4871:1996, Acoustics — Declaration and verification of noise emission values of machinery and equipment

ISO 7000, Graphical symbols for use on equipment — Registered symbols

ISO 7731, Ergonomics — Danger signals for public and work areas — Auditory danger signals

ISO 8995-1, Lighting of work places — Part 1: Indoor

ISO 11064-1, Ergonomic design of control centres — Part 1: Principles for the design of control centres

ISO 11202, Acoustics — Noise emitted by machinery and equipment — Determination of emission sound pressure levels at a work station and at other specified positions applying approximate environmental corrections

ISO 11428, Ergonomics — Visual danger signals — General requirements, design and testing

ISO 11429, Ergonomics — System of auditory and visual danger and information signals

ISO 12100:2010, Safety of machinery — General principles for design — Risk assessment and risk reduction

ISO 13732-1, Ergonomics of the thermal environment — Methods for the assessment of human responses to contact with surfaces — Part 1: Hot surfaces

ISO 13849-1, Safety of machinery — Safety-related parts of control systems — Part 1: General principles for design

ISO 13850:2015, Safety of machinery — Emergency stop function— Principles for design

ISO 13854, Safety of machinery — Minimum gaps to avoid crushing of parts of the human body

ISO 13857, Safety of machinery — Safety distances to prevent hazard zones being reached by upper and lower limbs

ISO 14119, Safety of machinery — Interlocking devices associated with guards — Principles for design and selection

ISO 14120, Safety of machinery — Guards — General requirements for the design and construction of fixed and movable guards

ISO 14122-1, Safety of machinery — Permanent means of access to machinery — Part 1: Choice of fixed means and general requirements of access

ISO 14122-2, Safety of machinery — Permanent means of access to machinery — Part 2: Working platforms and walkways

ISO 14122-3, Safety of machinery — Permanent means of access to machinery — Part 3: Stairs, stepladders and guard-rails

ISO 14122-4, Safety of machinery — Permanent means of access to machinery — Part 4: Fixed ladders

ISO 16069, Graphical symbols — Safety signs — Safety way guidance systems (SWGS)

ISO 20816-1, Mechanical vibration — Measurement and evaluation of machine vibration — Part 1: General guidelines

ISO 80079-36, Explosive atmospheres — Part 36: Non-electrical equipment for explosive atmospheres — Basic method and requirements

EN 811, Safety of machinery — Safety distances to prevent danger zones being reached by the lower limbs

EN 1088, Safety of machinery — Interlocking devices associated with guards - Principles for design and selection tandards iteh ai/catalog/standards/sist/c324c1a1-6b7c-41dd-aef7-535c5e1fb32e/iso-

EN 13463-1:2001, Non-electrical equipment for potentially explosive atmospheres — Part 1: Basic method and requirements

IEC 60079(all parts), Explosive atmospheres

IEC 60204-1:2016, Safety of machinery — Electrical equipment of machines — Part 1: General requirements

IEC 60519-4:2021, Safety in electroheat installations — Part 4: Particular requirements for arc furnace installations

IEC 60730-2-5, Automatic electrical controls — Part 2-5: Particular requirements for automatic electrical burner control systems

IEC 61310-1, Safety of machinery — Indication, marking and actuation — Part 1: Requirements for visual, acoustic and tactile signals

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12100:2010 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <u>https://www.iso.org/obp</u>
- IEC Electropedia: available at https://www.electropedia.org/

#### ISO 4529:2023(E)

#### 3.1

#### secondary steelmaking machinery and equipment

#### **SSME**

machinery and equipment for treatment of liquid steel under vacuum or atmospheric pressure

#### 3.2

#### material addition equipment

equipment for storage, conveying and adding material into liquid steel

#### 3.3

#### blowing equipment

equipment for blowing gas and/or powder on top or into liquid steel

Chemical heating and desulphurization. **EXAMPLE** 

#### 3.4

#### burner equipment

burner for atmospheric operation inside RH vessel

**EXAMPLE** To pre-heat refractory or maintain refractory temperature.

#### 3.5

#### positioning equipment

equipment for positioning of components

#### 3.6

# stirring equipment

equipment for homogenisation of liquid steel standards.iteh.ai)

#### 3.7

#### vacuum pump

equipment to reduce pressure with respect to atmospheric conditions

3.8

vacuum vessel equipment equipment to enable a treatment of liquid steel under vacuum conditions

#### 3.9

#### media handling equipment

equipment to store, supply and return process media

#### 3.10

#### electrical heating equipment

electrical equipment to provide thermal energy to liquid steel

#### 3.11

#### temperature measurement and sampling equipment

manual or automatic equipment for temperature measurement and taking samples of liquid steel and slag

#### 3.12

#### high-voltage switch gear

#### furnace breaker

device to connect and disconnect the ladle furnace to/from the electrical high voltage supply

#### 3.13

#### safety layout

graphical description of plant-related equipment regarding safety

#### 3.14

#### hazard zone

danger zone

any space within and/or around machinery in which a person can be exposed to a hazard

[SOURCE: ISO 12100:2010, 3.11]

#### 3.15

#### take-over-point

point where the *secondary steelmaking machinery and equipment (SSME)* (<u>3.1</u>) is connected to incoming/ outgoing material (e.g. liquid steel), process media, electricity (e.g. power supply and communication like input/output parameters)

Note 1 to entry: For example, ladle take-over-point: point where overhead cranes or other transport systems deposit or remove ladles.

#### 3.16

safeguard

guard or protective device

[SOURCE: ISO 12100:2010, 3.26]

#### 3.17

#### competent personnel

person who can demonstrate a combination of knowledge and skills to effectively, efficiently, and safely carry out specified tasks

Note 1 to entry: Competence is usually specified by activity [e.g. design, selection of equipment, installation, operation, *maintenance* (3.20), testing, *inspection* (3.20.1), *repair* (3.20.3)].

#### 3.18

#### authorized personnel

*competent personnel* (3.17) who has the permission to perform a specific task under defined requirements on a specific equipment

#### 3.19

#### trained personnel

person with the knowledge of systems, background, experience and ability to operate and/or maintain the equipment in the intended use and proper operation of the machinery/ equipment

Note 1 to entry: Background experiences are intended to be specific for the type of equipment.

#### 3.20

#### maintenance

activities carried out outside the production process

#### 3.20.1

#### inspection

basic checks (e.g, visual) of equipment

#### 3.20.2

#### service

periodic exchange of lances, cleaning (e.g. lance), lubrication, adjustment of limit switches

#### 3.20.3

#### repair

physical action taken to restore the intended function of faulty equipment

#### 3.20.4

#### reconditioning

measure to return to the nominal condition

Note 1 to entry: Foreseeable measures can be to replace worn parts or parts having expired the foreseen lifetime (could require dismantling/disassembling). These parts will normally meet manufacturers' original specification.

#### 3.20.5

#### functional test

checking the functionality of the exchanged or repaired parts

Note 1 to entry: It can be required to carry out adjustment work, e.g. test runs, verifying safety functions.

#### 3.21

#### alloying material

ferrous and/or non-ferrous metallic additions

#### 3.22

#### chimney effect

suction power caused by the thermal updraft of hot gases expanding

#### 3.23

#### control room

main room in which the control desk and monitoring facilities for a *secondary steelmaking machinery and equipment (SSME)* (3.1) are located

Note 1 to entry: It is a location where operating personnel is required permanently during the production process.

#### 3.24

#### local control stand

control units usually situated adjacent to the equipment

1500, 2022

Note 1 to entry: It is a location where operating personnel is required temporarily during the production process.

#### 3.25

#### portable control box

mobile control units connected to the control system, wired or wireless

Note 1 to entry: For example, to position equipment more precisely.

#### 3.26

#### ignition source

source of energy that initiates combustion

#### 3.27

manual control

control device which is manually operated

#### 3.27.1

#### hold-to-run control

control device which initiates and maintains machine functions only as long as the *manual control* (3.27) (actuator) is actuated

Note 1 to entry: Release of the button/device stops the function (e.g. movement) immediately.

#### 3.28

#### operating mode

state of the control system allowing to operate the *secondary steelmaking machinery and equipment (SSME)* (3.1) under defined conditions

Note 1 to entry: Such conditions (modes) could include production, safe stop, enabling, adjustment, inspection.

Note 2 to entry: The safety level of the operating mode(s) is defined as result of the risk assessment.

#### 3.29

#### slack rope and overload protection

device to detect slack rope and overload of winch systems

#### 3.30

#### manufacturer

natural or legal person declared as responsible for compliance with the requirements of the design and/or manufacturing of machinery

Note 1 to entry: The process of design and construction of machinery may involve several individuals or companies, but one is declared as the manufacturer.

#### 3.31

#### material handling system

equipment for storage, conveying and adding bulk material

# 4 Significant hazards and risk assessment **PREVIEW**

All the significant hazards, hazardous situations and events, as far as they are dealt with in this document, identified by risk assessment as significant for this type of machinery and which require action to eliminate or reduce the risk are listed in columns 1 and 2 of <u>Table 1</u>.

In addition, the manufacturer shall carry out a plant-related risk assessment, including interfaces to auxiliary equipment, according to ISO 12100:2010, Clause 4 to identify any other significant hazard of the machine/equipment. Significant hazards identified in this plant-related risk assessment but not dealt with in this document shall be reduced by applying the principles of ISO 12100.

### **5** Safety requirements

#### 5.1 General

The manufacturer of SSMEs shall take into account that different life cycle phases have to be considered with regard to safety and the need for risk reduction. In general, the following life cycle phases are common for SSMEs (see Figure 1).





#### Key

- 1 design, manufacturing and installation by the manufacturer
- 2 handover to and putting into service (first use for <sup>d</sup> its intended purpose) by the operator
- 3 operation
- 4 putting out of service
- 5 disassembly
- 6 disposal and recycling
- <sup>a</sup> Design, manufacturing, pre-assembly.
- <sup>b</sup> Transport/shipping to the construction site.

On site assembly.

Testing and commissioning.

Normal operation (production, intended use) including production changes and capacity changer.

- Emergency and fault operation.
- Maintenance and repair.
- Troubleshooting.

Special operation modes (if applicable).

# Figure 1 — Schematic representation of the life phases of an SSME

С

e

f

g

h

i

#### 5.2 General requirements for design and risk assessment

#### 5.2.1 General

#### ISO 4529:2023

SSME plants conforming to this document shall comply with the safety requirements and/or measures set out in <u>Clause 5</u> together with those set out in <u>Annexes A</u> and <u>B</u> for a typical installation, and the information for use as defined in <u>Clause 7</u>.

Special consideration shall be given to CO emission for vacuum treatment equipment due to process transients and/or equipment failure.

In general, risks and associated hazards are production- and plant-related. The variety of different plants (i.e. different combinations of equipment, different boundary conditions) could not be covered in all details in this document. To deal with this fact, an individual risk assessment of the SSME in question shall be carried out (see <u>Clause 4</u>) considering the safety requirements of this document.

The manufacturer shall include in the information for use all details required for a safe operating process under normal operating conditions. The manufacturer shall also describe the specific safety measures in case of special conditions, e.g. maintenance and adjustment work.

If in addition to the technical measures further measures for risk reduction by organizational precautions according to ISO 12100:2010, Clause 5 are necessary, the manufacturer shall include in the information for use details of these measures and the necessary information considering the residual risks.

Machinery shall comply with the safety requirements and/or protective/risk measures of this clause. In addition, the machine shall be designed according to the principles of ISO 12100:2010 for relevant but significant hazards which are not dealt with by this document.

#### 5.2.2 Design requirements

The manufacturer, in consultation with the user, should conduct a design layout review to ensure proper placement of the SSME. To ensure safe operation the following elements shall be included:

- operating procedures;
- accessibility;
- movement of parts of the equipment and material;
- position of emergency systems;
- maintenance and cleaning;
- prevention of hazardous conditions, caused by, e.g. emissions, heat, liquid steel;
- physical and ergonomic requirements;
- fire safety and evacuation.

Depending on the design of the SSME, the different operating modes shall be considered by the manufacturer. All these operating modes shall be assessed and considered in the risk assessment, except special operation modes if they are not foreseen by the manufacturer.

#### 5.2.3 Structural assembly

The manufacturer shall undertake and record design calculations to show that the structural assembly (e.g. steel sections, auxiliaries) which forms part of the equipment is adequate to withstand the load under intended use.

#### **5.2.4 Safety layout** <u>ISO 4529:20</u>

A safety layout shall be prepared. The aim of the safety layout is to give information (normally by means of one or more drawings) about the physical position of safety related elements at the SSME.

It is recommended to involve the user of the equipment, e.g. regarding escape routes, fire extinguishing systems, etc.

If applicable, the following shall at least be illustrated:

- areas where the risk of injury due to contact with liquid metal or slag including spraying is given;
- emergency stop buttons;
- escape and access routes (if necessary, e.g. for large plants);
- areas influenced by low oxygen and/or harmful gases (e.g. CO or asphyxiating gases);
- visible/audible warning devices;
- safety related marking;
- safety signs;
- fixed guards (e.g. fences);
- moveable guards (e.g. safety doors);
- light barriers or safety scanners.