



**SLOVENSKI STANDARD**  
**SIST EN 1366-10:2022+A1:2024**

**01-november-2024**

---

**Preskusi požarne odpornosti servisnih inštalacij - 10. del: Dimne lopute (vključno z dopnilom A1)**

Fire resistance tests for service installations - Part 10: Smoke control dampers

Feuerwiderstandsprüfungen für Installationen - Teil 10: Entrauchungsklappen

Essais de résistance au feu des installations techniques - Partie 10 : Volets de désenfumage

**Ta slovenski standard je istoveten z: EN 1366-10:2022+A1:2024**

---

[SIST EN 1366-10:2022+A1:2024](https://standards.iteh.ai/catalog/standards/sist/831a38fa-1b37-4170-bc5f-4de707118a24/sist-en-1366-10-2022a1-2024)

<https://standards.iteh.ai/catalog/standards/sist/831a38fa-1b37-4170-bc5f-4de707118a24/sist-en-1366-10-2022a1-2024>

**ICS:**

13.220.50	Požarna odpornost gradbenih materialov in elementov	Fire-resistance of building materials and elements
91.060.40	Dimniki, jaški, kanali	Chimneys, shafts, ducts

**SIST EN 1366-10:2022+A1:2024**

**en,fr,de**



EUROPEAN STANDARD

EN 1366-10:2022+A1

NORME EUROPÉENNE

EUROPÄISCHE NORM

September 2024

ICS 13.220.50; 91.140.30

Supersedes EN 1366-10:2022

English Version

## Fire resistance tests for service installations - Part 10: Smoke control dampers

Essais de résistance au feu des installations techniques  
- Partie 10 : Volets de désenfumage

Feuerwiderstandsprüfungen für Installationen  
- Teil 10: Entrauchungsklappen

This European Standard was approved by CEN on 24 July 2022 and includes Amendment 1 approved by CEN on 14 July 2024.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.

[SIST EN 1366-10:2022+A1:2024](https://standards.iteh.ai/catalog/standards/sist/831a38fa-1b37-4170-bc5f-4de707118a24/sist-en-1366-10-2022a1-2024)

<https://standards.iteh.ai/catalog/standards/sist/831a38fa-1b37-4170-bc5f-4de707118a24/sist-en-1366-10-2022a1-2024>



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

<b>Contents</b>	<b>Page</b>
European foreword .....	6
Introduction .....	8
1 Scope.....	9
2 Normative references.....	9
3 Terms and definitions.....	9
4 Test equipment.....	12
4.1 General.....	12
4.2 Test duct for surface mounted SCDs .....	12
4.3 Connecting duct for compartment boundary mounted SCDs .....	13
4.3.1 Compartmentation test.....	13
4.3.2 Maintenance of opening test.....	13
4.4 Cycling equipment.....	13
4.5 Condensing unit.....	13
4.6 Gas temperature measuring devices .....	13
4.7 Exhaust fan system.....	13
4.8 Perforated plate .....	14
4.9 Volume and flow measurement for duct mounted SCDs .....	14
4.10 Volume flow measurement for compartment boundary mounted SCDs.....	14
4.10.1 Compartmentation test.....	14
4.10.2 Maintenance of opening test.....	14
4.11 Ambient leakage measurement equipment.....	15
4.12 Pressure sensors for differential pressure control.....	15
4.12.1 Duct mounted smoke control dampers .....	15
4.12.2 Compartment boundary mounted smoke control dampers .....	15
4.13 Welded connecting tube.....	15
4.14 Extract fan connecting duct.....	15
4.15 Extraction fan .....	15
4.16 Thermocouples.....	15
4.17 Oxygen measuring equipment .....	15
4.18 Observation windows.....	16
5 Test specimens .....	16
5.1 Cross-section .....	16
5.2 Design.....	16
5.2.1 General.....	16
5.2.2 Supporting constructions .....	16
5.2.3 Inclusion of grilles .....	17
6 Test methods .....	17
6.1 General.....	17
6.2 Test sequence.....	17
6.3 Ambient leakage.....	19
6.3.1 Units of the largest size.....	19
6.3.2 Units of smallest size .....	19
6.4 Cycling requirements .....	19
6.4.1 General.....	19

6.4.2	Smoke control damper to be used in dedicated smoke control systems, operated only in the case of emergency .....	19
6.4.3	Smoke control damper to be used as part of a general HVAC system as well as a smoke control system, or as part of a smoke control systems that is cycled every day to check operation .....	19
6.4.4	Smoke control damper to be used as part of a general HVAC system as well as a smoke control system, that uses a modulating actuator .....	20
6.5	Selection of elevated temperature and fire resistance tests .....	20
6.6	Fire resistance tests and elevated temperature tests .....	21
6.6.1	Duct mounted smoke control dampers .....	21
6.6.2	Compartment boundary mounted smoke control dampers .....	22
6.6.3	Additional test information .....	25
6.7	Initiation regime .....	26
6.7.1	Smoke control dampers for systems with automatic activation (AA) .....	26
6.7.2	Smoke control damper for systems with manual activation (MA) .....	27
6.8	HOT400/30 extension test .....	29
6.9	Special constructions .....	29
7	Test procedure .....	29
7.1	Fire resistance or elevated temperature and maintenance of opening test for duct mounted smoke control dampers .....	29
7.1.1	General .....	29
7.1.2	Pre-test calibration .....	29
7.1.3	Ignition of furnace .....	31
7.1.4	Operate the damper .....	31
7.1.5	Furnace conditions .....	31
7.1.6	Thermocouples for insulation (I) .....	31
7.1.7	Oxygen measurements .....	32
7.1.8	General observations .....	32
7.1.9	Reduction of cross-section/maintenance of opening .....	32
7.1.10	Leakage calculations .....	32
7.1.11	Termination of test .....	32
7.2	Fire resistance tests for smoke control dampers mounted in a compartment boundary .....	33
7.2.1	General .....	33
7.2.2	Pre-test calibration .....	33
7.2.3	Ignition of furnace .....	33
7.2.4	Operate the damper .....	33
7.2.5	Furnace conditions .....	33
7.2.6	Thermocouples for insulation (I) .....	33
7.2.7	General observations .....	34
7.2.8	Leakage calculations .....	34
7.2.9	Termination of test .....	34
7.3	Maintenance of opening test for compartment boundary mounted smoke control dampers .....	34
7.3.1	General .....	34
7.3.2	Pre-test calibration .....	34
7.3.3	Ignition of furnace .....	35
7.3.4	Operate a damper .....	35
7.3.5	Furnace conditions .....	35
7.3.6	Thermocouples for insulation (I) .....	36
7.3.7	General observations .....	36
7.3.8	Reduction of cross-section/maintenance of opening .....	36
7.3.9	Termination of test .....	36

## EN 1366-10:2022+A1:2024 (E)

8	Performance criteria .....	37
8.1	Integrity.....	37
8.1.1	General.....	37
8.1.2	Integrity at perimeter .....	37
8.2	Insulation.....	40
8.2.1	General.....	40
8.2.2	Thermocouples at the compartment boundary outside of the furnace.....	40
8.3	Reduced leakage .....	40
8.4	Times and observations .....	41
8.5	Other.....	41
9	Test report.....	41
9.1	General.....	41
9.2	Duct mounted single and multi-compartment tests .....	42
9.3	Compartment boundary compartmentation test.....	43
9.4	Compartment boundary maintenance of opening test .....	43
10	Direct field of application of test results (DIAP) .....	44
10.1	Compartment boundary mounted smoke control dampers .....	44
10.2	Smoke control damper sizes.....	44
10.3	Duct mounted smoke control damper mounting positions .....	44
10.4	Distance between mounting positions in compartment boundary applications .....	44
10.5	Blade pivot axis.....	44
10.6	Pressure difference.....	45
10.7	Elevated temperatures .....	45
10.8	Cycling tests .....	45
10.8.1	Smoke control dampers meeting the cycling requirements for modulating applications.....	45
10.8.2	Smoke control dampers meeting the cycling requirements for use with combined smoke control and general HVAC applications and for smoke control systems that are cycle checked every day .....	45
10.8.3	Smoke control dampers meeting the cycling requirements for smoke control dampers that are operated only in the case of emergency.....	45
10.8.4	Load application.....	45
10.9	Initiation method.....	45
10.10	Duct mounted smoke control dampers – application to ducts other than that tested .....	46
10.10.1	Single compartment smoke control dampers.....	46
10.10.2	Multi compartment smoke control dampers .....	46
10.11	Compartment mounted smoke control dampers – application to <sup>A1</sup> deleted text <sub>A1</sub> constructions other than that tested .....	47
10.11.1	Single compartment smoke control dampers.....	47
10.11.2	Multi compartment smoke control dampers .....	47
10.12	Standard damper open or closed position.....	47
Annex A (normative)	Cycling test.....	73
A.1	General.....	73
A.2	Purpose of the test.....	73
A.3	Method of Application for loading .....	73
A.4	Background for the torque value (informative).....	79
Annex B (informative)	Leakage calculation from oxygen measurement .....	81
B.1	General.....	81

<b>B.2</b>	<b>Supporting information on leakage flowrate calculations.....</b>	<b>82</b>
<b>Annex C (normative)</b>	<b>Maintenance of opening calculation.....</b>	<b>87</b>
<b>C.1</b>	<b>Calculation of the theoretical total mass <math>M_{\max}</math> of hot gases during the fire test .....</b>	<b>87</b>
<b>C.2</b>	<b>Calculation of the actual total mass <math>M_{\text{actual}}</math> of hot gases during the fire test.....</b>	<b>89</b>
<b>Annex D (normative)</b>	<b>Optional High Operating Test HOT 400/30 classification .....</b>	<b>93</b>
<b>D.1</b>	<b>General .....</b>	<b>93</b>
<b>D.2</b>	<b>Tests .....</b>	<b>93</b>
<b>Annex E (informative)</b>	<b>Leakage and pressure classification clarification .....</b>	<b>98</b>
<b>Bibliography</b>	<b>.....</b>	<b>99</b>

**iTeh Standards**  
**(<https://standards.iteh.ai>)**  
**Document Preview**

[SIST EN 1366-10:2022+A1:2024](https://standards.iteh.ai/catalog/standards/sist/831a38fa-1b37-4170-bc5f-4de707118a24/sist-en-1366-10-2022a1-2024)

<https://standards.iteh.ai/catalog/standards/sist/831a38fa-1b37-4170-bc5f-4de707118a24/sist-en-1366-10-2022a1-2024>

**EN 1366-10:2022+A1:2024 (E)****European foreword**

This document (EN 1366-10:2022+A1:2024) has been prepared by Technical Committee CEN/TC 127 “Fire safety in buildings”, the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by March 2025, and conflicting national standards shall be withdrawn at the latest by March 2025.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes A1 EN 1366-10:2022 A1.

This document includes Amendment 1 approved by CEN on 14 July 2024.

The start and finish of text introduced or altered by amendment is indicated in the text by tags A1 A1.

This document has been prepared under a standardization request addressed to CEN by the European Commission. The Standing Committee of the EFTA States subsequently approves these requests for its Member States.

EN 1366, Fire resistance tests for service installations consists of the following:

- Part 1: Ventilation ducts
- Part 2: Fire dampers
- Part 3: Penetration seals
- Part 4: Linear joint seals
- Part 5: Service ducts and shafts
- Part 6: Raised access and hollow core floors
- Part 7: Conveyor systems and their closures
- Part 8: Smoke extraction ducts
- Part 9: Single compartment smoke extraction ducts
- Part 10: Smoke control dampers
- Part 11: Fire protective systems for cable systems and associated components
- Part 12: Non-mechanical fire barrier for ventilation ductwork
- Part 13: Chimneys

A1 This standard underwent a formal review process during 2016-2021. Various comments were considered, and these were only considered when they added clarity to the test procedure. No changes have been made that make historical data redundant. This was deliberately avoided where it was thought to be occurring.



The wording and figures have been clarified to show some more detail.

Changes include the fact that symmetry as a concept has been removed. This does not negate original tests but may now mean that some additional tests are needed. [A1](#)

Any feedback and questions on this document should be directed to the users' national standards body. A complete listing of these bodies can be found on the CEN website.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.

**iTeh Standards**  
**(<https://standards.iteh.ai>)**  
**Document Preview**

[SIST EN 1366-10:2022+A1:2024](https://standards.iteh.ai/catalog/standards/sist/831a38fa-1b37-4170-bc5f-4de707118a24/sist-en-1366-10-2022a1-2024)

<https://standards.iteh.ai/catalog/standards/sist/831a38fa-1b37-4170-bc5f-4de707118a24/sist-en-1366-10-2022a1-2024>

## EN 1366-10:2022+A1:2024 (E)

### Introduction

When smoke and heat exhaust ventilation is being considered, it becomes apparent that a clear path between the area where heat and smoke is being generated (source of the fire) and the outside of the building is needed.

To create this path ducts and an uninterrupted smoke extract path are needed. This means that smoke control dampers at the fire and along the path are open and will remain open. Smoke control dampers at branches, or on the surface of the duct, along the path are closed and will remain closed. In fact, if the duct crosses a compartment boundary it becomes part of the fire compartment in which the fire started.

The purpose of this document is to define test methods to evaluate the abilities of smoke control dampers to:

- a) be applicable to single compartment and/or multi compartment fire resisting applications;
- b) be applicable to automatic systems or systems with manual activation;
- c) change state from closed to open at elevated temperatures, (and vice versa);
- d) once opened maintain a defined cross-sectional area at elevated temperature or under fire conditions following the standard time/temperature curve; and
- e) maintain a satisfactory leakage performance when subjected to negative pressure at elevated temperatures or under fire conditions following the standard time/temperature curve.

The units are mounted for the tests in a manner representative of practice.

Temperature and integrity measurements are carried out on various parts of the test construction during the test. The required leakage measurements are measured by direct flow measurement at the prescribed pressure differentials. Ambient leakage of the units is also recorded.

The satisfactory passing of some, or all, of these tests will allow products to be assessed in accordance with EN 12101-8 and be classified to EN 13501-4. The required temperatures, pressure differentials etc. are stated in EN 12101-8. EN 13501-4 requires a classification report.

#### CAUTION:

The attention of all persons concerned with managing and carrying out this furnace testing is drawn to the fact that fire testing can be hazardous and that there is a possibility that toxic and/or harmful smoke and gases can be evolved during the test. Mechanical and operational hazards can also arise during the construction of the test elements or structures, their testing and disposal of test residues.

An assessment of all potential hazards and risks to health should be made and safety precautions should be identified and provided. Written safety instructions should be issued. Appropriate training should be given to relevant personnel. Laboratory personnel should ensure that they follow written safety instructions at all times.

## 1 Scope

This document specifies test methods for smoke control dampers to assess their performance under elevated temperature or fire conditions, as well as at ambient temperatures.

Smoke control damper tests are used to confirm that the furnace testing requirements of EN 12101-8 are met and EN 12101-8 is for consideration before carrying out these tests.

Smoke control dampers tested to this document are expected to be classified using EN 13501-4 and this document is expected to be considered before carrying out these tests.

**NOTE** Some smoke control dampers to be tested might require testing following the information given in EN 1366-2 and this needs consideration before carrying out testing.

This document is expected to be read in conjunction with EN 12101-8, EN 13501-4, EN 1366-2 and EN 1363-1, the latter giving further details for fire resistance testing.

For installation details, the requirements for smoke extraction ducts are for consideration and these are defined in EN 1366-8 and EN 1366-9.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1363-1, *Fire resistance tests — Part 1: General requirements*

EN 1366-2, *Fire resistance tests for service installations — Part 2: Fire dampers*

EN 1366-8, *Fire resistance tests for service installations — Part 8: Smoke extraction ducts*

EN 1366-9, *Fire resistance tests for service installations — Part 9: Single compartment smoke extraction ducts*

EN 1751, *Ventilation for buildings — Air terminal devices — Aerodynamic testing of damper and valves*

EN 10095, *Heat resisting steels and nickel alloys*

EN 13501-4, *Fire classification of construction products and building elements — Part 4: Classification using data from fire resistance tests on components of smoke control systems*

EN ISO 5167-1, *Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full — Part 1: General principles and requirements (ISO 5167-1)*

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

**EN 1366-10:2022+A1:2024 (E)****3.1****elevated temperature**

temperature in excess of normal ambient air, below those necessary for fire resistance testing (i.e. the standard fire curve in accordance with EN 1363-1), to which smoke and heat exhaust ducts for single compartments are tested

**3.2****HOT 400/30**

additional test and classification for a smoke control damper that requires proof of opening and closing operations for 30 minutes at 400 °C

**3.3****HVAC**

heating, ventilating and air conditioning

Note 1 to entry: Usually used with the addition of the word “system”.

**3.4****interface control unit**

device which controls the operation of the actuator located at the smoke control damper or within the same fire zone as the smoke control damper and usually associated with a smoke control/fire alarm system

**3.5****largest size**

greatest size of smoke control damper individual unit including the maximum width and height (as opposed to an assembly/battery of units) proposed for sale/manufacture

**3.6****modulating actuator**

smoke control damper control mechanism which can control the smoke control damper to be in a position or number of positions between fully open and fully closed in normal day to day operation (not fire conditions)

**3.7****penetration seal****fire stopping method**

product(s) used between the smoke control system duct/damper and the fire compartment structure to maintain the fire resistance, and tested in accordance with EN 1366-8 (ducts) or EN 1366-10 (dampers)

**3.8****safety position**

position (open or closed) into which specific projects could require certain dampers to move to, or remain in, depending upon the fire location within the building

Note 1 to entry: Specific projects can require certain smoke control dampers to move to an open or closed position, depending upon the fire location within the building.

**3.9****smallest size**

least size of smoke control damper individual unit including the minimum width and height proposed for sale/manufacture

**3.10****multi-compartment smoke control damper  
multi-compartment SCD**

device which can be open or closed to control the flow of smoke and hot gases into, from or within a duct for use in multi-compartment applications which is required to maintain compartmentation when closed

**3.11****single compartment smoke control damper  
single compartment SCD**

device which can be open or closed to control the flow of smoke and hot gases into, from or within a duct for use in single compartment applications at elevated temperatures (600 °C)

**3.12****builders work**

any construction formed from concrete, blockwork, light wall or other materials as part of general construction, such as used to construct shafts, walls and floors

**3.13****duct mounted smoke control damper  
duct mounted SCD**

<sup>A1</sup> smoke control damper mounted on the surface of, or in line (perpendicular to the duct axis) with a smoke control duct <sup>A1</sup>

**3.14****compartment mounted smoke control damper  
compartment mounted SCD**

smoke control damper mounted at a compartment boundary formed from builders' work <sup>A1</sup> *deleted text* <sup>A1</sup>

**3.15****smoke control damper for systems with automatic activation**

smoke control damper that is applicable to the smoke control systems that operate automatically on receipt of a smoke or fire alarm without any manual action/intervention and allow no firefighter overrides

Note 1 to entry: A smoke control system with an attended control room can also be accepted as an automatic system, provided that once initiated, the system does not cause the smoke control damper position to be changed.

**3.16****smoke control damper for systems with manual activation**


smoke control damper that is applicable to the smoke control systems (smoke and heat exhaust ventilation type or pressurization type), that will be put into operation, on detection smoke or fire, by human intervention (e.g. by pressing a button or pulling a handle) leading to a sequence of automatic actions in the operation of the smoke control system or a system that allows firefighter overrides

**3.17****thermal operating device**

temperature sensitive device such as a fusible element which responds to temperature to initiate a subsequent action such as causes the damper to change position

Note 1 to entry: Further information is given in Figure 1.

## EN 1366-10:2022+A1:2024 (E)

**Key**

- |    |  |
|----|--|
| 1  | fire compartments  |
| 2  | smoke reservoirs   |
| 4  | air inlets   |
| 5  | smoke barriers   |
| 6  | powered smoke and heat exhaust ventilator (fan)  |
| 7  | smoke control dampers for single compartments (EN 12101-8 and EN 1366-10)  |
| 8  | smoke control ducts for single compartments (EN 12101-7 and EN 1366-9)   |
| 9  | smoke control ducts for multi compartments (EN 12101-7 and EN 1366-8)  |
| 10 | smoke control dampers for multi compartments (EN 12101-8 and EN 1366-10) mounted inside or outside of wall or floor (compartmentation tests) |
| 11 | smoke control dampers for multi compartments (EN 12101-8 and EN 1366-10) mounted on the surface of the duct (surface of duct tests)          |
| 12 | electrical equipment   |

**Figure 1 — Example of powered smoke and heat exhaust ventilation system in cross-section**

## 4 Test equipment

### 4.1 General

In addition to the test equipment specified in EN 1363-1, the equipment in the following clauses is required (examples of test arrangements are given in Figure 4, Figure 5, Figure 8 and Figure 9).

### 4.2 Test duct for surface mounted SCDs

See 5.2.2.2 and 5.2.2.3.