

ISO/FDIS ~~4685:2023~~(E)

ISO/~~TC-147/SC-3~~/AWG-14

Secretariat: AFNOR

Date: 2023-08-14

Water quality — Radium-~~226~~ — Test method using ICP-MS

~~First edition~~

~~2023-06-06~~

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/FDIS 4685

<https://standards.iteh.ai/catalog/standards/sist/44fb9424-b606-4fcd-9e5d-292611c1d18d/iso-fdis-4685>

FDIS stage

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/FDIS 4685

<https://standards.iteh.ai/catalog/standards/sist/44fb9424-b606-4fcd-9e5d-292611c1d18d/iso-fdis-4685>

© ISO ~~2022~~2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
~~Email~~E-mail: copyright@iso.org
Website: ~~www.iso.org~~www.iso.org

Published in Switzerland

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 4685

<https://standards.iteh.ai/catalog/standards/sist/44fb9424-b606-4fed-9e5d-292611c1d18d/iso-fdis-4685>

~~Edited DIS -
MUST BE USED
FOR FINAL
DRAFT~~

Contents

Foreword	vii
Introduction	viii
1 Scope	1
2 Normative references	1
3 Term, definitions and symbols	2
3.1 Terms and definitions	2
3.2 Symbols	2
4 Principle	3
5 Sampling and sample storage	4
6 Chemical reagents and equipment	5
6.1 General	5
6.2 Chemical reagents	5
6.3 Equipment	5
7 Separation	6
8 Quality control	6
8.1 General	6
8.2 Variables that can influence the measurement	6
8.3 Instrument verification	6
8.4 Method verification	7
9 Expression of results	7
9.1 Data analysis	7
9.2 Background	7
9.3 Internal standard	8
9.4 Internal calibration	8
9.5 Detection limit	8
9.6 Limit of quantification	9
9.7 Conversion of mass concentration to activity concentration	9
9.8 Conversion from mass to volume units	9
10 Test report	9
Annex A (informative) Chemical separation of ²²⁶ Ra using a cation exchange and a crown ether based extraction chromatography resin ^{[20],[21],[22],[23]}	11
A.1 Principle	11
A.2 Technical resources	11
A.2.1 Reagents	11
A.2.2 Equipment	12
A.3 Procedure	12

A.3.1	Preconcentration of the sample	12
A.3.2	Tracer addition.....	12
A.3.3	Concentration step	12
A.3.4	Separation and purification	13
A.3.5	Sample preparation for ICP-MS measurement	13
	Bibliography	14
	Foreword	v
	Introduction.....	vi
1	Scope	1
2	Normative references	1
3	Term, definitions, symbols and abbreviated terms.....	2
4	Principle.....	3
5	Sampling and sample storage.....	5
5.1	Sampling.....	5
6	Chemical reagents and apparatus.....	5
6.1	General.....	5
6.2	Chemical reagents	5
6.3	Apparatus.....	6
7	Separation.....	6
7.1	Separation.....	6
8	Quality Control.....	6
8.1	General.....	6
8.2	Variables that can influence the measurement.....	7
8.3	Instrument verification	7
8.4	Method verification.....	8
9	Expression of results.....	8
9.1	Data analysis.....	8
9.2	Background	8
9.3	Internal standard.....	8
9.4	Internal calibration	9
9.5	Detection limit.....	9
9.6	Limit of quantification	9
9.7	Conversion of mass concentration to activity concentration.....	10
9.8	Conversion from mass to volume units	10
10	Test report.....	10

~~Annex A (informative) Chemical separation of radium 226 by method (cation exchange and crown ether based extraction chromatography resin) ^{[20], [21], [22], [23]}.....12~~
~~Bibliography15~~

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/FDIS 4685

<https://standards.iteh.ai/catalog/standards/sist/44fb9424-b606-4fcd-9e5d-292611c1d18d/iso-fdis-4685>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part-1. In particular, the different approval criteria needed for the different types of ISO ~~documents~~document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part—2 (see www.iso.org/directives).

~~Attention is drawn~~ISO draws attention to the possibility that ~~some of the~~elementsimplementation of this document may ~~be involve~~the subjectuse of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights- in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights. ~~Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).~~

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation ~~of~~ the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade ~~organization~~Organization (WTO) principles in the Technical Barriers to Trade (TBT), see ~~the~~ following URL: www.iso.org/iso/foreword.html.

This document was prepared by ISO/TC 147, *Water quality*, Subcommittee SC 3, *Radioactivity measurements*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

~~Edited DIS -
MUST BE USED
FOR FINAL
DRAFT~~

Introduction

Radionuclides are present throughout the environment; thus, water bodies (e.g. surface waters, ground waters, sea waters) contain radionuclides, which can be of either natural or anthropogenic origin:

- ~~naturally~~**Naturally**-occurring radionuclides, including ^3H , ^{14}C , ^{40}K and those originating from the thorium and uranium decay series, in particular ^{210}Pb , ^{210}Po , ^{222}Rn , ^{226}Ra , ^{228}Ra , ^{227}Ac , ^{232}Th , ^{231}Pa , ^{234}U , and ^{238}U , can be found in water bodies due to either natural processes (e.g. desorption from the soil and runoff by rain water) or released from technological processes involving naturally occurring radioactive materials (e.g. mining, mineral processing, oil, gas, and coal production, water treatment and the production and use of phosphate fertilisers);
- ~~anthropogenic~~**Anthropogenic** radionuclides such as ^{55}Fe , ^{59}Ni , ^{63}Ni , ^{90}Sr , ^{99}Tc , transuranic elements (e.g. Np, Pu, Am, and Cm), and some gamma emitting radionuclides such as ^{60}Co and ^{137}Cs can also be found in natural waters. Small quantities of anthropogenic radionuclides can be discharged from nuclear facilities to the environment as a result of authorized routine releases. The radionuclides present in liquid effluents are usually controlled before being discharged to the environment and water bodies. Anthropogenic radionuclides used for medical and industrial applications can be released to the environment after use. Anthropogenic radionuclides are also found in waters due to contamination from fallout resulting from above-ground nuclear detonations and accidents such as those that have occurred at the Chernobyl and Fukushima nuclear facilities.

Radionuclide activity concentrations in water bodies can vary according to local geological characteristics and climatic conditions and can be locally and temporally enhanced by releases from nuclear facilities during planned, existing, and emergency exposure situations. Some drinking water sources can thus contain radionuclides at activity concentrations that ~~could~~**can** present a human health risk. The World Health Organization (WHO) recommends to routinely monitor radioactivity in drinking waters and to take proper actions when needed to minimize the health risk.

National regulations usually specify the activity concentration limits that are authorized in drinking waters, water bodies, and liquid effluents to be discharged to the environment. These limits can vary for planned, existing, and emergency exposure situations. As an example, during either a planned or existing situation, the WHO guidance level for ^{226}Ra in drinking water is $1\text{ Bq}\cdot\text{l}^{-1}$ see NOTES 1 and 2. Compliance with these limits is assessed by measuring radioactivity in water samples and by comparing the results obtained, with their associated uncertainties, as specified by ISO/IEC Guide 98-3 and ISO 5667-20 and

NOTE 1 If the value is not specified in Annex-6 of Reference, the value has been calculated using the formula provided in Reference and the dose coefficient data from References and .

NOTE 2 The guidance level calculated in Reference is the activity concentration that results in an effective dose of $0,1\text{ mSv}\cdot\text{a}^{-1}$ to members of the public for an intake of $2\text{ l}\cdot\text{d}^{-1}$ of drinking water for one year. This is an effective dose that represents a very low level of risk to human health and which is not expected to give rise to any detectable adverse health effects.

This document contains method(s) to support laboratories, which need to determine ^{226}Ra in water samples. The method(s) described in this document can be used for various types of waters (see Clause 1). Minor modifications such as sample volume and counting time can be made if needed to ensure that the decision threshold, detection limit, and uncertainties are below the required limits. This can be done for several reasons such as emergency situations, lower national guidance limits, and operational requirements.

Water quality — Radium-226 — Test method using ICP-MS

WARNING — Persons using this document should be familiar with normal laboratory practice. This document does not purport to address all of the safety problems, if any, associated with its use. It is the responsibility of the user to establish appropriate safety and health practices

IMPORTANT — It is essential that tests conducted according to this document be carried out by suitably trained staff.

1 Scope

This document specifies methods used to determine ^{226}Ra concentration by inductively coupled plasma mass spectrometry (ICP-MS). The mass concentrations obtained can be converted into an activity concentration.

The method is applicable to test samples of drinking water, rainwater, surface and ground water, after proper sampling and handling, and test sample preparation.

The detection limit depends on the sample volume, the instrument used, the background count rate, the detection efficiency, the counting time, and the chemical yield. The detection limit of the method described in this document, using currently available equipment, is approximately $10 \text{ mBq}\cdot\text{l}^{-1}$, which is better than the WHO criteria for safe consumption of drinking water ($1 \text{ Bq}\cdot\text{l}^{-1}$).^{[4], [4]}

This method covers the measurement of ^{226}Ra in water at activity concentrations between $0,001 \text{ Bq}\cdot\text{l}^{-1}$ and $100 \text{ Bq}\cdot\text{l}^{-1}$. Samples with concentrations higher than $1 \text{ Bq}\cdot\text{l}^{-1}$ can be measured if a dilution is performed.^{[9], [9]}

The method described in this document is applicable in the event of an emergency situation.

In this method, filtration of the test sample is necessary. The analysis of ^{226}Ra adsorbed to suspended matter is not covered by this method. The analysis of the insoluble fraction requires a mineralization step that is not covered by this document. In this case, the measurement is made on the different phases obtained.

It is the user's responsibility to ensure the validity of this test method for the water samples tested.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3696, *Water for analytical laboratory use — Specification and test methods*

ISO/IEC Guide 98-3, *Uncertainty of measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

ISO/IEC Guide 99:2007, *International vocabulary of metrology — Basic and general concepts and associated terms (VIM)*

ISO 5667-1, *Water quality — Sampling — Part 1: Guidance on the design of sampling programmes and sampling techniques*

ISO 5667-3, *Water quality — Sampling — Part 3: Preservation and handling of water samples*

ISO 5667-10, *Water quality — Sampling — Part 10: Guidance on sampling of waste water*

ISO 17294-1:2004, *Water quality — Application of inductively coupled plasma mass spectrometry (ICP-MS) — Part 1: General guidelines*

ISO 17294-2:2016, *Water quality — Application of inductively coupled plasma mass spectrometry (ICP-MS) — Part 2: Determination of selected elements including uranium isotopes*

ISO 80000-10, *Quantities and units — Part 10: Atomic and nuclear physics*

ISO/IEC 17025, *General requirements for the competence of testing and calibration laboratories*

3 Term, definitions and symbols

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC Guide 98-3:2008, ISO/IEC Guide 99:2007 and ISO 80000-10 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.2 Symbols

Table 1 — Symbols

Symbol	Description	Unit
c_s	Specific activity corresponding to one gram of the radionuclide	Bq·g ⁻¹
L_D	Detection limit in mass concentration, the lowest mass concentration that can be considered statistically different from a blank sample	Bq·kg ⁻¹
L_Q	Limit of quantification, the lowest mass concentration that can be quantified with statistical uncertainty	g·kg ⁻¹
f	Correction factor	-
m	Mass of sample	kg
m/z	Mass to charge ratio measured by ICP-MS	—
m_c	Mass of the calibration standard tracer added to sample	g
m_{cs}	Mass of calibration standard added to standard	g
m_{IS}	Mass of the internal standard added to blank and sample	g
m_{ISS}	Mass of the internal standard solution added to a blank or a sample	g
N_0	Counts per second measured when performing ICP-MS measurement of a blank sample at a given mass-to-charge ratio	Counts·s ⁻¹
\bar{N}_0	Average number of counts per second for several blank samples measured by ICP-MS at a given mass-to-charge ratio	Counts·s ⁻¹

Symbol	Description	Unit
U	Expanded uncertainty and the coverage factor k with $k = 1, 2, \dots$, $U = k \cdot u$	—
u	Uncertainty such as counts per second, mass added etc.	—
$u(c)$	Standard uncertainty of the activity concentration result	Bq·kg ⁻¹
$u(\rho)$	Standard uncertainty associated with the measurement result	—
$u(\rho_V)$	Standard uncertainty associated with mass concentration of the calibration standard solution	g·g ⁻¹
ρ	Analyte mass for a given radionuclide per sample unit volume	g·g ⁻¹
ρ_c	Mass concentration of the calibration standard solution	g·g ⁻¹
ρ_{IS}	Mass of internal standard element or isotope per unit volume of the internal standard solution.	g·l ⁻¹
ρ_V	Volume concentration of the calibration standard solution	g·l ⁻¹
V	Volume	L
z	Electric charge of an ion	-

4 Principle

The principles of analysis using ICP-MS are described in ISO 17294-1 and ISO 17294-2.

²²⁶Ra is natural in origin, occurring in the ²³⁸U decay chain.

ICP-MS has been successfully used to measure the concentration of ²²⁶Ra in water samples^{[9], [10], [9], [10]}

The results can be converted to activity concentrations using specific activity as a conversion factor given in [Table 2](#).

Table 2 — ²²⁶Ra half-life and specific activity^{[9], [10]}

Isotope	Half-life years	Specific activity Bq·g ⁻¹
Radium-226	1,600·(7)·10 ³	3,658·(16)·10 ¹⁰

An example of the limit of detection that can be obtained with ICP-MS is given in [Table 3](#), with a typical measurement time of several minutes per sample, including sample uptake, analysis time and washout before the next sample.

Table 3 — Examples of detection limit^{[9], [10], [9], [10]}

Isotope	Limit of detection µg·l ⁻¹	Limit of detection Bq·l ⁻¹
Radium-226	2,70·10 ⁻⁷	0,01

Measurement by ICP-MS is affected by several interferences, which are shown in [Table 4](#).

Table 4 — ²²⁶Ra interferences affecting ICP-MS measurement

Interference name	Description	²²⁶ Ra interference
Isobaric	An isotope with a similar mass to the analyte	None