INTERNATIONAL STANDARD

ISO/IEC 9594-3

Ninth edition

Information technology — Open systems interconnection —

Part 3:

The Directory: Abstract service

*tos: ||standards.iten.ailco

PROOF/ÉPREUVE



Reference number ISO/IEC 9594-3:2020(E)

I ch SI A DARD Replands to the standard of the



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Website: www.iso.org Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see https://patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by ITU-T as ITU-T X.511 (10/2019) and drafted in accordance with its editorial rules. It was adopted by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*.

A list of all parts in the ISO/IEC 9594 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

CONTENTS

| Norn | ative references |
|--------------|--|
| 2.1 | Identical Recommendations International Standards |
| 2.2 | Paired Recommendations International Standards equivalent in technical content |
| 2.3 | Additional references |
| Defir | itions |
| 3.1 | OSI Reference Model security architecture definitions |
| 3.2 | Basic Directory definitions |
| 3.3 | Directory model definitions |
| 3.4 | Directory information base definitions |
| 3.5 | Directory entry definitions |
| 3.6 | Name definitions |
| 3.7 | Distributed operations definitions |
| 3.8 | Abstract service definitions |
| Abbr | eviations |
| | entions |
| | |
| | view of the Directory service |
| Infor | nation types and common procedures |
| | Introduction |
| 7.2 | Information types defined elsewhere |
| 7.3 | Common arguments |
| 7.4 | Information types defined elsewhere Common arguments Common results Service controls Entry information selection Entry information Filter Paged results Security parameters Common elements of procedure for access control |
| 7.5 | Service controls |
| 7.6 | Entry information selection |
| 7.7 | Entry information |
| 7.8 | Filter |
| 7.9 | Paged results |
| 7.10 | Security parameters |
| 7.11 | Common elements of procedure for access control |
| 7.12 | Managing the DSA Information Tree |
| 7.13 | Procedures for families of entries. |
| | tory authentication |
| 3.1 | Simple authentication procedure |
| 3.2 | Password policy |
| Bind. | Unbind operations, Change Password and Administer Password operations |
| 9.1 | Directory Bind |
| 9.2 | Directory Unbind |
| Direc | tory Read operations |
| 10.1 | Read |
| 10.2 | Compare |
| 10.3 | Abandon |
| Direc | tory Search operations |
| 11.1 | List |
| 11.2 | Search |
| Direc | tory Modify operations |
| 12.1 | Add Entry |
| 12.2 | Remove Entry |
| | |
| 12.3 | VIOGITY ENTRY |
| 12.3 12.4 | Modify Entry Modify DN |

ISO/IEC 9594-3:2020 (E)

| 10 | | |
|----------|--|---|
| 13 | Operations for LDAP messages | |
| | 13.1 LDAP Transport operation | |
| | • | |
| 14 | Errors | |
| | 14.1 Error precedence | |
| | 14.2 Abandoned | |
| | 14.3 Abandon Failed | |
| | 14.4 Attribute Error | |
| | 14.5 Name Error | |
| | 14.6 Referral | |
| | 14.7 Security Error | |
| | 14.8 Service Error | |
| | 14.9 Update Error | |
| 15 | Analysis of search arguments | |
| | 15.1 General check of search filter | |
| | 15.2 Check of request-attribute-profiles | |
| | 15.3 Check of controls and hierarchy selections | |
| | 15.4 Check of matching use | |
| Annex | x A – Abstract Service in ASN.1 | |
| Annex | x B – Operational semantics for Basic Access Control | |
| | | |
| IIIICA | C 1 Single family example | |
| | C.2 Multiple families example | , |
| A | D. E. daniel A. C. M. L. and L. L. and L. L. and L. | |
| Annex | (D – External ASN.1 module | |
| Annex | α E – Use of protected passwords for Bind operations | |
| Annex | F – Amendments and corrigenda | |
| | C.1 Single family example | |
| | . Sps. ilstandare Joseph | |
| | III. | |
| | | |

Introduction

This Recommendation | International Standard, together with the other Recommendations | International Standards, has been produced to facilitate the interconnection of information processing systems to provide directory services. A set of such systems, together with the directory information that they hold, can be viewed as an integrated whole, called the *Directory*. The information held by the Directory, collectively known as the Directory Information Base (DIB), is typically used to facilitate communication between, with or about objects such as application entities, people, terminals, and distribution lists.

The Directory plays a significant role in Open Systems Interconnection, whose aim is to allow, with a minimum of technical agreement outside of the interconnection standards themselves, the interconnection of information processing systems:

- from different manufacturers;
- under different managements;
- of different levels of complexity; and
- of different ages.

This Recommendation | International Standard defines the capabilities provided by the Directory to its users.

This Recommendation | International Standard provides the foundation frameworks upon which industry profiles can be defined by other standards groups and industry forums. Many of the features defined as optional in these frameworks may be mandated for use in certain environments through profiles. This ninth edition technically revises and enhances the eighth edition of this Recommendation | International Standard.

This ninth edition specifies versions 1 and 2 of the Directory protocols.

Rec. ITU-T X.511 (1993) | ISO/IEC 9594-3 (1995), Rec. ITU-T X.518 (1993) | ISO/IEC 9594-4 (1995) and Rec. ITU-T X.519 (1993) | ISO/IEC 9594-5 (1995) and their previous edition specified only version 1. Most of the services and protocols specified in this edition are designed to function under version 1. However, some enhanced services and protocols, e.g., signed errors, will not function unless all Directory entities involved in the operation have negotiated version 2. Whichever version has been negotiated, differences between the services and between the protocols defined in the nine editions, except for those specifically assigned to version 2; are accommodated using the rules of extensibility defined in Rec. ITU-T X.519 | ISO/IEC 9594-5.

Annex A, which is an integral part of this Recommendation International Standard, provides the ASN.1 module for the Directory abstract service.

Annex B, which is not an integral part of this Recommendation | International Standard, provides charts that describe the semantics associated with Basic Access Control as it applies to the processing of a Directory operation.

Annex C, which is not an integral part of this Recommendation | International Standard, gives examples of the use of families of entries.

Annex D, which is not an integral part of this Recommendation | International Standard, includes an updated copy of an external ASN.1 module referenced by this Directory Specification.

Annex E, which is not an integral part of this Recommendation | International Standard, provides a suggested technique for Bind protected password.

Annex F, which is not an integral part of this Recommendation | International Standard, lists the amendments and defect reports that have been incorporated to form this edition of this Recommendation | International Standard.

INTERNATIONAL STANDARD ITU-T RECOMMENDATION

Information technology – Open Systems Interconnection – The Directory: Abstract service definition

1 Scope

This Recommendation | International Standard defines in an abstract way the externally visible service provided by the Directory.

This Recommendation | International Standard does not specify individual implementations or products.

2 Normative references

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

2.1 Identical Recommendations | International Standards

- Recommendation ITU-T X.500 (2019) | ISO/IEC 9594-1:2020, Information technology Open Systems Interconnection – The Directory: Overview of concepts, models and services.
- Recommendation ITU-T X.501 (2019) | ISO/IEC 9594-2:2020, Information technology Open Systems Interconnection – The Directory: Models.
- Recommendation ITU-T X.509 (2019) | ISO/IEC 9594-8:2020, Information technology Open Systems Interconnection – The Directory: Public-key and attribute certificate frameworks.
- Recommendation ITU-T X.518 (2019) | ISO/IEC 9594-4:2020, Information technology Open Systems Interconnection – The Directory: Procedures for distributed operation.
- Recommendation ITU-T X.519 (2019) ISO/IEC 9594-5:2020, Information technology Open Systems Interconnection – The Directory Protocol specifications.
- Recommendation ITU-T X.520 (2019) | ISO/IEC 9594-6:2020, Information technology Open Systems Interconnection – The Directory: Selected attribute types.
- Recommendation ITU-T X.521 (2019) | ISO/IEC 9594-7:2020, Information technology Open Systems Interconnection – The Directory: Selected object classes.
- Recommendation ITU-T X.525 (2019) | ISO/IEC 9594-9:2020, Information technology Open Systems Interconnection – The Directory: Replication.
- Recommendation ITU-T X.680 (2015) | ISO/IEC 8824-1:2015, Information technology Abstract Syntax Notation One (ASN.1): Specification of basic notation.
- Recommendation ITU-T X.681 (2015) | ISO/IEC 8824-2:2015, Information technology Abstract Syntax Notation One (ASN.1): Information object specification.
- Recommendation ITU-T X.682 (2015) | ISO/IEC 8824-3:2015, Information technology Abstract Syntax Notation One (ASN.1): Constraint specification.
- Recommendation ITU-T X.683 (2015) | ISO/IEC 8824-4:2015, Information technology Abstract Syntax Notation One (ASN.1): Parameterization of ASN.1 specifications.

2.2 Paired Recommendations | International Standards equivalent in technical content

 Recommendation ITU-T X.800 (1991), Security architecture for Open Systems Interconnection for CCITT applications.

ISO 7498-2:1989, Information processing systems – Open Systems Interconnection – Basic Reference Model – Part 2: Security Architecture.

2.3 Additional references

- Recommendation ITU-T X.200 (1994) | ISO/IEC 7498-1:1994, Information technology Open Systems Interconnection – Basic Reference Model: The basic model.
- IETF RFC 2025 (1996), The Simple Public-Key GSS-API Mechanism (SPKM).
- IETF RFC 4422 (2006), Simple Authentication and Security Layer (SASL).
- IETF RFC 4511 (2006), Lightweight Directory Access Protocol (LDAP): The Protocol.

3 Definitions

For the purposes of this Recommendation | International Standard, the following definitions apply.

3.1 OSI Reference Model security architecture definitions

The following terms are defined in Rec. ITU-T X.800 | ISO 7498-2:

a) password.

3.2 Basic Directory definitions

The following terms are defined in Rec. ITU-T X.500 | ISO/IEC 9594-1:

- a) Directory;
- b) Directory Information Base;
- c) (Directory) User.

3.3 Directory model definitions

The following terms are defined in Rec. ITU-T X.501 ISO/IEC 9594-2:

- a) Directory System Agent;
- b) Directory User Agent.

3.4 Directory information base definitions

The following terms are defined in Rec. ITU-T X,501 (ISO/IEC 9594-2:

- a) alias entry;
- b) ancestor;
- c) compound entry;
- d) (Directory) entry;
- e) Directory Information Tree;
- f) family (of entries);
- g) immediate superior;
- h) immediately superior entry/object;
- i) object;
- j) object class;
- k) object entry;
- 1) subordinate;
- m) superior.

3.5 Directory entry definitions

The following terms are defined in Rec. ITU-T X.501 | ISO/IEC 9594-2:

- a) attribute;
- b) attribute type;
- c) attribute value;

- d) attribute value assertion;
- e) context;
- f) context type;
- g) context value;
- h) operational attribute;
- i) matching rule;
- j) user attribute.

3.6 Name definitions

The following terms are defined in Rec. ITU-T X.501 | ISO/IEC 9594-2:

- a) alias, alias name;
- b) distinguished name;
- c) (directory) name;
- d) purported name;
- e) relative distinguished name.

3.7 Distributed operations definitions

The following terms are defined in Rec. ITU-T X.518 | ISO/IEC 9594-4:

- a) bound DSA;
- b) chaining;
- c) initial performer;
- d) LDAP requester;
- e) referral.

3.8 Abstract service definitions

For the purposes of this Recommendation | International Standard, the following definitions apply.

- **3.8.1** additional search: A search that starts from joinBaseObject as specified by the originator in the search request.
- **3.8.2 contributing member**: A family member within a compound entry, which has made a contribution to either a Read, Search or Modify Entry operation.
- **3.8.3 explicitly unmarked entry**: An entry or a family member that is excluded from the **SearchResult** according to a specification given in a control attribute referenced by the governing-search-rule.
- **3.8.4 family grouping**: A set of members of a compound attribute that are grouped together for the purpose of operation evaluation.
- **3.8.5 filter**: An assertion about the presence or value of certain attributes of an entry in order to limit the scope of a search.
- **3.8.6 originator**: The user that originated an operation.
- **3.8.7 participating member**: A family member that is either a contributing member or is a member of a family grouping that as a whole matched a **search** filter.
- **3.8.8 Password expiration**: The situation where a user password has reached the end of its validity period: the account is locked and the user has to change the password before doing any other directory operation.
- **3.8.9 Password quality attributes**: Attributes that specify how a password shall be constructed. Password quality attributes include things like minimum length, mixture of characters (uppercase, lowercase, figures, punctuations, etc), and avoidance of trivial passwords.
- **3.8.10** Password history: List of old passwords and the times they were inserted in the history.
- **3.8.11 primary search**: The search that starts from **baseObject** as specified by the originator in the search request.

ISO/IEC 9594-3:2020 (E)

- relaxation: A progressive modification of the behaviour of a filter during a search operation so as to achieve more matched entries if too few are received, or fewer matched entries if too many are received.
- 3.8.13 reply: A DAP/DSP result or an error; or an LDAP result.
- 3.8.14 request: Information consisting of an operation code and associated components to convey a directory operation from a requester to a performer.
- 3.8.15 requester: A DUA, an LDAP client or a DSA sending a request to perform (i.e., invoke) an operation.
- 3.8.16 service controls: Parameters conveyed as part of an operation, which constrain various aspects of its performance.
- 3.8.17 strand: A family grouping comprising all the members in a path from a leaf family member up to the ancestor inclusive. A family member will reside in as many strands as there are leaf family members below it (as immediate or non-immediate subordinates).

4 **Abbreviations**

For the purposes of this Recommendation | International Standard, the following abbreviations apply:

ACI Access Control Information AVA Attribute Value Assertion DIB **Directory Information Base** DIT **Directory Information Tree DMD Directory Management Domain** Hungandardi darda seri da seri **DSA Directory System Agent** Lightweight Directory Access Protocol
Relative Distinguished N **DUA LDAP RDN**

5 **Conventions**

The term "Directory Specification" (as in "this Directory Specification") shall be taken to mean Rec. ITU-T X.511 ISO/IEC 9594-3. The term "Directory Specifications" shall be taken to mean the Rec. ITU-T X.500 | ISO/IEC 9594-1, Rec. ITU-T X.501 | ISO/IEC 9594-2, Rec. ITU-T X.511 | ISO/IEC 9594-3, Rec. ITU-T X.518 | ISO/IEC 9594-4, Rec. ITU-T X.519 | ISO/IEC 9594-5, Rec. ITU-T X.520 | ISO/IEC 9594-6, Rec ITU-T X.521 | ISO/IEC 9594-7 and Rec. ITU-T X.525 | ISO/IEC 9594-9.

If an International Standard or ITU-T Recommendation is referenced within normal text without an indication of the edition, the edition shall be taken to be the latest one as specified in the normative references clause.

Prior to year 2020, the parts making up the Directory Specifications progressed together and can therefore collectively be identified as the Directory Specifications of a specific edition using the format: Rec. ITU-T X.5** (yyyy) | ISO/IEC 9594-*:yyyy (e.g.; Rec ITU-T X.5** (1993) | ISO/IEC 9594-*:1995).

This Directory Specification makes extensive use of Abstract Syntax Notation One (ASN.1) for the formal specification of data types and values, as it is specified in Rec. ITU-T X.680 | ISO/IEC 8824-1, ITU-T X.681 (2015) | ISO/IEC 8824-2, ITU-T X.682 (2015) | ISO/IEC 8824-3, ITU-T X.683 (2015) | ISO/IEC 8824-4 and Rec. ITU-T X.690 | ISO/IEC 8825-1.

This Directory Specification presents ASN.1 notation in the bold Courier New typeface. When ASN.1 types and values are referenced in normal text, they are differentiated from normal text by presenting them in the bold Courier New typeface. The names of procedures, typically referenced when specifying the semantics of processing, are differentiated from normal text by displaying them in bold Times New Roman. Access control permissions are presented in italicized Times New Roman.

If the items in a list are numbered (as opposed to using "-" or letters), then the items shall be considered steps in a procedure.

6 Overview of the Directory service

As described in Rec. ITU-T X.501 | ISO/IEC 9594-2, the services of the Directory are provided through access points to directory user agents (DUAs), each acting on behalf of a user. These concepts are depicted in Figure 1. Through an access point, the Directory provides service to its users by means of a number of Directory operations.




Figure 1 – Access to the Directory

The Directory operations are of three different kinds:

- a) Directory Read operations, which interrogate a single Directory entry;
- b) Directory Search operations, which interrogate potentially several Directory entries; and
- c) Directory Modify operations.

The Directory Read operations, the Directory Search operations and the Directory Modify operations are specified in clauses 10, 11, and 12, respectively. Conformance to Directory operations is specified in Rec. ITU-T X.519 | ISO/IEC 9594-5.

7 Information types and common procedures

7.1 Introduction

This clause identifies, and in some cases defines, a number of information types which are subsequently used in the definition of Directory operations. The information types concerned are those which are common to more than one operation, are likely to be in the future, or which are sufficiently complex or self-contained as to merit being defined separately from the operation which uses them.

Several of the information types used in the definition of the Directory Service are actually defined elsewhere. Clause 7.2 identifies these types and indicates the source of their definition. Each of the clauses (7.3 to 7.10) identifies and defines an information type.

This clause also specifies some common elements of procedure that apply to most or all of the Directory operations.

7.2 Information types defined elsewhere

The following information types are defined in Rec. ITU-T X.501 | ISO/IEC 9594-2:

- a) Attribute;
- b) AttributeType;
- c) AttributeValue;
- d) AttributeValueAssertion;
- e) Context;
- f) ContextAssertion;
- g) DistinguishedName;
- h) Name;
- i) OPTIONALLY-PROTECTED;
- j) OPTIONALLY-PROTECTED-SEQ;
- $k) \quad \hbox{\tt RelativeDistinguishedName}.$