

ISO/FD TS 19096:2023 (E)

ISO-/DTS 19096:2023(E)

ISO/TC_164/SC_3/AVC

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/DTS 19096 Secretariat: DIN

<https://standards.iteh.ai/catalog/standards/sis/459575958e9045ad9d/iso-dts-19096> Date: 2023-05-05

Metallic materials — Instrumented indentation test for hardness and materials parameters — Evaluation of stress change using indentation force differences

Style Definition: Normal: Font: (Asian) Japanese, Line spacing: At least 12 pt
Style Definition: Heading 1: Font color: Auto, Indent: Left: 0 pt, First line: 0 pt, Outline numbered + Level: 1 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0 pt + Tab after: 21.6 pt + Indent at: 21.6 pt, Tab stops: 20 pt, Left + Not at 21.6 pt
Style Definition: Heading 2: Font: Bold, Outline numbered + Level: 2 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0 pt + Tab after: 18 pt + Indent at: 0 pt, Tab stops: Not at 18 pt
Style Definition: Heading 3: Font: Bold, Space After: 12 pt, Line spacing: Exactly 11.5 pt, Outline numbered + Level: 3 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0 pt + Tab after: 36 pt + Indent at: 0 pt
Style Definition: Heading 4: Font: Bold, Space After: 12 pt, Line spacing: Exactly 11.5 pt, Outline numbered + Level: 4 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0 pt + Tab after: 54 pt + Indent at: 0 pt, Tab stops: 47 pt, Left + Not at 51.05 pt
Style Definition: Heading 5: Font: Bold, Space After: 12 pt, Line spacing: Exactly 11.5 pt, Outline numbered + Level: 5 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0 pt + Tab after: 54 pt + Indent at: 0 pt, Tab stops: Not at 51.05 pt
Style Definition: Heading 6: Font: Bold, Space After: 12 pt, Line spacing: Exactly 11.5 pt, Outline numbered + Level: 6 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0 pt + Tab after: 72 pt + Indent at: 0 pt, Tab stops: Not at 51.05 pt
Style Definition: zzCopyright
Style Definition: Header: Font: (Asian) Japanese, Line spacing: At least 12 pt
Style Definition: FollowedHyperlink
Style Definition: Foreword Text: Tab stops: 19.85 pt, Left + 39.7 pt, Left + 59.55 pt, Left + 79.4 pt, Left + 99.25 pt, Left + 119.05 pt, Left + 138.9 pt, Left + 158.75 pt, Left + 178.6 pt, Left + 198.45 pt, Left
Style Definition: ISO_Comments: (Asian) Japanese
Style Definition: Body Text: Tab stops: 19.85 pt, Left + 39.7 pt, Left + 59.55 pt, Left + 79.4 pt, Left + 99.25 pt, Left + 119.05 pt, Left + 138.9 pt, Left + 158.75 pt, Left + 178.6 pt, Left + 198.45 pt, Left + Not at 20.15 pt
Formatted: zzCover, Left
Formatted: Font: 11 pt

~~© ISO 20XX~~

~~All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.~~

~~ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org~~

~~Published in Switzerland~~

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/DTS 19096

<https://standards.iteh.ai/catalog/standards/sist/b471da99-f575-43af-ad68-958e9045ad9d/iso-dts-19096>

© ISO 20## All rights reserved

ISO/FD TS_19096:2023 (E)

Formatted: Left

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/DTS 19096

<https://standards.iteh.ai/catalog/standards/sist/b471da99-f575-43af-ad68-958e9045ad9d/iso-dts-19096>

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office

CP 401 • Ch. de Blandonnet 8

CH-1214 Vernier, Geneva

Phone: +41 22 749 01 11

Fax: +41 22 749 09 47

Email: copyright@iso.org

Website: www.iso.org

Published in Switzerland

Formatted: Section start: New page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Formatted: zzContents, Indent: Left: 14.15 pt, Space Before: 0 pt

ISO/DTS 19096

<https://standards.iteh.ai/catalog/standards/sist/b471da99-f575-43af-ad68-958e9045ad9d/iso-dts-19096>

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols and designations	2
5 Principle	3
5.1 Shift of force/indentation depth curve by stress change.....	3
5.2 Derivation of stress change from force difference.....	3
6 Testing machine	4
7 Test piece	4
8 Procedure	5
9 Calculation of stress change	7
9.1 Force and projected area calculation at each state.....	7
9.2 Force difference.....	8
9.3 Projected area.....	8
9.4 Calculation of average stress change.....	8
10 Uncertainty of the results	9
11 Test report	10
Annex A (normative) Procedure for hardness uniformity verification	11
Annex B (normative) Combining with stress relief method	14
Annex C (informative) Determination of stress change ratio using Knoop indenter	17
Annex D (informative) Verification of instrumented indentation test residual stress measurement method by bending specimen	20
Annex E (informative) Comparison with hole-drilling and saw-cutting methods	23
Bibliography	32
Foreword	iv

Formatted: Font: Bold

Formatted: Font: 13 pt

Formatted: Font: 13 pt

iTech STANDARD PREVIEW
(standards.iteh.ai)

ISO/DTS 19096

958e9045ad9d/iso-dts-19096

575-43af-ad68-

Introduction	v
Foreword	vi
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols and designations	2
5 Principle	2
6 Testing machine	4
7 Test piece	4
8 Procedure	4
9 Calculation of stress change	6
10 Uncertainty of the results	8
11 Test report	9
Annex A.....	10
Annex B.....	11
Annex C.....	13
Annex D.....	15
Annex E.....	17
Bibliography	21

Formatted: Font color: Auto

Formatted: Font color: Auto

Formatted: Right, Space After: 0 pt, Line spacing: single

Formatted: Font color: Auto

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/DTS 19096

https://standards.iteh.ai/catalog/standards/sist/b477da35-13575-43af-ad68-958e9045ad9d/iso-dts-19096

Formatted: Space Before: 0 pt, Tab stops: 226.8 pt, Centered + 453.6 pt, Right + Not at 487.6 pt

Formatted: Font: Bold

Foreword

Formatted: Font color: Auto

Formatted: Foreword Title, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.–

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of patents. ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had received notice of patents which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.–

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

Formatted: English (United Kingdom)

This document was prepared by Technical Committee ISO/TC 164, *Mechanical testing of metals*, Subcommittee SC 3, *Hardness testing*.

Formatted: Font color: Auto, English (United Kingdom)

Formatted: Font: Cambria, Font color: Auto, English (United Kingdom)

Formatted: Font color: Auto, English (United Kingdom)

Formatted: Font: Cambria, Font color: Auto, English (United Kingdom)

Formatted: Font color: Auto, English (United Kingdom)

Formatted: English (United Kingdom)

Formatted: English (United Kingdom)

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Residual stress is defined as the “locked-in” stress that exists in materials and structures independent of the presence of any external loads. The mechanisms that create residual stress are diverse and include non-uniform plastic deformation, surface modification and thermal gradients.

Numerous techniques have been developed for evaluating residual stress, each with their own merits and drawbacks. Physical methods such as X-ray diffraction (XRD) and neutron diffraction are non-destructive tests based on measuring lattice parameters, and thus they are restricted to crystalline materials; in addition, they are sensitive to microstructure and to the test environment.–

On the other hand, destructive methods such as hole drilling and sectioning method let us quantify the residual stress mechanically and require no reference sample. However, these methods cannot avoid destruction of the sample and require a strain gauge attachment. Then the observed change in strain must be converted to the stress.

The results of these methods for determining residual stress can differ because the residual stress sensing depth and area in each method are different. The hole-drilling measures the amount of strain relaxation caused by the removal of the hole material. The spatial resolution of the method is approximately the size of the hole (typically 2 mm diameter). In case of XRD, the smaller size of irradiated area requires a longer measurement time. The indentation method requires less precise surface preparation than XRD because it obtains a direct response from the material, and strain gauges are unnecessary. It takes less than 30 seconds to measure one point and has high in-field applicability. This document, using a semi-destructive method for measuring stress change, makes it unnecessary to machine samples from in-service components or manufactured products exhibiting internal or external stress changes.

Residual stress is not a material property but a state of stress. In general, it has been observed that when a material is subject to stress change, its indentation curve is shifted upward or downward compared to the initial indentation curve, because the stress change makes indentation easier (relatively tensile) and more difficult (relatively compressive). In a constant depth test (fixed h_{max}): an increase in compressive stress squeezes the material around the indenter and hence a greater load is needed to reach to the same indentation depth than in the initial stress state. On the other hand, an increase in tensile stress releases the material and a smaller load is necessary to keep the same indentation depth than in the initial stress state. In fact, a smaller load/larger load is required at constant h_{max} from initial surface. It seems as if an imaginary (virtual) force works in the same/opposite direction as/to the indenting direction.–

To quantify the effect of stress on indentation behavior, the deviatoric stress concept along the indenting direction is proposed in this document. The method for calculation of the average stress change is given in Clause 8. The described procedure can be applied only when the observed change in force-displacement curves is a result of stress change. The proposed method measures the near-surface stress change in the direction parallel to the test surface.–

Similarly, in a constant load test (fixed L_{max}): compressive stress change makes indentation difficult and hence the indentation depth becomes shallow. Tensile stress change makes indentation easy and the indentation depth becomes deeper. Thus, in the elastic modulus approach, the sign (mode) of stress change can be determined by using this constant-load test as is similar to the above constant-depth (h_{max}) test in this proposal.–

The material for the reference and target states should be selected so as to maintain identical chemical composition with relatively little change of mechanical properties to the target material. This test method is limited to examinations that conform to the conditions given in Annex A. Annex A provides a procedure to achieve satisfactory results by sorting out locally hardening test points. The test point showing the largest deviation is reasonably considered as being from a locally severely changed region.

- Formatted: Font color: Auto
- Formatted: Font color: Auto
- Formatted: Right, Space After: 0 pt, Line spacing: single
- Formatted: Font color: Auto
- Formatted: Font color: Auto
- Formatted: Intro Title, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers
- Formatted: Body Text, Space Before: 0 pt, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers

Field Code Changed

Field Code Changed

Formatted: cite_sec

Formatted: cite_sec

Field Code Changed

Field Code Changed

Formatted: cite_app

Formatted: cite_app

Formatted: cite_app

Formatted: cite_app

Formatted: Font color: Auto

Formatted: Space Before: 0 pt, Tab stops: 226.8 pt, Centered + 453.6 pt, Right + Not at 487.6 pt

ISO/TS 19096:2023(E)

Formatted: Font: Bold

The test point showing the greatest deviation from the average value should be screened out and this process be repeated with remaining test points until the criterion is met. Nevertheless, it is recommended to carefully control the factors between the target and reference states, such as chemical composition, grain size, dislocation density and texture, which can cause errors in measurements.

Formatted: Font color: Auto

If the condition given in Annex A is not satisfied, destructive stress relief methods by electrical discharge machining or focused ion beam can be combined to obtain the reference state (stress-free state) without changing material properties following Annex B. The stress change from this document can be converted to the residual stress of the target state by considering the stress value of the reference state measured by other methods, such as X-ray diffraction and hole-drilling method.

Formatted: cite_app

Formatted: cite_app

Formatted: cite_app

Formatted: cite_app

This document proposes a method to measure the average stress change between reference and target states. Residual stress caused by non-uniform plastic forming and heat treatment usually shows stress components of the same sign in the region requiring stress evaluation. Therefore, there is high demand for the proposed method in many fields. Additionally, if the user wants to resolve stress components, Annex C in the draft can be utilized. The average stress change measured by this method is change of half the first invariant of stress tensor because the stress normal to the test surface is zero. In other words, the average normal stress change is always constant, even if the coordinate system is rotated on the surface.

Formatted: cite_app

Formatted: cite_app

The method proposed in the draft has been applied and verified for many different materials and conditions, and extensive evidence shows that it is both reasonable and useful, as shown in Annex D and E. The purpose of this item is to measure the stress change between reference and target states. As proposed in this draft, the relative stress change can be quantitatively determined and whether the stress change involved is tensile (indentation curve down) or compressive (indentation curve up) compared to the reference (initial) state. Thus, if the state of initial stress is known, it is possible to determine the magnitude and sign of the altered stress state as well.

Formatted: cite_app

Formatted: cite_app

Formatted: cite_app

Some materials show the sensitivity of indentation force to residual stress, which results the force difference greater in a tensile stress state than a compressive stress state, although the difference is in general not large. Even for materials showing different sensitivity of peak load in compressive vs. tensile stress, the load difference is a monotone function of stress change, so that the region of maximum stress can be identified. Furthermore, for many materials, the load difference sensitivity does not significantly violate the fundamental concept.

This document has been prepared to provide useful guidelines on how to extract a two-dimensional representation of the entire 3D residual stress state by means of local size-controllable indentations over the component surface. The testing surface may be indented in one-dimensional or two-dimensional indentation arrays for a more reliable evaluation of the entire bulk residual stress state. The stress state detected by the proposed methodology provides accurate measurement of the plane stress residual stress state from the near-surface region in the component.

Formatted: Font color: Auto

Formatted: Font color: Auto

Metallic materials — Instrumented indentation test for hardness and materials parameters
Evaluation of stress change using indentation force differences

1 1 Scope

This document specifies the method of instrumented indentation test for evaluation of stress change between reference and target states using indentation force differences.

This document primarily applies to measuring the stress change in a specific location and the stress difference between different locations.

2 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

~~ISO 14577-1:2015, Metallic materials — Instrumented indentation test for hardness and materials parameters — Part 1: Test method~~

~~ISO 14577-2:2015, Metallic materials — Instrumented indentation test for hardness and materials parameters — Part 2: Verification and calibration of testing machines~~

~~ISO 14577-3:2015, Metallic materials — Instrumented indentation test for hardness and materials parameters — Part 3: Calibration of reference blocks~~

~~ISO/IEC Guide 98-3:2008, Uncertainty of measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)~~

- Formatted: Different first page header
- Formatted: Font: 11 pt
- Formatted: zzSTDTitle, Space After: 0 pt, Line spacing: single, No page break before
- Formatted: Font: 11 pt, Not Bold
- Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers
- Formatted: Font color: Auto
- Formatted: Font: Font color: Auto
- Formatted: Font color: Auto
- Formatted: Font: Font color: Auto
- Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers
- Formatted: Font color: Auto
- Formatted: Body Text, Line spacing: single, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers
- Formatted: ...
- Formatted: std_publisher
- Formatted: std_docNumber
- Formatted: std_docPartNumber
- Formatted: std_year
- Formatted: std_docTitle, Font: Not Italic
- Formatted: std_docTitle
- Formatted: std_docTitle, Font: Not Italic
- Formatted: std_docTitle, Font: Not Italic
- Formatted: Font: Not Italic
- Formatted: std_publisher
- Formatted: std_docNumber
- Formatted: std_docPartNumber
- Formatted: std_year
- Formatted: std_docTitle, Font: Not Italic
- Formatted: std_docTitle
- Formatted: std_docTitle, Font: Not Italic
- Formatted: std_docTitle, Font: Not Italic
- Formatted: Font: Not Italic
- Formatted: ...
- Formatted: ...
- Formatted: ...
- Formatted: ...
- Formatted: ...
- Formatted: Font: Font color: Auto, English (United Kingdom)
- Formatted: ...
- Formatted: Font: Font color: Auto, English (United Kingdom)
- Formatted: ...
- Formatted: ...
- Formatted: ...

3 Terms and definitions

No terms and definitions are defined listed in this document.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <https://www.electropedia.org/>

4 Symbols and designations

For the purpose of this technical specification document, the symbols and designations in Table 1 shall be applied.

Table 1 — Symbols and designations

Symbol	Designation	Unit
A	Average projected area of reference and target states	mm ²
A_r	Projected area of reference state	mm ²
A_t	Projected area of target state	mm ²
ΔF	Force difference from target curve to reference curve at maximum indentation displacement	N
F_{max}	Maximum test force	N
$F_{r,0}$	Maximum test force on reference state	N
$F_{t,0}$	Maximum test force on target state	N
h	Indentation depth	mm
h_{max}	Maximum indentation depth (should be the same for target and reference state)	mm
p	Ratio of stress changes along one direction to that along the normal direction	-
r	Reference state (used as subscript)	-
t	Target state (used as subscript)	-
$\Delta\sigma_{avg}$ $\Delta\sigma'_{avg}$	Average stress change of surface stress change components.	MPa
$\Delta\sigma_{\perp}$ $\Delta\sigma'_{\perp}$	Stress change from reference state to target state along a direction perpendicular to indenting direction	MPa
$\Delta\sigma'_x$ $\Delta\sigma'_y$	Shear deviatoric stress component of stress change from reference state to target state	MPa
$\Delta\sigma'_z$ $\Delta\sigma'_z$	z component of shear deviatoric stress of stress change from reference state to target state	MPa

Table 1 — Symbols and designations

Formatted: Font: Bold

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers

Formatted: Font color: Auto

Formatted: Body Text

Formatted: English (United States)

Formatted: Font: Times New Roman, 12 pt, English (United States)

Formatted: English (United States)

Formatted: Hyperlink, No underline, Font color: Auto

Formatted: List Continue 1, Left, Space After: 0 pt, Add space between paragraphs of the same style, Line spacing: single, No bullets or numbering, Don't keep with next

Formatted: List Continue 1

Formatted: Font: English (United States)

Formatted: Hyperlink, Font color: Auto, English (United States)

Formatted

Formatted: Font color: Auto

Formatted: cite_tbl

Formatted: cite_tbl

Formatted

Formatted

Formatted Table

Formatted

Formatted: Font: Not Bold, Not Superscript/ Subscript

Formatted

Formatted

Formatted

Formatted

Formatted

Formatted

Formatted: Font: Not Italic

Formatted

Formatted: Font: Not Italic

Formatted

Formatted

Formatted

Formatted

Formatted

Formatted

Field Code Changed

Formatted

Field Code Changed

Formatted: Font: Not Italic

Formatted

Field Code Changed

Formatted: Font: Not Italic


Formatted

Field Code Changed

5 Principle

5.1 5.1-1 Shift of force/indentation depth curve by stress change

The stress change in the same material between two different states creates a shift in the force/indentation depth curve (see Figure-1). A stress increase to be in a relatively tensile state makes indentation easier because the material around the indenter is relaxed. Thus, the indentation force required to reach a given depth in a relatively tensile stress state is lower than that in the initial stress state. In a relatively compressive stress state, the reverse is true. Therefore, the stress change can be evaluated by measuring the indentation force difference at maximum indentation depth $(F_t - F_r) (= \Delta F)$ between the reference and target states.



- Key**
- X indentation depth
 - Y force
 - A tensile stress
 - B compressive stress
 - 1 compressive
 - 2 reference
 - 3 tensile

Figure-1 Change in morphology and force/indentation depth curve with stress change

5.2 5.2-2 Derivation of stress change from force difference

The stress change in one direction can be expressed as $\Delta\sigma$; $\Delta\sigma$: the stress normal to $\Delta\sigma$ on the surface can be expressed as $p\Delta\sigma$ (p is the stress ratio). Since the stress change normal to the surface

- Formatted: Font: Bold, Font color: Gray-95%
- Formatted: Right, Space After: 30 pt, Line spacing: Exactly 12 pt
- Formatted: Font color: Auto
- Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers
- Formatted: Heading 2, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Tab stops: 20 pt, Left
- Formatted: Body Text, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers
- Formatted: cite_fig, Font:
- Formatted: cite_fig, Font:
- Formatted: Font: Font color: Auto
- Field Code Changed
- Field Code Changed

- Formatted: Font: Font color: Auto
- Formatted: Figure title, Left, Level 1, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers
- Formatted: Font: Font color: Auto
- Formatted: Font: Font color: Auto
- Formatted: Font: Not Bold, Font color: Auto
- Formatted: Heading 2, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Tab stops: 20 pt, Left
- Formatted: Font color: Auto
- Formatted: Body Text, Left, Line spacing: single, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers
- Field Code Changed
- Formatted: Font color: Auto
- Field Code Changed
- Formatted: Font: 11 pt, Font color: Auto
- Formatted: Font color: Auto
- Field Code Changed
- Formatted: Font color: Auto