

**SLOVENSKI STANDARD
oSIST prEN IEC 61540:2025
01-maj-2025**

Prenosne naprave na preostali (diferenčni) tok brez vgrajene nadtokovne zaščite za gospodinjsko in podobno uporabo (IEC 61540:2023)

Portable residual current devices without integral overcurrent protection for household and similar use (PRCDs) (IEC 61540:2023)

Elektrisches Installationsmaterial - Ortsveränderliche Fehlerstrom-Schutzeinrichtungen (PRCDs) ohne eingebauten Überstromschutz für Hausinstallationen und für ähnliche Anwendungen (IEC 61540:2023)

Dispositifs différentiels portables à courant résiduel (PCDM) sans protection incorporée contre les surintensités pour usages domestiques et analogues (IEC 61540:2023)

Ta slovenski standard je istoveten z: prEN IEC 61540:2025

<https://standards.iteh.ai/catalog/standards/sist/0f93a992-6945-4908-8df3-ab18f1d018c0/osist-pren-iec-61540-2025>

ICS:

29.120.01	Električna dodatna oprema na splošno	Electrical accessories in general
-----------	--------------------------------------	-----------------------------------

oSIST prEN IEC 61540:2025

en,fr,de

**EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM**

**DRAFT
prEN IEC 61540**

February 2025

ICS 29.120.01

Will supersede HD 639 S1:2002; HD 639 S1:2002/corrigendum Jul. 2003; HD 639 S1:2002/A1:2003; HD 639 S1:2002/A2:2010

English Version

**Portable residual current devices (PRCDs) without integral overcurrent protection for household and similar use
(IEC 61540:2023)**

Dispositifs différentiels portables à courant résiduel (PCDM)
sans protection incorporée contre les surintensités pour
usages domestiques et analogues
(IEC 61540:2023)

Elektrisches Installationsmaterial - Ortsveränderliche
Fehlerstrom-Schutzeinrichtungen (PRCDs) ohne
eingebauten Überstromschutz für Hausinstallationen und
für ähnliche Anwendungen
(IEC 61540:2023)

This draft European Standard is submitted to CENELEC members for enquiry.
Deadline for CENELEC: 2025-05-02.

The text of this draft consists of the text of IEC 61540:2023 (23E/1320/FDIS).

If this draft becomes a European Standard, CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CENELEC in three official versions (English, French, German).
A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

<https://standards.iteh.ai/catalog/standards/510/093a992-6945-4908-84f3-ab18f1d018c0/osist-pren-iec-61540-2025>
CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

prEN IEC 61540:2025 (E)**European foreword**

This document (prEN IEC 61540:2025) consists of the text of IEC 61540:2023, prepared by IEC/SC 23E “Circuit-breakers and similar equipment for household use” of IEC/TC 23 “Electrical accessories”.

This document is currently submitted to the Enquiry.

The following dates are proposed:

- latest date by which the existence of (doa) dav + 6 months this document has to be announced at national level
- latest date by which this document has to be (dop) dav + 12 months implemented at national level by publication of an identical national standard or by endorsement
- latest date by which the national standards (dow) dav + 36 months conflicting with this document have to be withdrawn (to be confirmed or modified when voting)

This document will supersede HD 639 S1:2002 and all of its amendments and corrigenda (if any).

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[oSIST prEN IEC 61540:2025](#)

<https://standards.iteh.ai/catalog/standards/sist/0f93a992-6945-4908-8df3-ab18f1d018c0/osist-pren-iec-61540-2025>



INTERNATIONAL STANDARD

NORME INTERNATIONALE

Portable residual current devices (PRCDs) without integral overcurrent protection for household and similar use

iTeh Standards
<https://standards.iteh.ai>

Dispositifs différentiels portables à courant résiduel (PCDM) sans protection incorporée contre les surintensités pour usages domestiques et analogues

[oSIST prEN IEC 61540:2025](#)

<https://standards.iteh.ai/catalog/standards/sist/0f93a992-6945-4908-8df3-ab18f1d018c0/osist-pren-iec-61540-2025>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.120.01

ISBN 978-2-8322-7185-8

Warning! Make sure that you obtained this publication from an authorized distributor.

Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

FOREWORD	10
INTRODUCTION	12
1 Scope	13
2 Normative references	14
3 Terms and definitions, symbols and abbreviated terms	15
3.1 Definitions relating to plugs and socket-outlets	15
3.2 Definitions relating to residual current devices (RCDs)	16
3.2.1 Definitions relating to currents flowing from live parts to earth	16
3.2.2 Definitions relating to the energization of a residual current device (RCD)	17
3.2.3 Definitions relating to the operation and to the functions of a residual current device	17
3.2.4 Definitions relating to values and ranges of energizing quantities	18
4 Classification	18
4.1 According to the type of connection	18
4.1.1 PRCD intermediate adaptor	18
4.1.2 Non-rewireable residual current-protected cord extension sets	19
4.1.3 Residual current-protected plugs	19
4.1.4 In-line PRCDs	19
4.2 According to the type of terminals	19
4.3 According to behaviour after opening automatically in case of failure of the line voltage	19
4.4 According to their operating characteristics and behaviour in presence of DC components	19
4.5 According to the ambient air temperature	20
4.5.1 For use between -5°C and $+40^{\circ}\text{C}$	20
4.5.2 For use between -25°C and $+40^{\circ}\text{C}$	20
4.6 Classification according to the protective conductor path	20
4.6.1 PRCDs with switched protective conductor	20
4.6.2 PRCDs with non-switched protective conductor	20
4.7 According to the supply	20
4.7.1 PRCDs supplied from one phase and neutral (LNSE or LNE)	20
4.7.2 PRCDs supplied from two phases (LLSE or LLE)	20
4.8 According an additional function of detecting faults on the supply side	20
4.8.1 PRCDs not providing an additional function of detecting faults on the supply side	20
4.8.2 PRCDs providing an additional function of detecting faults on the supply side with a defined behaviour in case of supply failures or miswiring (PRCD-S)	20
5 Characteristics of PRCDs	20
5.1 Summary of characteristics	20
5.2 Rated quantities and other characteristics	21
5.2.1 Rated voltage	21
5.2.2 Rated current (I_n)	21
5.2.3 Rated residual operating current ($I_{\Delta n}$)	21
5.2.4 Rated residual non-operating current ($I_{\Delta no}$)	21
5.2.5 Rated frequency	21

5.2.6	Rated making and breaking capacity (I_m)	22
5.2.7	Rated residual making and breaking capacity ($I_{\Delta m}$)	22
5.2.8	Operating characteristics in case of residual currents comprising a DC component.....	22
5.3	Standard and preferred values	22
5.3.1	Preferred values of rated operational voltage (U_e).....	22
5.3.2	Standard values of rated current (I_n)	22
5.3.3	Standard values of rated residual operating current ($I_{\Delta n}$)	23
5.3.4	Standard value of residual non-operating current ($I_{\Delta no}$)	23
5.3.5	Standard minimum value of the non-operating overcurrent through the PRCD	23
5.3.6	Preferred values of rated frequency	23
5.3.7	Minimum value of the rated making and breaking capacity (I_m)	23
5.3.8	Minimum value of the rated residual making and breaking capacity ($I_{\Delta m}$)	23
5.3.9	Standard value of the rated conditional short-circuit current (I_{nc})	24
5.3.10	Standard value of the rated conditional residual short-circuit current ($I_{\Delta c}$)	24
5.3.11	Standard values of maximum break time.....	24
5.4	Coordination with short-circuit protective devices (SCPDs)	24
5.4.1	General	24
5.4.2	Rated conditional short-circuit current (I_{nc})	24
5.4.3	Rated conditional residual short-circuit current ($I_{\Delta c}$).....	24
6	Marking and other product information.....	24
6.1	Information and marking for PRCDs	24
6.2	Information to be provided in an instruction sheet	27
7	Standard conditions for operation in service and for installation.....	27
7.1	Standard conditions	27
7.2	Conditions for installations	28
7.3	Pollution degree.....	28
8	Requirements for construction and operation	28
8.1	Mechanical design	28
8.1.1	General	28
8.1.2	Plug part, socket-outlet parts and RCD part(s).....	29
8.1.3	Mechanism	34
8.1.4	Clearances and creepage distances (see Annex C)	35
8.1.5	Screws, current-carrying parts and connections.....	37
8.1.6	Terminals for external conductors for rewireable PRCDs	37
8.1.7	Terminations for non-rewireable PRCDs	39
8.1.8	Current-carrying parts.....	39
8.2	Protection against electric shock	40
8.2.1	General	40
8.2.2	Requirements relating to plugs and socket-outlets, whether incorporated or not in integral items	40
8.3	Dielectric properties	42
8.4	Temperature rise	42
8.4.1	Temperature rise limits	42

8.4.2	Ambient air temperature	42
8.5	Operating characteristic	42
8.6	Mechanical and electrical endurance	42
8.7	Performance at short-circuit currents	43
8.8	Resistance to mechanical shock and impact	43
8.9	Resistance to heat	43
8.10	Resistance to abnormal heat and to fire	43
8.11	Test device	43
8.11.1	General	43
8.11.2	Test function.....	43
8.12	Behaviour of PRCDs in case of failure of line voltage.....	44
8.13	Behaviour of PRCDs in case of overcurrent in the main circuit.....	44
8.14	Resistance of PRCDs against unwanted tripping due to surge currents to earth resulting from impulse voltages.....	44
8.15	Behaviour of PRCDs in case of an earth fault current comprising a DC component	44
8.16	Reliability.....	44
8.17	Resistance to tracking.....	44
8.18	Electromagnetic compatibility (EMC).....	44
8.19	Standing current in the protective conductor	45
8.20	Electrical performance	45
8.20.1	Protective conductor path	45
8.20.2	Contact mechanism	45
8.20.3	Operation with supply failure and hazardous live protective conductor conditions	46
8.20.4	Behaviour of PRCDs in case of external fault current in the protective conductor	46
9	Test.....	46
9.1	General	46
9.1.1	Characteristics of PRCDs checked by means of type tests	46
9.1.2	For certification purposes, type tests to be carried out in test sequences.....	47
9.1.3	Routine tests	48
9.2	Test conditions	48
9.3	Test of indelibility of marking	48
9.4	Test of reliability of screws, current-carrying parts and connections	49
9.5	Test of reliability of terminals for external conductors	50
9.6	Verification of protection against electric shock.....	51
9.6.1	Test with conductors of the smallest and largest cross-sections	51
9.6.2	Test with plug completely withdrawn	52
9.6.3	Test with engagement surface in horizontal position	52
9.6.4	Verification of the resistance between the earthing terminal and the accessible metal part.....	52
9.6.5	Verification of the isolation between the earthing terminal and the accessible metal part.....	52
9.6.6	Stray wire test for rewirable PRCDs	52
9.6.7	Stray wire verification for non-rewireable PRCDs	53
9.6.8	Verification of high electrical resistance of the conductive operating means	53
9.7	Test of dielectric properties.....	53
9.7.1	Resistance to humidity.....	53

9.7.2	Insulation resistance of the main circuit	54
9.7.3	Dielectric strength of the main circuit.....	54
9.7.4	Secondary circuit of detection transformers	55
9.7.5	Verification of impulse withstand voltages.....	55
9.8	Temperature-rise test.....	58
9.8.1	Test conditions	58
9.8.2	Ambient air temperature	58
9.8.3	Test procedure	59
9.8.4	Measurement of the temperature-rise of different parts.....	59
9.8.5	Temperature-rise of a part	59
9.9	Verification of the operating characteristic	59
9.9.1	Test circuit.....	59
9.9.2	Off-load tests with residual sinusoidal alternating currents at the reference temperature of $(20 \pm 2)^\circ\text{C}$	59
9.9.3	Verification of the correct operation with load at the reference temperature	60
9.9.4	Tests at the temperature limits.....	61
9.9.5	Additional tests for PRCDs classified according to 4.8.2	61
9.9.6	Verification of protective conductor contact behaviour	64
9.9.7	Verification of behaviour in case of external fault current in the protective conductor	64
9.9.8	Verification of standing current in the protective conductor	65
9.10	Verification of mechanical and electrical endurance	65
9.10.1	Normal operation of socket-outlets and plugs of the PRCD	65
9.10.2	Test of the RCD part of the PRCD	66
9.11	Verification of the behaviour of the PRCD under overcurrent conditions	67
9.11.1	List of the overcurrent tests	67
9.11.2	Short-circuit tests	67
9.11.3	Verification of the making and breaking capacity of the plug and socket-outlet(s) of the PRCD, separate or incorporated in integral items	72
9.12	Verification of resistance to mechanical shock and impact	72
9.12.1	General	72
9.13	Test of resistance to heat.....	75
9.14	Resistance of insulating material to abnormal heat and to fire.....	76
9.14.1	General	76
9.14.2	Glow-wire test.....	76
9.15	Verification of the trip-free mechanism	77
9.15.1	General test conditions	77
9.15.2	Test procedure	77
9.16	Verification of the test device	77
9.16.1	Verification of the operation of the test device to disconnect the load	77
9.16.2	Verification of the ampere-turns	77
9.17	Verification of the behaviour of PRCDs in case of failure of the line voltage	77
9.17.1	Determination of the limiting value of the line voltage (U_X).....	77
9.17.2	Verification of the behaviour in case of failure of the line voltage	78
9.17.3	Verification of the re-closing of PRCDs classified according to 4.3.2 at restoration of the line voltage after automatic opening on failure of the line voltage	79
9.18	Verification of limiting values of the non-operating current under overcurrent conditions	79

9.19	Verification of resistance against unwanted tripping due to surge currents to earth resulting from impulse voltages for PRCDs of $I_{\Delta n} \geq 0,010 \text{ A}$	79
9.20	Verification of the correct operation with residual currents having a DC component for PRCDs according to 4.4.2.....	79
9.20.1	General	79
9.20.2	Verification of the correct operation in case of a continuous rise of a residual pulsating direct current.....	79
9.20.3	Verification of the correct operation in case of suddenly appearing residual pulsating direct currents	80
9.20.4	Verification at the reference temperature of the correct operation with load	80
9.20.5	Verification of the correct operation in case of residual pulsating direct currents superimposed by a smooth direct current of 0,006 A	80
9.21	Verification of reliability.....	81
9.21.1	Climatic test.....	81
9.21.2	Test with temperature of 40 °C	82
9.22	Verification of ageing	83
9.23	Resistance to tracking.....	84
9.24	Test on pins provided with insulating sleeves.....	84
9.25	Test of mechanical strength of non-solid pins of plugs and portable socket-outlets.....	84
9.26	Verification of the effects of strain on the conductors	84
9.27	Checking of the torque exerted by plug-in PRCDs on fixed socket-outlets	85
9.28	Tests of the cord anchorage.....	85
9.29	Flexing test of non-rewireable PRCDs.....	86
9.30	Verification of the electromagnetic compatibility (EMC)	87
9.31	Tests replacing verifications of creepage distances and clearances for electronic circuits connected between live conductors (phases and neutral) and/or between live conductors and the earth circuit when the contacts are in the closed position	87
9.31.1	PRCDs shall not create fire and/or shock hazards under abnormal conditions likely to occur in service.....	87
9.31.2	When PRCDs are exposed to abnormal conditions, no part shall reach temperatures likely to cause danger of fire to the surroundings of the PRCDs and no live parts shall become accessible.....	87
9.31.3	Unless otherwise specified, the tests are made on PRCDs while they are mounted, connected and loaded as specified in 9.8	88
9.32	Requirements for capacitors and specific resistors and inductors used in electronic circuits connected between live conductors (phases and neutral) and/or between live conductors and the earth circuit when the contacts are in the closed position	90
9.32.1	Capacitors	90
9.32.2	Resistors and inductors	90
9.33	Verification of the behaviour of the PRCD under temporary over voltage (TOV) conditions	90
9.33.1	General	90
9.33.2	Test for all PRCDs	90
9.33.3	Verification after the tests	91
Annex A (normative)	Test sequences and number of samples to be submitted for verification of conformity to this document	119
A.1	Verification of conformity	119
A.2	Test sequences	119
A.3	Number of samples to be submitted for full test procedure	121

A.4	Number of samples to be submitted for simplified test procedures in case of submitting simultaneously a range of PRCDs of the same fundamental design.....	121
Annex B (normative)	Routine tests.....	126
B.1	General.....	126
B.2	Tripping test.....	126
B.3	Dielectric strength test	126
B.4	Performance of the test device.....	126
B.5	Stray wire test.....	126
B.6	Correct continuity test.....	127
Annex C (normative)	Determination of clearances and creepage distances.....	128
C.1	General.....	128
C.2	Orientation and location of a creepage distance.....	128
C.3	Creepage distances where more than one material is used.....	128
C.4	Creepage distances split by floating conductive part.....	128
C.5	Measurement of creepage distances and clearances	128
Annex D (normative)	List of tests, additional test sequences and numbers of samples for verification of compliance of PRCDs with the requirements of electromagnetic compatibility (EMC).....	132
D.1	General.....	132
D.2	EMC tests already included in the product standard.....	132
D.3	Additional tests of IEC 61543 to be applied.....	132
Annex E (informative)	Application of PRCD according to 4.8.2 (PRCD-S)	134
E.1	Explanation of switched protective conductor function and application	134
E.2	Examples of incorrect supply wiring	135
Annex F (informative)	Examples of terminal designs	138
Annex G (informative)	Correspondence between ISO and AWG copper conductors	141
Annex H (informative)	Methods for determination of short-circuit power-factor	142
Bibliography.....		143
Figure 1 – Examples of types of connection classified according to 4.1.....	92	
Figure 2 – Standard test wire 1,0 mm	93	
Figure 3 – Gauge for checking non-accessibility of live parts through shutters and of live parts of socket-outlets with increased protection.....	94	
Figure 4 – Test circuit for the verification of the correct operation of PRCDs, in the case of residual pulsating direct currents	95	
Figure 5 – Test circuit for the verification of the correct operation of PRCDs, in the case of residual pulsating direct currents superimposed by a smooth direct current	96	
Figure 6 – Verification of behaviour in case of external fault current in the protective conductor.....	97	
Figure 7 – Test circuit for the verification of the rated making and breaking capacity and of the coordination	98	
Figure 8 – Tumbling barrel.....	99	
Figure 9 – Arrangement for compression test.....	99	
Figure 10 – Ball-pressure test apparatus.....	100	
Figure 11 – Arrangement and dimensions of the electrodes for the tracking test	100	
Figure 12 – Apparatus for testing the cord retention.....	101	
Figure 13 – Apparatus for flexing test	102	

Figure 14 – Arrangement for mechanical strength test on PRCDs provided with cords (9.12.6).....	103
Figure 15 – Test apparatus for the verification of the minimum I_{2t} and I_p values to be withstood by the PRCD (9.11.2.1 a)).....	104
Figure 16 – Stabilizing period for reliability test (9.21.1.4).....	105
Figure 17 – Reliability test cycle (9.21.1.4)	106
Figure 18 – Example for test circuit for verification of ageing of electronic components (9.22).....	107
Figure 19 – Current ring wave 0,5 μ s/100 kHz	107
Figure 20 – Example of test circuit for the verification of resistance to unwanted tripping	108
Figure 21 – Minimum creepage distances and clearances as a function of peak value of voltage.....	109
Figure 22 – Minimum creepage distances and clearances as a function of peak value of operating voltage	110
Figure 23 – Test cycle for low temperature test (9.9.4).....	111
Figure 24 – Test circuit for the verification of operating characteristic (9.9), endurance test (9.10), trip-free mechanism (9.15) and behaviour in case of failure of line voltage (9.17).....	112
Figure 25 – Test circuit for the verification of PRCD when plugged into incompatible supply systems (9.9.5.4)	113
Figure 26 – Verification of correct operation for hazardous live PE (see Table 15)	114
Figure 27 – Verification of open neutral for LNSE types, and open line for LLSE types	115
Figure 28 – Verification of a standing current in the protective conductor in normal service (9.9.8).....	116
Figure 29 – Verification of open protective conductor (see 9.9.5.5)	117
Figure 30 – Standard test finger.....	118
Figure C.1 – Examples of methods of measuring creepage distances and clearances.....	131
Figure E.1 – Examples of incorrect supply wirings for LLSE types.....	136
Figure E.2 – Examples of incorrect supply wirings for LNSE types	137
Figure F.1 – Examples of pillar terminals	138
Figure F.2 – Examples of screw terminals and stud terminals	139
Figure F.3 – Examples of saddle terminals.....	140
Figure F.4 – Examples of lug terminals	140
Table 1 – Standard values of rated current and corresponding preferred values of rated operational voltages.....	23
Table 2 – Standard values of maximum break time for AC residual currents	24
Table 3 – Marking or information item	25
Table 4 – Standard conditions for operation in service	27
Table 5 – Minimum cross-sectional area of flexible cable or cord suitable for non-rewireable plugs and non-rewireable socket-outlets of PRCDs	33
Table 6 – Clearances and creepage distances	36
Table 7 – Connectable cross-sections of copper conductors for screw-type terminals	38
Table 8 – Degree of protection of PRCD parts	41
Table 9 – Temperature-rise values.....	42

Table 10 – List of type tests	47
Table 11 – Cross-sectional area for test conductors.....	48
Table 12 – Screw thread diameters and applied torques	49
Table 13 – Conductor composition.....	51
Table 14 – Test voltage for verification of impulse withstand voltage	57
Table 15 – Supply failure and hazardous live protective conductor (PE) connections for test with reference to correct supply connections for LNSE and LLSE types	62
Table 16 – Tests to verify the behaviour of PRCDs under overcurrent conditions	67
Table 17 – List of tests of resistance to mechanical shock and impact	73
Table 18 – Torque applied to the spanner for the test of 9.12.3.....	74
Table 19 – Tripping current ranges for PRCDs in case of pulsating DC current.....	80
Table 20 – Make-up of cables suitable for the retention test of rewireable PRCDs	85
Table 21 – Maximum permissible temperatures under abnormal conditions.....	89
Table A.1 – Test sequences.....	120
Table A.2 – Number of samples to be submitted for full test procedure	121
Table A.3 – Reduction of number of samples	123
Table A.4 – Reduction of additional test sequences	124
Table A.5 – Reduction of additional test sequences	125
Table D.1 – EMC test.....	132
Table D.2 – Additional tests	133

iteh Standards
(<https://standards.iteh.ai>)

Document Preview

[oSIST prEN IEC 61540:2025](#)

<https://standards.iteh.ai/catalog/standards/sist/0f93a992-6945-4908-8df3-ab18f1d018c0/osist-pren-iec-61540-2025>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PORTABLE RESIDUAL CURRENT DEVICES (PRCDS) WITHOUT INTEGRAL OVERCURRENT PROTECTION FOR HOUSEHOLD AND SIMILAR USE

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61540 has been prepared by subcommittee 23E: Circuit-breakers and similar equipment for household use, of IEC technical committee 23: Electrical accessories. It is an International Standard.

This second edition cancels and replaces the first edition published in 1997 and its Amendment 1:1998. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) The content of the document was revised and aligned with IEC 60755 (group safety publication for residual current devices) and standard library "blocks and modules".
- b) Introduction of classification "4.3 According to behaviour after opening automatically in case of failure of the line voltage".