

ISO/FDIS 19234:2023(E)

~~Date: 2023-10-13~~

ISO/TC 113/SC 2

Secretariat: BSI

Hydrometry — Low-cost baffles to aid fish passage on triangular profile gauging weirs

~~FDIS stage~~

iTeh Standards First edition

(<https://standards.iteh.ai>)

Document Preview

ISO/FDIS 19234

<https://standards.iteh.ai/catalog/standards/sist/3f5722d5-0d6b-4e80-a7fb-ca0c9cc6d257/iso-fdis-19234>

ISO/FDIS 19234:2023(E)

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO Copyright Office

CP 401 • CH-1214 Vernier, Geneva

Phone: + 41 22 749 01 11

Email: copyright@iso.org

Website: www.iso.org

Published in Switzerland.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/FDIS 19234](#)

<https://standards.iteh.ai/catalog/standards/sist/3f5722d5-0d6b-4e80-a7fb-ca0c9cc6d257/iso-fdis-19234>

Contents

Foreword.....iv

Introduction v

1 Scope..... 1

2 Normative references 1

3 Terms and definitions..... 1

4 Symbols..... 3

5 Principles 4

5.1 General principles 4

5.2 Crump weirs — Structures that conform to ISO 4360 5

5.3 Flat-V weirs — Structures that conform to ISO 4377 7

5.4 Suitability for fish species..... 8

6 Installation — General considerations..... 9

6.1 Site selection and application..... 9

6.2 Baffle dimensions 11

6.3 Baffle material and construction..... 13

6.4 Limitations for baffle installations 14

7 Installation at Crump weir — Weirs that conform to ISO 4360..... 16

7.1 General baffle arrangements for Crump weirs 16

7.2 Location of the first baffle on Crump weirs..... 21

7.3 Limitations for baffle installations on Crump weirs 21

8 Installation at flat-V weir — Weirs that conform to ISO 4377 22

8.1 General baffle arrangements for flat-V weirs..... 22

8.2 Location of the first baffle on flat-V weirs 30

8.3 Limitations for baffle installations on flat-V weirs 30

9 Maintenance considerations..... 32

Bibliography 33

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 113, *Hydrometry*, Subcommittee SC 2, *Flow measurement structures*.

This first edition cancels and replaces (ISO/TR 19234:2016), which has been technically revised, ~~restructured and now includes low-cost baffles on flat-V weirs.~~

The main changes are as follows:

- ~~— this document has been restructured;~~
- ~~— low-cost baffles on flat-V weirs have been included.~~

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Flow gauging structures such as triangular profile weirs are commonly used for the measurement of open channel flows. This document applies to weirs operating under modular flow conditions, with flow passing through critical depth. To operate under these conditions, such weirs require a sufficient head difference to be generated between upstream and downstream. At structures operating in the modular flow range, flow rate is solely a function of the upstream head.

In recent years, greater emphasis has been placed on environmental issues, including the free migration of fish in watercourses. It is acknowledged that the head drop required to achieve modular flow can inhibit the movement of fish. It has become important, therefore, to consider ways of aiding fish migration without significantly affecting flow measurement accuracy.

Applied research has shown that baffles of suitable form and placement on the downstream face of triangular profile weirs can partially mitigate fish passage impacts while retaining the gauging function.

NOTE The coefficient of discharge of the weir would normally remain the same although it is an option to recalibrate the coefficient to take into account the placement of baffles.

The baffle system described in this document was adapted from an optimal solution for aiding fish passage^{[1][2]} on non-gauging sloping weirs commonly used for other purposes (e.g. abstraction, flow diversion, power generation, navigation).

The following Excel¹ spreadsheet tools can be used to design the layout of the baffles ~~in accordance with~~ ~~according to~~ this document:

- Crump weir spreadsheet (LCB placement sheet for Crump weirs 2023.xlsm);
- Flat-V weir spreadsheet (LCB placement sheet for flat-V weirs 2023.xlsx).

The spreadsheet tools are available at: <https://standards.iso.org/iso/19234//ed-1/en/>

ISO/FDIS 19234

<https://standards.iteh.ai/catalog/standards/sist/3f5722d5-0d6b-4e80-a7fb-ca0c9cc6d257/iso-fdis-19234>

¹ Excel is the trademark of a product supplied by Microsoft. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO of the product named. Equivalent products may be used if they can be shown to lead to the same results.

Hydrometry — Low-cost baffles to aid fish passage on triangular profile gauging weirs

1 Scope

This document specifies how to integrate baffles to aid the passage of fish on the downstream face of triangular profile weirs that conform to ISO 4360 (including Crump weirs) and ISO 4377 (flat-V weirs).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 772, *Hydrometry — Vocabulary and symbols*

ISO 4360, *Hydrometry — Open channel flow measurement using triangular profile weirs*

ISO 4377, *Hydrometric determinations — Flow measurement in open channels using structures — Flat-V weirs*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 772 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

anguillid

eel and lamprey

long and cylindrical body-shaped species including eel (*Anguilla anguilla*) and lamprey (*Lampetra fluviatilis* and *Petromizon marinus*)

3.2

non-migratory salmonid

fish of the family Salmonidae that migrates solely in freshwater including brown trout (*Salmo trutta*) and grayling (*Thymallus thymallus*)

3.3

coarse fish

non-salmonid fish found in freshwater habitats

ISO/FDIS 19234:2023(E)

3.4

Crump weir

weir with a triangular profile in the streamwise direction and a horizontal crest in the transverse direction used for gauging

Note 1 to entry: This **weir** was named after the inventor E.S. Crump. The upstream slope is 1:2 and downstream slope is 1:5 (see ISO 4360).

3.5

anadromous *adi*

living and migrating between the sea and freshwater

3.6

flat-V weir

triangular profile weir (3.15) with a transverse V-shaped crest used for gauging

Note 1 to entry: The upstream slope is 1:2 and downstream slope is 1:5 (parallel to the centreline). The cross-slopes **may** be between 1:10 and 1:40 (see ISO 4377).

3.7

low-cost baffle

LCB

low-cost deflector attached to the downstream face of the structure to aid fish passage

Note 1 to entry: These are low-cost baffles in comparison to having to incorporate a formal fish pass in a gauging weir.

Note 2 to entry: These are perpendicular to the downstream slope of the weir. The geometry of the baffle is precisely described in Figure 4.

3.8

migratory salmonid

fish of the family Salmonidae that migrates between the sea and fresh water including salmon (*Salmo salar*) and sea trout (*Salmo trutta*)

3.9

modular flow

flow that is independent of variations in tailwater level

3.10

plunging flow

flow passing an obstruction that is directed towards the floor and defined as $H_2/H_1 \leq 0,50$

$$H_2/H_1 \leq 0,50$$

where

- H_1 is the depth of water on the upstream side of baffle relative to the base of the baffle;
- H_2 is the depth of water on the downstream side of baffle relative to the base of the baffle

Note 1 to entry: Unstable flow conditions can occur for ratios of H_2/H_1 between 0,51 to 0,59.

Note 2 to entry: See Figure 5 below for **diagraman illustration of plunging flow**.

3.11

potamodromous, adi
 living and migrating solely in freshwater

3.12 reflection
 change in direction of the position of the gaps in the baffles

3.13 streaming flow
 flow passing an obstruction that remains at or near the surface and defined as $H_2/H_1 \geq 0,60$

$$H_2/H_1 \geq 0,60$$

where

- H_1 is the depth of water on the upstream side of baffle relative to the base of the baffle;
- H_2 is the depth of water on the downstream side of baffle relative to the base of the baffle

Note 1 to entry: Unstable flow conditions can occur for ratios of H_2/H_1 between 0,51 to 0,59.

Note 2 to entry: See Figure 5 below for diagraman illustration of streaming flow.

3.14 structural head difference SHD
 difference in elevation (in metres) between the invert (lowest level) of the crest of the *triangular profile weir* (3.15) and the downstream water surface at a flow exceeded 95 % of the time

Note 1 to entry: See Figure 3 below for diagraman illustration of structural head difference.

3.15 triangular profile weir
 weir with a triangular profile in the streamwise direction

Note 1 to entry: This includes *Crump weirs* (3.6) and *flat-V weirs* (3.8).

3.16 V_{full}
 flow that just fills the whole width of a flat-V weir at the crest

4 Symbols

Symbol	Term	Unit
<i>a</i>	baffle width	m
<i>b</i>	breadth of the weir crest perpendicular to the flow direction	m
<i>c</i>	gap offset distance immediately downstream from the reflection (see Figure 6)	m
<i>d</i>	distance between baffles, centre to centre along the slope (see Figure 6) (a * suffix indicates the dimension in plan view)	m

ISO/FDIS 19234:2023(E)

Symbol	Term	Unit
d_L	intermediate variable used in the Crump weir spreadsheet for calculating cutting lengths for the baffles – left-hand-side baffle	—
d_R	intermediate variable used in Crump weir spreadsheet for calculating cutting lengths for the baffles – right-hand-side baffle	—
f	offset distance between the position of gaps in successive baffles (see Figure 6)	m
h	gauged head relative to the crest elevation (upstream head is implied if no subscript is used); for flat-V weirs, the crest elevation is taken from the invert of the V	m
H	total head, energy head, relative to crest elevation; for flat-V weirs, the crest elevation is taken from the invert of the V	m
H_1	depth of water on the upstream side of baffle relative to the base of the baffle	m
H_2	depth of water on the downstream side of baffle relative to the base of the baffle	m
L	for Crump weirs, this is the distance from the crest to the base of the upstream face of the first baffle along the slope (in plane view); for flat-V weirs, this distance is the smallest distance to the base of the upstream face of the first baffle (see Figures 6 and 7 for clarity) (a * suffix indicates the dimension in plan view)	m
L_1	distance from the crest to the centre of the first baffle along the slope (only relevant to Crump weirs)	m
L_2	rounded up value of L_1 (only relevant to Crump weirs)	m
L_a	maximum apron length	m
p	height of the weir crest above the upstream bed level	m
q	gap width	m
Q_{nn}	flow that is exceeded for nn % of the time	m ³ /s
R	radius	mm
T	height of the first baffle	m
T_s	height of subsequent baffles used in the Crump weir spreadsheet	m
V_{full}	flow that fills the whole width of the flat-V weir at the crest	m ³ /s
z_L	intermediate variable used in the Crump weir spreadsheet to determine local coordinates (left-hand-side) for determining the gap location	—
z_R	intermediate variable used in the Crump weir spreadsheet to determine local coordinates (right-hand-side) for determining the gap location	—
Δ_x	axis in the direction of the flow (perpendicular to the crest) used in the Crump weir spreadsheet	—
Δ_y	axis in the direction perpendicular to the face of the crest (vertical upwards) used in the Crump weir spreadsheet	—
Δ_z	axis in the direction along the crest used in the Crump weir spreadsheet	—

5 Principles

5.1 General principles

Baffles are placed in horizontal parallel rows on the downstream sloping face of the weir. There is a gap in each row of baffles that runs at an angle progressively across and down the weir face. This forms an

oblique flow path that can be reflected from side to side in narrower channels forming a V-shaped pattern in plan view (as shown in Figures 1 and 2). The baffles retard flow, maintain a consistent depth of water, and substantially reduce the acceleration of the water on the downstream face of the weir. The oblique flow path formed by the gaps provides a passage route for fish with greater flow depth and lower velocities than over the baffles. The baffles also spread the dissipation of flow energy over the length of the downstream slope of the weir, creating a series of small hydraulic jumps and reducing the intensity of a final hydraulic jump at the junction with the tailwater pool.

The solution creates conditions that fish can exploit to find passage over a wide range of flows. Fish can exploit the low velocity flow path, or, when flow tops the baffles, they can swim straight up the slope, taking advantage of the lower velocities created by the baffles. However, if the top baffle is too close to the weir crest, it can affect gauging performance.

For the application of this document, users shall either apply ISO 4360 (including Crump weirs) or ISO 4377 (flat-V weirs).

5.2 Crump weirs — Structures that conform to ISO 4360

Baffles are placed in rows that are parallel to the crest on the downstream sloping face of the weir. See Figure 1.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/FDIS 19234](https://standards.iteh.ai/catalog/standards/sist/3f5722d5-0d6b-4e80-a7fb-ca0c9cc6d257/iso-fdis-19234)

<https://standards.iteh.ai/catalog/standards/sist/3f5722d5-0d6b-4e80-a7fb-ca0c9cc6d257/iso-fdis-19234>