### ISO/**DISFDIS** 4931-1:2023(E)

ISO/TC 59

Date: 2024-02-05

Secretariat: SN

Date: 2024-06-13

Buildings and civil engineering works—\_\_Principles, framework and guidance for resilience design—\_\_

## Part 1: Adaptation to climate change Standards (https://standards.iteh.ai) Document Preview

SO/FDIS 4931-

https://standards.iteh.ai/catalog/standards/iso/58363300-cecc-4a05-b42b-41dc539fe326/iso-fdis-4931-1

# FDIS stage

#### ISO/DISFDIS 4931-1:2023(E2024(en)

#### © ISO <u>2023</u>2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: + 41 22 749 01 11

Fax: +41 22 749 09 47

Email<u>E-mail</u>: copyright@iso.org Website: <u>www.iso.org</u>

Published in Switzerland

# iTeh Standards (https://standards.iteh.ai) Document Preview

**ISO/FDIS 4931-1** 

https://standards.iteh.ai/catalog/standards/iso/58363300-cecc-4a05-b42b-41dc539fe326/iso-fdis-4931-1

## Contents

Forew	vord	iv
Introd	luction	v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4 4.1 4.2	Principles Change-oriented perspective Preparing for uncertainty with certainty	4 4
4.3 4.4 4.5 4.6	Synergy between adaptation to and mitigation of climate change Synergy with community and urban resilience Equity Sustainability	5 5
5	Framework	5
6 6.1 6.2 6.3	Identifying changes in climatic impact-drivers General Climatic impact-driver Projected climatic design parameter	6 6
7 7.1 7.2 7.3 7.4 7.5	Identifying resilience limits and decision making on strategies General Identifying gap between existing and required resilience Designing adaptation strategies Identifying resilience limit Decision making on strategies	8 8 11 12
8	Monitoring and optimization	
9https: Annex	Decommissioningloo/standarda/standard	
Annex	B (informative) GWLs that assets with different service lives may experience	20
Annex	c C (informative) Examples of PCDPs of some typical CIDs for building design	21
Annex	x D (informative) Thames Estuary 2100 Plan	23
Annex	E (informative) Typical types of adaptation strategies	27
Annex	x F (informative) Resilience design of Spaulding Rehabilitation Hospital	29
Annex	x G (informative) Design of Qinghai-Tibet Railway embankment adapting to permafr thawing	
Annex	x H (informative) Decommissioning	31
Bibliography		32

#### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 59, *Buildings and civil engineering works*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

### Introduction

Adaptation to climate change has become an urgent need globally. According to the United Nations Environment Programme (UNEP)'s Adaptation Gap Report 2022, "the world must urgently increase efforts to adapt to the impacts of climate change that are already here and to those that are to come".

In the context of global climate change, buildings and civil engineering works with service lives of decades or even centuries will face new climate challenges. These challenges include the increase of frequency and intensity in extreme weather events such as heatwaves, wildfires and floods, as well as chronic changes such as sea level rise. This can result in increase of vulnerability in built assets designed based on the climate of the past decades, risking human health and well-being, and causing economic loss and social impacts. Therefore, adaptation to climate change in buildings and civil engineering works should be considered in a timely manner.

This document provides a design approach called the resilience design adaptive to climate change (RDACC), which offers specific guidance on how to produce buildings and civil engineering works with climate change resilience. It is a method for adaptation to climate change at the engineering level.

The typical actions of RDACC include:

- — identifying changes in climatic impact-drivers;
- — identifying resilience limits and decision making on strategies;
- — monitoring and optimization;
- — decommissioning.

This document is useful to stakeholders including asset owners and users, investors, authorities, standards developers, meteorologists, engineers, architects, manufacturers, builders, and other parties involved in the RDACC.

https://standards.iteh.ai/catalog/standards/iso/58363300-cecc-4a05-b42b-41dc539fe326/iso-fdis-4931-1

## iTeh Standards (https://standards.iteh.ai) Document Preview

https://standards.iteh.ai/catalog/standards/iso/58363300-cecc-4a05-b42b-41dc539fe326/iso-fdis-4931-1

# Buildings and civil engineering works———Principles, framework and guidance for resilience design———

## Part 1: Adaptation to climate change

#### 1 Scope

The document provides principles, framework, and guidance for resilience design adaptive to climate change (RDACC) in buildings and civil engineering works. RDACC is applicable to both new construction and retrofits.

RDACC does not address:

- adaptation to climate change in the production and procurement of building materials, components and devices;
- adaptation to climate change in construction processes;
- climate change mitigation in buildings and civil engineering works;
- — emergency management related to climate change in buildings and civil engineering works.

#### 2 Normative references

There are no normative references in this document.

#### 3 Terms and definitions

#### <u>ISO/FDIS 4931-1</u>

https://standards.iteh.ai/catalog/standards/iso/58363300-cecc-4a05-b42b-41dc539fe326/iso-fdis-4931-1

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— — ISO Online browsing platform: available at <u>https://www.iso.org/obp</u>

— — IEC Electropedia: available at https://www.electropedia.org/

#### 3.1

#### adaptation to climate change

climate change adaptation

process of adjustment to actual or expected *climate* (3.3(3.3)) and its effects

Note 1 to entry: In human systems, adaptation seeks to moderate or avoid harm or exploit beneficial opportunities.

Note 2 to entry: In some natural systems, human intervention can facilitate adjustment to expected climate and its effects.

[SOURCE: ISO 14090:2019, 3.1]

#### 3.2

#### asset

whole building or structure or unit of construction works, or a system or a component or part thereof

[SOURCE: ISO 15686-5:2017, 3.4.1]

#### 3.3

#### climate

statistical description of the weather in terms of the mean and variability of relevant quantities over a period of time ranging from months to thousands or millions of years

[SOURCE: ISO 14050:2020, 3.8.1]

#### 3.4

climate change

change in *climate* (3.3(3.3)) that persists for an extended period, typically decades or longer

[SOURCE: ISO 14050:2020, 3.8.3]

#### 3.5

#### climate change mitigation

human intervention to reduce greenhouse gas emissions or enhance greenhouse gas removals

[SOURCE: ISO 14050:2020, 3.8.6]

iTeh Standards

#### 3.6

#### climate projection

simulated response of the *climate* (3.3(3.3)) system to a scenario of future emissions or concentrations of greenhouse gases (GHGs) and aerosols and changes in land use, generally derived using climate models

[SOURCE: IPCC, 2022]

#### <u>ISO/FDIS 4931-1</u>

3.https://standards.iteh.ai/catalog/standards/iso/58363300-cecc-4a05-b42b-41dc539fe326/iso-fdis-4931-1

#### climatic impact-driver

CID

physical *climate* (3.3(3.3)) system condition (e.g. means, events, extremes) that affects an element of society or ecosystems

[Adapted fromSOURCE: IPCC, 2022, modified]

#### 3.8

#### constraint

factor that makes it harder to plan and implement adaptation actions

[Adapted fromSOURCE: IPCC, 2014, modified]

#### 3.9

#### existing resilience

*resilience* (3.17(3.17)) that an *asset* (3.2(3.2)) currently designed can achieve in face of the *CID* (3.7(3.7)) changing to a certain magnitude

#### 3.10 global climate model GCM

complex mathematical representation of the major *climate* (3.3(3.3)) system components (atmosphere, land surface, ocean, and sea ice) and their interactions

[SOURCE: GFDL]

#### 3.11

#### global warming level

global climate-change emissions relative to pre-industrial levels, expressed as global surface air temperature

[SOURCE: IPCC, 2022]

#### 3.12

#### impact

result of a change or existing condition that may be adverse, neutral or beneficial

[SOURCE: ISO 15392:2019, 3.17]

#### 3.13

#### maladaptation

actions that may lead to increased risk of adverse climate-related outcomes, including via increased greenhouse gas (GHG) emissions, increased or shifted vulnerability to *climate change* (3.4(3.4),), more inequitable outcomes, or diminished welfare, now or in the future

[SOURCE: IPCC, 2022]

#### 3.14

#### projected climatic design parameter PCDP

meteorological parameter for buildings and civil engineering design base on *climate projections* (3.6(3.6))

#### 3.15

#### **Representative Concentration Pathway**

#### RCP

scenarios that include time series of emissions and concentrations of the full suite of greenhouse gases (GHGs) and aerosols and chemically active gases, as well as land use/land cover

[SOURCE: IPCC, 2022]

#### 3.16

#### required resilience

*resilience* (3.17(3.17)) that an *asset* (3.2(3.2)) is desired to have in face of a CID (3.7(3.7))

#### 3.17

#### resilience

adaptive capacity in a complex and changing environment

[SOURCE: ISO 31073:2022, 3.3.39, modified — "of an organization" has been removed.]

© ISO 2024 - All rights reserved

#### 3.18

## resilience design adaptive to climate change RDACC

design approach to produce an *asset* (3.2(3.2)) with *resilience* (3.17(3.17)) to adapt to changing climatic conditions due to *climate change* (3.4(3.4)) throughout its *service life* (3.20(3.19))

#### 3.19

#### resilience limit

maximum magnitude of <u>the CID (3.7</u>) that the asset can adapt to, beyond which there is no feasible strategy

#### 3.20

#### service life

period of time after installation during which a facility or its component parts meet or exceed the performance requirements

[SOURCE: ISO 15686-1:2011, 3.25]

#### 3.21

## Shared Socioeconomic Pathway SSP

different levels of emissions and *climate change* (3.4(3.4)) along the dimension of the *RCPs* (3.15(3.15)) explored against the backdrop of different socio-economic development pathways on the other dimension in a matrix

[SOURCE: IPCC, 2022]

#### **4** Principles

# 4.1 Change-oriented perspective cument Preview

In the context of global climate change, buildings and civil engineering works can face different climatic conditions which are beyond initial anticipations during their service lives. Extreme weather events such as heatwaves and floods are projected to occur more frequently and intensely in some areas, while slow-onset changes such as sea level rise and permafrost thawing will gradually emerge in some areas over time. To address these changes, RDACC should adopt a change-oriented perspective for asset to adapt to future environment.

NOTE See <u>Annex AAnnex A</u> for Global Building Resilience Guidelines capturing principles for incorporating future focused climate risk into building codes and standards.

#### 4.2 Preparing for uncertainty with certainty

Although there are some uncertainties in climate projections, this should not be an excuse for inaction. RDACC should take innovative measures to mitigate the impacts of uncertainties.

#### 4.3 Synergy between adaptation to and mitigation of climate change

RDACC should take into account the synergistic effects of adaptation and mitigation of climate change. Actions which can achieve both adaptation and mitigation should be prioritized<sub>7i</sub> and maladaptation should be avoided.

EXAMPLE Better thermal performance of buildings can reduce energy consumption and provide protection from heatwaves in summer.

4

#### 4.4 Synergy with community and urban resilience

RDACC should work within the framework of community and urban resilience, serving as the fundamental resilience element.

NOTE Improving the drainage capacity of individual buildings is part of a comprehensive approach to dealing with urban waterlogging and stormwater discharge. It demands coordination at community and city levels over, for example, rainwater storage of a building <u>which</u> serves as a cushion for community discharge systems.

#### 4.5 Equity

RDACC should take into account the needs of assets users of all ages, gender, financial means, ethnicities, education, and physical abilities to ensure equitable reduction of risk and vulnerability

#### 4.6 Sustainability

RDACC should be carried out within the framework of sustainable development. Climate, economic, social and environmental factors should be considered when adopting <u>an</u> adaptation strategy.

#### **5** Framework

RDACC involves a series of actions integrated into the asset's lifecycle, including design, operation, and decommissioning phases (see Figure 1 Figure 1):):

— In design phase, identify how the climatic conditions at the asset's location may change during its service life (see <u>Clause 6</u><u>Clause 7</u><u>Clause 7</u><u>Cl</u>

These actions can be applied to a specific project with the following guidelines.

- When no projected climatic design parameter (PCDP) sets are available to quantify magnitude of changes in CIDs at the asset's location, RDACC should start from identifying changes in CIDs (see <u>Clause 6Clause 6).</u>
  - — When the PCDP sets are available, but no resilience limits are specified in current standards, specification, etc., RDACC should start from identifying resilience limits (see <u>7.1</u> to <u>7.4</u><del>7.1-7.4</del>).
  - — When both PCDP sets and resilience limits are available, RDACC can directly start from adaptation strategies design (see 7.37.3) and decision making (see 7.57.5).
- During operation phase, monitor the changes in CIDs and effectiveness of implemented strategies, and embrace the latest climate knowledge and technological advancements to optimize strategies (see <u>Clause 8Clause 8).</u>).
- Decommissioning is required when assets are no longer fit for purpose, and further adaptation is not a viable option (see <u>Clause 9</u><u>Clause 9</u>).