

2022-06-16

ISO/~~DIS~~ FDIS 4250-2:2022(E)

ISO/TC 31/SC 6

Secretariat: SCC

Date: 2022-12-19

Earth-mover tyres and rims ~~—~~ ==

Part ~~2~~: Loads and inflation pressures

Pneumatiques et jantes pour engins de terrassement ~~—~~ ==

Partie ~~2~~: Charges et pressions de gonflage

ITIH STANDARD PREVIEW
(standards.iteh.ai)

ISO/FDIS 4250-2

<https://standards.iteh.ai/catalog/standards/sist/e5dedeeb-ed96-48b2-8d52-462ba6034f63/iso-fdis-4250-2>

FDIS stage

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: + 41 22 749 01 11

Fax: +41 22 749 09 47

~~Email~~E-mail: copyright@iso.org
Website: ~~www.iso.org~~www.iso.org

Published in Switzerland

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 4250-2

<https://standards.iteh.ai/catalog/standards/sist/e5dedeeb-ed96-48b2-8d52-462ba6034f63/iso-fdis-4250-2>

Contents

Foreword	iv
1 Scope	1
2 Normative references.....	1
3 Terms and definitions	1
3.1 Masses.....	1
3.2 Operating conditions	2
4 Special conditions.....	3
5 Selection of tyres for new machine design.....	4
6 Inflation pressures	4
7 Load/inflation tables	4
8 Load capacities for earth-mover tyres used for industrial service	5
Bibliography	28

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/FDIS 4250-2

<https://standards.iteh.ai/catalog/standards/sist/e5dedeeb-ed96-48b2-8d52-462ba6034f63/iso-fdis-4250-2>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 31, *Tyres, rims and valves*, Subcommittee SC 6, *Off-the-road tyres and rims*.

~~ISO 4250 series consists of the following parts which specify the technical elements relating to designations and dimensions of tyres and rims for earth-movers under the general title, 'Earth-mover tyres and rims'~~

~~Part 1: Tyre dimensions and designations~~

~~Part 2: Loads and inflation pressures~~

~~Part 3: Rims~~

This seventh edition cancels and replaces the sixth edition (ISO 4250-2:2017), which has been technically revised.

The main changes are as follows:

Deletion and addition of certain tyre size designations to harmonize with ISO 4250-1 and ISO 4250-3

A list of all parts in the ISO 4250 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

~~Earth-mover tyres and rims — Part 2: Loads and inflation pressures~~

Earth-mover tyres and rims —

Part 2: Loads and inflation pressures

1 Scope

This document gives working definitions of masses and load cycles and specifies tyre loads and reference inflation pressures for tyres primarily intended for earth-mover machines.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4223-1, *Definitions of some terms used in the tyre industry — Part 1: Pneumatic tyres*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 4223-1 and the following apply. ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

NOTE For a list of equivalent terms for tyres, valves and tubes, see ISO 3877-1.

3.1 ~~3.1~~ Masses

3.1.1

maximum load

load of individual tyres determined by the manufacturer's rated gross machine mass (GMM) distribution assigned to each axle, divided by the number of tyres for that axle

Note 1 to entry: The maximum GMM includes operating, optional equipment, special modifications and field modification masses and payload defined in 3.1.1.1 to 3.1.1.5 inclusive.

Note 2 to entry: If tyre ballast is used, this is also included in the determination of GMM.

3.1.1.1

operating mass

actual mass of the base machine with equipment specified by the manufacturer, operator (75 kg), full fuel tank and full lubricating, hydraulic and cooling systems

Note 1 to entry: Net weight is an alternate term for operating mass.

ISO/FDIS 4250-2:2022(E)

3.1.1.2

optional equipment mass

difference in *operating mass* (3.1.1.1)(3.1.1.1) between the optional item and standard item replaced

EXAMPLE Engine, brakes, tyres.

Note 1-to entry:- This includes the operating mass of additional items offered by the manufacturer which are not replacements for standard items (such as cabs, body-liners, sideboards, air-conditioners).

3.1.1.3

mass of special modifications

difference in the *operating mass* (3.1.1.1)(3.1.1.1) of the machine due to modifications not previously covered in *optional equipment mass* (3.1.1.2)(3.1.1.2) that includes additional reinforcements, etc.

3.1.1.4

payload

total mass of the material being carried

3.1.1.5

field modification

operating mass (3.1.1.1)(3.1.1.1) change due to machine alterations made other than by the original manufacturer

EXAMPLE Modifications for additional capacity, reinforcements.

3.2 ~~3.2~~ — Operating conditions

3.2.1

maximum speed

peak velocity attained by the machine

3.2.2

earth-moving haulage service

cycle where a machine self-loads or receives a load from loading equipment, transports it elsewhere and returns unloaded

Note 1-to entry:- Transportation usually occurs over unimproved surfaces at medium speeds, up to 65 km/h and short distances, up to 4 km one way.

Note 2-to entry:- Machines in this category are mainly haulage trucks (dumpers) and tractor-scrappers.

3.2.3

loader service

earth-moving slow speed service where the machine is used to pick up material and move it a short distance away

Note 1-to entry:- Tyre loads fluctuate depending on the conditions involved when the equipment picks up the load.

Note 2-to entry:- Transportation speeds are low, up to 10 km/h and distances are short, usually less than 75 m one way.

Note-3-to entry:- Tyres for loader service may also be used in load-carry service and dozer service.

3.2.4

load-carry service

cycle where the machine, primarily intended for loader service, picks up a load, transports it elsewhere and returns unloaded

Note 1-to entry:- Transportation usually occurs over unimproved surfaces at low speeds, up to 25 km/h, and short distances, up to 600 m. Load capacities for loader and load-and-carry cycles are provided in [Table 24](#), [Table 24](#).

Note 2-to entry:- Machines in this category consist mainly of wheel loaders, log stackers and material-handling equipment.

Note 3-to entry:- Tyre manufacturers should be consulted for specific conditions.

3.2.5

dozer service

condition where a machine is used to move materials (usually earth) by pushing, dragging or grading

Note 1-to entry:- Tyre loads are relatively constant and speeds are low, up to 10 km/h.

Note 2-to entry:- Travel distances vary depending on work situations.

3.2.6

grader service

condition where a machine is used in construction and road maintenance

Note 1-to entry:- Tyre loads are relatively constant during work cycles.

Note 2-to entry:- Grader speeds are slower during working periods, with typical transportation speeds reaching about 40 km/h.

Note 3-to entry:- Travel distances vary depending on the work situations.

3.2.7

creep

movement of equipment at a very low speed

Note 1-to entry:- Speed is commonly not over 120 m in 60 min.

Note 2-to entry:- During creep motion, loads on the tyres are usually very high and consideration shall be given to the type of surface over which the equipment is travelling.

Note 3-to entry:- Tyre manufacturers should be consulted for specific conditions.

3.2.8

drive-away

self-propelled movement of a machine from one location to another under non-working conditions

Note 1-to entry:- This condition is not part of the standard.

Note 2-to entry:- Tyre manufacturers should be consulted for specific conditions.

3.2.9

industrial service

tyres used on industrial vehicles

EXAMPLES-EXAMPLE counterbalanced lift truck, container handler, straddle carrier, aircraft tow tractor, mobile crusher, log stacker

4 Special conditions

For longer hauls and/or speeds in excess of those indicated in [Tables 1 to 23](#), [Tables 1 to 23](#), and drive-away conditions, tyre manufacturers should be consulted for instructions regarding permissible loads and the required inflation pressures.

5 Selection of tyres for new machine design

Selection of size and strength index of the tyre used on each axle shall be based on the highest individual wheel load as determined by gross machine mass (GMM) distribution, including load transfer and the machine application.

Maximum load per tyre shall not be greater than that specified in the applicable tables.

The performance of machines fitted with earth-mover tyres depends on the operating conditions and more particularly on the specific ground pressure which is governed by the inflation pressure. It is therefore advisable to select tyre size on the basis of low inflation pressure.

6 Inflation pressures

6.1 Tyres covered by this document that have a speed symbol A2, ~~10 km~~10 km/h shall not exceed a cold inflation pressure of 1 000 kPa. All other tyres cold inflation pressure shall not exceed 800 kPa. Rim and wheel manufacturers shall be consulted to determine if the rim and wheel are of sufficient strength for the intended service conditions.

6.2 Inflation pressures shown in the load/inflation tables are reference cold inflation pressures and do not include any pressure build-up due to vehicle operation. In practice, the tyre inflation pressure recommended by the different tyre manufacturers can vary according to the reference cold inflation pressure.

6.3 In agreement with tyre manufacturers, inflation pressures can be adjusted to compensate for extreme atmospheric temperature or special vehicle operating conditions.

7 Load/inflation tables

Load/inflation relations for diagonal ply rating marked tyres are given in ~~Tables 1 to 9~~ Tables 1 to 9:

- a) ~~a) Table 1~~ Table 1 - diagonal ply rating marked narrow-base tyres for earth-moving slow speed service, speed symbol A2, 10-km/h (loaded conditions);
- b) ~~b) Table 2~~ Table 2 - diagonal ply rating marked narrow-base tyres for earth-moving service for relatively short hauls, speed symbol B, 50-km/h;
- c) ~~c) Table 3~~ Table 3 - diagonal ply rating marked wide-base tyres for earth-moving slow speed service, speed symbol A2, 10-km/h (loaded conditions);
- d) ~~d) Table 4~~ Table 4 - diagonal ply rating marked wide-base and 75 series tyres for earth-moving service for relatively short hauls, speed symbol B, 50-km/h;
- e) ~~e) Table 5~~ Table 5 - diagonal ply rating marked 65 series tyres for earth-moving service for relatively short hauls, speed symbol B, 50-km/h;
- f) ~~f) Table 6~~ Table 6 - diagonal ply rating marked 65, 70, 80 and 85-series tyres for earth-moving slow speed service, speed symbol A2, 10-km/h;
- g) ~~g) Table 7~~ Table 7 - diagonal ply rating marked tyres in grader service, speed symbol A8, 40-km/h;
- h) ~~h) Table 8~~ Table 8 - diagonal ply rating marked tyres, speed symbol A2, 10-km/h;
- i) ~~i) Table 9~~ Table 9 - diagonal ply rating marked tyres for compactor service, speed symbol A2, 10-km/h;

Load/inflation relations for symbol-marked radial ply tyres are given in ~~Tables 10 to 23~~ Tables 10 to 23:

- j) ~~j) Table 10~~ Table 10 - 70, 75 and 80 series radial ply tyres for earth-moving slow speed service, speed symbol A2, 10 km/h;
- k) ~~k) Table 11~~ Table 11 - 70, 75 and 80 series radial ply tyres for earth-moving haulage service, speed symbol B, 50 km/h;
- l) ~~l) Table 12~~ Table 12 - symbol-marked narrow-base radial tyres, speed symbol A2, 10 km/h (loaded conditions);
- m) ~~m) Table 13~~ Table 13 - symbol-marked wide-base radial tyres, speed symbol A2, 10 km/h (loaded conditions);
- n) ~~n) Table 14~~ Table 14 - symbol-marked narrow-base radial tyres, speed symbol B, 50 km/h;
- o) ~~o) Table 15~~ Table 15 - symbol-marked wide-base and 75 series radial tyres, speed symbol B, 50 km/h;
- p) ~~p) Table 16~~ Table 16 - symbol-marked 90 series radial tyres, speed symbol B, 50 km/h;
- q) ~~q) Table 17~~ Table 17 - symbol-marked 80 series radial tyres, speed symbol B, 50 km/h;
- r) ~~r) Table 18~~ Table 18 - symbol-marked 65, 75 and 80 series radial tyres, speed symbol B, 50 km/h;
- s) ~~s) Table 19~~ Table 19 - symbol-marked 65, 75 and 80 series radial tyres, speed symbol A2, 10 km/h;
- t) ~~t) Table 20~~ Table 20 - radial tyres for compactor service, speed symbol A2, 10 km/h (loaded conditions);
- u) ~~u) Table 21~~ Table 21 - symbol-marked radial tyres in grader service, speed symbol A8, 40 km/h;
- v) ~~v) Table 22~~ Table 22 - symbol-marked 65 series metric radial tyres for earth-moving slow speed service, speed symbol A2, 10 km/h;
- w) ~~w) Table 23~~ Table 23 - symbol-marked 65 series metric radial tyres for earth-moving service for relatively short hauls, speed symbol B, 50 km/h;

8 Load capacities for earth-mover tyres used for industrial service

For industrial service, it is recommended to use specific tyres designed for this purpose.

If tyres designed for earth-mover application are used, a formal approval from the tyre and wheel manufacturers is required as not all the earth-mover tyres can be used in such conditions.

Consult the tyre and rim manufacturers for applicable load capacities.

Table 1 — Diagonal ply rating marked narrow-base tyres for earth-moving slow speed service, speed symbol A2, 10 km/h (loaded conditions)

Tyre size designation	Ply rating	Load index	Load ^{a b} kg	Inflation pressure ^b kPa
12.00—20	14	164	5_000	600
	16	167	5_450	700
	20	171	6_150	825
	24	175	6_900	1_000
12.00—24 and	8	156	4_000	325
	14	168	5_600	575

ISO/FDIS 4250-2:2022(E)

Tyre size designation	Ply rating	Load index	Load ^{a b} kg	Inflation pressure ^b kPa
12.00—25	16	171	6-150	675
	18	173	6-500	750
	20	175	6-900	825
13.00—24 and 13.00—25	8	159	4-375	300
	12	168	5-600	450
	18	176	7-100	675
	20	178	7-500	750
	22	180	8-000	825
14.00—20	20	178	7-500	700
	24	182	8-500	850
14.00—24 and 14.00—25	8	163	4-875	275
	10	168	5-600	350
	12	172	6-300	425
	16	177	7-300	550
	20	182	8-500	700
	24	186	9-500	850
	28	188	10-000	925
16.00—21	20	183	8-750	550
	24	187	9-750	650
	28	190	10-600	775
16.00—24 and 16.00—25	12	176	7-100	325
	16	181	8-250	425
	20	187	9-750	550
	24	190	10-600	650
	28	193	11-500	750
	32	196	12-500	875
	36	199	13-600	975
18.00—24 and 18.00—25	12	181	8-250	275
	16	188	10-000	375
	20	193	11-500	475
	24	196	12-500	550
	28	199	13-600	650
	32	202	15-000	750
	36	204	16-000	850
	40	206	17-000	950
18.00—33	24	201	14-500	550
	28	204	16-000	650
	32	207	17-500	750

Tyre size designation	Ply rating	Load index	Load ^{a b} kg	Inflation pressure ^b kPa
	36	209	18_500	850
18.00—49	24	209	18_500	550
	28	212	20_000	650
	32	215	21_800	750
21.00—24 and 21.00—25	16	194	11_800	325
	20	198	13_200	400
	24	202	15_000	500
	28	205	16_500	575
21.00—35	28	211	19_500	575
	32	214	21_200	650
	36	217	23_000	750
	40	219	24_300	825
	44	220	25_000	900
21.00—49	28	218	23_600	575
	32	220	25_000	650
	36	223	27_250	750
	40	225	29_000	825
	44	227	30_750	900
24.00—25	24	208	18_000	425
	30	212	20_000	525
24.00—29	24	210	19_000	425
	30	215	21_800	525
24.00—35	36	222	26_500	650
	42	225	29_000	750
	48	228	31_500	850
	54	231	34_500	975
24.00—43	36	226	30_000	650
	42	229	32_500	750
	48	231	34_500	850
24.00—49	36	229	32_500	650
	42	231	34_500	750
	48	234	37_500	850
27.00—33	24	216	22_400	350
	30	221	25_750	450
	36	225	29_000	550
27.00—49	36	233	36_500	575
	42	236	40_000	675
	48	239	43_750	775

Tyre size designation	Ply rating	Load index	Load ^{a b} kg	Inflation pressure ^b kPa
30.00—51	40	240	45-000	575
	46	243	48-750	650
	52	246	53-000	750
33.00—51	42	245	51-500	550
	50	248	56-000	650
	58	251	61-500	750
36.00—51	42	249	58-000	500
	50	253	65-000	600
	58	256	71-000	675
40.00—57	52	260	80-000	550
	60	263	87-500	650
	68	265	92-500	725

^a— For stationary service conditions, the loads in this table may be increased up to 60 % with no increase in inflation pressure.
^b— For special equipment with a high centre of gravity, consult the tyre manufacturer.

Table 2 — Diagonal ply rating marked narrow-base tyres for earth-moving service for relatively short hauls, speed symbol B, 50 km/h

Tyre size designation	Ply rating	Load index	Load ^a kg	Inflation pressure kPa
12.00—20	14	144	2-800	425
	16	146	3-000	475
12.00—24 and 12.00—25	8	135	2-180	225
	14	146	3-000	375
	16	149	3-250	450
	18	152	3-550	500
	20	154	3-750	550
13.00—24 and 13.00—25	8	138	2-360	200
	12	146	3-000	300
	18	155	3-875	450
	20	156	4-000	500
	22	158	4-250	550
14.00—20	16	153	3-650	375
	20	157	4-125	475
14.00—24 and 14.00—25	8	141	2-575	175
	10	146	3-000	225
	12	150	3-350	275
	16	156	4-000	375
	20	161	4-625	475
	24	165	5-150	575