



Designation: B746/B746M – 02 (Reapproved 2012)

Standard Specification for Corrugated Aluminum Alloy Structural Plate for Field-Bolted Pipe, Pipe-Arches, and Arches¹

This standard is issued under the fixed designation B746/B746M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

1.1 This specification covers corrugated aluminum alloy structural plate used in the construction of pipe, pipe-arches, arches, underpasses, box culverts, and special shapes for field assembly. Appropriate fasteners are also described. The pipe, arches, and other shapes are generally used for drainage purposes, pedestrian and vehicular underpasses, and utility tunnels. Aluminum box culvert shapes are covered in Specification [B864/B864M](#).

1.2 This specification does not include requirements for bedding, backfill, or the relationship between earth cover load and plate thickness of the pipe. Experience has shown that the successful performance of this product depends upon the proper selection of plate thickness, type of bedding and backfill, controlled manufacture in the plant, and care in the installation. The purchaser must correlate the above factors and also the corrosion and abrasion requirements of the field installation with the plate thickness. The structural design of corrugated aluminum structural plate pipe and the proper installation procedures are given in Practices [B790/B790M](#) and [B789/B789M](#), respectively. A procedure for using life-cycle cost analysis techniques to evaluate alternate drainage system designs using corrugated metal pipe is given in Practice [A930](#).

1.3 The values stated in either inch-pound units or SI units are to be regarded separately as standard. The values stated in each system are not exact equivalents; therefore, each system shall be used independently of the other.

2. Referenced Documents

2.1 ASTM Standards:²

¹ This specification is under the jurisdiction of ASTM Committee B07 on Light Metals and Alloys and is the direct responsibility of Subcommittee B07.08 on Corrugated Aluminum Pipe and Corrugated Aluminum Structural Plate.

Current edition approved May 1, 2012. Published June 2012. Originally approved in 1989. Last previous edition approved in 2007 as B746/B746M-02 (2007). DOI: 10.1520/B0746_B0746M-02R12.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

- [A153/A153M](#) Specification for Zinc Coating (Hot-Dip) on Iron and Steel Hardware
- [A307](#) Specification for Carbon Steel Bolts and Studs, 60 000 PSI Tensile Strength
- [A325](#) Specification for Structural Bolts, Steel, Heat Treated, 120/105 ksi Minimum Tensile Strength
- [A449](#) Specification for Hex Cap Screws, Bolts and Studs, Steel, Heat Treated, 120/105/90 ksi Minimum Tensile Strength, General Use
- [A563](#) Specification for Carbon and Alloy Steel Nuts
- [A563M](#) Specification for Carbon and Alloy Steel Nuts (Metric)
- [A930](#) Practice for Life-Cycle Cost Analysis of Corrugated Metal Pipe Used for Culverts, Storm Sewers, and Other Buried Conduits
- [B209](#) Specification for Aluminum and Aluminum-Alloy Sheet and Plate
- [B209M](#) Specification for Aluminum and Aluminum-Alloy Sheet and Plate (Metric)
- [B221](#) Specification for Aluminum and Aluminum-Alloy Extruded Bars, Rods, Wire, Profiles, and Tubes -022012
- [B221M](#) Specification for Aluminum and Aluminum-Alloy Extruded Bars, Rods, Wire, Profiles, and Tubes (Metric)
- [B666/B666M](#) Practice for Identification Marking of Aluminum and Magnesium Products
- [B695](#) Specification for Coatings of Zinc Mechanically Deposited on Iron and Steel
- [B789/B789M](#) Practice for Installing Corrugated Aluminum Structural Plate Pipe for Culverts and Sewers
- [B790/B790M](#) Practice for Structural Design of Corrugated Aluminum Pipe, Pipe-Arches, and Arches for Culverts, Storm Sewers, and Other Buried Conduits
- [B864/B864M](#) Specification for Corrugated Aluminum Box Culverts
- [E29](#) Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications
- [F467](#) Specification for Nonferrous Nuts for General Use
- [F467M](#) Specification for Nonferrous Nuts for General Use (Metric)
- [F468](#) Specification for Nonferrous Bolts, Hex Cap Screws, and Studs for General Use

- F468M** Specification for Nonferrous Bolts, Hex Cap Screws, and Studs for General Use (Metric)
- F568M** Specification for Carbon and Alloy Steel Externally Threaded Metric Fasteners (Metric) (Withdrawn 2012)³
- F593** Specification for Stainless Steel Bolts, Hex Cap Screws, and Studs
- F594** Specification for Stainless Steel Nuts
- F738M** Specification for Stainless Steel Metric Bolts, Screws, and Studs
- F836M** Specification for Style 1 Stainless Steel Metric Nuts (Metric)

2.2 American National Standards:⁴

- B18.2.1** Square and Hex Bolts and Screws, Inch Series
- B18.2.2** Square and Hex Nuts
- B18.2.3.6M** Bolts, Metric, Heavy Hex
- B18.2.4.6M** Hex Nuts, Heavy, Metric

3. Terminology

3.1 Definitions of Terms Specific to This Standard:

3.1.1 *arch*—a part circle shape spanning an open invert between the footings on which it rests.

3.1.2 *box culvert*—a rectangular box with short-radius in upper corners and a long-radius crown. It can be with full invert or with footing pads.

3.1.3 *fabricator*—the producer of the components for the finished product.

3.1.4 *flat plate*—sheet or plate used to fabricate structural plate.

3.1.5 *manufacturer*—the producer of the flat plate and accessories.

3.1.6 *pipe*—a conduit having full circular shape; also, in a general context, all structure shapes covered by this specification.

3.1.7 *pipe-arch*—an arch shape with an approximate semi-circular crown, small-radius corners, and large-radius invert.

3.1.8 *pipe, horizontal ellipse*—an elliptically shaped pipe with the horizontal diameter approximately 20 % greater than the nominal diameter.

3.1.9 *pipe, vertically elongated*—an elliptically shaped pipe with the vertical diameter up to 10 % greater than the nominal diameter.

3.1.10 *purchaser*—the purchaser of the finished product.

3.1.11 *special shape*—a shape, other than described elsewhere in this section, suitable for fabrication with structural plate.

3.1.12 *structural plate*—a corrugated and curved plate which is field assembled with other structural plates to form the required structure.

3.1.13 *vehicular underpass*—a high arch shape with an approximate semicircular crown, large-radius sides, small-radius corners between sides and invert, and large-radius invert.

4. Ordering Information

4.1 Orders for material under this specification shall include the following information as necessary to adequately describe the desired product:

4.1.1 Name of material (aluminum alloy structural plate and accessories),

4.1.2 Description of structure (see Section 3),

4.1.3 Number of structures,

4.1.4 ASTM designation and year of issue, as B746—__ for inch-pound units or B746M—__ for SI units.

4.1.5 Dimensions of structure (diameter or span and rise, and length, etc.) (see 7.2),

4.1.6 Thickness of plate (see 7.1),

4.1.7 Type of bolts; whether aluminum, stainless steel, or steel bolts are required or permitted. If not specified, steel bolts and nuts shall be furnished (see 5.3 and Note 2),

4.1.8 End treatment (bevel, skew, grade or slope corrections, or other special provision if required by the project plans or specifications),

4.1.9 Special requirements (including extrusion reinforcement locations and shapes), if required, and

4.1.10 Certification, if required.

NOTE 1—Typical ordering descriptions are as follows: (1) Structural plates and fasteners for two aluminum alloy structural plate pipes, per ASTM B746—__, 180-in. dia., 0.100-in. plate thickness, each 140-ft nominal centerline length with end treatment as shown on plans. (2) Structural plates and fasteners for one aluminum alloy structural plate pipe arch, per ASTM B746—__, 3860 mm span by 2460 mm rise, 3.81 mm plate thickness, 27.0 m nominal centerline length with square ends.

5. Materials

5.1 *Flat Plate*—Insofar as applicable, flat plate shall conform to the requirements of Specification B209 or B209M. The plates shall be fabricated from alloy 5052-H141. The mechanical properties for alloy 5052-H141 shall conform to the requirements of Table 1.

5.2 *Extrusions*—The extrusions for circumferential or longitudinal stiffeners, or secondary structural components, shall

TABLE 1 Mechanical Properties of Aluminum Structural Plate, Alloy 5052-H141^A

Specified Thickness		Tensile Strength, min		Yield Strength (0.2 % offset), min		Elongation, % min in 2 in. or 50 mm
in.	mm	ksi	MPa	ksi	MPa	
0.100–0.150	2.54–3.81	35.5	245	24.0	165	6
0.175–0.250	4.44–6.35	34.0	235	24.0	165	8

^A To determine conformance with this specification, each value for tensile strength and for yield strength shall be rounded to the nearest 0.1 ksi (1 MPa) and each value for elongation to the nearest 0.5%, both in accordance with the rounding method of Practice E29.