

---

---

**Coating powders —**

**Part 5:**

**Determination of flow properties of a  
powder/air mixture**

*Poudres pour revêtement —*

**iTEH Standards**

*Partie 5: Détermination de l'aptitude à la fluidisation d'un mélange  
poudre/air*

**(<https://standards.iteh.ai>)**  
**Document Preview**

[ISO 8130-5:2021](#)

<https://standards.iteh.ai/catalog/standards/iso/2c08a595-ec36-4057-a609-b14404d72a62/iso-8130-5-2021>



Reference number  
ISO 8130-5:2021(E)

**iTeh Standards**  
**(<https://standards.iteh.ai>)**  
**Document Preview**

[ISO 8130-5:2021](#)

<https://standards.iteh.ai/catalog/standards/iso/2c08a595-ec36-4057-a609-b14404d72a62/iso-8130-5-2021>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

## Contents

	Page
<b>Foreword</b>	<b>iv</b>
<b>1 Scope</b>	<b>1</b>
<b>2 Normative references</b>	<b>1</b>
<b>3 Terms and definitions</b>	<b>1</b>
<b>4 Principle</b>	<b>1</b>
<b>5 Apparatus</b>	<b>1</b>
<b>6 Sampling</b>	<b>3</b>
<b>7 Procedure</b>	<b>4</b>
7.1 Calibration of apparatus	4
7.2 Determination of flow properties	4
<b>8 Expression of results</b>	<b>4</b>
<b>9 Precision</b>	<b>5</b>
<b>10 Test report</b>	<b>5</b>

# iTeh Standards

## (<https://standards.iteh.ai>)

### Document Preview

[ISO 8130-5:2021](#)

<https://standards.iteh.ai/catalog/standards/iso/2c08a595-ec36-4057-a609-b14404d72a62/iso-8130-5-2021>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 35, *Paints and varnishes*, Subcommittee SC 9, *General test methods for paints and varnishes*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 139, *Paints and varnishes*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 8130-5:1992), which has been technically revised. The main changes compared to the previous edition are as follows:

- the scope has been revised editorially;
- Annex A has been deleted;
- [Clause 3](#) on terms and definitions has been added;
- requirements for test temperature and humidity have been introduced;
- the text has been editorially revised and the normative references have been updated.

A list of all parts in the ISO 8130 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html)

## Coating powders —

### Part 5: Determination of flow properties of a powder/air mixture

#### 1 Scope

This document specifies a method for estimating the flow properties of a mixture of coating powder and air.

The results obtained are influenced by the composition of the coating powder, its density, particle size distribution and particle shape, together with the tendency of the particles to agglomerate and to accept a charge.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8130-14, *Coating powders — Part 14: Vocabulary*

ISO 15528, *Paints, varnishes and raw materials for paints and varnishes — Sampling*

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8130-14 apply.

<https://standards.iteh.ai/catalog/standards/iso/2c08a595-ec36-4057-a609-b14404d72a62/iso-8130-5-2021>

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

#### 4 Principle

A specified quantity of coating powder is placed in a vessel and is fluidized with clean dry air under known conditions of temperature, humidity and atmospheric pressure. The height of the powder during and after fluidization is measured and the mass at which the fluidized powder flows through a specified orifice during a specified interval of time is then determined.

The measurements are used to calculate the fluidization factor,  $\phi$ , and the powder flow rate,  $R$ , which together define the transport and spraying characteristics of the powder.

#### 5 Apparatus

Ordinary laboratory apparatus, together with the following.

**5.1 Apparatus for the determination of flow properties**, consisting of a fluidization vessel with a circular opening in the wall, a device for measuring the height of powder in the vessel and a collecting receptacle for weighing the amount of powder that flows through the orifice.

An example of a suitable apparatus is shown in [Figure 1](#).

A typical apparatus consists of the elements described in [5.1.1](#) to [5.1.3](#).

**5.1.1 Vessel for fluidizing the powder (vessel A)**, outer diameter approximately 110 mm, inner diameter approximately 100 mm, height not less than approximately 200 mm, for example made of transparent poly(methyl methacrylate) and having a bottom made of a suitable material of uniform porosity and a maximum pore size of approximately 40 µm diameter.

To avoid difficulties when cleaning the bottom of the vessel or due to plugging, it is recommended that unit G is removable (e.g. by a screw joint) for air admission (beneath the porous bottom of the container A).

NOTE A disc of 5 mm thickness capable of passing air at a rate of approximately  $(200 \pm 10)$  l/h under a pressure of 5 kPa above atmospheric has been found to be satisfactory.

A 4 mm-diameter circular opening D that can be closed with stopper E shall be situated in the wall of the vessel, 10 mm above the top of the porous disc.

**5.1.2 Air regulation unit B**, with flowmeter F for adjusting the air flow.

**5.1.3 Container C**, sufficiently large to collect the powder discharged during measurement of the flow factor (see [Figure 1](#)).

iTeh Standards  
(<https://standards.iteh.ai>)  
Document Preview

**5.2 Clean dry compressed air.**

**5.3 Timer**, accurate to 1 s.

**5.4 Analytical balance**, of capacity 500 g, capable of weighing to 0,1 g.

**5.5 Ruler**, preferably made of metal, graduated in millimetres.

**5.6 Spatula.**