



International
Standard

ISO 4064-1

**Water meters for cold potable water
and hot water —**

Part 1:

**Metrological and technical
requirements**

Compteurs d'eau potable froide et d'eau chaude —

Partie 1: Exigences métrologiques et techniques

**Fifth edition
2024-12**

International Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 4064-1:2024](https://standards.iteh.ai/catalog/standards/iso/d0489891-d08e-4499-8ce4-ea0f8fbfb041/iso-4064-1-2024)

<https://standards.iteh.ai/catalog/standards/iso/d0489891-d08e-4499-8ce4-ea0f8fbfb041/iso-4064-1-2024>

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 4064-1:2024

<https://standards.iteh.ai/catalog/standards/iso/d0489891-d08e-4499-8ce4-ea0f8fbfb041/iso-4064-1-2024>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
3.1 Water meter and its constituents.....	2
3.2 Metrological characteristics.....	5
3.3 Operating conditions.....	7
3.4 Test conditions.....	8
3.5 Electronic and electrical equipment.....	10
4 Metrological requirements	11
4.1 Values of Q_1 , Q_2 , Q_3 , and Q_4	11
4.2 Accuracy class and maximum permissible error.....	12
4.2.1 General.....	12
4.2.2 Accuracy class 1 water meters.....	12
4.2.3 Accuracy class 2 water meters.....	12
4.2.4 Meter temperature classes.....	12
4.2.5 Water meters with separable calculator and measurement transducer.....	13
4.2.6 Relative error of indication.....	13
4.2.7 Reverse flow.....	13
4.2.8 Water temperature and water pressure.....	13
4.2.9 Absence of flow or of water.....	13
4.2.10 Static pressure.....	13
4.3 Requirements for meters and ancillary devices.....	13
4.3.1 Connections between electronic parts.....	13
4.3.2 Adjustment device.....	14
4.3.3 Correction device.....	14
4.3.4 Calculator.....	14
4.3.5 Indicating device.....	14
4.3.6 Ancillary devices.....	14
5 Water meters equipped with electronic devices	15
5.1 General requirements.....	15
5.2 Power supply.....	16
5.2.1 General.....	16
5.2.2 External power supply.....	16
5.2.3 Non-replaceable battery.....	16
5.2.4 Replaceable battery.....	17
6 Technical requirements	17
6.1 Materials and construction of water meters.....	17
6.2 Adjustment and correction.....	18
6.3 Installation conditions.....	18
6.4 Rated operating conditions.....	19
6.5 Pressure loss.....	19
6.6 Marks and inscriptions.....	20
6.7 Indicating device.....	21
6.7.1 General requirements.....	21
6.7.2 Types of indicating device.....	22
6.7.3 Verification devices — First element of an indicating device — Verification scale interval.....	23
6.8 Protection devices.....	24
6.8.1 General.....	24
6.8.2 Electronic sealing devices.....	24
7 Metrological controls	25
7.1 Reference conditions.....	25

ISO 4064-1:2024(en)

7.2	Type evaluation and approval.....	25
7.2.1	External examination.....	25
7.2.2	Number of samples.....	25
7.2.3	Errors (of indication).....	26
7.2.4	Repeatability.....	26
7.2.5	Overload water temperature.....	26
7.2.6	Durability.....	26
7.2.7	Interchange error.....	27
7.2.8	Static magnetic field.....	27
7.2.9	Documentation.....	27
7.2.10	Type approval certificate.....	28
7.2.11	Modification of an approved type.....	28
7.2.12	Type evaluation of a water meter with electronic devices.....	29
7.3	Initial verification.....	29
Annex A (normative) Performance tests for water meters with electronic devices.....		31
Annex B (informative) Checking facilities.....		33
Annex C (informative) Permissible errors in service and subsequent verification.....		37
Annex D (normative) Requirements for software-controlled water meters.....		38
Bibliography.....		46

iTeh Standards (<https://standards.iteh.ai>) Document Preview

[ISO 4064-1:2024](https://standards.iteh.ai/catalog/standards/iso/d0489891-d08e-4499-8ce4-ea0f8fbfb041/iso-4064-1-2024)

<https://standards.iteh.ai/catalog/standards/iso/d0489891-d08e-4499-8ce4-ea0f8fbfb041/iso-4064-1-2024>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 30, *Measurement of fluid flow in closed conduits*, Subcommittee SC 7, *Volume methods including water meters* and OIML Technical Subcommittee TC 8/SC 5, *Water meters*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 92, *Water meters*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This fifth edition of ISO 4064-1 cancels and replaces the fourth edition (ISO 4064-1:2014), which has been technically revised.

The main changes are as follows:

- a few editorial and technical changes were done throughout the document.

This edition of ISO 4064-1 is identical to the corresponding edition of OIML R 49-1, which has been issued concurrently. OIML R 49-1 was approved for final publication by the International Committee of Legal Metrology at its 59th meeting in October 2024. It will be submitted to the International Conference on Legal Metrology in 2025 for formal sanction.

A list of all parts in the ISO 4064 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Water meters for cold potable water and hot water —

Part 1: Metrological and technical requirements

1 Scope

This document specifies the metrological and technical requirements for water meters for cold potable water and hot water flowing through a fully charged, closed conduit. These water meters incorporate devices which indicate the accumulated volume.

In addition to water meters based on mechanical principles, this document applies to devices based on electrical or electronic principles, and mechanical principles incorporating electronic devices, used to measure the volume of cold potable water and hot water.

This document also applies to electronic ancillary devices. Ancillary devices are optional. However, it is possible for national or regional regulations to render some ancillary devices mandatory in relation to the utilization of water meters.

NOTE Any national regulations apply in the country of use.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4064-2:2024|OIML R 49-2:2024, *Water meters for cold potable water and hot water — Part 2: Test methods*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

NOTE 1 This terminology conforms to that used in ISO/IEC Guide 99:2007|OIML V 2-200:2012^[1], OIML V 1^[8] and OIML D 11^[9]. Modified versions of some terms defined in References ^[1], ^[8] and ^[9] are listed here.

NOTE 2 The following terms are referenced in the other parts of the ISO 4064| OIML R 49 series but are not cited within the main body of this document: *tariff control device* (3.1.9), *pre-setting device* (3.1.10), *meter for two constant partners* (3.1.12), *in-line meter* (3.1.13), *cartridge meter connection interface* (3.1.21), *meter with exchangeable metrological module* (3.1.22), *connection interface for meters with exchangeable metrological modules* (3.1.24), *non-adjustable water meter* (3.1.25), *adjustable water meter* (3.1.26), *initial intrinsic error* (3.2.7), *resolution of a displaying device* (3.2.14), *overload flow rate* (3.3.3), *transitional flow rate* (3.3.4), *combination meter changeover flow rate* (3.3.6), *minimum admissible temperature* (3.3.7), *maximum admissible temperature* (3.3.8), *working pressure* (3.3.11), *test flow rate* (3.3.13), *nominal diameter* (3.3.14), *temperature stability* (3.4.8), *preconditioning* (3.4.9), *recovery* (3.4.11), *automatic checking facility* (3.5.5), *permanent automatic checking facility type P automatic checking facility* (3.5.6), *intermittent automatic checking facility type I automatic checking facility* (3.5.7), *non-automatic checking facility type N checking facility* (3.5.8).

NOTE 3 Attention is drawn to the fact that the term "verification" or "initial verification" is equivalent to the term "conformity assessment" in the context of application of the European Measuring Instruments Directive.

3.1 Water meter and its constituents

3.1.1

water meter

instrument intended to measure, memorize, and display the volume of water passing through the *measurement transducer* (3.1.2) at *metering conditions* (3.2.11)

Note 1 to entry: A water meter includes at least a measurement transducer, a calculator (including adjustment or correction devices, if present) and an indicating device. These three devices can be in different housings.

Note 2 to entry: A water meter may be a combination meter (see 3.1.16).

Note 3 to entry: In this International Standard, a water meter is also referred to as a "meter".

3.1.2

measurement transducer

part of the meter that transforms the *flow rate* (3.3.1) or volume of water to be measured into signals which are passed to the *calculator* (3.1.4) and includes the *sensor* (3.1.3)

Note 1 to entry: The measurement transducer may function autonomously or use an external power source and may be based on a mechanical, electrical or electronic principle.

3.1.3

sensor

element of a meter that is directly affected by a phenomenon, body or substance carrying a quantity to be measured

[SOURCE: ISO/IEC Guide 99:2007|OIML V 2-200:2012 (VIM), 3.8, modified — "meter" replaces "measuring system"; original note to entry removed; original examples removed, "Note 1 to entry" added.]

Note 1 to entry: For a water meter, the sensor may be a disc, piston, wheel or turbine element, the electrodes on an electromagnetic meter, or another element. The element senses the flow rate or volume of water passing through the meter and is referred to as a "flow sensor" or "volume sensor".

3.1.4

calculator

part of the meter that transforms the output signals from the *measurement transducer(s)* (3.1.2) and, possibly, from associated measuring instruments and stores the results in memory until they are used

Note 1 to entry: The gearing is considered to be the calculator in a mechanical meter.

Note 2 to entry: The calculator may be capable of communicating both ways with ancillary devices.

3.1.5

indicating device

part of the meter that provides an indication corresponding to the volume of water passing through the meter

Note 1 to entry: For the definition of the term "indication", see ISO/IEC Guide 99:2007|OIML V 2-200:2012 (VIM), 4.1.

Note 2 to entry: In this International Standard, the volume of water passing through the meter refers to the accumulated volume.

3.1.6

adjustment device

part of the meter that allows an adjustment of the meter such that the error curve of the meter is generally shifted parallel to itself to fit in the envelope of the *maximum permissible error(s)* (3.2.5)

Note 1 to entry: For the definition of the term "adjustment of a measuring system", see ISO/IEC Guide 99:2007|OIML V 2-200:2012 (VIM), 3.11.

3.1.7

correction device

device connected to or incorporated in the meter for automatic correction of the volume of water at *metering conditions* (3.2.11), by taking into account the *flow rate* (3.3.1) and/or the characteristics of the water to be measured and the pre-established calibration curves

Note 1 to entry: For the definition of the term “correction”, see ISO/IEC Guide 99:2007|OIML V 2-200:2012 (VIM), 2.53.

3.1.8

ancillary device

device intended to perform a specific function, directly involved in elaborating, transmitting or displaying measured values

Note 1 to entry: For the definition of “measured value”, see ISO/IEC Guide 99:2007|OIML V 2-200:2012 (VIM), 2.10.

Note 2 to entry: The main ancillary devices are:

- a) zero-setting device;
- b) price-indicating device;
- c) repeating indicating device;
- d) printing device;
- e) memory device;
- f) tariff control device;
- g) pre-setting device;
- h) self-service device;
- i) flow sensor movement detector (for detecting movement of the flow sensor before this is clearly visible on the indicating device);
- j) remote or automatic reading device (which may be incorporated permanently or added temporarily).

Note 3 to entry: Depending on national regulations, ancillary devices may be subject to legal metrological control.

<https://standards.iteh.ai/catalog/standards/iso/d0489891-d08e-4499-8ce4-ea0f8fbfb041/iso-4064-1-2024>

3.1.9

tariff control device

device that allocates measured values into different registers depending on tariff or other criteria, each register having the possibility to be read individually

3.1.10

pre-setting device

device that permits the selection of the quantity of water to be measured and which automatically stops the flow of water after the selected quantity has been measured

3.1.11

associated measuring instrument

instrument connected to the *calculator* (3.1.4) or the *correction device* (3.1.7) for measuring a quantity, characteristic of water, with a view to making a correction and/or a conversion

3.1.12

meter for two constant partners

meter that is permanently installed and only used for deliveries from one supplier to one customer

3.1.13

in-line meter

type of meter that is fitted into a closed conduit by means of the meter end connections provided

Note 1 to entry: The end connections may be flanged or threaded.

3.1.14

complete meter

meter whose *measurement transducer* (3.1.2), *calculator* (3.1.4), and *indicating device* (3.1.5) are not separable

3.1.15

combined meter

meter whose *measurement transducer* (3.1.2), *calculator* (3.1.4), and *indicating device* (3.1.5) are separable

3.1.16

combination meter

meter comprising one large meter, one small meter, and a changeover device that, depending on the magnitude of the *flow rate* (3.3.1) passing through the meter, automatically directs the flow through either the small or the large meter, or both

Note 1 to entry: The meter reading is obtained from two independent totalizers, or from one totalizer which adds up the values from both meters.

3.1.17

equipment under test

EUT

complete meter (3.1.14), sub-assembly or *ancillary device* (3.1.8) that is subjected to a test

3.1.18

concentric meter

type of meter that is fitted into a closed conduit by means of a manifold

Note 1 to entry: The inlet and outlet passages of the meter and the manifold are coaxial at the interface between them.

3.1.19

concentric meter manifold

pipe fitting specific to the connection of a *concentric meter* (3.1.18)

3.1.20

cartridge meter

type of meter that is fitted into a closed conduit by means of an intermediate fitting called a connection interface

Note 1 to entry: The inlet and outlet passages of the meter and the connection interface are either concentric or axial as specified in ISO 4064-4^[5].

3.1.21

cartridge meter connection interface

pipe fitting specific to the connection of an axial or concentric *cartridge meter* (3.1.20)

3.1.22

meter with exchangeable metrological module

meter comprising a connection interface and an *exchangeable metrological module* (3.1.23) from the same *type approval* (3.4.13)

3.1.23

exchangeable metrological module

self-contained module comprising a *measurement transducer* (3.1.2), a *calculator* (3.1.4) and an *indicating device* (3.1.5)

3.1.24

connection interface for meters with exchangeable metrological modules

pipe fitting specific to the connection of exchangeable metrological modules

3.1.25

non-adjustable water meter

water meter (3.1.1) whose indication cannot be altered in any way (e.g. without changing the internal dimensions and/or method of operation), and which has no *adjustment device* (3.1.6) or *correction device* (3.1.7).

Note 1 to entry: This category should also include mechanical meters with an internal adjustment device where the adjustment cannot be altered at initial verification stage as the meter would need to be dismantled.

Note 2 to entry: The meter should not have a correction device, *i.e.* the indicating device of the meter should either be purely mechanical or be electronic but with a constant multiplying factor applied to the indication and set to the same value for all meters (such as a device which counts the number of rotations of the shaft and multiplies by a fixed value to give total volume passed).

3.1.26

adjustable water meter

water meter (3.1.1) that is connected to or incorporates an adjustment and/or *correction device* (3.1.7)

3.1.27

software-controlled water meter

water meter (3.1.1) that incorporates and utilizes legally relevant software modules

3.2 Metrological characteristics

3.2.1

actual volume

V_a
total volume of water passing through the meter, disregarding the time taken

Note 1 to entry: This is the measurand.

Note 2 to entry: The actual volume is calculated from a reference volume as determined by a suitable measurement standard, taking into account differences in metering conditions, as appropriate.

3.2.2

indicated volume

V_i
volume of water indicated by the meter, corresponding to the actual volume

3.2.3

primary indication

indication which is subject to legal metrological control

3.2.4

error

measured quantity value minus a reference quantity value

[SOURCE: ISO/IEC Guide 99:2007|OIML V 2-200:2012 (VIM), 2.16, modified — “error” replaces “measurement error”; original notes to entry removed; “Note 1 to entry” added, “Note 2 to entry” added.]

Note 1 to entry: For the application of this part of ISO 4064|OIML R 49, the indicated volume is considered as the measured quantity value and the actual volume as the reference quantity value. The difference between indicated volume and actual volume is referred to as: error (of indication).

Note 2 to entry: In this International Standard, the error (of indication) is expressed as a percentage of the actual

volume, and is equal to: $\frac{(V_i - V_a)}{V_a} \times 100\%$

3.2.5

maximum permissible error

MPE

extreme value of measurement *error* (3.2.4), with respect to a known reference quantity value, permitted by specifications or regulations for a given meter

[SOURCE: ISO/IEC Guide 99:2007|OIML V 2-200:2012 (VIM), 4.26, modified — "meter" replaces "measurement, measuring instrument, or measuring system"; original notes removed]

3.2.6

intrinsic error

error (3.2.4) of a meter determined under *reference condition(s)* (3.4.5)

[SOURCE: OIML D 11:2013, 3.8, modified — "a meter" replaces "indication"]

3.2.7

initial intrinsic error

intrinsic error (3.2.6) of a meter as determined prior to *performance test(s)* (3.4.6) and *durability* (3.2.10) evaluations

[SOURCE: OIML D 11:2013, 3.9, modified — "meter" replaces "measuring instrument"]

3.2.8

fault

difference between the *error* (3.2.4) (of indication) and the *intrinsic error* (3.2.6) of a meter

[SOURCE: OIML D 11:2013, 3.10, modified — "of indication" placed in parentheses; "meter" replaces "measuring instrument"; original notes removed]

3.2.9

significant fault

fault (3.2.8) greater than the value specified in this part of ISO 4064|OIML R 49

Note 1 to entry: See 5.1.2, which specifies the value of a significant fault.

3.2.10

durability

ability of a meter to maintain its performance characteristics over a period of use

[SOURCE: OIML D 11:2013, 3.18, modified — "meter" replaces "measuring instrument"]

3.2.11

metering conditions

conditions of the water, the volume of which is to be measured, at the point of measurement

EXAMPLE Water temperature, water pressure.

3.2.12

first element of an indicating device

element which, in an *indicating device* (3.1.5) comprising several elements, carries the graduated scale with the verification scale interval

3.2.13

verification scale interval

lowest value scale division of the *first element of an indicating device* (3.2.12)

3.2.14

resolution of a displaying device

smallest difference between displayed indications that can be meaningfully distinguished

[SOURCE: ISO/IEC Guide 99:2007|OIML V 2-200:2012 (VIM), 4.15, modified – “Note 1 to entry” added]

Note 1 to entry: For a digital indicating device, this is the change in the indication when the least significant digit changes by one step.

3.3 Operating conditions

3.3.1

flow rate

Q

$Q = dV/dt$ where V is *actual volume* (3.2.1) and t is the time taken for this volume to pass through the meter

Note 1 to entry: ISO 4006:1991[3], 4.1.2 prefers the use of the symbol q_V for this quantity, but Q is used in this International Standard as it is well established in the industry.

3.3.2

permanent flow rate

Q_3

highest *flow rate* (3.3.1) within the *rated operating condition(s)* (3.4.4) at which the meter is to operate within the *maximum permissible error(s)* (3.2.5)

Note 1 to entry: In this International Standard, flow rate is expressed in m^3/h . See 4.1.3.

3.3.3

overload flow rate

Q_4

highest *flow rate* (3.3.1) at which the meter is to operate for a short period of time, within the *maximum permissible error(s)* (3.2.5), while maintaining its metrological performance when it is subsequently operating within the *rated operating condition(s)* (3.4.4)

Note 1 to entry: the definition of short period of time can vary between economies and/or applications, but for example 2 hours in a 24 hours period.

3.3.4

transitional flow rate

Q_2

flow rate (3.3.1) between the *permanent flow rate* (3.3.2) and the *minimum flow rate* (3.3.5) that divides the flow rate range into two zones, the upper flow rate zone and the lower flow rate zone, each characterized by its own *maximum permissible error(s)* (3.2.5)

3.3.5

minimum flow rate

Q_1

lowest *flow rate* (3.3.1) at which the meter is to operate within the *maximum permissible error(s)* (3.2.5)

3.3.6

combination meter changeover flow rate

Q_x

flow rate (3.3.1) at which the flow in the larger meter stops with decreasing flow rate (Q_{x1}) or starts with increasing flow rate (Q_{x2})

3.3.7

minimum admissible temperature

mAT

minimum water temperature that a meter can withstand permanently, within its *rated operating condition(s)* (3.4.4), without deterioration of its metrological performance

Note 1 to entry: mAT is the lower of the rated operating conditions for temperature.

3.3.8
maximum admissible temperature
MAT

maximum water temperature that a meter can withstand permanently, within its *rated operating condition(s)* (3.4.4), without deterioration of its metrological performance

Note 1 to entry: MAT is the upper of the rated operating conditions for temperature.

3.3.9
maximum admissible pressure
MAP

maximum internal pressure that a meter can withstand permanently, within its *rated operating condition(s)* (3.4.4), without deterioration of its metrological performance

3.3.10
working temperature

T_w
water temperature in the pipe measured upstream of the meter

3.3.11
working pressure

p_w
average water pressure (gauge) in the pipe measured upstream and downstream of the meter

3.3.12
pressure loss

Δp
irrecoverable decrease in pressure, at a given *flow rate* (3.3.1), caused by the presence of the meter in the pipeline

3.3.13
test flow rate

mean *flow rate* (3.3.1) during a test, calculated from the indications of a calibrated reference device

3.3.14
nominal diameter

DN
alphanumeric designation of size for components of a pipework system, which is used for reference purposes

Note 1 to entry: The nominal diameter is expressed by the letters DN followed by a dimensionless whole number which is indirectly related to the physical size, in millimetres, of the bore or outside diameter of the end connections.

Note 2 to entry: The number following the letters DN does not represent a measurable value and should not be used for calculation purposes except where specified in the relevant standard.

Note 3 to entry: In those standards which use the DN designation system, any relationship between DN and component dimensions should be given, e.g. DN/OD or DN/ID.

3.4 Test conditions

3.4.1
influence quantity

quantity that, in a direct measurement, does not affect the quantity that is actually measured, but affects the relation between the indication and the measurement result

[SOURCE: ISO/IEC Guide 99:2007|OIML V 2-200:2012 (VIM) 2.52, modified – original examples and notes removed; “EXAMPLE” added]

EXAMPLE The ambient temperature of the meter is an influence quantity, whereas the temperature of the water passing through the meter affects the measurand.