

~~2023-02-20~~

ISO/FDIS 31101:2023(E)

ISO/TC 299

Secretariat: SIS

~~2023-06-12~~

Robotics — Application services provided by service robots — Safety management systems requirements

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 31101](#)

<https://standards.iteh.ai/catalog/standards/sist/406d1bd3-bff6-4581-9e9b-853a30b8a371/iso-31101>

© ISO ~~2022~~ 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO Copyright Office
CP 401 • CH-1214 Vernier, Geneva
Phone: + 41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org
Published in Switzerland.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 31101](#)

<https://standards.iteh.ai/catalog/standards/sist/406d1bd3-bff6-4581-9e9b-853a30b8a371/iso-31101>

Contents

Foreword	v
Introduction.....	vi
1 Scope	8
2 Normative references	8
3 Terms and definitions.....	9
4 Context of the organization	17
4.1 Understanding the organization and its context	17
4.2 Understanding the needs and expectations of interested parties.....	18
4.3 Determining the scope of the application service safety management system.....	19
4.4 Application service safety management system.....	19
5 Leadership.....	20
5.1 Leadership and commitment.....	20
5.2 Policy.....	20
5.3 Roles, responsibilities and authorities.....	21
6 Planning.....	22
6.1 Actions to address risks and opportunities.....	22
6.2 Application service safety objectives and planning to achieve them	22
6.3 Planning of changes.....	23
6.4 Safety risk assessment.....	24
6.4.1 General.....	24
6.4.2 Preparation of safety risk assessment.....	24
6.4.3 Safety risk analysis	24
6.4.4 Safety risk evaluation	26
6.5 Activities for safety risk reduction.....	26
6.5.1 General.....	26
6.5.2 Determination of safety risk reduction measure	26
6.5.3 Determination of compliance obligations on the operation	27
6.5.4 Planning implementation of the safety risk reduction measures	28
7 Support.....	29
7.1 Resources	29
7.2 Competence	29
7.3 Awareness.....	29
7.4 Communication.....	30
7.4.1 General.....	30
7.4.2 Internal communication	30
7.4.3 Communication with interested parties.....	31
7.5 Documented information	31
7.5.1 General.....	31
7.5.2 Creating and updating documented information.....	31
7.5.3 Control of documented information.....	32
8 Operation	32
8.1 Operational planning and control.....	32
8.2 Communication with users	33
8.3 Consideration for the third party of application service	34
8.4 Emergency preparedness and response.....	35
8.5 Managing hazardous events	36
9 Performance evaluation	38
9.1 Monitoring, measurement, analysis, and evaluation	38
9.2 Internal audit.....	38
9.2.1 General.....	38
9.2.2 Internal audit programme	39

9.3	Management review	39
9.3.1	General	39
9.3.2	Management review inputs	39
9.3.3	Management review results	40
10	Improvement	40
10.1	Continual improvement	40
10.2	Nonconformity and corrective action	41
Annex A (informative)	Example of interested parties in application service and relationship to the defined terms	42
Annex B (informative)	Classification of the relationship between operation contents of application service and robot use restriction intended by robot system providers	2
Annex C (informative)	Examples of information for use of service robots	5
Annex D (informative)	Examples of hazards in operation and their causes	9
Bibliography	16

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 31101](https://standards.iteh.ai/catalog/standards/sist/406d1bd3-bff6-4581-9e9b-853a30b8a371/iso-31101)

<https://standards.iteh.ai/catalog/standards/sist/406d1bd3-bff6-4581-9e9b-853a30b8a371/iso-31101>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

~~Attention is drawn~~ ISO draws attention to the possibility that some of the elements/implementation of this document may involve the subject of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights. ISO in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 299, *Robotics*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

When operating service robots that ~~coexists~~coexist with people, proper management of their residual safety risks ~~are~~is needed. To achieve ~~it~~this, in the same manner as ~~they do for~~with general machineries, application service providers, who intended to start application services provided by service robots, need to consider the safety in operation as well as the robot system providers need to consider the safety in design. For application service providers to safely operate service robots with residual safety risks, ~~the~~communication between the robot system providers and the application service provider ~~are~~is important. For example, the robot system providers provide ~~proper~~appropriate information for use; ~~the~~when application service providers operate ~~the~~ robots based on the comprehension of this information for use communicated ~~from~~by the robot system providers of the service robot; ~~the~~The application service providers then give feedback to the robot system providers on the safety-related information obtained from actual operation ~~to the robot system providers~~.

For some service robots, the design safety requirements ~~in the design~~ have already been standardized in ISO 13482:2014. There have been ~~the~~ application service providers that operate ~~the~~ robots ~~in~~within the scope of these standards. Although these application service providers have ~~been operating~~operated their application services safely, based on a certain level of knowledge and experience, their methodology ~~have~~has not ~~been systemized and~~ yet been systematized, nor have the terms ~~have not~~ been standardized. It is considered that by systemizing and documenting an optimal methodology to operate application services provided by service robots safely, ~~it could be clarified~~ the criteria to be satisfied by new application service providers and would be clarified which would then ~~it could~~ promote sound development of the industry.

0.1 Aim of this document

The purpose of this document is to provide application service providers using service robots with the ~~requirements of~~ safety management system requirements for ~~the~~ application services provided by service robots as a safe operating framework ~~of safe operation~~.

~~This document is not intended to increase or change an organization's legal requirements.~~

0.2 Contents of this document

The safety management system for the application services provided by service robots is ~~founded~~based on the concept of Plan-Do-Check-Act (PDCA). The PDCA model provides an iterative process used by organizations to achieve continual improvement. It can be briefly described as follows:

- Plan: establish safety objectives and processes necessary to deliver results in accordance with the organization's safety policy
- Do: implement the processes as planned.
- Check: monitor and measure processes against the safety policy, including its commitments, safety objectives and operating criteria, and report the results.
- Act: take actions to continually improve.

In this document, the following verbal forms are used:

- “shall” indicates a requirement;
- “should” indicates a recommendation;
- “may” indicates a permission;
- “can” indicates a possibility or a capability.

Information marked as “Note” is intended to assist the understanding or use of the document.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 31101](https://standards.iteh.ai/catalog/standards/sist/406d1bd3-bff6-4581-9e9b-853a30b8a371/iso-31101)

<https://standards.iteh.ai/catalog/standards/sist/406d1bd3-bff6-4581-9e9b-853a30b8a371/iso-31101>

Robotics — Application services provided by service robots — Safety management systems requirements

1 Scope

This document specifies the requirements of safety management systems for application services provided by service robots (application service safety management system (hereafter ASSMS)) that an application service provider can use for the safety of its users and its third parties when it provides application service in unstructured human spaces with trained and untrained persons. (e.g. giving directions for visitors in airport or shopping mall, carrying goods to patients in hospital, delivering food to customers in restaurant.)

This document is applicable to any organization that wishes to:

- a) improve safety performance of application services provided by service robots,
- b) establish, implement, maintain and improve safety management systems for application services provided by service robots,
- c) assure itself of conformity with its stated application service safety policy, and
- d) demonstrate conformity with this document.

The requirements of this document can be conformed to by integrating safety management systems for application services provided by service robots into, or making it compatible with, other management systems or processes within the organization.

The requirements of this document can be conformed to by multiple organizations without omission depending on what shall be done as an organization and a safety management.

Although intended for application services provided by service robots, this standard document can also be applied to services using robots other than service robots.

This document is not intended to be used as a product safety standard.

NOTE There are cases that where the safety management systems for application services provided by service robots established in accordance with the requirements of this document can not apply directly when the service robots to be used, robot systems, contents of service, places of operation, users or so, differ.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 13482:2014, *Robots and robotic devices — Safety requirements for personal care robots*

ISO 12100:2010, *Safety of machinery — General principles for design — Risk assessment and risk reduction*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 13482:2014 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

organization

person or group of people that has its own functions with responsibilities, authorities and relationships to achieve its *objectives* (3.6)

Note 1 to entry: The concept of organization includes, but is not limited to, sole-trader, company, corporation, firm, enterprise, authority, partnership, association, charity or institution, or part or combination thereof, whether incorporated or not, public or private.

Note 2 to entry: If the organization is part of a larger entity, the term “organization” refers only to the part of the larger entity that is within the scope of the application service safety *management system* (3.4).

3.2

interested party

person or *organization* (3.1) that can affect, be affected by, or perceive itself to be affected by a decision or activity

Note 1 to entry: A robot system provider is an interested party related to ASSMS. <https://standards.iteh.ai/sist/406d1bd3-bff6-4581-9e9b-853a30b8a371/iso-31101>

3.3

top management

person or group of people who directs and controls an *organization* (3.1) at the highest level

Note 1 to entry: Top management has the power to delegate authority and provide resources within the organization.

Note 2 to entry: If the scope of the *management system* (3.4) covers only part of an organization, then top management refers to those who direct and control that part of the organization.

3.4

management system

set of interrelated or interacting elements of an *organization* (3.1) to establish *policies* (3.5) and *objectives* (3.6), as well as *processes* (3.8) to achieve those objectives

Note 1 to entry: A management system can address a single discipline or several disciplines.

ISO/~~DIS~~FDIS 31101:2022/2023(E)

Note 2 to entry: The management system elements include the organization's structure, roles and responsibilities, planning and operation.

3.5 policy

intentions and direction of an *organization* (3.1) as formally expressed by its *top management* (3.3)

3.6 objective

result to be achieved

Note 1 to entry: An objective can be strategic, tactical, or operational.

Note 2 to entry: Objectives can relate to different disciplines (such as finance, health and safety, and environment). They can be, for example, organization-wide or specific to a project, product or *process* (3.8).

Note 3 to entry: An objective can be expressed in other ways, e.g. as an intended result, as a purpose, as an operational criterion, as an application service safety objective or by the use of other words with similar meaning (e.g. aim, goal, or target).

Note 4 to entry: In the context of application service safety *management systems* (3.4), application service safety objectives are set by the *organization* (3.1), consistent with the application service safety *policy* (3.5), to achieve specific results.

3.7 risk

effect of uncertainty

Note 1 to entry: An effect is a deviation from the expected — positive or negative.

Note 2 to entry: Uncertainty is the state, even partial, of deficiency of information related to, understanding or knowledge of, an event, its consequence, or likelihood.

Note 3 to entry: Risk is often characterized by reference to potential events (as defined in ISO Guide 73) and consequences (as defined in ISO Guide 73), or a combination of these.

Note 4 to entry: Risk is often expressed in terms of a combination of the consequences of an event (including changes in circumstances) and the associated likelihood (as defined in ISO Guide 73) of occurrence.

Note 5 to entry: In this document, where the term “risks and opportunities” is used this means *safety risks* (3.39), *safety opportunities* (3.40) and other risks and other opportunities for the management system.

Note 6 to entry: This constitutes one of the common terms and core definitions for ISO management system standards given in Annex-SL of the Consolidated ISO Supplement to the ISO/IEC Directives, Part 1. Note 5 to entry has been added to clarify the term “risks and opportunities” for its use within this document.

3.8 process

set of interrelated or interacting activities that uses or transforms inputs to deliver a result

Note 1 to entry: Whether the result of a process is called an output, a product or a service depends on the context of the reference.

3.9

competence

ability to apply knowledge and skills to achieve intended results

3.10

documented information

information required to be controlled and maintained by an *organization* (3.1) and the medium on which it is contained

Note 1 to entry: Documented information can be in any format and media and from any source.

Note 2 to entry: Documented information can refer to:

- the *management system* (3.4), including related *processes* (3.8);
- information created in order for the organization to operate (documentation);
- evidence of results achieved (records).

3.11

performance

measurable result

Note 1 to entry: Performance can relate either to quantitative or qualitative findings.

Note 2 to entry: Performance can relate to managing activities, *processes* (3.8), products, services, systems or *organizations* (3.1).

3.12

continual improvement

recurring activity to enhance *performance* (3.11)

3.13

effectiveness

extent to which planned activities are realized and planned results are achieved

3.14

requirement

need or expectation that is stated, generally implied or obligatory

Note 1 to entry: “Generally implied” means that it is custom or common practice for the *organization* (3.1) and *interested parties* (3.2) that the need or expectation under consideration is implied.

Note 2 to entry: A specified requirement is one that is stated, e.g. in *documented information* (3.10).

3.15

ISO/~~DIS~~ **FDIS 31101:2022** **2023(E)**

conformity

fulfilment of a *requirement* (3.14)

3.16

nonconformity

non-fulfilment of a *requirement* (3.14)

3.17

corrective action

action to eliminate the cause(s) of a *nonconformity* (3.16) and to prevent recurrence

3.18

audit

systematic and independent *process* (3.8) for obtaining evidence and evaluating it objectively to determine the extent to which the audit criteria are fulfilled

Note 1 to entry: An audit can be an internal audit (first party) or an external audit (second party or third party), and it can be a combined audit (combining two or more disciplines).

Note 2 to entry: An internal audit is conducted by the *organization* (3.1) itself, or by an external party on its behalf.

Note 3 to entry: “Audit evidence” and “audit criteria” are defined in ISO 19011.

3.19

measurement

process (3.8) to determine a value

3.20

monitoring

determining the status of a system, a *process* (3.8) or an activity

Note 1 to entry: To determine the status, there can be a need to check, supervise or critically observe.

3.21

application service safety performance

measurable result related to the safety of an *application service* (3.26)

Note 1 to entry: Examples of metrics to measure *performances* (3.11) relevant to the safety of an application service are:

- continuous operation time without an *accident* (3.43);
- the number of near-hits (generally known as an incident which is a *hazardous event* (3.41) but does not cause a *harm* (3.41) as a result);
- the number of improvement proposals;

- the number of persons with safety-related qualification;
- the number of emergency tests.

3.22

outsource (verb)

make an arrangement where an external *organization* (3.1) performs part of an organization's function or *process* (3.8)

Note 1 to entry: An external organization is outside the scope of the *management system* (3.4), although the outsourced function or process is within the scope.

3.23

robot

programmed actuated mechanism with a degree of autonomy to perform locomotion, manipulation or positioning

[SOURCE: ~~3.1 of~~ ISO 8373:2021, [3.1](#)]

3.24

service robot

robot (3.23) in personal use or professional use that performs useful tasks for humans or equipment

[SOURCE: ~~3.7 of~~ ISO 8373:2021, [3.7](#)]

3.25

robot system

system constructed for an *application service* (3.26), including *service robots* (3.24), safeguarding and complementary protective measures independently installed by an *application service provider* (3.30), communication networks, and so on

3.26

application service

action to provide benefit to a *user* (3.27) by interaction between a *service robot* (3.24) or a *robot system* (3.25) and the *user* (3.27)

Note 1 to entry: Trials are regarded as an application service.

3.27

user

beneficiary, person who receives the benefit, of the *application services* (3.26) provided by the *service robot* (3.24)

Note 1 to entry: In some applications, a user could be both the operator and the beneficiary.

3.28

user limit

limit or condition to limit to be a *user* (3.27) by his/her category and/or characteristics

Note 1 to entry: Examples of user limit are body height, body mass, age, skill, disease, clinical history, body condition or so.

3.29

user's behaviour limit

limit or condition to limit the behaviour of a *user* (3.27)

Note 1 to entry: Examples of user's behaviour limit are acting in accordance with the operation procedure of a service robot specified by the *robot system provider* (3.33), putting on a protective equipment or so.

3.30

application service provider

organization (3.1) that initiatively performs planning, implementation and providing *application service* (3.26) and has overall responsibility of *application service* (3.26) including safety. In the case of that application service provider *outsources* (3.22) operation task to *operator agency* (3.31), it provides a *robot system* (3.25) to an *operator agency* (3.31) for a defined use

Note 1 to entry: There are several cases in market to establish robot system for application service. The simplest case is using general-purpose robot system which robot system provider supply. However, in many cases, integration of robot system according to each application service are needed. When application service provider performs system integration by itself, it takes on the role and responsibilities of a *robot system provider* (3.33) including to certify that the robot system meets relevant safety standards if necessary. When application service provider outsourced system integration, outsourcing partner takes on these role and responsibilities depends on contract.

Note 2 to entry: When application service provider performs planning application service, it can apply organizational measures, and/or person-based measures to ensure the safety of application service.

3.31

operator agency

organization (3.1) that has the responsibility to manage and operate a *service robot* (3.24)

Note 1 to entry: *Operator agency* (3.31) can be a part of *application service provider* (3.30), otherwise can be a different *organization* (3.1) which outsourced by *application service provider* (3.30).

EXAMPLE 1 The application of a delivery robot for transporting food and food-related items between an *operator agency* (3.31) such as a restaurant, and a *user* (3.27) such as a restaurant customer. The restaurant, the *operator agency* (3.31), that manages a person, the *operator* (3.23), who programs the delivery destination and initiates the *service robot* (3.4) to accomplish the delivery task.