



International  
Standard

**ISO 24163-2**

**Clamp-in tyre valves for tyre  
pressure monitoring systems —**

**Part 2:  
Test methods and performance**

*Valves à visser pour système de contrôle de la pression des  
pneus —*

*Partie 2: Méthodes d'essai et exigences de performance*

**First edition  
2024-01**

ISO 24163-2:2024

<https://standards.iteh.ai/catalog/standards/iso/fdc4d2d3-b679-4d9d-8ec3-b44483e038ac/iso-24163-2-2024>

iTeh Standards  
(<https://standards.iteh.ai>)  
Document Preview

ISO 24163-2:2024

<https://standards.iteh.ai/catalog/standards/iso/fdc4d2d3-b679-4d9d-8ec3-b44483e038ac/iso-24163-2-2024>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

|                                                               |           |
|---------------------------------------------------------------|-----------|
| <b>Foreword</b>                                               | <b>iv</b> |
| <b>1 Scope</b>                                                | <b>1</b>  |
| <b>2 Normative references</b>                                 | <b>1</b>  |
| <b>3 Terms and definitions</b>                                | <b>1</b>  |
| <b>4 Test fixture and valve hole dimensions</b>               | <b>2</b>  |
| <b>5 Test methods and performance requirements</b>            | <b>3</b>  |
| 5.1 General                                                   | 3         |
| 5.1.1 Appearance                                              | 3         |
| 5.1.2 Operating pressure                                      | 3         |
| 5.1.3 Installation procedure                                  | 3         |
| 5.1.4 Samples                                                 | 3         |
| 5.2 Leakage test method                                       | 3         |
| 5.3 Valve core tests                                          | 5         |
| 5.3.1 Valve core specification for leakage tests              | 5         |
| 5.3.2 Valve core room temperature leakage test                | 5         |
| 5.3.3 Valve core low temperature leakage test                 | 5         |
| 5.3.4 Valve core high temperature leakage test                | 5         |
| 5.3.5 Valve core over torque resistance test                  | 6         |
| 5.3.6 Valve core endurance test                               | 6         |
| 5.3.7 Valve core air flow rate test                           | 7         |
| 5.4 Valve cap seal                                            | 7         |
| 5.4.1 Room temperature test (optional, for sealing caps only) | 7         |
| 5.5 Valve to rim seal                                         | 8         |
| 5.5.1 Valve to rim seal leakage test — General                | 8         |
| 5.5.2 Valve to rim seal low temperature leakage test          | 8         |
| 5.5.3 Valve to rim seal high temperature leakage test         | 8         |
| 5.5.4 Valve to rim seal peak temperature leakage test         | 9         |
| 5.6 Valve mechanical resistance                               | 9         |
| 5.6.1 Over torque nut test                                    | 9         |
| 5.6.2 High pressure test                                      | 9         |
| 5.6.3 Radial force resistance (nose resistance)               | 9         |
| 5.7 Environmental resistance                                  | 11        |
| 5.7.1 Ozone test                                              | 11        |
| 5.7.2 Neutral salt spray (NSS) test                           | 12        |

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at [www.iso.org/patents](http://www.iso.org/patents). ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 31, *Tyres, rims and valves*, Subcommittee SC 9, *Valves for tube and tubeless tyres*.

A list of all parts in the ISO 24163 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

<https://standards.iteh.ai/catalog/standards/iso/fdc4d2d3-b679-4d9d-8ec3-b44483e038ac/iso-24163-2-2024>

# Clamp-in tyre valves for tyre pressure monitoring systems —

## Part 2: Test methods and performance

### 1 Scope

This document specifies test methods for clamp-in tyre valves for tyre pressure monitoring systems (TPMSs).

These methods are defined to determine the minimum level of performance requested.

This document applies to the tyre valve assembled on the rim hole with diameter of 11,3 mm for passenger cars or for light duty vehicles.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3877-2, *Tyres, valves and tubes — List of equivalent terms — Part 2: Tyre valves*

ISO 9227, *Corrosion tests in artificial atmospheres — Salt spray tests*

ISO 9413, *Tyre valves — Dimensions and designation*

ISO 14960-2, *Tubeless tyres — Valves and components — Part 2: Clamp-in tubeless tyre valve-test method*

ISO 24163-1, *Tyre valves — Clamp-in tyre valves for tyre pressure monitoring systems — Part 1: Definition, types, dimensions and valve interface*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 3877-2, ISO 9413, ISO 24163-1, ISO 14960-2 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

#### 3.1 clamp-in tyre valve

valve for tubeless tyre, designed to be used with a valve core, a cap, an O-ring or a rubber grommet and to be fixed with a hex nut and potentially a ring washer

#### 3.2 tyre pressure monitoring system TPMS

system which directly monitors the tyre pressure and which alerts in case of under pressure

### 3.3

#### valve assembly

clamp-in tyre pressure monitoring system (TPMS) (3.2) valve (with a valve core, a cap, a nut, an O-ring or a rubber grommet and potentially a washer) fixed on the test fixture

## 4 Test fixture and valve hole dimensions

For each test, the material and the test fixture should be representative of the actual rim.

Break both edges on both sides of the valve hole either by a 45° chamfer or a radius from 0,3 mm to 0,4 mm. Emery cloth or suitable tooling is recommended. The material of rim or fixture shall be aluminium alloy or steel.

Unless otherwise stated, for all the tests, the conditions in Table 1 shall be applied for the installation of the valve.


**Table 1 — Test Fixture**

| Test                                      | Nominal hole diameter<br>11,3 mm                                                                                             |                                                                                                                         |
|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
|                                           | Test hole diameter<br>mm                                                                                                     | Test plate thickness<br>mm                                                                                              |
| Valve to rim seal leakage tests (see 5.5) | Specific fixture, see 5.5                                                                                                    |                                                                                                                         |
| Over torque nut test (see 5.6.1)          | $11,7^{+0}_{-0,05}$                                                                                                          | $3,5 \pm 0,05$                                                                                                          |
| High pressure test (see 5.6.2)            | $11,7^{+0}_{-0,05}$                                                                                                          | $3,5 \pm 0,05$                                                                                                          |
| Radial force resistance (see 5.6.3)       | $11,3^{+0,05}_{-0}$                                                                                                          | $3,5 \pm 0,05$                                                                                                          |
| Ozone test (see 5.7.1)                    | Ozone test on seal alone:<br>Specific fixture, see 5.7.1<br>Ozone test on complete valve<br>assembly:<br>$11,3^{+0,05}_{-0}$ | Ozone test on seal alone:<br>Specific fixture, see 5.7.1<br>Ozone test on complete valve<br>assembly:<br>$3,5 \pm 0,05$ |
| Neutral salt spray test (see 5.7.2)       | $11,3^{+0,05}_{-0}$                                                                                                          | $3,5 \pm 0,05$                                                                                                          |

As described in ISO 9413 and ISO 24163-1, several types of clamp-in valves exist.

Furthermore, several types of tyre pressure monitoring systems (TPMSs) exist and this document does not consider the attachment system between valve and sensor housing.

In this document a simplified illustration of a TPMS clamp-in valve is used (Figure 1).



#### Key

1 TPMS

**Figure 1 — Simplified representation of a TPMS clamp-in valve**