

SLOVENSKI STANDARD SIST EN 300 356-7 V4.1.2:2004

01-april-2004

8][]HUbc'ca fYÿ'Y'n']bhY[f]fUb]a]'ghcf]hj Ua]'fHG8 BL'!'G][bU]nUV]'U'ýh''+'fGG+L'!
YffHUfUn']]WU=G8 B!i dcfUVb]ý_Y[UXY'U'fHGI DL'nUa YXbUfcXb]'j a Ygb]_'!'+"XY'.
8 cdc'b]'bU'ghcf]hYj .'dfYbcg`'[j cghihYfa]bU'U'fHDL'Qhf]dcfc]'c'+|| !H'E"+'' z'("hc _U
ff%-' LzgdfYa Yb'YbcQ

Integrated Services Digital Network (ISDN); Signalling System No.7 (SS7); ISDN User Part (ISUP) version 4 for the international interface; Part 7: Terminal Portability (TP) supplementary service [ITU-T Recommendation Q.733, clause 4 (1993) modified]

(standards.iteh.ai)

SIST EN 300 356-7 V4.1.2:2004 https://standards.iteh.ai/catalog/standards/sist/c8b192e8-3b76-4e1f-9753-67e654d441c4/sist-en-300-356-7-v4-1-2-2004

Ta slovenski standard je istoveten z: EN 300 356-7 Version 4.1.2

ICS:

33.080 Digitalno omrežje z

integriranimi storitvami

(ISDN)

Integrated Services Digital

Network (ISDN)

SIST EN 300 356-7 V4.1.2:2004

en

SIST EN 300 356-7 V4.1.2:2004

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 300 356-7 V4.1.2:2004 https://standards.iteh.ai/catalog/standards/sist/c8b192e8-3b76-4e1f-9753-67e654d441c4/sist-en-300-356-7-v4-1-2-2004

ETSI EN 300 356-7 V4.1.2 (2001-07)

European Standard (Telecommunications series)

Integrated Services Digital Network (ISDN);
Signalling System No.7 (SS7);
ISDN User Part (ISUP) version 4 for the international interface;
Part 7: Terminal Portability (TP) supplementary service

[ITU-T Recommendation Q.733, clause 4 (1993) modified]

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 300 356-7 V4.1.2:2004 https://standards.iteh.ai/catalog/standards/sist/c8b192e8-3b76-4e1f-9753-67e654d441c4/sist-en-300-356-7-v4-1-2-2004



Reference REN/SPAN-01082-07

Keywords
ISDN, ISUP, SS7, supplementary service, TP, endorsement

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la

iTeh Sous-Préfecture de Grasse (06) N° 7803/88 / IEW

(standards.iteh.ai)

<u>SIST EN 300 356-7 V4.1.2:2004</u> https://standards.iteh.ai/catalog/standards/sist/c8b192e8-3b76-4e1f-9753-67e654d441c4/sist-en-300-356-7-v4-1-2-2004

Important notice

Individual copies of the present document can be downloaded from: http://www.etsi.org

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at http://www.etsi.org/tb/status/

If you find errors in the present document, send your comment to: editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2001.
All rights reserved.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://www.etsi.org/ipr).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Services and Protocols for Advanced Networks (SPAN).

The present document is part 7 of a multi-part deliverable covering the ISDN User Part (ISUP) version 4 for the international interface, as identified below:

- Part 1: "Basic services [ITU-T Recommendations Q.761 to Q.764 (1999) modified]";
- Part 2: "ISDN supplementary service [ITU-T Recommendation Q.730 (1999) modified]";
- Part 3: "Calling Line Identification Presentation (CLIP) supplementary service [ITU-T Recommendation Q.731, clause 3 (1993) modified]"; standards iteh ai
- Part 4: "Calling Line Identification Restriction (CLIR) supplementary service [ITU-T Recommendation Q.731, clause 4 (1993) modified]"; SIST EN 300 356-7 V4.1.2:2004
- Part 5: "Connected Line Identification Presentation (COLP) supplementary service [ITU-T Recommendation Q.731, clause 5 (1993) modified]*, 124/sist-en-300-356-7-v4-1-2-2004
- Part 6: "Connected Line Identification Restriction (COLR) supplementary service [ITU-T Recommendation Q.731, clause 6 (1993) modified]";
- Part 7: "Terminal Portability (TP) supplementary service [ITU-T Recommendation Q.733, clause 4 (1993) modified]";
- Part 8: "User-to-User Signalling (UUS) supplementary service [ITU-T Recommendation Q.737, clause 1 (1997) modified]";
- Part 9: "Closed User Group (CUG) supplementary service [ITU-T Recommendation Q.735, clause 1 (1993) modified]";
- Part 10: "Subaddressing (SUB) supplementary service [ITU-T Recommendation Q.731, clause 8 (1992) modified]";
- Part 11: "Malicious Call Identification (MCID) supplementary service [ITU-T Recommendation Q.731, clause 7 (1997) modified]";
- Part 12: "Conference Call, add-on (CONF) supplementary service [ITU-T Recommendation Q.734, clause 1 (1993) and implementors guide (1998) modified]";
- Part 14: "Explicit Call Transfer (ECT) supplementary service [ITU-T Recommendation Q.732, clause 7 (1996) and implementors guide (1998) modified]";
- Part 15: "Diversion supplementary service [ITU-T Recommendation Q.732, clauses 2 to 5 (1999) modified]";
- Part 16: "Call Hold (HOLD) supplementary service [ITU-T Recommendation Q.733, clause 2 (1993) modified]";
- Part 17: "Call Waiting (CW) supplementary service [ITU-T Recommendation Q.733, clause 1 (1992) modified]";

4

- Part 18: "Completion of Calls to Busy Subscriber (CCBS) supplementary service [ITU-T Recommendation Q.733, clause 3 (1997) modified]";
- Part 19: "Three-Party (3PTY) supplementary service [ITU-T Recommendation Q.734, clause 2 (1996) and implementors guide (1998) modified]";
- Part 20: "Completion of Calls on No Reply (CCNR) supplementary service [ITU-T Recommendation Q.733, clause 5 (1999) modified]";
- Part 21: "Anonymous Call Rejection (ACR) supplementary service [ITU-T Recommendation Q.731, clause 4 (1993)]";
- Part 31: "Protocol Implementation Conformance Statement (PICS) proforma specification for basic services";
- Part 32: "Test Suite Structure and Test Purposes (TSS&TP) specification for basic services";
- Part 33: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for basic services";
- Part 34: "Protocol Implementation Conformance Statement (PICS) proforma specification for supplementary services";
- Part 35: "Test Suite Structure and Test Purposes (TSS&TP) specification for supplementary services";
- Part 36: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for supplementary services".

In accordance with ITU-T Recommendation I.130 [1], the following three level structure is used to describe the supplementary telecommunication services as provided by European public telecommunications operators under the pan-European Integrated Services Digital Network (ISDN):

- Stage 1: is an overall service description, from the user's stand-point;
- Stage 2: identifies the functional capabilities and information flows needed to support the service described in stage 1; and https://standards.iteh.ai/catalog/standards/sist/c8b192e8-3b76-4e1f-9753-
- Stage 3: defines the signalling system protocols and switching functions needed to implement the service described in stage 1.

The present document details the stage three aspects (signalling system protocols and switching functions) needed to support the Terminal Portability (TP) supplementary service. The stage 1 and stage 2 aspects are detailed in ETS 300 053 [2] and ETS 300 054 [3], respectively.

National transposition dates		
Date of adoption of this EN:	13 July 2001	
Date of latest announcement of this EN (doa):	31 October 2001	
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 April 2002	
Date of withdrawal of any conflicting National Standard (dow):	30 April 2002	

Endorsement notice

The elements of ITU-T Recommendation Q.733, clause 4 (1993) apply, with the following modifications.

NOTE: New or modified text is indicated using sidebars. In addition, underlining and/or strike-out are used to highlight detailed modifications where necessary.

Global modifications to ITU-T Recommendation Q.733, clause 4

Insert the following two clauses (Scope and References) at the start of clause 4.

Scope

The present document specifies the stage three of the Terminal Portability (TP) supplementary service for the pan-European Integrated Services Digital Network (ISDN) as provided by the European public telecommunications operators by means of the Signalling System No.7 protocol for the ISDN User Part (ISUP). Stage three identifies the protocol procedures and switching functions needed to support a telecommunication service (see ITU-T Recommendation I.130 [1]).

The present document does not specify the additional protocol requirements where the service is provided to the user via a telecommunications network that is not an ISDN.

The present document does not specify the additional protocol requirements for the national signalling interface.

Although the present document applies only to the international interconnection, the specification of functions, formats and codes of messages and signals, and actions performed at originating and destination local exchanges are retained.

Formats, codes and procedures marked for national use are included for informative purposes for the international interface specification. If these items so marked are supported within a national network and operator's network, then it is proposed that they shall be supported in this manner.

NOTE: In the case where a national signalling system behaves differently, the international gateway exchange is to support both the concerned national and international network.

The TP supplementary service allows a user to move a terminal from one socket to another within one given basic access during the active state of the call. It also allows a user to move a call from one terminal to another terminal within one given basic access during the active state of the call. 356-7-v4-1-2-2004

The TP supplementary service is applicable to interactive circuit-switched telecommunication services requiring the attendance of a human being, such as telephony, videotelephony etc.

References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- [1] ITU-T Recommendation I.130 (1988): "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [2] ETSI ETS 300 053 (1991): "Integrated Services Digital Network (ISDN); Terminal Portability (TP) supplementary service; Service Description".
- [3] ETSI ETS 300 054 (1991): "Integrated Services Digital Network (ISDN); Terminal Portability (TP) supplementary service; Functional capabilities and information flows".

[4]	ETSI EN 300 055-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Terminal Portability (TP) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
[5]	ETSI ETS 300 121 (1992): "Integrated Services Digital Network (ISDN); Application of the ISDN User Part (ISUP) of CCITT Signalling System No.7 for international ISDN interconnections (ISUP version 1)".
[6]	ETSI EN 300 356-1: "Integrated Services Digital Network (ISDN); Signalling System No.7 (SS7); ISDN User Part (ISUP) version 4 for the international interface; Part 1: Basic services [ITU-T Recommendations Q.761 to Q.764 (1999) modified]".
[7]	ETSI EN 300 356-2: "Integrated Services Digital Network (ISDN); Signalling System No.7 (SS7); ISDN User Part (ISUP) version 4 for the international interface; Part 2: ISDN supplementary service [ITU-T Recommendation Q.730 (1999) modified]".
[8]	ETSI EN 300 403-1 (V1.3.2): "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 1: Protocol specification [ITU-T Recommendation Q.931 (1993), modified]".

Throughout the text of ITU-T Recommendation Q.733, clause 4

Replace references as shown in table 1.

Table 1

Reference in ITU-T Recommendation	Modified reference
Q.733, clause 4 Tah ST	ANDARD PREVIEW
ITU-T Recommendation I.253.4	ETS 300 053 [2]
ITU-T Recommendation Q.83, clause 4	ETS 300 054 [3] itch ai)
ITU-T Recommendation Q.730	ITU-T Recommendation Q.730 as modified by EN 300 356-2 [7]
ITU-T Recommendation Q.761	ITU-T Recommendation Q.761 as modified by EN 300 356-1 [6]
ITU-T Recommendation Q.762	ITU-T Recommendation Q762 as modified by EN 300 356-1 [6]
ITU-T Recommendation Qu763//standards.iteh.a	ITU-To Recommendation Q.763 as modified by EN 300 356-1 [6]
ITU-T Recommendation Q.764 67e654d	TU-T Recommendation Q.764 as modified by EN 300 356-1 [6]
ITU-T Recommendation Q.767	ETS 300 121 [5]
ITU-T Recommendation Q.931	ITU-T Recommendation Q.931 as modified by EN 300 403-1 [8]
ITU-T Recommendation Q.953, clause 4	EN 300 055-1 [4]

Subclause 4.4

Add the following text:

The notification to the public network that a call was suspended/resumed in a private network is transported in the generic notification parameter of the Call progress message. No Suspend/Resume messages shall be sent and no related timer shall be started. The event indicator shall be coded "progress" in both cases.

Subclause 4.5.2.3.1

Modify the text as follows:

If Terminal Portability is supported in the succeeding national network, the outgoing international gateway exchange acts like a transit exchange (see 4.5.2.2.1).

Subclause 4.5.2.3.2

Modify the text as follows:

If Terminal Portability is not supported in the succeeding national network, the outgoing international gateway exchange discards the Suspend and Resume messages received from the international network. No notification is given.

7

ETSI EN 300 356-7 V4.1.2 (2001-07)

Subclause 4.5.2.4.2

Modify the text as follows:

If Terminal Portability is not supported in the national network, the incoming international gateway exchange discards the Suspend and Resume messages received from the international network. No notification is given.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 300 356-7 V4.1.2:2004 https://standards.iteh.ai/catalog/standards/sist/c8b192e8-3b76-4e1f-9753-67e654d441c4/sist-en-300-356-7-v4-1-2-2004

ETSI