

ISO/~~DIS~~ FDIS 5309:2022(E)

ISO/TC 20/SC 16/~~WG-5~~

Secretariat: ANSI

Date: 2023-6-108-31

## Civil small and light unmanned aircraft systems (UAS) — Vibration test methods

iTeh STANDARD PREVIEW

FDIS stage

ISO/FDIS 5309

<https://standards.iteh.ai/catalog/standards/sist/46edfc32-f44f-4dba-bd88-f2d5914ee2e3/iso-fdis-5309>

© ISO ~~2022~~2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: + 41 22 749 01 11  
~~Email~~E-mail: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 5309

<https://standards.iteh.ai/catalog/standards/sist/46cdfc32-f44f-4dba-bd88-f2d5914ee2e3/iso-fdis-5309>

## Contents

Foreword .....	v
Introduction.....	vi
1 Scope .....	1
2 Normative references.....	1
3 Terms and definitions .....	1
4 Types of vibration test.....	1
4.1 Standard vibration test.....	1
4.2 Transportation vibration test.....	1
5 Test conditions.....	2
5.1 General .....	2
5.2 Conditions for standard vibration test.....	3
5.2.1 Random test.....	3
5.2.2 Sinusoidal test .....	3
5.2.3 Sine-on-random test .....	3
5.3 Conditions for transportation vibration test.....	7
5.3.1 Random test.....	7
5.3.2 Vehicle field test.....	8
5.4 Vibration test requirements and recommendations.....	8
5.5 Control level tolerance requirements.....	9
5.5.1 Random input control .....	9
5.5.2 Sinusoidal control .....	9
6 Test procedure .....	9
6.1 Random test .....	9
6.1.1 General.....	9
6.1.2 Check before test.....	9
6.1.3 Test article installation .....	9
6.1.4 Test process.....	9
6.1.5 Check after test.....	10
6.2 Sinusoidal test .....	10
6.2.1 General.....	10
6.2.2 Check before test.....	10
6.2.3 Test article installation .....	10
6.2.4 Test process.....	10
6.2.5 Check after test.....	11

6.3	Sine-on-random test.....	11
6.3.1	General.....	11
6.3.2	Check before test.....	11
6.3.3	Test article installation.....	11
6.3.4	Test process.....	11
6.3.5	Check after test.....	12
7	Test report.....	12
Annex A (informative) Information to be given in the relevant functions.....		13
Bibliography.....		14

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO/FDIS 5309

<https://standards.iteh.ai/catalog/standards/sist/46cdfc32-f44f-4dba-bd88-f2d5914ee2e3/iso-fdis-5309>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at [www.iso.org/patents](http://www.iso.org/patents). ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical ISO/TC 20, *Aircraft and space vehicles*, Subcommittee SC 16, *Unmanned aircraft systems*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

In recent years, the market for lightweight and small civil unmanned aircraft systems (UAS) has developed rapidly. Application areas range from consumer-grade unmanned aircraft vehicles fitted with a camera to industrial-grade unmanned aircraft vehicles used in various safety and inspection operations (e.g. in agriculture, electrical distribution and public safety). As a consequence of being transported from job site to job site, the UAS is exposed to a vibration environment during its lifetime. This document sets out a vibration environment that reflects the situation the UAS experiences during transportation and flight, and to which it can be tested so as to verify whether the test article complies with the applicable performance standards (excluding durability requirements) when subjected to vibration levels specified for the appropriate installation.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 5309

<https://standards.iteh.ai/catalog/standards/sist/46edfc32-f44f-4dba-bd88-f2d5914ee2e3/iso-fdis-5309>

# Civil small and light unmanned aircraft systems (UAS) — Vibration test methods

## 1 Scope

This document specifies the test conditions and methods to be used for the vibration testing of unmanned aircraft system (UAS, including unmanned aircraft and ground station) which applies to level II through V according to ISO 21895.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2041, *Mechanical vibration, shock and condition monitoring — Vocabulary*

ISO 21384-4, *Unmanned aircraft systems — Part 4: Vocabulary*

ISO 21895, *Categorization and classification of civil unmanned aircraft systems*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 2041 and ISO 21384-4 [and the following](#) apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ~~—~~ISO Online browsing platform: available at <https://www.iso.org/obp>  
[https://standards.iteh.ai/catalog/standards/sist/46cedfc32-f44f-4dba-bd88-f2d5914ee2e3/iso-](https://standards.iteh.ai/catalog/standards/sist/46cedfc32-f44f-4dba-bd88-f2d5914ee2e3/iso-21384-4)
- ~~—~~IEC Electropedia: available at <https://www.electropedia.org/>

### 3.1

#### power spectral density

~~{PSD}~~

degree of variation in energy for each frequency to the acceleration signal in a specific frequency range as a function of frequency

## 4 Types of vibration test

### 4.1 Standard vibration test

Standard vibration test is performed to verify whether the UA can work normally when it is subjected to a vibration environment expected during flight, including engine(s) running and rotor(s) turning on ground (e.g. ground resonance prevention). The test may be performed under the conditions involving random test, sinusoidal test, and sine-on-random test.

Measured values should be collected from representative operations and used in testing whenever possible.

### 4.2 Transportation vibration test

Transportation vibration test is performed to verify whether UAS can work normally after it is subjected to conditions involving vibration induced by transportation.

## 5 Test conditions

### 5.1 General

The types of vibration test to which the UA (S) is to be exposed to is dependent on the powerplant type described in [Table 1](#).

Generally speaking, sinusoidal vibration test is applicable to verify whether the design of the product meets the requirements and whether the product is intact after sinusoidal vibration test. Random vibration test mainly simulates the vibration adaptability of products under broadband excitation, especially when the resonance point cannot be determined. Sine-on-random vibration test is mainly used to assess the adaptability of the test article under the condition of superposition of broadband excitation and sinusoidal fixed frequency.

**Table 1 — Types of vibration test**

UA configuration	Engine/power plant type <sup>a</sup>	Type of vibration test	
Multicopter	Electric motor	Standard vibration	Random; sinusoidal
	/	Transportation vibration	Random test or vehicle field test
Fixed-wing	Electric motor	Standard vibration	Sinusoidal
	Turbine engine, piston engine		Sinusoidal
	Mixed power plant		Envelope value according to the type of mixed power plant
	/	Transportation vibration	Random test or vehicle field test
Unmanned helicopter	Electric motor	Standard vibration	Random; sinusoidal
	Turbine engine, piston engine		Sine-on-random (known frequency)
	Mixed power plant		Random (unknown frequency)
			Envelope value according to the type of mixed power plant
	/	Transportation vibration	Random test or vehicle field test
Ground station (vehicle-mounted/carried)	/	Transportation vibration	Random test or vehicle field test

**NOTE 1a.** The engine/power plant types include but are not limited to electric motor, piston engine, turbine engine, mixed power plant, rocket engine, and compressed air power plant according to ISO 21895. In this document, only the commonly used engine/power plant types are considered (e.g. electric motor, piston engine, turbine engine, and mixed power plant).

## 5.2 Conditions for standard vibration test

### 5.2.1 Random test

- a) ~~a)~~ Measurements: measured values shall be used wherever possible. If measured values are not available, the values shown in [Table 2](#) ~~Table 2~~ shall be used.
- b) ~~b)~~ Axial direction: test shall be performed in each of the test article's three orthogonal axes.
- c) ~~c)~~ Test duration: 1 h for each axis or the time specified by relevant specification of the test article.

### 5.2.2 Sinusoidal test

- a) ~~a)~~ Measurements: measured values shall be used wherever possible. If measured values are not available, the values shown in [Table 2](#) ~~Table 2~~ shall be used.
- b) ~~b)~~ Axial direction: test shall be performed in each of the test article's three orthogonal axes.
- c) ~~c)~~ Test duration: 1 h for each axis or the time specified by relevant specification of the test article.

### 5.2.3 Sine-on-random test

- a) ~~a)~~ Measurements: measured values shall be used wherever possible. If measured values are not available, the values shown in [Table 2](#) ~~Table 2~~ shall be used.
- b) ~~b)~~ Axial direction: test shall be performed in each of the test article's three orthogonal axes.
- c) ~~c)~~ Test duration: 1 h for each axis or the time specified by relevant specification of the test article.

Table 2 — Standard vibration test magnitude

UA configuration	Engine/power plant type	Maximum take-off mass kg		Type of vibration	Magnitude
Multicopter	Electric motor	Level II, III, IV		Random; sinusoidal	Refer to <a href="#">Table 3</a> <del>Table 3</del> and <a href="#">Table 4</a> <del>Table 4</del> for details
		Level IV	≤ 10	Random; sinusoidal	Refer to <a href="#">Table 3</a> <del>Table 3</del> and <a href="#">Table 4</a> <del>Table 4</del> for details
			> 10	Random; sinusoidal	Refer to <a href="#">Table 5</a> <del>Table 5</del> and <a href="#">Table 6</a> <del>Table 6</del> for details
		Level V	≤ 50	Random; sinusoidal	Refer to <a href="#">Table 5</a> <del>Table 5</del> and <a href="#">Table 6</a> <del>Table 6</del> for details
			> 50	Random; sinusoidal	Refer to <a href="#">Table 7</a> <del>Table 7<sup>a</sup></del> and <a href="#">Table 8</a> <del>Table 8<sup>a</sup></del> for details

UA configuration	Engine/power plant type	Maximum take-off mass kg	Type of vibration	Magnitude
Fixed-wing	Electric motor	Level II, III, IV, V	Sinusoidal	Refer to <a href="#">Table 9</a> <del>Table 9</del> <sup>a</sup> for details
	Turbine engine, piston engine	Level V	Sinusoidal	Refer to <a href="#">Table 10</a> <del>Table 10</del> <sup>a</sup> for details
	Mixed power plant	Envelope value according to the type of mixed power plant		
Unmanned helicopter	Electric motor	Level V	Random; sinusoidal	Refer to <a href="#">Table 7</a> <del>Table 7</del> <sup>a</sup> and <a href="#">Table 8</a> <del>Table 8</del> <sup>a</sup> for details
	Turbine engine, piston engine	Level V	Sine-on-random (known frequency)	Refer to <a href="#">Figure 1</a> <del>Figure 1</del> and <a href="#">Table 11</a> <del>Table 11</del> <sup>a</sup> for details
			Random (unknown frequency)	Refer to <a href="#">Table 12</a> <del>Table 12</del> <sup>a</sup> for details
	Mixed power plant	Envelope value according to the type of mixed power plant		

**NOTE 1** For UA that belongs to both multicopter and fixed-wing, both magnitudes shall be considered based on the engine/power plant type.

**NOTE 2** The classification of level ~~is according to~~ shall be in accordance with ISO 21895.

<sup>a</sup> For test ~~article~~ articles weighing greater than 22,5 kg, a reduction in test levels for frequencies above 60 Hz is allowed using the following schedule:

- test levels may be reduced by 0,10 dB for each 0,5 kg test article weight increment above 22,5 kg to a maximum reduction of 6,0 dB;
- a 6,0 dB reduction would reduce the PSD level to 1/4 of the original level.

**Table 3 — Random test levels for multicopter UA (electric motor, level II, III and IV with maximum take-off mass ≤ 10 kg)**

Frequency Hz	PSD g <sup>2</sup> /Hz
30	0,01
100	0,06
850	0,002
1 000	0,002

**Table 4 — Sinusoidal test levels for multicopter UA (electric motor, level II, III and IV with maximum take-off mass ≤ 10 kg)**

Frequency Hz	Acceleration g	Logarithmic sweep rate oct/min
30	2,0	1
100	5,0	
850	0,8	
1 000	0,8	

**Table 5 — Random test levels for multicopter UA (electric motor, level IV with maximum take-off mass > 10 kg and level V with maximum take-off mass ≤ 50 kg)**

Frequency Hz	PSD g <sup>2</sup> /Hz
10	0,001
100	0,03
600	0,000 2
1 000	0,000 2

**Table 6 — Sinusoidal test levels for multicopter UA (electric motor, level IV with maximum take-off mass > 10 kg and level V with maximum take-off mass ≤ 50 kg)**

Frequency Hz	Acceleration g	Logarithmic sweep rate oct/min
10	0,4	1
100	3,0	
600	0,2	
1 000	0,2	

**Table 7 — Random test levels for multicopter UA (electric motor, level V with maximum take-off mass > 50 kg) and unmanned helicopter (electric motor, level V)**

Frequency Hz	PSD g <sup>2</sup> /Hz
10	0,012
40	0,012
100	0,002
500	0,002
2 000	0,000 13

**Table 8 — Sinusoidal test levels for multicopter UA (electric motor, level V with maximum take-off mass > 50 kg) and unmanned helicopter (electric motor, level V)**

Frequency Hz	Double-amplitude mm/g	Logarithmic sweep rate oct/min
15	0,25 mm	1
55	0,25 mm	
500	1,5 g	